

ENTRANCE & SIDEROAD IMPROVEMENT SCHEDULE FOR RURAL/URBAN "PPP" PROJECTS																
LOCATION	TYPE OF ENTRANCE	EX MATERIAL TYPE	WIDTH	LT OFFSET	RT OFFSET	LENGTH (FROM EDGE OF PVT/BIT SHLD TO LIMITS OF IMPROVEMENTS)	PR HOT-MIX ASPHALT CONC THICKNESS	HOT-MIX ASPHALT SURF. REM BUTT JOINT	P. C. C. SURF. REM. - BUTT JOINT	PREP OF BASE	AGG. BASE REPAIR	AGGREGATE BASE COURSE TY-B	AGGREGATE SURF COURSE TY-B	BIT (P. C.)	AGG (P. C.)	INCIDENTAL HOT-MIX ASPHALT SURFACING N50
LT/RT/STA	FE/PE/CE/MB/SR	EARTH/AGG/BIT/PCC	FOOT	FOOT	FOOT	FOOT	INCH	SQ YD	SQ YD	SQ YD	TON	TON	TON	TON	TON	TON
RT	426+90.00	PE	AGG	30		10	3.5	0		44	2.53		0.00	0.02	0.09	8.71
RT	428+11.00	MB	BIT	0	19	8	3.5	17		17	0.96		0.00	0.01	0.07	6.62
RT	428+30.00	PE	AGG	16		10	3.5	0		29	1.65		0.00	0.01	0.06	5.66
LT	428+97.00	SR	BIT	22		10	1.5	58		49	2.78		0.00	0.02	0.10	4.11
LT	429+04.00	PE	CONC	30		8	1.5	46		46	2.63		0.00	0.02	0.09	3.88
LT	429+42.00	MB	BIT	0		8	3.5	6		6	0.34		0.00	0.00	0.02	2.31
RT	429+43.00	MB	BIT	0		8	3.5	0		0	0.00		0.00	0.00	0.00	0.00
LT	429+69.00	MB	BIT	0		8	3.5	42		42	2.38		0.00	0.03	0.17	16.38
LT	429+71.00	MB				8	3.5	42	42	2.38		0	0.03	0.17	16.38	
LT	429+74.00	MB				8	3.5	42	42	2.38		0	0.03	0.17	16.38	
RT	430+15.00	PE	AGG	30		10	3.5	0		44	2.53		0.00	0.02	0.09	8.71
RT	430+35.00	PE	CONC	70		8	1.5	10		19	1.09		0.00	0.01	0.04	1.61
RT	431+63.00	SR	BIT	28		10	1.5	20		20	1.11		0.00	0.01	0.04	1.64
RT	431+63.00	SR	BIT	28		10	1.5	20		20	1.11		0.00	0.01	0.04	1.64
LT	434+75.00	SR	BIT	22		10	1.5	20		17	0.96		0.00	0.01	0.03	1.42
LT	434+75.00	SR	BIT	22		10	1.5	20		17	0.96		0.00	0.01	0.03	1.42
RT	435+72.00	PE	CONC	45		8	1.5	10		14	0.77		0.00	0.01	0.03	1.14
LT	436+28.00	PE	CONC	25		8	1.5	10		9	0.52		0.00	0.00	0.02	0.77
RT	436+60.00	PE	CONC	22		8	1.5	10		8	0.48		0.00	0.00	0.02	0.71
LT	437+86.00	SR	BIT	17		10	1.5	20		15	0.84		0.00	0.01	0.03	1.23
LT	437+86.00	SR	BIT	17		10	1.5	20		15	0.84		0.00	0.01	0.03	1.23
RT	439+49.00	PE	CONC	24		8	1.5	10		9	0.51		0.00	0.00	0.02	0.75
LT	441+07.00	SR	BIT	25		10	1.5	20		18	1.04		0.00	0.01	0.04	1.53
RT	441+15.00	SR	BIT	44		10	1.5	20		27	1.52		0.00	0.01	0.05	2.24
RT	441+70.00	CE	BIT	100		10	1.5	20		51	2.89		0.00	0.02	0.10	4.26
RT	444+25.00	SR	BIT	45		0	0.0	20		26	1.49		0.00	0.01	0.05	0.00
LT	444+25.00	SR	BIT	22		10	1.5	20		17	0.96		0.00	0.01	0.03	1.42
RT	445+37.00	PE	CONC	58		8	1.5	10		16	0.94		0.00	0.01	0.03	1.38
LT	447+39.00	SR	BIT	18		10	1.5	20		15	0.86		0.00	0.01	0.03	1.27
RT	447+39.00	SR	BIT	18		10	1.5	20		15	0.86		0.00	0.01	0.03	1.27
RT	448+69.00	CE	CONC	30		10	1.5	20		20	1.11		0.00	0.01	0.04	1.64
LT	450+55.00	SR	BIT	18		10	1.5	20		15	0.86		0.00	0.01	0.03	1.27
RT	450+55.00	SR	BIT	18		10	1.5	20		15	0.86		0.00	0.01	0.03	1.27
LT	452+29.00	PE	CONC	22		8	1.5	10		8	0.48		0.00	0.00	0.02	0.71
LT	453+61.00	SR	BIT	14		10	1.5	20		13	0.76		0.00	0.01	0.03	1.12
RT	453+71.00	SR	BIT	20		10	1.5	20		16	0.91		0.00	0.01	0.03	1.34
RT	455+39.00	PE	BIT	22		8	1.5	46		39	2.23		0.00	0.01	0.08	3.29
LT	459+66.00	CE	AGG	32		15	8.0	0		78	4.46		1.76	0.02	0.12	25.88
RT	461+00.00	CE	AGG	30		15	8.0	0		75	4.27		1.66	0.02	0.11	24.89
RT	461+65.00	SR	BIT	30		10	1.5	58		58	3.29		0.00	0.02	0.12	4.85
RT	462+51.00	CE	AGG	30		15	8.0	0		75	4.27		1.66	0.02	0.11	24.89
RT	472+02.00	PE	AGG	14		15	3.5	0		48	2.75		1.40	0.01	0.06	6.27
LT	472+88.00	PE	AGG	22		15	3.5	0		62	3.51		1.93	0.01	0.08	7.67
RT	475+40.00	PE	AGG	32		15	3.5	0		78	4.46		2.59	0.02	0.10	9.41
RT	494+84.00	PE	AGG	40		15	3.5	0		92	5.22		3.12	0.02	0.11	10.80
LT	499+70.00	SR	BIT	46		10	1.5	58		76	4.30		0.00	0.03	0.15	6.35
LT	501+42.00	PE	AGG	28		15	3.5	0		72	4.08		2.33	0.02	0.09	8.71
LT	501+50.00	MB	BIT	0	15	8	3.5	17		17	0.96		0.00	0.01	0.07	6.62
LT	501+65.00	PE	AGG	14		15	3.5	0		48	2.75		1.40	0.01	0.06	6.27
RT	502+88.00	PE	AGG	26		15	3.5	0		68	3.89		2.19	0.02	0.09	8.36