

ENTRANCE & SIDEROAD IMPROVEMENT SCHEDULE FOR RURAL/URBAN "PPP" PROJECTS																	
LOCATION		TYPE OF ENTRANCE	EX MATERIAL TYPE	WIDTH	LT OFFSET	RT OFFSET	LENGTH (FROM EDGE OF PVT/BIT SHLD TO LIMITS OF IMPROVEMENTS)	PR. HOT-MIX ASPHALT CONC THICKNESS	HOT-MIX ASPHALT SURF. REM. - BUTT JOINT	P. C. C. SURF. REM. - BUTT JOINT	PREP OF BASE	AGG. BASE REPAIR	AGGREGATE BASE COURSE TY-B	AGGREGATE SURF COURSE TY-B	BIT (P. C.)	AGG (P. C.)	INCIDENTAL HOT-MIX ASPHALT SURFACING N50
LT/RT/STA		FE/PE/CE/MB/SR	EARTH/AGG/BIT/PCC	FOOT	FOOT	FOOT	FOOT	INCH	SQ YD	SQ YD	SQ YD	TON	TON	TON	TON	TON	TON
LT	527+69.00	MB	BIT	0		19	8	3.5	21		21	1.21		0.00	0.02	0.09	8.36
LT	527+70.00	MB	BIT	0		19	8	3.5	21		21	1.21		0	0.02	0.09	8.36
RT	527+88.00	SR	AGG	40			15	8.0	0		92	5.22		2.14	0.03	0.13	29.87
RT	545+90.00	PE	AGG	60			15	3.5	0		60	3.44		4.45	0.00	0.02	1.63
RT	546+23.00	MB	BIT	0			0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
RT	548+37.00	PE	AGG	24			15	3.5	0		65	3.70		2.06	0.02	0.08	8.01
RT	548+59.00	MB	BIT	0		21	8	3.5	20		20	1.16		0.00	0.02	0.08	8.01
RT	550+60.00	PE	AGG	50			15	3.5	0		52	2.94		3.79	0.00	0.01	1.42
LT	551+31.00	MB	BIT	0			0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
LT	554+27.00	SR	BIT	14			10	1.5	58		40	2.28		0.00	0.02	0.08	3.36
RT	554+27.00	SR	BIT	14			10	1.5	58		40	2.28		0.00	0.02	0.08	3.36
RT	556+31.00	PE	AGG	28			15	3.5	0		72	4.08		2.33	0.02	0.09	8.71
LT	557+04.00	CE	AGG	34			15	8.0	0		82	4.65		1.85	0.02	0.12	26.88
RT	557+19.00	PE	AGG	30			15	3.5	0		75	4.27		2.46	0.02	0.09	9.06
RT	558+22.00	PE	AGG	20			15	3.5	0		58	3.32		1.79	0.01	0.07	7.32
LT	558+23.00	MB	BIT	0			8	3.5	38		38	2.18		0.00	0.03	0.15	14.98
RT	558+24.00	MB	BIT	0			8	3.5	38		38	2.18		0	0.03	0.15	14.98
RT	581+08.00	PE	EARTH	12			15	3.5	0		45	2.56		1.26	0.01	0.06	5.92
LT	581+95.00	MB	BIT	0	31		8	3.5	20		20	1.11		0.00	0.01	0.08	7.67
LT	581+96.00	MB	BIT	0	31		8	3.5	20		20	1.11		0	0.01	0.08	7.67
RT	582+26.00	PE	AGG	18			15	3.5	0		55	3.13		1.66	0.01	0.07	6.97
LT	591+24.00	PE	AGG	14			15	3.5	0		48	2.75		1.40	0.01	0.06	6.27
LT	591+39.00	MB	BIT	0			8	3.5	37		37	2.13		0.00	0.03	0.15	14.63
LT	606+35.00	SR	BIT	36			10	1.5	58		64	3.67		0.00	0.02	0.13	5.41
RT	607+60.00	SR	BIT	34			10	1.5	58		62	3.54		0.00	0.02	0.12	5.23
LT	636+16.00	PE	AGG	8			15	3.5	0		38	2.18		1.00	0.01	0.05	5.23
RT	637+22.00	PE	AGG	8			15	3.5	0		38	2.18		1.00	0.01	0.05	5.23
LT	655+21.00	CE	AGG	300			15	8.0	15		525	29.90		14.47	0.04	0.21	46.74
LT	656+33.00	MB	BIT	0			0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
LT	660+61.00	SR	BIT	30			10	1.5	58		58	3.29		0.00	0.02	0.12	4.85
LT	701+62.00	SR	AGG	14			15	8.0	0		48	2.75		0.90	0.01	0.08	16.92
LT	701+62.00	SR	AGG	14			15	8.0	0		48	2.75		0.90	0.01	0.08	16.92
RT	707+79.00	PE	AGG	30			15	3.5	0		75	4.27		2.46	0.02	0.09	9.06
LT	708+14.00	MB	BIT	0			8	3.5	17		17	0.96		0.00	0.01	0.07	6.62
RT	749+09.00	SR	BIT	18			10	1.5	58		44	2.53		0.00	0.02	0.09	3.73
RT	766+93.00	SR	BIT	26			10	1.5	58		53	3.04		0.00	0.02	0.11	4.48
RT	766+93.00	SR	BIT	26			10	1.5	58		53	3.04		0.00	0.02	0.11	4.48
TOTAL									3,899		11,907	797		283	4	20	2,050