
**STRUCTURE GEOTECHNICAL REPORT
CIRCLE INTERCHANGE RECONSTRUCTION
RETAINING WALL 31 (PROPOSED SN 016-1820)
F.A.I ROUTE 90/94 (KENNEDY EXPRESSWAY)
IDOT D-91-227-13/ PTB 163-001
COOK COUNTY, ILLINOIS**

**For
AECOM
303 East Wacker Drive
Chicago, IL 60601
(312) 938-0300**

**Submitted by
Wang Engineering, Inc.
1145 North Main Street
Lombard, IL 60148
(630) 953-9928**

**Original: May 10, 2019
Revised: November 13, 2019**

Technical Report Documentation Page

1. Title and Subtitle Structure Geotechnical Report Circle Interchange Reconstruction Retaining Wall 31, F.A.I. Route 90/94 Station 8546+77.99 to Station 8548+87.21		2. Report Date Original: May 10, 2019 Revised: November 13, 2019
4. Route / Section / County FAI 90/94/2015-019R / Cook		3. Report Type <input checked="" type="checkbox"/> SGR <input type="checkbox"/> RGR <input type="checkbox"/> Draft <input checked="" type="checkbox"/> Final <input checked="" type="checkbox"/> Revised
6. PTB / Item No. 163/001		7. Existing Structure Number(s) Not available
9. Prepared by Wang Engineering, Inc. 1145 N Main Street Lombard, IL 60148		8. Proposed Structure Number(s) 016-1820
Contributor(s) Author: Metin W. Seyhun, P.E. QC/QA: Mohammed Kothawala, P.E., D.GE. PIC: Corina T. Farez, P.E., P.G.		Author Phone Number/Email Address (630) 953-9928 Ext 1018 mseyhun@wangeng.com
10. Prepared for AECOM 303 East Wacker Drive Chicago, IL 60601		Structural Engineer Matt Santeford, P.E., S.E. TranSystems Corporation
Contact Phone Number (847) 407-5235		
11. Abstract <p>A new Retaining Wall 31 will be constructed to support the west embankment to the Madison NB Exit Ramp. The 207.6-foot long MSE wall will start at Station 8546+77.99 and end at Station 8548+87.21. The maximum total height near the ramp abutment will be about 22 feet and will have a 3.5-foot tall parapet on the top.</p> <p>Beneath the pavement, the subsurface soils consists of up to 2 to 15 feet of fill materials, up to 5 feet stiff clay crust, up to 43 feet of very soft to medium stiff silty clay, 28 feet of stiff to hard clay to silty clay loam, and 33 feet of very dense silt to silty loam and sand to gravelly sand extending to the bedrock. Sound bedrock was encountered at elevations 480.8 and 482.0 feet. Groundwater was observed at elevations 556.1 and 585.6 during drilling. Groundwater is also present within the granular layers just above the top of bedrock and at peached locations.</p> <p>The proposed MSE wall is feasible with the use of Class I LCCF fill material as well as backfill area for temporary excavation slope of 1:2 (V:H) with Temporary Soil Retention System left in place. The wall will have a maximum factored bearing resistance of 1,500 psf using a geotechnical resistance factor of 0.65. Considering the unloading and reloading effect and the use of LCCF, the settlement is not a concern.</p> <p>It should be noted that there will be large cuts (up to 12 feet) in front of drilled soldier pile retaining wall 30 in order to install MSE wall 31. Therefore, drilled soldier pile retaining wall 30 design must take into account of the effect of these excavations during construction to ensure no excessive deflection of wall 30 occurs, to prevent any negative impact to the adjacent existing parking lot structure.</p>		
12. Path to archived file S:\Netprojects\11000401\Reports\SGRs\Walls\1820 Wall 31\RPT_Wang_NSB_MWS_11000401Wall31RevisedFinal_20191113.doc		

TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
1.1	PROJECT DESCRIPTION	1
1.2	PROPOSED STRUCTURE	2
1.3	EXISTING STRUCTURE.....	2
2.0	SITE CONDITIONS AND GEOLOGICAL SETTING.....	3
2.1	PHYSIOGRAPHY	3
2.2	SURFICIAL COVER	3
2.3	BEDROCK	4
3.0	METHODS OF INVESTIGATION.....	4
3.1	SUBSURFACE INVESTIGATION	4
3.2	VANE SHEAR TESTS	5
3.3	LABORATORY TESTING	5
4.0	RESULTS OF FIELD AND LABORATORY INVESTIGATIONS	6
4.1	SOIL CONDITIONS.....	6
4.2	GROUNDWATER CONDITIONS	7
4.3	SEISMIC DESIGN CONSIDERATIONS.....	8
5.0	ANALYSIS AND RECOMMENDATIONS	8
5.1	RETAINING WALL TYPE EVALUATION.....	8
5.2	MSE WALLS	8
5.2.1	<i>Bearing Resistance and External Stability Analyses</i>	8
5.2.2	<i>Settlement Analyses</i>	10
5.2.3	<i>Global Stability Analyses.....</i>	10
6.0	CONSTRUCTION CONSIDERATIONS	10
6.1	EXCAVATION.....	10
6.2	DEWATERING	10
6.3	FILLING AND BACKFILLING.....	11
6.4	WALL CONSTRUCTION	11
6.5	CONSTRUCTION MONITORING.....	11

7.0	QUALIFICATIONS.....	12
	REFERENCES	13
	EXHIBITS	
	1. <i>Site Location Map</i>	
	2. <i>Site and Regional Geology</i>	
	3. <i>Boring Location Plan</i>	
	4. <i>Subsurface Soil Data Profile</i>	
	APPENDIX A	
	<i>Boring Logs and Rock Core Photographs</i>	
	APPENDIX B	
	<i>Laboratory Test Results</i>	
	APPENDIX C	
	<i>Global Stability Analyses</i>	
	APPENDIX D	
	<i>Type, Size, and Location Plan</i>	
	APPENDIX E	
	<i>In-Progress Cross-Section Drawings</i>	

**STRUCTURE GEOTECHNICAL REPORT
CIRCLE INTERCHANGE RECONSTRUCTION
RETAINING WALL 31 (PROPOSED SN 016-1820)
F.A.I. ROUTE 90/94 (KENNEDY EXPRESSWAY)
IDOT D-91-227-13/PTB 163-001
COOK COUNTY, ILLINOIS
FOR
AECOM**

1.0 INTRODUCTION

This report presents the results of Wang Engineering, Inc. (Wang) subsurface investigation, laboratory testing, geotechnical engineering evaluations and recommendations for a new Mechanically Stabilized Earth (MSE) retaining wall to support the west side embankment to the existing Madison NB Exit Ramp. The new wall is designated as SN 016-1820 (Retaining Wall 31) and will be constructed in connection with the Circle Interchange Reconstruction project in the City of Chicago, Cook County, Illinois. A *Site Location Map* is presented as Exhibit 1.

The purpose of our investigation was to characterize the site soil and groundwater conditions, perform geotechnical engineering analyses, and provide recommendations for the design and construction of the new wall structure.

1.1 Project Description

The Circle Interchange is over 50 years old and has significant congestion and safety problems. The project is aiming to improve safety and mobility as well as upgrade the mainline and interchange facilities. The project will also improve other modes of transportation such as transit, pedestrians and bicyclists within the same corridor.

The Circle Interchange Reconstruction project is along Interstate 90/94 (I-90/94) from south of Roosevelt Road to north of Lake Street, along Interstate 290 (I-290) from Loomis Street to the Circle Interchange; and along Congress Parkway from the Circle Interchange to Canal Street/Old Post Office. The routes typically have three lanes of traffic in each direction with mostly one lane ramp at interchanges. Locally, the north leg is known as the Kennedy Expressway, the south leg as the Dan

Ryan Expressway and the west leg as the Eisenhower Expressway. Within the project area, there are several cross street bridges over I-90/94 and I-290 considered for reconstruction. Along I-90/94, from south to north, the cross street overpasses include Taylor Street, Van Buren Street, Jackson Boulevard, and Adams Street. Along I-290, from west to east, the cross street overpasses include Morgan Street, Peoria Street, and Halsted Street.

The proposed improvements include additional through lanes in each direction on I-90/94. The horizontal alignment and vertical profiles throughout the interchange will be improved. A new two-lane flyover, Ramp NW (Flyover) will be constructed for I-90/94 northbound to I-290 westbound traffic. Cross street bridges, Morgan Street, Harrison Street, Halsted Street, Peoria Street, Taylor Street, Adams Street, Jackson Boulevard, and Van Buren Street will be reconstructed. Various existing ramps will be reconstructed and about fifty new retaining walls will be constructed.

1.2 Proposed Structure

Based on the Type, Size, and Location (TSL) plan received on April 4, 2019 provided by TranSystems Corporation (TranSystems), the proposed Retaining Wall 31 (SN 016-1820) will support the west embankment of the Madison NB Exit Ramp. The 207.6-foot long MSE Wall will start at Station 8546+77.99 and end at Station 8548+87.21 with offset of 20.41 to 27.67 feet left. The maximum total height near the ramp abutment will be 22 feet and will have a 3.5-foot tall parapet on the top. There is a new Soldier Pile and Lagging Wall 30 (SN 016-1819) proposed to retain the east side embankment of Madison Exit Ramp and will be constructed first under Contract 62A76. The TSL plan is included in *Appendix D*.

1.3 Existing Structure

There is an existing Retaining Wall 23 constructed in 1957. The existing wall is cast-in-place concrete retaining wall on metal shell piles and spread footing that measure 178.84 feet from Madison Street southeast wingwall south to Monroe Street. Maximum height from top of wall to bottom of footing measures 18.1 feet. The existing wall is to be removed and replaced with an MSE wall.

2.0 SITE CONDITIONS AND GEOLOGICAL SETTING

The site is located within the City of Chicago at the I-90/94 and I-290 Circle Interchange. On the USGS *Chicago Loop 7.5 Minute Series* map, the wall is located in the NW¹/₄ of Section 16, Tier 39 N, Range 14 E of the Third Principal Meridian.

The following review of published geologic data, with emphasis on factors that might influence the design and construction of the proposed engineering works, is meant to place the project area within a geological framework and confirm the dependability and consistency of the present subsurface investigation results. For the study of the regional geologic framework, Wang considered northeastern Illinois in general and Cook County in particular. Exhibit 2 illustrates the *Site and Regional Geology*.

2.1 Physiography

The wall is situated within the Chicago Lake Plain Physiographic Subsection. The area is characterized by a flat surface that slopes gently toward the lake, largely made of groundmoraine till covered by thin and discontinuous lacustrine silt and clay. The ground elevation along the wall ranges from 585 feet at the south end to 592 feet at the north end.

2.2 Surficial Cover

The project area was shaped during the Wisconsin-age glaciation, and more than 75-foot thick drift covers the bedrock (Leetaru et al. 2004). The glacial cover is made up of clay and silt of the Equality Formation of the Mason Group and diamictons of the Wadsworth and Lemont Formations of the Wedron Group (Hansel and Johnson 1996). The Equality Formation is made up of bedded silt and clay, locally laminated, with lenses and/or thin beds of sand and gravel. The Wadsworth Formation consists of relatively homogenous, massive, gray till with clay to silty clay matrix, with dolostone and shale clasts and occasional lenses of sorted and stratified silt. The Wadsworth Formation is underlain by the pebbly silty clay loam to silty loam diamicton of the Yorkville Member of the Lemont Formation, known informally as the Chicago “hardpan.”

From a geotechnical viewpoint, the Equality Formation is characterized by low strength, medium to high plasticity, and medium to high moisture content, whereas the Wadsworth Formation is characterized by low plasticity, medium to low moisture content, medium to very stiff consistency, poor permeability, and

low compressibility. The Yorkville Member (hardpan) is characterized by low plasticity, high blow counts, and low moisture content (Bauer et al. 1991; Peck and Reed 1954).

2.3 Bedrock

In the project area, the glacial deposits unconformably rest over approximately 350-foot thick Silurian-age dolostone (Leetaru et al 2004). The top of bedrock may be encountered at about 480 feet elevation or 95 feet below ground surface (bgs) or more. The Silurian dolostone dips gently eastward at a pace of 15 feet per mile. Only inactive faults are known in the area, and the seismic risk is minimal (Leetaru et al. 2004; Willman 1971). There are no records of mining activity in the area, but deep tunnel excavations are known to exist.

Our subsurface investigation results fit into the local geologic context. The borings drilled in the project area revealed the native sediments consist of clay to silty clay diamicton of the Wadsworth Formation resting on top of more competent silty clay loam diamicton (hardpan) of the Lemont Formation, which in turn is underlain by bedrock. Sound dolostone bedrock was sampled at depths of 111.5 and 112.5 feet bgs, corresponding to 480.8 and 482.0 feet elevation, within the predicted range based on published geological data.

3.0 METHODS OF INVESTIGATION

The following sections outline the subsurface and laboratory investigations. All elevations in this report are based on NAVD 1988.

3.1 Subsurface Investigation

Wang drilled three structure borings, designated as 31-RWB-01 through 31-RWB-03 in June 2014. Wang has also referenced two nearby structure borings located at the east side of the wall, designated as 30-RWB-01 and 30-RWB-03 drilled in July 2014. In addition, Wang performed one Shelby tube boring, designated as 30-ST-01 for nearby structure. Wang also performed Boring VST-03 to obtain in-situ vane shear strength of soft clay. The as-drilled boring locations were surveyed by Dynasty Group, Inc. and station and offset information for each boring were provided by AECOM. Boring location data are presented in the *Boring Logs* (Appendix A). The as-drilled boring locations are shown in the *Boring Location Plan* (Exhibit 3).

ATV- and truck-mounted drilling rigs equipped with hollow stem augers, were used to advance and maintain an open borehole to 10 feet depth after that mud rotary was used to the boring termination depth. Soil sampling was performed according to AASHTO T 206, "*Penetration Test and Split Barrel Sampling of Soils.*" The soil was sampled at 2.5-foot intervals to 30 feet bgs and at 5-foot intervals to boring termination depths or bedrock. Soil samples collected from each sampling interval were placed in sealed jars and transported to Wang Geotechnical Laboratory in Lombard, Illinois for further examination and laboratory testing.

Field boring logs, prepared and maintained by a Wang engineer or geologist, include lithological descriptions, visual-manual soil/rock classifications, results of Rimac and pocket penetrometer unconfined compressive strength tests, results of Standard Penetration Tests (SPT) recorded as blows per 6 inches of penetration. The SPT N value, shown on the soil profile, is the sum of the second and third blows per 6 inches. The soils were described and classified according to Illinois Division of Highways (IDH) Textural Classification system. The field logs were finalized by an experienced engineering geologist after verifying the field visual classifications and laboratory test results.

Groundwater observations were made during drilling to a depth of 10 feet before using rotary wash method. Due to safety considerations, boreholes were backfilled with grout immediately upon completion.

3.2 Vane Shear Tests

Wang performed vane shear tests in Boring VST-03. Boring VST-03 is located about 60 feet east of Wall 31. Vane shear tests were performed in undisturbed and remolded conditions using calibrated RocTest vane shear equipment. The sensitivity shown on the boring logs is the ratio of shear strength in undisturbed and remolded conditions. In general, the vane shear values for soft clays were significantly higher than the corresponding values from unconfined compressive strength tests using the RIMAC apparatus. Vane shear test results were used on our engineering analyses.

3.3 Laboratory Testing

The soil samples were tested in the laboratory for moisture content (AASHTO T265). Atterberg limits (AASHTO T 89/T 90) and particle size analyses (AASHTO T 88) tests were performed on selected soil samples representing the main soil layers encountered during the investigation. Field visual descriptions of the soil samples were verified in the laboratory. Laboratory test results are

shown in the *Boring Logs* (Appendix A), in the *Soil Profile* (Exhibit 4), and in the *Laboratory Test Results* (Appendix B).

4.0 RESULTS OF FIELD AND LABORATORY INVESTIGATIONS

Detailed descriptions of the soil conditions encountered during our subsurface investigation are presented in the attached *Boring Logs* (Appendix A) and in the *Soil Profile* (Exhibit 4). Please note that strata contact lines represent approximate boundaries between soil types. The actual transition between soil types in the field may be gradual in horizontal and vertical directions.

4.1 Soil Conditions

Borings drilled on the Madison NB Exit Ramp encountered 3 to 6 inches of asphalt overlying 8 to 18 inches of concrete followed by crushed stone base course. In descending order, the general lithologic succession encountered beneath the pavement structure: 1) man-made ground (fill); 2) stiff silty clay to silty clay loam; 3) very soft to medium stiff clay to silty clay; 4) stiff to very stiff clay to silty clay loam; 5) very dense silt to silty loam and sand to gravelly sand; and 6) strong dolostone.

1) Man-made ground (fill)

Underneath the pavement structure, the borings encountered 2 to 15 feet of fill. Granular fill consists of loose to medium dense, brown gravelly sand to sandy gravel. Cohesive fill includes soft to stiff, brown and gray silty clay loam to clay loam. The granular fill layer has N-values of 4 to 24 blows per foot and moisture content values of 4 to 24%. The cohesive fill layer has unconfined compressive strength (Q_u) values of 0.3 to 1.9 tsf and moisture content values of 19 and 25%.

2) Stiff silty clay to silty clay loam

Beneath the fill, at elevation of 585.8 feet, Boring 30-ST-01 encountered 5-foot thick of stiff, brown to gray silty clay to silty clay loam. This layer has Q_u value of 1.6 tsf and moisture content values of 19 and 27%.

3) Very soft to medium stiff clay to silty clay

At elevations of 574.8 to 586.5 feet (5.5 to 15.5 feet bgs), the borings revealed up to 43 feet of very soft to medium stiff, gray clay to silty clay with Rimac Q_u values of 0.08 to 0.83 tsf and moisture content values of 18 to 30%. This layer is commonly known as the “*Chicago Blue Clay*.”

Laboratory index testing on samples from this layer showed liquid limit (L_L) values of 30 to 34% and plastic limit (P_L) values of 16 to 17%. The UU triaxial test on Shelby tube samples from Boring 30-ST-1 show undrained cohesion of 432 psf. The CU triaxial test on a Shelby tube sample from Boring 30-RWB-03 shows drained cohesion of 340 psf. The UC test on a Shelby tube sample from 30-RWB-03 shows undrained shear strength of 480 psf.

As discussed in Section 3.2, undrained shear strength values from vane shear tests were generally higher than Rimac tests. In-situ undisturbed vane shear strengths obtained in Boring VST-03 between elevations 574 and 542 feet ranged from 370 to 1680 psf.

4) Stiff to very stiff clay to silty clay loam

At elevations of 541.4 to 545.1 feet (37 to 52 feet bgs), the borings encountered up to 28 feet of stiff to hard clay to silty clay loam. The unit has Q_u values of 0.9 to 3.5 tsf and moisture content values of 11 to 27%. Laboratory index testing on samples from this layer showed a liquid limit (L_L) value of 39% and a plastic limit (P_L) value of 18%.

(5) Very dense silt to silty loam and sand to gravelly sand

At elevations of 511.8 and 513.6 feet (82 and 80 feet bgs), Borings 30-RWB-01 and 31-RWB-03 encountered up to 33 feet of very dense silt to silty loam and sand to gravelly sand. This layer has N values of over 50 blows per foot.

(6) Strong dolostone

Borings 30-RWB-01 and 31-RWB-03 encountered strong bedrock at elevations of 482.0 and 480.8 feet or 111.5 and 112.5 feet bgs, respectively. Based on the 2 and 10-foot long rock cores obtained from the borings, the measured RQD values are 21 and 38% corresponding very poor to poor rock quality. *Bedrock core photograph is shown in Appendix A.*

4.2 Groundwater Conditions

Groundwater was observed during drilling at elevations of 556.1 and 585.6 feet (37 and 8 feet bgs) in Borings 30-ST-01 and 31-RWB-03, respectively. Water-bearing silt and gravel layers may also be present at deeper levels. A Piezometer 30-PZ-01 was installed for the nearby structure about 80 feet east of the proposed Retaining Wall 31 on November 21, 2014 and monitored until March 2017. The screen was placed with the top and bottom elevations at 503.7 and 493.7 feet (89.5 to 99.5 feet bgs), respectively within granular layers above bedrock. Piezometer readings show an average water table

elevation of 545.8 feet indicating groundwater under hydrostatic pressure within the granular deposit encountered on top of the bedrock. Within upper granular fill layers, we anticipate perched water may be encountered during times of heavy precipitation.

4.3 Seismic Design Considerations

The retaining wall is located in Seismic Performance Zone (SPZ) 1 and is not required to be designed for seismic forces as per 2012 IDOT *Bridge Manual* (IDOT 2012).

5.0 ANALYSIS AND RECOMMENDATIONS

5.1 Retaining Wall Type Evaluation

Based on TSL, the proposed Retaining Wall 31 (SN 016-1820) will support the approach embankment to the Madison NB Exit Ramp structure. The 208-foot long back-to-back MSE walls will start at Station 8546+77.99 and end at Station 8548+87.21. The maximum total height near the Madison Bridge east abutment will be about 22 feet and will have a 3.5-foot tall parapet on the top.

The following sections present the results of our geotechnical engineering analyses and recommendations for the MSE wall design and construction.

5.2 MSE Walls

The MSE retaining wall base should be established a minimum of 3.5 feet below the finished grade at the front face of the wall for frost protection.

5.2.1 Bearing Resistance and External Stability Analyses

Based on our boring data, the foundation soils at the MSE wall base elevations consist of up to 29 feet of soft to medium stiff clay to silty clay. We estimate, without foundation treatment, the soils will have a nominal bearing resistance of 2,300 psf and a factored bearing resistance of 1,500 psf based on a geotechnical resistance factor of 0.65 (AASHTO 2017).

We have considered reinforcement lengths equal to 70 percent of the total wall height or a minimum of 8 feet. We analyzed several alternatives for the fill material to be used in the reinforcement zone as well as temporary excavation with slope of 1:2 (V:H) backfill area. We understand the temporary excavation slope of 1:2 (V:H) will not be possible along the entire wall alignment due to the Wall 30 and right of way constrains. A temporary soil retention system (TSRS) is proposed to be installed

prior to the excavations for the MSE wall 31. We recommend that the TSRS be left in place after the Wall 31 construction to eliminate lateral earth pressures on the LCCF. The following fill alternatives were considered for the MSE wall and temporary excavation slope.

1. Using regular fill material (unit weight of 125 pcf) for the MSE wall reinforced zone area; and
2. Using IDOT District One Class III Lightweight Cellular Concrete Fill (LCCF) for the MSE wall reinforcement zone and the temporary excavation slope of 1:2 (V:H); and
3. Using IDOT District One Class I LCCF for the MSE wall reinforcement zone and the temporary excavation slope of 1:2 (V:H).

For Option 1, at the highest portion of the wall near Station 8548+87.21, the wall will apply a maximum factored equivalent bearing pressure of 5,900 psf with a regular MSE wall fill material (unit weight is 125 pcf) and which exceeds the factored bearing resistance available, thus Option 1 is not feasible.

In Option 2, to reduce the applied wall pressure, we have considered IDOT District One Special Provisions Class III LCCF with as-cast density ranging from 36 to 44 pcf for the MSE wall zone and the temporary excavation slope of 1:2 (V:H) backfill and TSRS left in place creating no lateral earth pressures on the LCCF. We estimate the wall will apply a maximum equivalent factored bearing pressure of 1,700 psf which exceeds the factored bearing resistance, thus Option 2 is also not feasible.

In Option 3, to further reduce the applied wall pressure, we have considered IDOT District One Special Provisions Class I LCCF with as-cast density ranging from 24 to 32 pcf for the MSE wall zone and the temporary excavation slope of 1:2 (V:H) backfill and TSRS left in place creating no lateral earth pressures on the LCCF. We estimate the wall will apply a maximum equivalent factored bearing pressure of 1,400 psf; thus, the foundation soils will have sufficient bearing resistance to support the wall.

The estimated friction angle between an MSE wall base and underlying cohesive soil is 30°, and the corresponding friction coefficient is 0.58. MSE retaining walls are designed based on a geotechnical sliding resistance factor of 1.0 for soil-on-soil contact (AASHTO 2017).

We recommend Option 3 with 0.7 H reinforcement width and the temporary excavation slope of 1:2 (V:H) with TSRS left in place.

5.2.2 Settlement Analyses

Considering the unloading and reloading effect and the placement of LCCF, the applied service pressure will be less than the existing pressure. Therefore, the settlement is not concern.

5.2.3 Global Stability Analyses

Global stability analysis was performed near Station 8548+75 for both short-term (undrained) and long-term (drained) soil conditions using Class I LCCF for MSE wall and backfill area for temporary excavation. The computer program, SLIDE Version 6.0, was used to calculate the FOS. The minimum required FOS against global instability according to IDOT is 1.5 for both conditions. We estimate the MSE wall section has a short-term FOS of 1.49 (Appendix C-1) and a long-term FOS of 1.87 (Appendix C-2). The abandonment of the temporary soil retention system in place will improve global slope stability by providing additional resistance.

6.0 CONSTRUCTION CONSIDERATIONS

6.1 Excavation

Any required excavations should be performed in accordance with local, state, and federal regulations including current OSHA regulations. The potential effect of ground movements upon nearby structures and utilities should be considered during construction.

At the southern end, it is understood that the drilled soldier retaining wall 30 (SN016-1819) will be constructed prior to Wall 31. This wall will act to eliminate all lateral forces on Wall 31 LCCF. It should be noted that there will be large cuts (up to 12 feet) in front of Wall 30 in order to install Wall 31 MSE wall. Therefore, drilled soldier pile retaining Wall 30 design must take into account of the effect of these deep excavations to ensure no excessive deflection of Wall 30 occurs, to prevent any negative impact to the adjacent existing parking lot structure.

As per TSL plan, the Madison NB Exit Ramp traffic will be detoured during MSE wall construction.

6.2 Dewatering

Based on the results of our investigation and proposed excavation for the wall, perched water is likely to be encountered during construction during times of heavy precipitation which should be removed through conventional sump and pump methods.

6.3 Filling and Backfilling

All fill and backfill materials will be as per IDOT *Standard Specification for Road and Bridge Construction* (IDOT 2016).

6.4 Wall Construction

The wall should be constructed as per IDOT *Standard Specification for Road and Bridge Construction* (IDOT 2016). Class I LCCF should be as per IDOT District One special provision dated June 18, 2018.

6.5 Construction Monitoring

There is no need for special construction monitoring for the retaining wall except normally required by the IDOT *Standard Specification for Road and Bridge Construction* (IDOT 2016).


7.0 QUALIFICATIONS


The analysis and recommendations submitted in this report are based upon the data obtained from the borings drilled at the locations shown on the boring logs and in Exhibit 3. This report does not reflect any variations that may occur between the borings or elsewhere on the site, variations whose nature and extent may not become evident until the course of construction. In the event that any changes in the design and/or location of Retaining Wall 31 (SN016-1820) are planned, we should be timely informed so that our recommendations can be adjusted accordingly.


It has been a pleasure to assist AECOM and the Illinois Department of Transportation on this project. Please call if there are any questions, or if we can be of further service.

Respectfully Submitted,

WANG ENGINEERING, INC.


Metin W. Seyhun, P.E.
Senior Geotechnical Engineer


Nesam S. Balakumaran
Project Geotechnical Engineer





Corina T. Farez, P.E., P.G.
Project Manager


REFERENCES

- AMERICAN ASSOCIATION OF STATE HIGHWAY TRANSPORTATION OFFICIALS (2017) *LRFD Bridge Design Specifications*. United States Department of Transportation, Washington, D.C.
- BAUER, R.A., CURRY, B.B., GRAESE, A.M., VAIDEN, R.C., SU, W.J., and HASEK, M.J., 1991, *Geotechnical Properties of Selected Pleistocene, Silurian, and Ordovician Deposits of Northeastern Illinois*: Environmental Geology 139, Illinois State Geological Survey, 69 p.
- HANSEL, A.K., and JOHNSON, W.H. (1996) *Wedron and Mason Groups: Lithostratigraphic Reclassification of the Wisconsin Episode, Lake Michigan Lobe Area: ISGS Bulletin 104*. Illinois State Geological Survey, Champaign, IL. 116 p.
- LEETARU, H.E., SARGENT, M.L., AND KOLATA, D.R., 2004, *Geologic Atlas of Cook County for Planning Purposes*, ISGS, Champaign, IL
- ILLINOIS DEPARTMENT OF TRANSPORTATION (2015) *Geotechnical Manual*. IDOT Bureau of Materials and Physical Research, Springfield, IL.
- ILLINOIS DEPARTMENT OF TRANSPORTATION (2016) *Standard Specifications for Road and Bridge Construction*. IDOT Division of Highways, Springfield, IL.
- ILLINOIS DEPARTMENT OF TRANSPORTATION (2018) *Lightweigh Cellular Concrete Fill Special Provision*. IDOT District One. dated June 18, 2018
- ILLINOIS DEPARTMENT OF TRANSPORTATION (2012) *Bridge Manual*. IDOT Bureau of Bridges and Structures, Springfield, IL.
- WILLMAN, H.B., 1971, *Summary of the Geology of the Chicago Area*, ISGS Circular C460: Urbana, Illinois State Geological Survey, p. 77.
- PECK, R.B., and REED, W.C., 1954, *Engineering Properties of Chicago Subsoils*: University of Illinois Engineering Experiment Station Bulletin No. 423: Urbana, University of Illinois, 62 p.
- FEDERAL HIGHWAY ADMINISTRATION (1983) *Design and Construction of Stone Columns Vol 1*. US Department of Transportation Report No. FHWA/RD-83/026, McLean, Virginia.


EXHIBITS





RETAINING WALL 31, SN 016-1820
NW 1/4 Sec. 16, T 39N, R 14E of 3rd PM



Cook County




SITE LOCATION MAP: CIRCLE INTERCHANGE RECONSTRUCTION RETAINING WALL 31, SN 016-1820, COOK COUNTY		
SCALE: GRAPHICAL	EXHIBIT 1	DRAWN BY: NSB CHECKED BY: MWS
		1145 N. Main Street Lombard, IL 60148 www.wangeng.com
FOR AECOM		1100-04-01



Modified after Bretz (1926)



REGIONAL GEOLOGY




Wedron Group

- Wadsworth Formation
- Lemont Formation
- Tiskilwa Formation

Modified after Hansel and Johnson (1996)

Legend

- Qls
Glacial lake bottom
(Covered by lacustrine deposits)



Contours interval 25 ft
Modified after Leetaru et al. (2004)

SITE AND REGIONAL GEOLOGY: CIRCLE INTERCHANGE RECONSTRUCTION,
RETAINING WALL 31, SN 016-1820, COOK COUNTY, IL

SCALE: GRAPHIC AL

EXHIBIT 2


DRAWN BY: R. KC
CHECKED BY: C. Marin





1145 N. Main Street
Lombard, IL 60148
www.wangeng.com

FOR AECOM

1100-04-01




Lithology Graphics




Site Map Scale 1 inch equals 165 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 1.5x

Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148

Soil Profile Retaining Wall 31 (SN 016-1820)



Jane Byrne Interchange
 Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4

Bench Mark: Set "X" on northwest corner of handhole along east edge of SB I-90/94 20 feet north of Madison Street. Elev. 596.13.


Existing Structure: Existing Retaining Wall 23. Constructed in 1957 under F.A.I. Route 90/94, Section 0202.6-1P. Cast-in-place concrete retaining wall on metal shell piles and spread footing that measures 178'-10 1/8" from Madison Street SE Wingwall south to Monroe Street. Maximum height from top of wall to bottom of footing measures 18'-1". The existing retaining wall is to be removed and replaced.

Traffic on Madison NB Exit Ramp will be detoured during construction.


No Salvage.

Notes:

- 1.) Wall offsets are measured from the $\text{\textcircled{M}}$ of Madison NB Exit Ramp to the front face of the precast panels.
- 2.) F.F. denotes Front Face.
- 3.) B.F. denotes Back Face.
- 4.) Proposed drainage information shown is conceptual and will be determined during final design.



LEGEND:



HIGHWAY CLASSIFICATION

Madison NB Exit Ramp
 Functional Class: Interstate
 ADT: 5,200 (2012); 6,000 (2040)
 ADTT: 94 (2012); 0 (2040)
 DHV: ____ (2040)
 Design Speed: 30 m.p.h.
 Posted Speed: 30 m.p.h.
 One-Way Traffic
 Directional Distribution: 100%

NB C-D Road
 Functional Class: Interstate
 ADT: NA (2012); 17,000 (2040)
 ADTT: NA (2012); 440 (2040)
 DHV: 1,680 (2040)
 Design Speed: 30 m.p.h.
 Posted Speed: 30 m.p.h.
 One-Way Traffic
 Directional Distribution: 100%

DESIGN SPECIFICATIONS

2017 AASHTO LRFD Bridge Design Specifications 8th Edition


DESIGN STRESSES

FIELD UNITS

$f'_c = 3,500$ psi
 $f_y = 60,000$ psi (Reinforcement)

PRECAST UNITS


$f'_c = 4,500$ psi




* For elevations, see Table 1 on Sheet 2 of 2.

ELEVATION

(Looking East at F.F. of Wall)



PROFILE GRADE
 (NB C-D Road)



GENERAL PLAN
RETAINING WALL 31 ALONG MADISON NB EXIT RAMP
F.A.I. RTE. 90/94 (KENNEDY EXPRESSWAY)
SECTION 2015-019R
COOK COUNTY
STATION 8546+76.97 TO STATION 8548+88.79
STRUCTURE NO. 016-1820

BORING LOCATION PLAN: RETAINING WALL 31 ALONG MADISON NB EXIT RAMP, SN 016-1820, COOK COUNTY, IL

SCALE: GRAPHICAL	EXHIBIT 3	DRAWN BY: RKC
FOR AECOM		CHECKED BY: N. Balakumaran
Wang Engineering		1145 N. Main Street Lombard, IL 60148 www.wangeng.com
1100-04-01		



USER NAME = jnpilotte	DESIGNED - JNP	REVISED -
PLOT SCALE = 32.0000' / in.	CHECKED - WJC/MDS	REVISED -
PLOT DATE = 4/12/2019	DRAWN - JNP	REVISED -
	CHECKED - WJC/MDS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

F.A.I. RTE. 90/94	SECTION 2015-019R	COUNTY COOK	TOTAL SHEETS 2	SHEET NO. 1
CONTRACT NO. 62A76				ILLINOIS FED. AID PROJECT

APPENDIX A



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 30-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.54 ft
 North: 1899863.46 ft
 East: 1171695.35 ft
 Station: 8545+20.14
 Offset: 45.6914 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	593.24	1/2-inch thick, ASPHALT --PAVEMENT--															
	592.5	8-inch thick, CONCRETE --PAVEMENT--															
	592.0	6-inch thick, loose black SANDY LOAM, little gravel --FILL--			1	4 3 5	NP	12						9	0 0 0	0.16 B	26
		Loose, brownish red SANDY GRAVEL, trace brick fragments --FILL--			2	3 3 2	NP	14				25		10	0 0 0	0.16 B	25
	588.0	Loose, black SANDY LOAM, little gravel --FILL--			3	4 3 3	NP	17						11	0 0 0	0.16 B	25
	585.5	Loose to medium dense, brown GRAVELLY SAND, trace brick fragments --FILL--			4	3 4 3	NP	15				30		12	0 0 2	0.33 B	24
					5	15 9 7	NP	22									
	580.5	Very soft to soft, gray CLAY to SILTY CLAY, trace gravel			6	0 1 0	0.33 B	25				35		13	0 1 2	< 0.25 P	31
					7	0 0 0	0.16 B	25									
					8	0 0 0	0.16 B	27				40		14	0 0 2	0.08 B	27

GENERAL NOTES

Begin Drilling **07-24-2014** Complete Drilling **07-27-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **5.50 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 30-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.54 ft
 North: 1899863.46 ft
 East: 1171695.35 ft
 Station: 8545+20.14
 Offset: 45.6914 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	536.8	Very stiff, gray SILTY CLAY to SILTY CLAY LOAM, trace to some gravel	45	X	15	0 0 0	0.25 B	26		536.8		65	X	19	5 9 12	3.50 N/6	25
			50	X	16	0 0 1	0.33 B	25				70	X	20	7 12 15	2.87 B	19
			55	X	17	2 5 6	0.25 B	23				75	X	21	4 5 7	1.39 B	25
			60	X	18	4 7 10	1.72 B	19				80	X	22	11 11 10	0.16 B	27

GENERAL NOTES

Begin Drilling **07-24-2014** Complete Drilling **07-27-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **5.50 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 30-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.54 ft
 North: 1899863.46 ft
 East: 1171695.35 ft
 Station: 8545+20.14
 Offset: 45.6914 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	511.8	Very dense, gray SILT, trace gravel															
			85	23	23	30 45 25/3	NP	19				105	27	27	50/6	NP	9
	506.8	Gray fine SAND; moist															
	504.5	Very dense, gray SILTY LOAM, trace gravel	90	24	24	20 28 36	NP	17				110	28	28	18 24 35	NP	10
			95	25	25	52/6	NP	12		482.0	Strong, light gray, poor rock mass quality, bedded slightly weathered DOLOSTONE, with shale partings, up to 18-inch beds, <2-inch spaced joints, horizontal joints with none or less than <0.2-inch infilling, hard joint wall, with stylonitic surfaces, and moderately vuggy porosity. Run 1 - RECOVERY = 100% RQD = 21% Boring terminated at 113.50 ft	115	1				
			100	26	26	36 50/5	NP	10				120					


GENERAL NOTES

WATER LEVEL DATA


Begin Drilling **07-24-2014** Complete Drilling **07-27-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring backfilled upon completion**

While Drilling ∇ **5.50 ft**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



Boring 30-RWB-01:
 Run #1, 111.5' to 113.5', RECOVERY = 100% , RQD = 21%

BEDROCK CORE: CIRCLE INTERCHANGE RECONSTRUCTION RETAINING WALL 30, SN 016-1819, COOK COUNTY		
SCALE : GRAPHIC	30-RWB-01	DRAWN BY: A. HAPPEL CHECKED BY: C. Marin
		1145 N. Main Street Lombard, IL 60148 www.wangeng.com
FOR AECOM		1100-04-01



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 30-RWB-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.36 ft
 North: 1900001.45 ft
 East: 1171691.10 ft
 Station: 8546+56.85
 Offset: 31.0382 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	593.13	13-inch thick, ASPHALT															
		21-inch thick, CONCRETE and BRICK															
	591.4	Loose to very dense, brown and gray LOAM to SANDY LOAM, little gravel and brick fragments --FILL--			1	2 3 5	NP	16						9	1 2 2	0.25 B	22
			5		2	5 19 5	NP	19				25		10	0 2 4	0.33 B	24
					3	5 3	NP	16						11	3 2 3	0.41 B	26
	586.1	Medium dense, gray SANDY GRAVEL --FILL--			4	5 6 5	NP							12	2 2 2	0.49 B	25
			10														
	582.9	Stiff, gray and brown, SILTY CLAY, trace gravel			5	2 3 4	1.72 B	24									
					6	1 2 2	0.49 B	24						13	0 2 3	0.33 B	26
	580.4	Very soft to soft, gray CLAY to SILTY CLAY, trace gravel			7	0 0 2	0.41 B	21									
					8	0 0 1	0.41 B	26						14	2 3 2	0.41 B	25
			15														
			20														

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **07-24-2014** Complete Drilling **07-27-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **A&K** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 30-RWB-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.36 ft
 North: 1900001.45 ft
 East: 1171691.10 ft
 Station: 8546+56.85
 Offset: 31.0382 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
			45		15	3 3 4	0.49 B	25		528.4		65		19	5 11 18	2.87 B	19
											Boring terminated at 65.00 ft						
			50		16	3 4 4	0.49 B	25				70					
	541.6	Very stiff, gray SILTY CLAY, trace gravel															
			55		17	7 10 13	2.79 B	21				75					
			60		18	6 10 13	2.95 B	17				80					

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **07-24-2014** Complete Drilling **07-27-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **A&K** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 N. Main Street
 Lombard/IL/60148
 Telephone: 6309539928
 Fax: 6309539938

BORING LOG 30-RWB-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 16, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 591.35 ft
 North: 1900153.32 ft
 East: 1171655.49 ft
 Station: 8548+07.17
 Offset: 04.31 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	
	591.13	13-inch thick ASPHALT --PAVEMENT--																
	590.3	9-inch thick CONCRETE --PAVEMENT--																
		Loose to medium dense, black, brown, and white SANDY GRAVEL, trace brick fragments --FILL--			1	5 6 5	NP	6										
			5		2	4 4 3	NP	9				25		3	P U S H	0.25 P	18	
					3	6 3 2	NP	12										
	583.3	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			4	1 1 3	0.98 B	22						4	P U S H	< 0.25 P	24	
			10		5	1 1 1	0.41	24										
		--L _L (%)=32, P _L (%)=17-- --%Gravel=3.2-- --%Sand=19.5-- --%Silt=49.2-- --%Clay=28.1-- --A-6 (10)--			1			25						5	P U S H	< 0.25 P	26	
			15											6	P U S H	< 0.25 P	27	
			20		2			23										

GENERAL NOTES				WATER LEVEL DATA			
Begin Drilling	06-25-2014	Complete Drilling	06-25-2014	While Drilling	groundwater not observed		
Drilling Contractor	Wang Testing Services	Drill Rig		At Completion of Drilling	mud in the borehole		
Driller	R&J	Logger	S. Woods	Time After Drilling	NA		
Drilling Method	2.25" IDA HSA to 10' mud rotary thereafter, boring backfilled upon completion			Depth to Water	NA		
				The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.			

WANGENGINC 11000401.GPJ WANGENG.GDT 11/12/19



wangeng@wangeng.com
 1145 N. Main Street
 Lombard/IL/60148
 Telephone: 6309539928
 Fax: 6309539938

BORING LOG 30-RWB-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 16, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 591.35 ft
 North: 1900153.32 ft
 East: 1171655.49 ft
 Station: 8548+07.17
 Offset: 04.31 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	544.3	Stiff to hard, gray SILTY CLAY to SILTY CLAY LOAM, trace to some gravel	45	Vertical lines	7	P C S H	< 0.25 P	26		526.3	Boring terminated at 65.00 ft	65	Vertical lines	8	5 10 16	4.18 B	20
	50		P C S H	1.00 P	21		70										
	55		5 6 10	2.67 N/6	22		75										
	60		4 5 6	1.56 B	20		80										

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **06-25-2014** Complete Drilling **06-25-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" IDA HSA to 10' mud rotary thereafter, boring backfilled upon completion**

While Drilling **groundwater not observed**
 At Completion of Drilling **▼ mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **▼ NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 11/12/19



BORING LOG 30-ST-01

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.58 ft
 North: 1900053.37 ft
 East: 1171690.05 ft
 Station: 8547+07.45
 Offset: 28.0086 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--UU test-- --Shear strength (Cu) = 432 psf--			9	PUSH	< 0.25 P	26									
			45		10	PUSH	0.50 P	24									
					11	PUSH	0.25 P	25									
	545.1	Stiff, gray SILTY CLAY, trace gravel			12	PUSH	0.50 P	16									
		--UC test-- --Shear strength (Cu) = 560 psf--	50														
		--UC test-- --Shear strength (Cu) = 1790 psf--			13	PUSH	1.25 P	22									
			55														
	536.6	Boring terminated at 57.00 ft			7	468	1.89 B	22									
			60														

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-22-2014** Complete Drilling **10-22-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 15', mud rotary thereafter, boring backfilled upon completion**

While Drilling ∇ **8.00 ft**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 31-RWB-01

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Jane Byrne Interchange**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 580.25 ft
 North: 1899899.70 ft
 East: 1171625.80 ft
 Station: 8545+50.88
 Offset: 26.4632 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	579.8	6-inch thick, ASPHALT --PAVEMENT--															
		18-inch thick, CONCRETE --PAVEMENT--															
	578.3	Dense, gray and white CRUSHED STONE --BASE COURSE--		X	1	9 19 13	NP	3					X	9	1 1 1	0.16 B	22
	576.9	Stiff, brown and gray SILTY CLAY LOAM, trace gravel --FILL--		X	2	2 1 2	1.00 P	19				25	X	10	1 1 2	0.25 B	26
	574.8	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel		X	3	1 1 2	0.57 B	26					X	11	1 2 3	0.41 B	26
				X	4	1 2 3	0.25 B	32					X	12	1 3 2	0.49 B	25
				X	5	0 0 1	0.25 B	26					X	13	2 2 3	0.49 B	26
				X	6	0 2 1	0.25 B	26					X	14	3 4 5	1.64 B	24
				X	7	1 1 2	0.16 B	26		543.5	Stiff to very stiff, gray SILTY CLAY to SILTY CLAY LOAM, trace gravel						
				X	8	1 1 2	0.16 B	25					X	14	3 4 5	1.64 B	24

GENERAL NOTES

Begin Drilling **06-25-2014** Complete Drilling **06-26-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **N&K** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 31-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 580.25 ft
 North: 1899899.70 ft
 East: 1171625.80 ft
 Station: 8545+50.88
 Offset: 26.4632 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	518.5									518.5	Very stiff, gray SILTY CLAY, trace gravel						
			45	X	15	4 6 9	2.71 B	18				65	X	19	8 10 12	2.46 B	22
										515.3	Boring terminated at 65.00 ft						
			50	X	16	4 4 7	1.72 B	17				70					
	528.5	Stiff to very stiff, gray CLAY, trace gravel --L _L (%)=39, P _L (%)=18-- --%Gravel=3.1-- --%Sand=5.7-- --%Silt=48.1-- --%Clay=43.0-- --A-6 (19)--															
			55	X	17	5 7 9	3.36 B	24				75					
			60	X	18	7 8 9	1.00 P	28				80					

GENERAL NOTES

Begin Drilling **06-25-2014** Complete Drilling **06-26-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **N&K** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 31-RWB-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 586.94 ft
 North: 1900047.77 ft
 East: 1171641.00 ft
 Station: 8547+00.89
 Offset: 20.9256 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	586.4	6-inch thick ASPHALT --PAVEMENT--															
		18-inch thick CONCRETE --PAVEMENT--															
	584.9	Medium dense, gray and white CRUSHED STONE --BASE COURSE--			1	12 14 7	NP							9	1 1 1	0.25 B	27
	583.4	Stiff, brown and gray SILTY CLAY LOAM, trace gravel --FILL--			2	2 2 3	1.89 B	24				25		10	1 2 1	0.50 N/6	
	581.4	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			3	1 2 1	0.66 B	26						11	2 1 2	0.33 B	26
					4	0 2 1	0.08 B	27						12	1 2 3	0.33 B	25
					5	1 1 1	0.16 B	28									
					6	0 0 1	0.16 B	27						13	2 2 3	0.83 N/6	
					7	1 1 2	0.16 B	20									
					8	1 2 1	0.33 B	26						14	1 2 2	0.25 P	30

GENERAL NOTES

Begin Drilling **06-24-2014** Complete Drilling **06-24-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **N&K** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 31-RWB-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 586.94 ft
 North: 1900047.77 ft
 East: 1171641.00 ft
 Station: 8547+00.89
 Offset: 20.9256 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	545.2																
		Medium stiff to very stiff, gray SILTY CLAY, trace gravel															
			45		15	3 3 3	1.07 B	22				65		19	4 5 7	1.64 B	26
										521.9	Boring terminated at 65.00 ft						
			50		16	4 6 9	1.80 B	22									
			55		17	4 6 10	0.90 B	16									
			60		18	10 8 10	3.28 B	16									

GENERAL NOTES

Begin Drilling **06-24-2014** Complete Drilling **06-24-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig ..
 Driller **N&K** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 N. Main Street
 Lombard/IL/60148
 Telephone: 6309539928
 Fax: 6309539938

BORING LOG 31-RWB-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 16, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.12 ft
 North: 1900194.50 ft
 East: 1171641.58 ft
 Station: 8548+48.97
 Offset: 16.22 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	551.4																
		Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel	45		15	1 2 3	0.74 B	24				65		19	4 8 12	1.50 P	21
			50		16	3 2 4	< 0.25 P	30				70		20	5 8 10	2.21 B	26
	541.4																
		Stiff to very stiff, gray SILTY CLAY to SILTY CLAY LOAM, trace gravel	55		17	2 5 7	1.72 B	23				75		21	1 4 5	1.39 B	28
			60		18	4 6 8	1.50 P	22				80		22	7 17 35	2.46 B	11
										513.6	Very dense, gray SILTY LOAM,						

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **06-24-2014** Complete Drilling **06-24-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig

Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling ∇ **5.50 ft**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 11/12/19



wangeng@wangeng.com
 1145 N. Main Street
 Lombard/IL/60148
 Telephone: 6309539928
 Fax: 6309539938

BORING LOG 31-RWB-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 16, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.12 ft
 North: 1900194.50 ft
 East: 1171641.58 ft
 Station: 8548+48.97
 Offset: 16.22 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	
		trace gravel																
	506.4	Very dense, gray, fine to medium SAND, trace gravel	85	X	23	37 50/3	NP	19		491.4	Very dense, gray SILTY LOAM to SILT	105	X	27	28 28 45	NP	24	
			90	X	24	20 25 25	NP	10		486.4	Very dense, gray SILT to fine SAND	110	X	28	27 39 34	NP	17	
			95	X	25	16 25 28	NP	19		480.6	Strong, light gray, poor rock mass quality, bedded slightly weathered DOLOSTONE, with shale partings, up to 20-inch beds, 3-inch spaced joints, horizontal and vertical joints with 115 none or less than <0.2-inch infilling, hard joint wall, with stylolitic surfaces, and moderately vuggy porosity. Run 1 - RECOVERY = 100% RQD = 38%							
			100	X	26	29 34 39	NP	19				120						

GENERAL NOTES

Begin Drilling **06-24-2014** Complete Drilling **06-24-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **5.50 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 11/12/19



wangeng@wangeng.com
 1145 N. Main Street
 Lombard/IL/60148
 Telephone: 6309539928
 Fax: 6309539938

BORING LOG 31-RWB-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Jane Byrne Interchange**
 Location **Section 16, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.12 ft
 North: 1900194.50 ft
 East: 1171641.58 ft
 Station: 8548+48.97
 Offset: 16.22 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	470.6	Boring terminated at 122.50 ft															
			125														
			130														
			135														
			140														


GENERAL NOTES

Begin Drilling **06-24-2014** Complete Drilling **06-24-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**


WATER LEVEL DATA

While Drilling ▽ **5.50 ft**
 At Completion of Drilling ▽ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ▽ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



Borin 31-RWB-03:
Run #1, 112.5' to 122.5', RECOVERY = 100% , RQD = 38%

BEDROCK CORE: CIRCLE INTERCHANGE RECONSTRUCTION CHICAGO, IL		
SCALE : GRAPHIC	31-RWB-03	DRAWN BY: A. HAPPEL CHECKED BY: C. Marin
		1145 N. Main Street Lombard, IL 60148 www.wangeng.com
FOR AECOM		1100-04-01



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG VST-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.21 ft
 North: 1899985.05 ft
 East: 1171693.33 ft
 Station: 8415+53.90
 Offset: 182.276 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)		
	592.9	ASPHALT --PAVEMENT-- Medium dense, brown gravelly coarse SAND --FILL--	5		1	5 7 7	NP	6			--S _{u undis} = 425.9 psf-- --S _{u remold} = 371.3 psf-- --Sensitivity = 1.1-- --In-Situ Vane Shear, 22.0 feet-- --S _{u undis} = 371.3 psf-- --S _{u remold} = 305.8 psf-- --Sensitivity = 1.2-- --In-Situ Vane Shear, 24.5 feet-- --S _{u undis} = 382.2 psf-- --S _{u remold} = 316.7 psf-- --Sensitivity = 1.2--	25		2					
	586.5	Medium stiff, brown and gray SILTY CLAY LOAM	10		2	3 2 2	0.75 P	26			--In-Situ Vane Shear, 27.0 feet-- --S _{u undis} = 393.1 psf-- --S _{u remold} = 338.5 psf-- --Sensitivity = 1.2-- --In-Situ Vane Shear, 29.5 feet-- --S _{u undis} = 622.5 psf-- --S _{u remold} = 371.3 psf-- --Sensitivity = 1.7-- --In-Situ Vane Shear, 32.0 feet-- --S _{u undis} = 535.1 psf-- --S _{u remold} = 327.6 psf-- --Sensitivity = 1.6--	30		3					
	580.2	Soft, gray SILTY CLAY	15		3	3 2 2	NR				--In-Situ Vane Shear, 34.5 feet-- --S _{u undis} = 535.1 psf-- --S _{u remold} = 393.1 psf-- --Sensitivity = 1.4-- --In-Situ Vane Shear, 37.0 feet-- --S _{u undis} = 655.2 psf-- --S _{u remold} = 404.1 psf-- --Sensitivity = 1.6--	35		4					
	575.0	--In-Situ Vane Shear, 19.5 feet--	20		4	1 1 1	0.25 P	23			--In-Situ Vane Shear, 39.5 feet--	40		1					

GENERAL NOTES

Begin Drilling **12-02-2015** Complete Drilling **12-02-2015**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **F. Bozga** Checked by **A. Kurnia**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 4/26/19



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG VST-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Jane Byrne Interchange**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 593.21 ft
 North: 1899985.05 ft
 East: 1171693.33 ft
 Station: 8415+53.90
 Offset: 182.276 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--S _{u undis} = 622.5 psf-- --S _{u remold} = 382.2 psf-- --Sensitivity = 1.6--				VS											
		--In-Situ Vane Shear, 42.0 feet-- --S _{u undis} = 851.8 psf-- --S _{u remold} = 458.7 psf-- --Sensitivity = 1.9--	10		10	VS											
		--In-Situ Vane Shear, 44.5 feet-- --S _{u undis} = 928.3 psf-- --S _{u remold} = 600.6 psf-- --Sensitivity = 1.5--	45		11	VS											
		--In-Situ Vane Shear, 47.0 feet-- --S _{u undis} = 1266.8 psf-- --S _{u remold} = 633.4 psf-- --Sensitivity = 2.0--			12	VS											
			50														
	541.7	--In-Situ Vane Shear, 51.0 feet-- --S _{u undis} = 1681.8 psf-- --S _{u remold} = 1266.8 psf-- --Sensitivity = 1.3--			13	VS											
		Boring terminated at 51.50 ft															
			55														
			60														

GENERAL NOTES


Begin Drilling **12-02-2015** Complete Drilling **12-02-2015**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **F. Bozga** Checked by **A. Kurnia**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

APPENDIX B



COBBLES	GRAVEL	SAND		SILT AND CLAY
		coarse	fine	

Specimen Identification	IDH Classification	LL	PL	PI	Cc	Cu
● 30-RWB-03#1 13.5 ft	Silty Clay Loam	32	17	15		
■ 30-RWB-03#4 28.5 ft	Silty Clay	34	17	17		
▲ 31-RWB-01#17 53.5 ft	Clay	39	18	21		
★ 31-RWB-03#12 28.5 ft	Silty Clay	30	16	14		

Specimen Identification	D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay
● 30-RWB-03#1 13.5 ft	9.5	0.018	0.002		3.2	19.5	49.2	28.1
■ 30-RWB-03#4 28.5 ft	9.5	0.012	0.002		5.1	16.3	48.1	30.5
▲ 31-RWB-01#17 53.5 ft	9.5	0.005			3.1	5.7	48.1	43.0
★ 31-RWB-03#12 28.5 ft	9.5	0.013	0.002		4.5	13.5	53.2	28.8



Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

GRAIN SIZE DISTRIBUTION

Project: Jane Byrne Interchange
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01

WEI GRAIN SIZE IDH 11000401.GPJ US_LAB.GDT 4/16/19

UNCONFINED COMPRESSIVE STRENGTH of COHESIVE SOIL
(AASHTO T 208 / ASTM D 2166)

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-RWB-03, ST#5 (33.5-35.0ft)
Type/Condition: ST/Undisturbed
Liquid Limit (%): NA
Plastic Limit (%): NA


Analyst name: A. Mohammed
Date received: 6/25/2014
Test date: 11/15/2014
Sample description: Gray Silty Clay

Sand(%): NA
Silt(%): NA
Clay(%): NA

Average initial height $h_0 = 6.04$ in
Average initial diameter $d_0 = 2.85$ in
Height to diameter ratio = 2.12
Mass of wet sample = 1285.00 g
Mass of dry sample and tare = 1040.60 g
Mass of tare = 14.03 g
Specific gravity = 2.76 (estimated)

Initial water content $w = 25.17\%$ (specimen)
Initial unit weight $g = 127.43$ pcf
Initial dry unit weight $g_d = 101.80$ pcf
Initial void ratio $e_0 = 0.69$
Initial degree of saturation $S_r = 100\%$
Average Rate of Strain = 1%/min
Unconfined compressive strength $q_u = 0.48$ tsf
Shear Strength = 0.24 tsf


Displacement (in)	Force (lbs)	Strain (%)	Stress (tsf)
Δh	F	e	s
0.00	0.00	0.00	0.00
0.03	4.15	0.50	0.05
0.06	8.30	0.99	0.09
0.09	11.41	1.49	0.13
0.12	16.59	1.99	0.18
0.15	20.74	2.48	0.23
0.18	24.89	2.98	0.27
0.21	26.96	3.48	0.29
0.24	30.07	3.97	0.33
0.27	32.15	4.47	0.35
0.30	33.18	4.97	0.36
0.35	35.26	5.79	0.38
0.40	39.41	6.62	0.42
0.45	41.48	7.45	0.43
0.50	43.55	8.28	0.45
0.55	45.63	9.10	0.47
0.60	46.67	9.93	0.48
0.65	46.67	10.76	0.47
0.70	47.70	11.59	0.48
0.80	47.70	13.24	0.47
0.90	48.74	14.90	0.47



NOTES:

Prepared by: *[Signature]* Date: 11/17/14
Checked by: *[Signature]* Date: 11/17/14

Unconfined Axial Stress v. Axial Strain
30-RWB-03, ST#5 (33.5-35.0ft)



UNCONFINED COMPRESSIVE STRENGTH of COHESIVE SOIL
(AASHTO T 208 / ASTM D 2166)

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-ST-01, ST#12 (49.0-51.0ft)
Type/Condition: ST/Undisturbed
Liquid Limit (%): NA
Plastic Limit (%): NA


Analyst name: S. Woods
Date received: 10/22/2014
Test date: 11/17/2014
Sample description: Gray Silty Clay

Sand(%): NA
Silt(%): NA
Clay(%): NA

Average initial height $h_0 = 6.04$ in
Average initial diameter $d_0 = 2.85$ in
Height to diameter ratio = 2.12
Mass of wet sample = 1272.10 g
Mass of dry sample and tare = 1190.70 g
Mass of tare = 187.80 g
Specific gravity = 2.76 (estimated)

Initial water content $w = 26.84\%$ (specimen)
Initial unit weight $\gamma = 125.48$ pcf
Initial dry unit weight $\gamma_d = 98.93$ pcf
Initial void ratio $e_0 = 0.74$
Initial degree of saturation $S_r = 100\%$
Average Rate of Strain = 1%/min
Unconfined compressive strength $q_u = 0.56$ tsf
Shear Strength = 0.28 tsf


Displacement (in)	Force (lbs)	Strain (%)	Stress (tsf)
Δh	F	e	s
0.00	0.00	0.00	0.00
0.03	12.44	0.50	0.14
0.06	20.74	0.99	0.23
0.09	26.96	1.49	0.30
0.12	29.04	1.99	0.32
0.15	33.18	2.48	0.36
0.18	37.33	2.98	0.41
0.21	39.41	3.47	0.43
0.24	41.48	3.97	0.45
0.27	43.55	4.47	0.47
0.30	45.63	4.96	0.49
0.35	47.70	5.79	0.51
0.40	49.78	6.62	0.52
0.45	49.78	7.45	0.52
0.50	51.85	8.27	0.54
0.55	53.92	9.10	0.55
0.60	53.92	9.93	0.55
0.65	53.92	10.76	0.54
0.70	56.00	11.58	0.56
0.80	56.00	13.24	0.55
0.90	56.00	14.89	0.54



NOTES:

Prepared by: *[Signature]* Date: 11/19/14
Checked by: *[Signature]* Date: 11/19/14

Unconfined Axial Stress v. Axial Strain
30-ST-01,ST#12 (49.0-51.0ft)



UNCONFINED COMPRESSIVE STRENGTH of COHESIVE SOIL
(AASHTO T 208 / ASTM D 2166)

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-ST-01, ST#13 (52.0-54.0ft)
Type/Condition: ST/Undisturbed
Liquid Limit (%): NA
Plastic Limit (%): NA

Analyst name: S. Woods
Date received: 10/22/2014
Test date: 11/17/2014
Sample description: Gray Silty Clay

Average initial height $h_0 = 6.03$ in
Average initial diameter $d_0 = 2.85$ in
Height to diameter ratio = 2.11
Mass of wet sample = 1331.10 g
Mass of dry sample and tare = 1200.00 g
Mass of tare = 72.52 g
Specific gravity = 2.76 (estimated)

Sand(%): NA
Silt(%): NA
Clay(%): NA
Initial water content $w = 18.06\%$ (specimen)
Initial unit weight $g = 131.35$ pcf
Initial dry unit weight $g_d = 111.26$ pcf
Initial void ratio $e_0 = 0.55$
Initial degree of saturation $S_r = 91\%$
Average Rate of Strain = 1%/min
Unconfined compressive strength $q_u = 1.79$ tsf
Shear Strength = 0.89 tsf


Displacement (in)	Force (lbs)	Strain (%)	Stress (tsf)
Δh	F	e	s
0.00	0.00	0.00	0.00
0.03	24.89	0.50	0.28
0.06	39.41	0.99	0.44
0.09	56.00	1.49	0.62
0.12	68.44	1.99	0.75
0.15	78.81	2.49	0.86
0.18	89.18	2.98	0.97
0.21	97.48	3.48	1.06
0.24	105.77	3.98	1.14
0.27	114.07	4.47	1.23
0.30	120.29	4.97	1.29
0.35	130.66	5.80	1.39
0.40	138.96	6.63	1.46
0.45	149.33	7.46	1.56
0.50	155.55	8.29	1.61
0.55	161.77	9.11	1.65
0.60	167.99	9.94	1.70
0.65	167.99	10.77	1.69
0.70	174.22	11.60	1.73
0.80	178.36	13.26	1.74
0.90	186.66	14.91	1.79



NOTES:

Prepared by: Shifdd Date: 11/19/14
Checked by: Jeny Date: 11/19/14

Unconfined Axial Stress v. Axial Strain
30-ST-01, ST#13 (52.0-54.0ft)



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-ST-01, ST# 11 (46.0-48.0ft)
Type/Condition: ST/Undisturbed

Analyst name: M. de los Reyes
Date received: 10/22/2014
Test date: 11/24/2014
Sample description: Gray SILTY CLAY


Initial height $h_0 = 5.76$ in
Initial diameter $d_0 = 2.87$ in
Initial area $A_0 = 6.46$ in²
Mass of wet sample and tare $M_i = 1223.54$ g
Mass of dry sample and tare $M_d = 977.10$ g
Mass of tare $M_t = 13.34$ g
Mass of sample $M_s = 1210.20$ g
Estimated specific gravity $G_s = 2.78$
Cell confining pressure $\sigma_3 = 10.0$ psi
Rate of strain = 1 %/min
Proving Ring Factor = 1.000
Height to diameter ratio = 2.01

Initial water content $w = 25.57\%$
Initial unit weight $\gamma_w = 124.02$ pcf
Initial dry unit weight $\gamma_d = 98.77$ pcf
Initial void ratio $e_0 = 0.756$
Initial degree of saturation $S_r = 94\%$

Liquid Limit (%): NA
Plastic Limit (%): NA
Sand(%): NA
Silt(%): NA
Clay(%): NA


Deviator stress at failure $D\sigma_f = 0.85$ tsf
Major principal stress at failure $\sigma_1 = 1.57$ tsf

Axial Displacement (in) Δh	Axial Force (lbs) F	Axial Strain (%) e	Deviator Stress (psi) $\sigma_1 - \sigma_3$
0.00	0.00	0.00	0.00
0.01	5.20	0.11	0.80
0.01	9.49	0.22	1.47
0.02	12.49	0.33	1.93
0.03	15.00	0.44	2.31
0.03	17.23	0.56	2.65
0.04	18.79	0.66	2.89
0.04	20.26	0.75	3.11
0.05	22.10	0.88	3.39
0.06	23.88	1.00	3.66
0.06	24.61	1.06	3.77
0.09	31.25	1.63	4.76
0.12	36.15	2.11	5.48
0.15	41.35	2.69	6.23
0.18	45.70	3.20	6.85
0.22	50.11	3.76	7.47
0.25	54.36	4.32	8.05
0.28	57.67	4.80	8.50
0.31	61.59	5.36	9.02
0.34	64.74	5.88	9.43
0.37	68.08	6.43	9.86
0.40	71.14	6.97	10.25
0.43	74.01	7.51	10.60
0.46	76.68	8.03	10.92
0.49	79.16	8.55	11.21
0.52	81.76	9.12	11.50
0.56	84.12	9.64	11.77
0.58	85.92	10.16	11.95
0.62	88.03	10.71	12.17
0.68	91.55	11.77	12.51
0.74	94.89	12.82	12.81
0.80	98.10	13.92	13.07
0.86	100.80	14.96	13.27
0.92	103.52	16.06	13.45



Prepared by: Jay Date: 11/25/14
Checked by: LF Date: 11/25/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#11 (46.0-48.0ft) @ 10 psi



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-ST-01, ST# 11 (46.0-48.0ft)
Type/Condition: ST/Undisturbed

Analyst name: M. de los Reyes
Date received: 10/22/2014
Test date: 11/24/2014
Sample description: Gray SILTY CLAY

Initial height h_0 = 5.75 in
Initial diameter d_0 = 2.83 in
Initial area A_0 = 6.30 in²
Mass of wet sample and tare M_i = 1239.89 g
Mass of dry sample and tare M_d = 997.90 g
Mass of tare M_t = 13.59 g
Mass of sample M_s = 1226.30 g
Estimated specific gravity G_s = 2.78
Cell confining pressure σ_3 = 20.0 psi
Rate of strain = 1 %/min
Proving Ring Factor = 1.000
Height to diameter ratio = 2.03

Initial water content w = 24.58%
Initial unit weight γ_w = 128.96 pcf
Initial dry unit weight γ_d = 103.51 pcf
Initial void ratio e_0 = 0.676
Initial degree of saturation S_r = 100%

Liquid Limit (%): NA
Plastic Limit (%): NA
Sand(%): NA
Silt(%): NA
Clay(%): NA

Deviator stress at failure $D\sigma_f$ = 0.87 tsf
Major principal stress at failure σ_1 = 2.31 tsf


Axial Displacement (in)	Axial Force (lbs)	Axial Strain (%)	Deviator Stress (psi)
Δh	F	e	$\sigma_1 - \sigma_3$
0.00	0.00	0.00	0.00
0.01	5.20	0.11	0.82
0.01	9.49	0.22	1.50
0.02	12.49	0.33	1.98
0.03	15.00	0.44	2.37
0.03	17.23	0.56	2.72
0.04	18.79	0.66	2.96
0.04	20.26	0.75	3.19
0.05	22.10	0.88	3.48
0.06	23.88	1.00	3.75
0.06	24.61	1.06	3.86
0.09	31.25	1.64	4.88
0.12	36.15	2.11	5.62
0.15	41.35	2.69	6.39
0.18	45.70	3.20	7.02
0.22	50.11	3.76	7.65
0.25	54.36	4.33	8.25
0.28	57.67	4.81	8.71
0.31	61.59	5.37	9.25
0.34	64.74	5.88	9.67
0.37	68.08	6.44	10.11
0.40	71.14	6.98	10.50
0.43	74.01	7.52	10.86
0.46	76.68	8.04	11.19
0.49	79.16	8.56	11.49
0.52	81.76	9.13	11.79
0.56	84.12	9.65	12.06
0.58	85.92	10.17	12.25
0.62	88.03	10.72	12.47
0.68	91.55	11.78	12.82
0.74	94.89	12.83	13.13
0.80	98.10	13.94	13.40
0.86	100.80	14.97	13.60
0.92	103.52	16.07	13.79



Bulge Failure

Prepared by: Jay Date: 11/25/14
Checked by: Lib Date: 11/25/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#11 (46.0-48.0ft) @ 20 psi



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-ST-01, ST# 11 (46.0-48.0ft)
Type/Condition: ST/Undisturbed

Analyst name: M. de los Reyes
Date received: 10/22/2014
Test date: 11/24/2014
Sample description: Gray SILTY CLAY


Initial height $h_0 = 5.69$ in
Initial diameter $d_0 = 2.87$ in
Initial area $A_0 = 6.48$ in²
Mass of wet sample and tare $M_i = 1234.04$ g
Mass of dry sample and tare $M_d = 997.20$ g
Mass of tare $M_t = 13.44$ g
Mass of sample $M_s = 1220.60$ g
Estimated specific gravity $G_s = 2.78$
Cell confining pressure $\sigma_3 = 40.0$ psi
Rate of strain = 1 %/min
Proving Ring Factor = 1.000
Height to diameter ratio = 1.98

Initial water content $w = 24.07\%$
Initial unit weight $\gamma_w = 125.96$ pcf
Initial dry unit weight $\gamma_d = 101.52$ pcf
Initial void ratio $e_0 = 0.709$
Initial degree of saturation $S_r = 94\%$

Liquid Limit (%): NA
Plastic Limit (%): NA
Sand(%): NA
Silt(%): NA
Clay(%): NA

Deviator stress at failure $D\sigma_f = 0.84$ tsf
Major principal stress at failure $\sigma_1 = 3.72$ tsf


Axial Displacement (in) Δh	Axial Force (lbs) F	Axial Strain (%) e	Deviator Stress (psi) $\sigma_1 - \sigma_3$
0.00	0.00	0.00	0.00
0.01	5.20	0.11	0.80
0.01	9.49	0.23	1.46
0.02	12.49	0.34	1.92
0.03	15.00	0.45	2.30
0.03	17.23	0.57	2.64
0.04	18.79	0.66	2.88
0.04	20.26	0.76	3.10
0.05	22.10	0.89	3.38
0.06	23.88	1.01	3.64
0.06	24.61	1.07	3.75
0.09	31.25	1.65	4.74
0.12	36.15	2.13	5.46
0.15	41.35	2.72	6.20
0.18	45.70	3.23	6.82
0.22	50.11	3.80	7.43
0.25	54.36	4.37	8.02
0.28	57.67	4.86	8.46
0.31	61.59	5.42	8.98
0.34	64.74	5.94	9.39
0.37	68.08	6.50	9.82
0.40	71.14	7.05	10.20
0.43	74.01	7.59	10.55
0.46	76.68	8.12	10.86
0.49	79.16	8.64	11.15
0.52	81.76	9.22	11.45
0.56	84.12	9.75	11.71
0.58	85.92	10.27	11.89
0.62	88.03	10.83	12.11
0.68	91.55	11.90	12.44
0.74	94.89	12.96	12.74
0.80	98.10	14.08	13.00
0.86	100.80	15.12	13.19
0.92	103.52	16.23	13.37



Bulge Failure

Prepared by: Jay Date: 11/25/14
Checked by: AK Date: 11/25/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#11 (46.0-48.0ft) @ 40 psi



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-ST-01, ST# 5 (28.0-30.0ft)
Type/Condition: ST/Undisturbed

Analyst name: M. de los Reyes
Date received: 10/22/2014
Test date: 11/25/2014
Sample description: Gray CLAY trace Gravel


Initial height h_0 = 5.66 in
Initial diameter d_0 = 2.84 in
Initial area A_0 = 6.36 in²
Mass of wet sample and tare M_i = 1260.27 g
Mass of dry sample and tare M_d = 1034.40 g
Mass of tare M_t = 15.37 g
Mass of sample M_s = 1244.90 g
Estimated specific gravity G_s = 2.78
Cell confining pressure σ_3 = 15.0 psi
Rate of strain = 1 %/min
Proving Ring Factor = 1.000
Height to diameter ratio = 1.99

Initial water content w = 22.17%
Initial unit weight γ_w = 131.78 pcf
Initial dry unit weight γ_d = 107.87 pcf
Initial void ratio e_0 = 0.608
Initial degree of saturation S_r = 100%

Liquid Limit (%): NA
Plastic Limit (%): NA
Sand(%): NA
Silt(%): NA
Clay(%): NA

Deviator stress at failure $D\sigma_f$ = 0.55 tsf
Major principal stress at failure σ_1 = 1.63 tsf


Axial Displacement (in)	Axial Force (lbs)	Axial Strain (%)	Deviator Stress (psi)
Δh	F	e	$\sigma_1 - \sigma_3$
0.00	0.00	0.00	0.00
0.00	2.19	0.02	0.34
0.01	6.65	0.11	1.05
0.01	8.68	0.21	1.36
0.02	9.80	0.30	1.54
0.02	10.62	0.40	1.66
0.03	11.43	0.50	1.79
0.03	12.23	0.60	1.91
0.04	13.05	0.70	2.04
0.05	13.85	0.80	2.16
0.05	14.59	0.90	2.28
0.08	18.07	1.39	2.80
0.10	21.22	1.85	3.28
0.13	24.15	2.33	3.71
0.16	26.92	2.81	4.12
0.19	29.31	3.30	4.46
0.21	31.62	3.77	4.79
0.24	33.69	4.27	5.07
0.27	35.67	4.76	5.35
0.30	37.52	5.26	5.59
0.33	39.26	5.75	5.82
0.35	40.98	6.24	6.05
0.38	42.30	6.74	6.21
0.41	43.63	7.23	6.37
0.44	45.02	7.74	6.53
0.47	46.27	8.25	6.68
0.50	47.54	8.80	6.82
0.53	48.59	9.29	6.93
0.55	49.78	9.77	7.07
0.61	51.13	10.75	7.18
0.67	52.87	11.74	7.34
0.72	54.48	12.72	7.48
0.77	55.74	13.68	7.57
0.83	57.19	14.64	7.68



Bulge Failure

Prepared by: Jay Date: 11/27/14
Checked by: LF Date: 11/27/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#5 (28.0-30.0ft) @ 15 psi



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95


Project: Circle Interchange	Analyst name: M. de los Reyes
Client: AECOM	Date received: 10/22/2014
WEI Job No.: 1100-04-01	Test date: 12/8/2014
Soil Sample ID: 30-ST-01, ST# 5 (28.0-30.0ft)	Sample description: Gray CLAY trace Gravel
Type/Condition: ST/ Undisturbed	
Initial height $h_0 =$ 5.57 in	Initial water content $w =$ 21.72%
Initial diameter $d_0 =$ 2.79 in	Initial unit weight $\gamma_w =$ 133.25 pcf
Initial area $A_0 =$ 6.13 in ²	Initial dry unit weight $\gamma_d =$ 109.47 pcf
Mass of wet sample and tare $M_i =$ 1208.11 g	Initial void ratio $e_0 =$ 0.585
Mass of dry sample and tare $M_d =$ 994.90 g	Initial degree of saturation $S_r =$ 100%
Mass of tare $M_t =$ 13.21 g	
Mass of sample $M_s =$ 1194.90 g	Liquid Limit (%): NA
Estimated specific gravity $G_s =$ 2.78	Plastic Limit (%): NA
Cell confining pressure $\sigma_3 =$ 30.0 psi	Sand(%): NA
Rate of strain = 1 %/min	Silt(%): NA
Proving Ring Factor = 1.000	Clay(%): NA
Height to diameter ratio = 1.99	
	Deviator stress at failure $D\sigma_f =$ 1.19 tsf
	Major principal stress at failure $\sigma_1 =$ 3.35 tsf

Axial Displacement (in) Δh	Axial Force (lbs) F	Axial Strain (%) e	Deviator Stress (psi) $\sigma_1 - \sigma_3$
0.00	0.00	0.00	0.00
0.01	5.72	0.10	0.93
0.01	19.48	0.20	3.17
0.02	25.13	0.29	4.09
0.02	29.11	0.39	4.73
0.03	32.31	0.49	5.24
0.03	35.02	0.59	5.68
0.04	37.43	0.69	6.06
0.04	39.56	0.79	6.40
0.05	41.37	0.90	6.69
0.06	43.16	0.99	6.97
0.08	51.13	1.49	8.21
0.11	57.49	1.99	9.19
0.14	62.94	2.48	10.01
0.17	67.62	2.98	10.70
0.19	72.05	3.48	11.34
0.22	76.18	4.00	11.93
0.25	79.51	4.52	12.38
0.28	82.84	5.02	12.83
0.31	85.73	5.51	13.21
0.33	89.47	5.99	13.72
0.36	92.01	6.48	14.03
0.39	94.10	6.97	14.28
0.42	96.81	7.46	14.61
0.44	98.26	7.96	14.75
0.47	100.32	8.46	14.97
0.50	102.90	8.99	15.27
0.53	105.67	9.47	15.60
0.55	106.69	9.96	15.66
0.61	109.97	10.95	15.97
0.67	111.22	11.98	15.96
0.72	115.98	12.98	16.46
0.78	117.30	13.97	16.45
0.84	118.58	14.99	16.44



Prepared by: Jay Date: 12/10/14
Checked by: AF Date: 12/10/14


Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#5 (28.0-30.0ft) @ 30 psi



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST


AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange	Analyst name: M. de los Reyes
Client: AECOM	Date received: 10/22/2014
WEI Job No.: 1100-04-01	Test date: 11/25/2014
Soil Sample ID: 30-ST-01, ST# 8 (37.0-39.0ft)	Sample description: Gray CLAY
Type/Condition: ST/Undisturbed	
Initial height $h_0 =$ 5.59 in	Initial water content $w =$ 25.03%
Initial diameter $d_0 =$ 2.79 in	Initial unit weight $\gamma_w =$ 129.56 pcf
Initial area $A_0 =$ 6.12 in ²	Initial dry unit weight $\gamma_d =$ 103.62 pcf
Mass of wet sample and tare $M_i =$ 1349.07 g	Initial void ratio $e_0 =$ 0.674
Mass of dry sample and tare $M_d =$ 1116.20 g	Initial degree of saturation $S_r =$ 100%
Mass of tare $M_t =$ 185.67 g	
Mass of sample $M_s =$ 1163.40 g	Liquid Limit (%): NA
Estimated specific gravity $G_s =$ 2.78	Plastic Limit (%): NA
Cell confining pressure $\sigma_3 =$ 10.0 psi	Sand(%): NA
Rate of strain = 1 %/min	Silt(%): NA
Proving Ring Factor = 1.000	Clay(%): NA
Height to diameter ratio = 2.00	
	Deviator stress at failure $D\sigma_r =$ 0.40 tsf
	Major principal stress at failure $\sigma_1 =$ 1.12 tsf

Axial Displacement (in)	Axial Force (lbs)	Axial Strain (%)	Deviator Stress (psi)	
Δh	F	e	$\sigma_1 - \sigma_3$	
0.00	0.00	0.00	0.00	
0.01	0.79	0.10	0.13	
0.01	1.35	0.19	0.22	
0.02	1.94	0.29	0.32	
0.02	2.65	0.38	0.43	
0.03	3.40	0.48	0.55	
0.03	3.89	0.58	0.63	
0.04	4.23	0.69	0.69	
0.04	4.61	0.80	0.75	
0.05	5.26	0.90	0.85	
0.06	5.91	1.01	0.96	
0.08	8.53	1.50	1.37	
0.11	10.77	2.00	1.72	
0.14	12.28	2.49	1.96	
0.17	14.38	2.97	2.28	
0.19	16.33	3.45	2.58	
0.22	18.04	3.91	2.83	
0.25	19.99	4.44	3.12	
0.28	22.33	4.93	3.47	
0.30	24.21	5.44	3.74	
0.33	24.75	5.94	3.81	
0.36	25.62	6.43	3.92	
0.39	27.16	6.92	4.13	
0.41	28.53	7.41	4.32	
0.44	29.58	7.94	4.45	
0.47	31.51	8.46	4.72	
0.50	32.87	9.03	4.89	
0.53	33.13	9.52	4.90	
0.56	33.40	10.02	4.91	
0.61	34.75	10.99	5.06	
0.67	36.76	12.02	5.29	
0.73	37.50	13.01	5.33	
0.78	37.86	13.97	5.32	
0.84	39.53	14.95	5.49	

Prepared by: Jay Date: 11/29/14
 Checked by: Asf Date: 11/29/14


Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#8 (37.0-39.0ft) @ 10 psi



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST


AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange	Analyst name: M. de los Reyes
Client: AECOM	Date received: 10/22/2014
WEI Job No.: 1100-04-01	Test date: 11/25/2014
Soil Sample ID: 30-ST-01, ST# 8 (37.0-39.0ft)	Sample description: Gray CLAY
Type/Condition: ST/Undisturbed	
Initial height $h_0 =$ 6.15 in	Initial water content $w =$ 24.56%
Initial diameter $d_0 =$ 2.83 in	Initial unit weight $\gamma_w =$ 116.04 pcf
Initial area $A_0 =$ 6.28 in ²	Initial dry unit weight $\gamma_d =$ 93.16 pcf
Mass of wet sample and tare $M_i =$ 1364.76 g	Initial void ratio $e_0 =$ 0.862
Mass of dry sample and tare $M_d =$ 1132.60 g	Initial degree of saturation $S_r =$ 79%
Mass of tare $M_t =$ 187.16 g	
Mass of sample $M_s =$ 1177.60 g	Liquid Limit (%): NA
Estimated specific gravity $G_s =$ 2.78	Plastic Limit (%): NA
Cell confining pressure $\sigma_3 =$ 20.0 psi	Sand(%): NA
Rate of strain = 1 %/min	Silt(%): NA
Proving Ring Factor = 1.000	Clay(%): NA
Height to diameter ratio = 2.18	
	Deviator stress at failure $D\sigma_f =$ 0.56 tsf
	Major principal stress at failure $\sigma_1 =$ 2.00 tsf

Axial Displacement (in)	Axial Force (lbs)	Axial Strain (%)	Deviator Stress (psi)	
Δh	F	e	$\sigma_1 - \sigma_3$	
0.00	0.00	0.00	0.00	
0.01	5.73	0.09	0.91	
0.01	8.36	0.18	1.33	
0.02	10.30	0.27	1.63	
0.02	11.70	0.37	1.86	
0.03	13.29	0.46	2.11	
0.03	14.67	0.55	2.32	
0.04	15.61	0.65	2.47	
0.05	16.74	0.74	2.64	
0.05	18.03	0.83	2.85	
0.06	19.05	0.93	3.00	
0.09	21.32	1.39	3.35	
0.11	25.46	1.85	3.98	
0.14	28.22	2.29	4.39	
0.17	29.68	2.74	4.60	
0.20	33.48	3.19	5.16	
0.22	36.29	3.63	5.57	
0.25	39.60	4.09	6.05	
0.28	40.01	4.53	6.08	
0.31	42.05	4.98	6.36	
0.33	43.49	5.43	6.55	
0.36	42.93	5.87	6.43	
0.39	42.81	6.32	6.38	
0.42	43.84	6.76	6.51	
0.44	49.10	7.22	7.25	
0.47	49.42	7.68	7.26	
0.50	50.25	8.19	7.34	
0.53	50.66	8.65	7.37	
0.56	49.76	9.11	7.20	
0.62	49.48	10.02	7.09	
0.67	50.97	10.95	7.23	
0.73	55.40	11.85	7.77	
0.78	52.76	12.75	7.33	
0.84	54.57	13.65	7.50	

Prepared by: Jay Date: 11/29/14
 Checked by: AL Date: 11/29/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#8 (37.0-39.0ft) @ 20 psi




UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange	Analyst name: M. de los Reyes
Client: AECOM	Date received: 10/22/2014
WEI Job No.: 1100-04-01	Test date: 11/25/2014
Soil Sample ID: 30-ST-01, ST# 8 (37.0-39.0ft)	Sample description: Gray CLAY
Type/Condition: ST/Undisturbed	
Initial height $h_0 =$ 5.62 in	Initial water content $w =$ 25.15%
Initial diameter $d_0 =$ 2.78 in	Initial unit weight $\gamma_w =$ 131.56 pcf
Initial area $A_0 =$ 6.07 in ²	Initial dry unit weight $\gamma_d =$ 105.13 pcf
Mass of wet sample and tare $M_i =$ 1365.90 g	Initial void ratio $e_0 =$ 0.650
Mass of dry sample and tare $M_d =$ 1129.10 g	Initial degree of saturation $S_r =$ 100%
Mass of tare $M_t =$ 187.40 g	
Mass of sample $M_s =$ 1178.50 g	Liquid Limit (%): NA
Estimated specific gravity $G_s =$ 2.78	Plastic Limit (%): NA
Cell confining pressure $\sigma_3 =$ 40.0 psi	Sand(%): NA
Rate of strain = 1 %/min	Silt(%): NA
Proving Ring Factor = 1.000	Clay(%): NA
Height to diameter ratio = 2.02	


Deviator stress at failure $D\sigma_f =$ 0.56 tsf
Major principal stress at failure $\sigma_1 =$ 3.44 tsf

Axial Displacement (in)	Axial Force (lbs)	Axial Strain (%)	Deviator Stress (psi)	
Δh	F	e	$\sigma_1 - \sigma_3$	
0.00	0.00	0.00	0.00	
0.01	3.12	0.10	0.51	
0.01	7.74	0.21	1.27	
0.02	9.80	0.32	1.61	
0.02	11.02	0.42	1.81	
0.03	11.93	0.52	1.95	
0.03	12.78	0.62	2.09	
0.04	13.53	0.72	2.21	
0.05	14.21	0.82	2.32	
0.05	14.91	0.92	2.43	
0.06	15.56	1.02	2.54	
0.08	18.81	1.50	3.05	
0.11	22.09	1.99	3.56	
0.14	25.22	2.47	4.05	
0.17	28.10	2.96	4.49	
0.19	30.83	3.42	4.90	
0.22	33.40	3.94	5.28	
0.25	35.78	4.43	5.63	
0.28	37.76	4.92	5.91	
0.30	39.62	5.41	6.17	
0.33	41.34	5.89	6.41	
0.36	42.72	6.39	6.58	
0.39	44.06	6.87	6.76	
0.42	45.37	7.39	6.92	
0.44	46.58	7.91	7.06	
0.47	47.59	8.42	7.18	
0.50	48.63	8.97	7.29	
0.53	49.60	9.46	7.39	
0.56	50.32	9.96	7.46	
0.62	51.75	10.96	7.59	
0.67	53.00	11.96	7.68	
0.73	54.00	12.93	7.74	
0.78	54.94	13.90	7.79	
0.84	55.92	14.90	7.83	

Bulge Failure

Prepared by: Jay Date: 11/25/14
Checked by: h/f Date: 11/29/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#8 (37.0-39.0ft) @ 40 psi




UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange	Analyst name: M. de los Reyes
Client: AECOM	Date received: 10/22/2014
WEI Job No.: 1100-04-01	Test date: 12/4/2014
Soil Sample ID: 30-ST-01, ST# 9 (40.0-42.0ft)	Sample description: Gray SILTY CLAY trace Gravel
Type/Condition: ST/Undisturbed	
Initial height $h_0 =$ 5.59 in	Initial water content $w =$ 25.15%
Initial diameter $d_0 =$ 2.85 in	Initial unit weight $\gamma_w =$ 126.10 pcf
Initial area $A_0 =$ 6.37 in ²	Initial dry unit weight $\gamma_d =$ 100.76 pcf
Mass of wet sample and tare $M_i =$ 1363.86 g	Initial void ratio $e_0 =$ 0.722
Mass of dry sample and tare $M_d =$ 1127.30 g	Initial degree of saturation $S_r =$ 97%
Mass of tare $M_t =$ 186.86 g	
Mass of sample $M_s =$ 1177.00 g	Liquid Limit (%): NA
Estimated specific gravity $G_s =$ 2.78	Plastic Limit (%): NA
Cell confining pressure $\sigma_3 =$ 10.0 psi	Sand(%): NA
Rate of strain = 1 %/min	Silt(%): NA
Proving Ring Factor = 1.000	Clay(%): NA
Height to diameter ratio = 1.96	

Deviator stress at failure $D\sigma_f =$ 0.60 tsf
Major principal stress at failure $\sigma_1 =$ 1.32 tsf


Axial Displacement (in)	Axial Force (lbs)	Axial Strain (%)	Deviator Stress (psi)
Δh	F	e	$\sigma_1 - \sigma_3$
0.00	0.00	0.00	0.00
0.00	7.42	0.07	1.17
0.01	11.75	0.15	1.84
0.01	13.72	0.25	2.15
0.02	14.82	0.34	2.32
0.02	15.91	0.44	2.49
0.03	17.06	0.53	2.66
0.04	17.72	0.63	2.77
0.04	18.55	0.74	2.89
0.05	19.55	0.83	3.05
0.05	20.52	0.93	3.19
0.08	25.36	1.41	3.93
0.11	29.81	1.90	4.59
0.13	33.81	2.38	5.18
0.16	37.44	2.87	5.71
0.19	40.62	3.36	6.16
0.21	43.58	3.85	6.58
0.24	45.64	4.36	6.85
0.27	47.74	4.88	7.13
0.30	49.37	5.38	7.34
0.33	50.82	5.87	7.51
0.35	52.06	6.35	7.66
0.38	53.15	6.83	7.78
0.41	54.54	7.30	7.94
0.44	55.07	7.79	7.98
0.46	56.13	8.29	8.08
0.49	57.02	8.83	8.16
0.52	57.52	9.31	8.19
0.55	57.92	9.78	8.21
0.60	59.66	10.73	8.36
0.66	59.81	11.73	8.29
0.71	60.03	12.73	8.23
0.77	61.62	13.71	8.35
0.82	61.36	14.71	8.22



Bulge Failure

Prepared by: Jay Date: 12/8/14
Checked by: AK Date: 12/8/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#9 (40.0-42.0ft) @ 10 psi




UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange	Analyst name: M. de los Reyes
Client: AECOM	Date received: 10/22/2014
WEI Job No.: 1100-04-01	Test date: 12/4/2014
Soil Sample ID: 30-ST-01, ST# 9 (40.0-42.0ft)	Sample description: Gray SILTY CLAY trace Gravel
Type/Condition: ST/Undisturbed	
Initial height $h_0 =$ 6.15 in	Initial water content $w =$ 25.09%
Initial diameter $d_0 =$ 2.83 in	Initial unit weight $\gamma_w =$ 113.50 pcf
Initial area $A_0 =$ 6.28 in ²	Initial dry unit weight $\gamma_d =$ 90.74 pcf
Mass of wet sample and tare $M_i =$ 1339.32 g	Initial void ratio $e_0 =$ 0.912
Mass of dry sample and tare $M_d =$ 1108.30 g	Initial degree of saturation $S_r =$ 76%
Mass of tare $M_t =$ 187.42 g	
Mass of sample $M_s =$ 1151.90 g	Liquid Limit (%): NA
Estimated specific gravity $G_s =$ 2.78	Plastic Limit (%): NA
Cell confining pressure $\sigma_3 =$ 20.0 psi	Sand(%): NA
Rate of strain = 1 %/min	Silt(%): NA
Proving Ring Factor = 1.000	Clay(%): NA
Height to diameter ratio = 2.18	


Deviator stress at failure $D\sigma_1 =$ 0.64 tsf
Major principal stress at failure $\sigma_1 =$ 2.08 tsf

Axial Displacement (in) Δh	Axial Force (lbs) F	Axial Strain (%) e	Deviator Stress (psi) $\sigma_1 - \sigma_3$	
0.00	0.00	0.00	0.00	
0.00	1.15	0.05	0.18	
0.01	1.33	0.13	0.21	
0.01	5.78	0.22	0.92	
0.02	8.51	0.30	1.35	
0.02	10.15	0.39	1.61	
0.03	11.31	0.48	1.79	
0.04	12.04	0.57	1.90	
0.04	12.66	0.66	2.00	
0.05	13.28	0.76	2.10	
0.05	13.79	0.85	2.18	
0.08	16.38	1.31	2.57	
0.11	18.78	1.77	2.94	
0.14	21.19	2.21	3.30	
0.16	23.68	2.65	3.67	
0.19	26.24	3.09	4.05	
0.22	28.79	3.51	4.42	
0.24	31.09	3.97	4.75	
0.27	33.62	4.42	5.11	
0.30	35.97	4.87	5.45	
0.33	38.20	5.31	5.76	
0.35	40.44	5.73	6.07	
0.38	42.54	6.16	6.35	
0.41	44.64	6.58	6.64	
0.43	46.42	7.03	6.87	
0.46	48.36	7.49	7.12	
0.49	50.17	7.99	7.35	
0.52	51.78	8.43	7.55	
0.55	53.41	8.87	7.75	
0.60	56.46	9.76	8.11	
0.66	58.84	10.68	8.36	
0.71	60.90	11.59	8.57	
0.77	63.06	12.47	8.78	
0.82	64.78	13.35	8.93	

Bulge Failure

Prepared by: Jay Date: 12/8/14
Checked by: LF Date: 12/8/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#9 (40.0-42.0ft) @ 20 psi



UNCONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 296 / ASTM D 2850-95

Project: Circle Interchange
Client: AECOM
WEI Job No.: 1100-04-01
Soil Sample ID: 30-ST-01, ST# 9 (40'-42.0ft)
Type/Condition: ST/Undisturbed


Analyst name: M. de los Reyes
Date received: 10/22/2014
Test date: 12/4/2014
Sample description: Gray SILTY CLAY trace Gravel

Initial height $h_0 = 6.15$ in
Initial diameter $d_0 = 2.83$ in
Initial area $A_0 = 6.28$ in²
Mass of wet sample and tare $M_i = 1359.88$ g
Mass of dry sample and tare $M_d = 1123.30$ g
Mass of tare $M_t = 162.98$ g
Mass of sample $M_s = 1196.90$ g
Estimated specific gravity $G_s = 2.78$
Cell confining pressure $\sigma_3 = 40.0$ psi
Rate of strain = 1 %/min
Proving Ring Factor = 1.000
Height to diameter ratio = 2.18

Initial water content $w = 24.64\%$
Initial unit weight $\gamma_w = 117.94$ pcf
Initial dry unit weight $\gamma_d = 94.63$ pcf
Initial void ratio $e_0 = 0.833$
Initial degree of saturation $S_r = 82\%$

Liquid Limit (%): NA
Plastic Limit (%): NA
Sand(%): NA
Silt(%): NA
Clay(%): NA


Deviator stress at failure $D\sigma_r = 0.82$ tsf
Major principal stress at failure $\sigma_1 = 3.70$ tsf

Axial Displacement (in)	Axial Force (lbs)	Axial Strain (%)	Deviator Stress (psi)	
Δh	F	e	$\sigma_1 - \sigma_3$	
0.00	0.00	0.00	0.00	
0.01	5.58	0.09	0.89	
0.01	12.60	0.18	2.00	
0.02	16.16	0.27	2.57	
0.02	18.61	0.35	2.95	
0.03	20.70	0.44	3.28	
0.03	22.53	0.53	3.57	
0.04	24.15	0.62	3.82	
0.04	25.77	0.70	4.07	
0.05	27.26	0.79	4.31	
0.05	28.69	0.88	4.53	
0.08	34.92	1.31	5.48	
0.11	40.22	1.74	6.29	
0.13	45.14	2.18	7.03	
0.16	49.31	2.62	7.64	
0.19	53.47	3.09	8.25	
0.22	56.33	3.56	8.65	
0.25	59.38	4.02	9.07	
0.27	61.91	4.47	9.41	
0.30	63.59	4.92	9.62	
0.33	65.52	5.36	9.87	
0.36	67.26	5.80	10.08	
0.39	69.54	6.26	10.38	
0.41	70.21	6.71	10.42	
0.44	71.72	7.16	10.60	
0.47	73.23	7.59	10.77	
0.50	73.72	8.07	10.79	
0.52	74.69	8.50	10.88	
0.55	75.58	8.94	10.95	
0.61	76.98	9.84	11.05	
0.66	79.33	10.73	11.27	
0.72	79.72	11.62	11.21	
0.77	81.54	12.53	11.35	
0.83	81.51	13.46	11.23	

Bulge Failure

Prepared by: Sung Date: 12/8/14
Checked by: lit Date: 12/8/14

Unconsolidated-Undrained Triaxial Test
Deviator Stress v. Axial Strain
30-ST-01,ST#9 (40.0-42.0ft) @ 40 psi





CONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 297 / ASTM D 4767

Project: Circle Interchange Reconstruction	Tested by: Wang Engineering, Inc.
Client: AECOM	Prepared by: M. Snider
Soil Sample ID: Boring 30-RWB-03, ST#4, 28.5' to 30'	Test date: October 17, 2014
Sample description: Gray SILTY CLAY (CL)	WEI Job No.: 1100-04-01
Initial sample height: 5.67 in	Tare mass: 13.60 g
Initial sample diameter: 2.84 in	Measured sample mass w/out Tare: 1220.60 g
Initial sample mass: 1220.60 g	Tare and final sample mass: 1224.50 g
Soil specific gravity: 2.75 (estimated)	Tare and dry sample mass: 995.60 g
Dry sample mass: 982.00 g	Saturation (B) coefficient: 99%
Final sample mass: 1210.90 g	Rate of loading: 1.0E-02 %/min
Initial water content: 24.30% (specimen)	Volume change during consolidation: 0.68 in ³
Initial unit weight: 129.22 pcf	Void ratio after consolidation: 0.619
Initial dry unit weight: 103.96 pcf	Dry unit weight after consolidation: 105.98 pcf
Initial void ratio: 0.651	Height after consolidation: 5.63 in
Initial saturation: 102.7%	Volume after consolidation: 35.30 in ³
Final water content: 23.31% (specimen)	Area after consolidation: 6.27 in ²
Liquid Limit, %: 34	Time at 50% Consolidation: 43.70 min
Plastic Limit, %: 17	Effective consolidation stress: 10.0 psi
% Sand: 16.3	Shear modulus: 399.01 psi
% Silt: 48.1	
% Clay: 30.5	

Axial displacement (Dh)	Axial force (F)	Pore pressure (u)	Axial strain (eps)	Deviator stress	Total vertical stress	Effective vertical stress	Effective horizontal stress	Shear stress, q=q'	Effective spherical stress, p'	Total spherical stress, p	Effective Principal Stress Ratio
in	pound	psi	%	psi	psi	psi	psi	psi	psi	psi	psi
0.00	0.000	0.00	0.00	0.0	10.0	10.0	10.00	0.00	10.00	10.00	1.00
0.01	21.327	1.77	0.10	3.4	13.4	11.6	8.23	1.70	9.93	11.70	1.41
0.01	30.154	2.84	0.20	4.8	14.8	12.0	7.16	2.40	9.56	12.40	1.67
0.02	35.240	3.40	0.30	5.6	15.6	12.2	6.60	2.80	9.40	12.80	1.85
0.02	38.822	3.81	0.40	6.2	16.2	12.4	6.19	3.08	9.27	13.08	2.00
0.03	41.851	4.09	0.50	6.6	16.6	12.5	5.91	3.32	9.23	13.32	2.12
0.03	44.033	4.31	0.60	7.0	17.0	12.7	5.69	3.49	9.18	13.49	2.23
0.04	46.127	4.47	0.70	7.3	17.3	12.8	5.53	3.65	9.18	13.65	2.32
0.05	48.278	4.59	0.80	7.6	17.6	13.0	5.41	3.82	9.23	13.82	2.41
0.05	50.500	4.72	0.90	8.0	18.0	13.3	5.28	3.99	9.27	13.99	2.51
0.06	52.643	4.80	1.00	8.3	18.3	13.5	5.20	4.16	9.35	14.16	2.60
0.08	58.375	5.04	1.50	9.2	19.2	14.1	4.96	4.59	9.55	14.59	2.85
0.11	63.494	5.10	2.00	9.9	19.9	14.8	4.90	4.96	9.86	14.96	3.02
0.14	68.063	5.04	2.50	10.6	20.6	15.5	4.96	5.29	10.25	15.29	3.13
0.17	70.323	4.94	3.00	10.9	20.9	15.9	5.06	5.44	10.50	15.44	3.15
0.20	72.049	4.85	3.50	11.1	21.1	16.2	5.15	5.54	10.69	15.54	3.15
0.23	74.417	4.74	4.00	11.4	21.4	16.7	5.26	5.70	10.95	15.70	3.17
0.26	77.403	4.68	4.50	11.8	21.8	17.1	5.32	5.89	11.22	15.89	3.21
0.28	78.221	4.59	5.00	11.9	21.9	17.3	5.41	5.93	11.34	15.93	3.19
0.31	80.973	4.49	5.50	12.2	22.2	17.7	5.51	6.10	11.61	16.10	3.21
0.34	83.021	4.42	6.00	12.4	22.4	18.0	5.58	6.22	11.81	16.22	3.23
0.37	83.097	4.33	6.50	12.4	22.4	18.1	5.67	6.20	11.86	16.20	3.19
0.40	83.782	4.23	7.00	12.4	22.4	18.2	5.77	6.21	11.98	16.21	3.15
0.43	85.298	4.13	7.50	12.6	22.6	18.4	5.87	6.29	12.16	16.29	3.15
0.45	87.749	4.07	8.00	12.9	22.9	18.8	5.93	6.44	12.37	16.44	3.17
0.48	87.854	3.98	8.50	12.8	22.8	18.8	6.02	6.41	12.43	16.41	3.13
0.51	89.666	3.92	9.00	13.0	23.0	19.1	6.08	6.51	12.59	16.51	3.14
0.54	90.655	3.85	9.50	13.1	23.1	19.2	6.15	6.54	12.69	16.54	3.13
0.57	90.272	3.78	10.00	13.0	23.0	19.2	6.22	6.48	12.70	16.48	3.08
0.62	92.152	3.66	11.00	13.1	23.1	19.4	6.34	6.54	12.88	16.54	3.06
0.68	93.932	3.53	12.00	13.2	23.2	19.7	6.47	6.59	13.06	16.59	3.04
0.74	95.639	3.48	13.00	13.3	23.3	19.8	6.52	6.64	13.15	16.64	3.04
0.79	95.932	3.45	14.00	13.2	23.2	19.7	6.55	6.58	13.13	16.58	3.01
0.85	97.761	3.36	15.00	13.3	23.3	19.9	6.64	6.63	13.27	16.63	3.00

Notes:

$p = S1 + S3 / 2$ $q = S1 - S3 / 2$

$p' = S1' + S3' / 2$ $q' = S1' - S3' / 2$

Wet Method Saturation

Prepared by: Jay

Date: 10/20/14

Checked by: RF

Date: 10/20/14





CONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 297 / ASTM D 4767

Project: Circle Interchange Reconstruction	Tested by: Wang Engineering, Inc.
Client: AECOM	Prepared by: M. Snider
Soil Sample ID: Boring 30-RWB-03, ST#4, 28.5' to 30'	Test date: October 17, 2014
Sample description: Gray SILTY CLAY (CL)	WEI Job No.: 1100-04-01
Initial sample height: 5.58 in	Tare mass: 163.02 g
Initial sample diameter: 2.81 in	Measured sample mass w/out Tare: 1180.70 g
Initial sample mass: 1180.70 g	Tare and final sample mass: 1319.20 g
Soil specific gravity: 2.75 (estimated)	Tare and dry sample mass: 1112.50 g
Dry sample mass: 949.48 g	Saturation (B) coefficient: 99%
Final sample mass: 1156.18 g	Rate of loading: 1.0E-02 %/min
Initial water content: 24.35% (specimen)	Volume change during consolidation: 1.55 in ³
Initial unit weight: 130.17 pcf	Void ratio after consolidation: 0.566
Initial dry unit weight: 104.68 pcf	Dry unit weight after consolidation: 109.61 pcf
Initial void ratio: 0.639	Height after consolidation: 5.50 in
Initial saturation: 104.7%	Volume after consolidation: 33.00 in ³
Final water content: 21.77% (specimen)	Area after consolidation: 6.00 in ²
Liquid Limit, %: 34	Time at 50% Consolidation: 147.96 min
Plastic Limit, %: 17	Effective consolidation stress: 20.0 psi
% Sand: 16.3	Shear modulus: 554.42 psi
% Silt: 48.1	
% Clay: 30.5	

Axial displacement (Dh)	Axial force (F)	Pore pressure (u)	Axial strain (eps)	Deviator stress	Total vertical stress	Effective vertical stress	Effective horizontal stress	Shear stress, q=q'	Effective spherical stress, p'	Total spherical stress, p	Effective Principal Stress Ratio
in	pound	psi	%	psi	psi	psi	psi	psi	psi	psi	psi
0.00	0.000	0.00	0.00	0.0	20.0	20.0	20.00	0.00	20.00	20.00	1.00
0.01	27.865	2.41	0.10	4.6	24.6	22.2	17.59	2.32	19.91	22.32	1.26
0.01	39.947	4.04	0.20	6.6	26.6	22.6	15.96	3.32	19.28	23.32	1.42
0.02	47.125	5.19	0.30	7.8	27.8	22.6	14.81	3.91	18.73	23.91	1.53
0.02	52.355	6.02	0.40	8.7	28.7	22.7	13.98	4.34	18.33	24.34	1.62
0.03	56.180	6.68	0.50	9.3	29.3	22.6	13.32	4.66	17.98	24.66	1.70
0.03	59.335	7.22	0.60	9.8	29.8	22.6	12.78	4.91	17.69	24.91	1.77
0.04	62.043	7.70	0.70	10.3	30.3	22.6	12.30	5.13	17.43	25.13	1.83
0.04	64.279	8.08	0.80	10.6	30.6	22.5	11.92	5.31	17.23	25.31	1.89
0.05	66.371	8.42	0.90	11.0	31.0	22.5	11.58	5.48	17.06	25.48	1.95
0.06	68.343	8.70	1.00	11.3	31.3	22.6	11.30	5.64	16.93	25.64	2.00
0.08	76.590	9.56	1.50	12.6	32.6	23.0	10.44	6.29	16.73	26.29	2.20
0.11	83.223	10.15	2.00	13.6	33.6	23.4	9.85	6.80	16.65	26.80	2.38
0.14	87.185	10.44	2.50	14.2	34.2	23.7	9.56	7.08	16.64	27.08	2.48
0.17	91.163	10.54	3.00	14.7	34.7	24.2	9.46	7.37	16.82	27.37	2.56
0.20	94.672	10.55	3.50	15.2	35.2	24.7	9.45	7.61	17.06	27.61	2.61
0.22	98.308	10.54	4.00	15.7	35.7	25.2	9.46	7.86	17.33	27.86	2.66
0.25	100.616	10.53	4.50	16.0	36.0	25.5	9.47	8.01	17.47	28.01	2.69
0.28	103.593	10.46	5.00	16.4	36.4	25.9	9.54	8.20	17.74	28.20	2.72
0.31	106.695	10.38	5.50	16.8	36.8	26.4	9.62	8.40	18.02	28.40	2.75
0.33	108.078	10.30	6.00	16.9	36.9	26.6	9.70	8.46	18.17	28.46	2.74
0.36	109.794	10.20	6.50	17.1	37.1	26.9	9.80	8.55	18.35	28.55	2.75
0.39	111.815	10.10	7.00	17.3	37.3	27.2	9.90	8.66	18.57	28.66	2.75
0.42	113.620	10.00	7.50	17.5	37.5	27.5	10.00	8.76	18.76	28.76	2.75
0.45	115.300	9.86	8.00	17.7	37.7	27.8	10.14	8.84	18.98	28.84	2.74
0.47	116.907	9.75	8.50	17.8	37.8	28.1	10.25	8.91	19.16	28.91	2.74
0.50	119.099	9.65	9.00	18.1	38.1	28.4	10.35	9.03	19.38	29.03	2.74
0.53	120.059	9.57	9.50	18.1	38.1	28.5	10.43	9.05	19.49	29.05	2.74
0.56	121.123	9.42	10.00	18.2	38.2	28.7	10.58	9.08	19.66	29.08	2.72
0.61	123.174	9.25	11.00	18.3	38.3	29.0	10.75	9.13	19.89	29.13	2.70
0.67	124.986	9.20	12.00	18.3	38.3	29.1	10.80	9.16	19.96	29.16	2.70
0.73	127.297	9.09	13.00	18.5	38.5	29.4	10.91	9.23	20.14	29.23	2.69
0.78	128.889	8.95	14.00	18.5	38.5	29.5	11.05	9.23	20.29	29.23	2.67
0.84	129.935	8.90	15.00	18.4	38.4	29.5	11.10	9.20	20.31	29.20	2.66

Notes:

$p = S_1 + S_3 / 2$ $q = S_1 - S_3 / 2$

$p' = S_1' + S_3' / 2$ $q' = S_1' - S_3' / 2$

Wet Method Saturation

Prepared by: Jerry

Date: 10/20/14

Checked by: AT

Date: 10/20/14





CONSOLIDATED-UNDRAINED TRIAXIAL COMPRESSION TEST

AASHTO T 297 / ASTM D 4767

Project: Circle Interchange Reconstruction	Tested by: Wang Engineering, Inc.
Client: AECOM	Prepared by: M. Snider
Soil Sample ID: Boring 30-RWB-03, ST#4, 28.5' to 30'	Test date: October 17, 2014
Sample description: Gray SILTY CLAY (CL)	WEI Job No.: 1100-04-01
Initial sample height: 5.55 in	Tare mass: 250.10 g
Initial sample diameter: 2.84 in	Measured sample mass w/out Tare: 1241.80 g
Initial sample mass: 1241.80 g	Tare and final sample mass: 1454.10 g
Soil specific gravity: 2.75 (estimated)	Tare and dry sample mass: 1277.40 g
Dry sample mass: 1027.30 g	Saturation (B) coefficient: 99%
Final sample mass: 1204.00 g	Rate of loading: 1.0E-02 %/min
Initial water content: 20.88% (specimen)	Volume change during consolidation: 2.02 in ³
Initial unit weight: 134.81 pcf	Void ratio after consolidation: 0.450
Initial dry unit weight: 111.53 pcf	Dry unit weight after consolidation: 118.34 pcf
Initial void ratio: 0.539	Height after consolidation: 5.44 in
Initial saturation: 106.6%	Volume after consolidation: 33.07 in ³
Final water content: 17.20% (specimen)	Area after consolidation: 6.08 in ²
Liquid Limit, %: 34	Time at 50% Consolidation: 134.46 min
Plastic Limit, %: 17	Effective consolidation stress: 40.0 psi
% Sand: 16.3	Shear modulus: 1123.92 psi
% Silt: 48.1	
% Clay: 30.5	

Axial displacement (Dh)	Axial force (F)	Pore pressure (u)	Axial strain (eps)	Deviator stress	Total vertical stress	Effective vertical stress	Effective horizontal stress	Shear stress, q=q'	Effective spherical stress, p'	Total spherical stress, p	Effective Principal Stress Ratio
in	pound	psi	%	psi	psi	psi	psi	psi	psi	psi	psi
0.00	0.000	0.00	0.00	0.0	40.0	40.0	40.00	0.00	40.00	40.00	1.00
0.01	51.882	3.69	0.10	8.5	48.5	44.8	36.31	4.26	40.57	44.26	1.23
0.01	82.417	7.35	0.20	13.5	53.5	46.2	32.65	6.77	39.41	46.77	1.41
0.02	98.057	9.81	0.30	16.1	56.1	46.3	30.19	8.04	38.23	48.04	1.53
0.02	108.560	11.66	0.40	17.8	57.8	46.1	28.34	8.89	37.23	48.89	1.63
0.03	116.589	13.17	0.50	19.1	59.1	45.9	26.83	9.54	36.38	49.54	1.71
0.03	122.916	14.40	0.60	20.1	60.1	45.7	25.60	10.05	35.65	50.05	1.79
0.04	128.382	15.45	0.70	21.0	61.0	45.5	24.55	10.49	35.03	50.49	1.85
0.04	132.763	16.34	0.80	21.7	61.7	45.3	23.66	10.83	34.50	50.83	1.92
0.05	136.494	17.13	0.90	22.3	62.3	45.1	22.87	11.13	34.00	51.13	1.97
0.06	139.315	17.81	1.00	22.7	62.7	44.9	22.19	11.35	33.53	51.35	2.02
0.08	149.668	20.18	1.50	24.3	64.3	44.1	19.82	12.13	31.95	52.13	2.22
0.11	158.081	21.59	2.00	25.5	65.5	43.9	18.41	12.74	31.15	52.74	2.38
0.14	164.429	22.40	2.50	26.4	66.4	44.0	17.60	13.19	30.79	53.19	2.50
0.17	170.712	22.89	3.00	27.2	67.2	44.4	17.11	13.62	30.73	53.62	2.59
0.19	173.876	23.13	3.50	27.6	67.6	44.5	16.87	13.80	30.67	53.80	2.64
0.22	180.271	23.29	4.00	28.5	68.5	45.2	16.71	14.24	30.95	54.24	2.70
0.25	184.170	23.37	4.50	28.9	68.9	45.6	16.63	14.47	31.10	54.47	2.74
0.28	185.727	23.36	5.00	29.0	69.0	45.7	16.64	14.51	31.16	54.51	2.74
0.31	189.456	23.31	5.50	29.5	69.5	46.1	16.69	14.73	31.42	54.73	2.76
0.33	190.888	23.29	6.00	29.5	69.5	46.2	16.71	14.76	31.47	54.76	2.77
0.36	194.829	23.21	6.50	30.0	70.0	46.8	16.79	14.99	31.78	54.99	2.78
0.39	195.711	23.10	7.00	29.9	69.9	46.8	16.90	14.97	31.87	54.97	2.77
0.42	199.881	23.00	7.50	30.4	70.4	47.4	17.00	15.21	32.21	55.21	2.79
0.44	202.321	22.85	8.00	30.6	70.6	47.8	17.15	15.31	32.46	55.31	2.79
0.47	202.734	22.66	8.50	30.5	70.5	47.9	17.34	15.26	32.60	55.26	2.76
0.50	205.242	22.63	9.00	30.7	70.7	48.1	17.37	15.36	32.73	55.36	2.77
0.53	206.156	22.45	9.50	30.7	70.7	48.2	17.55	15.35	32.90	55.35	2.75
0.55	208.356	22.47	10.00	30.9	70.9	48.4	17.53	15.43	32.96	55.43	2.76
0.61	212.113	22.32	11.00	31.1	71.1	48.7	17.68	15.53	33.21	55.53	2.76
0.67	214.243	22.10	12.00	31.0	71.0	48.9	17.90	15.51	33.41	55.51	2.73
0.72	215.481	22.00	13.00	30.8	70.8	48.8	18.00	15.42	33.42	55.42	2.71
0.74	215.974	21.98	13.30	30.8	70.8	48.8	18.02	15.40	33.42	55.40	2.71
0.75	217.803	22.00	13.60	31.0	71.0	49.0	18.00	15.48	33.48	55.48	2.72


Notes:

$p = s_1 + s_3/2$ $q = s_1 - s_3/2$
 $p' = s_1' + s_3'/2$ $q' = s_1' - s_3'/2$
 Wet Method Saturation


Prepared by: Jay Date: 10/20/14
 Checked by: KL Date: 10/20/14




**Triaxial Compression Total and Effective Stress Paths at Failure (p-q Space)
 Max Effective Stress Ratio, Sample 30RWB-03, ST#4, 28.5' to 30'**




Sample 30-RWB-03, ST#4, 28.5' to 30': Stress v. Strain and Pore Pressure v. Strain Curves
 All Confining Pressures



Sample 30-RWB-03, ST#4, 28.5' to 30': A-Parameter During Shearing
 All Confining Pressures



APPENDIX C



Undrained Analysis for MSE Wall at Station 8548+75, Ref Borings 31-RWB-03 and VST-03

Layer ID	Description	Unit Weight (pcf)	Undrained Cohesion (psf)	Undrained Friction Angle (degrees)
1	Loose to M Dense Gr SAND to SA GRAVEL FILL	125	0	30
2	Soft to M Stiff CL LOAM FILL	120	1200	0
3	Soft to M Stiff CL to SI CL	110	480	0
4	Soft to M Stiff CL to SI CL	110	590	0
5	M Stiff CL to SI CL	115	850	0
6	Stiff CL to SI CL	120	1300	0

GLOBAL STABILITY ANALYSIS: CIRCLE INTERCHANGE RECONSTRUCTION, RETAINING WALL 31, SN 016-1820, CHICAGO, IL

SCALE: GRAPHICAL

APPENDIX C-1


DRAWN BY: NSB
CHECKED BY: MWS



1145 N. Main Street
Lombard, IL 60148
www.wangeng.com

FOR AECOM

1100-04-01



Drained Analysis for MSE Wall at Station 8548+75, Ref Borings 31-RWB-03 and VST-03

Layer ID	Description	Unit Weight (pcf)	Drained Cohesion (psf)	Drained Friction Angle (degrees)
1	Loose to M Dense Gr SAND to SA GRAVEL FILL	125	0	30
2	Soft to M Stiff CL LOAM FILL	120	100	30
3	Soft to M Stiff CL to SI CL	110	0	28
4	Soft to M Stiff CL to SI CL	110	0	28
5	M Stiff CL to SI CL	115	0	28
6	Stiff CL to SI CL	120	100	30

GLOBAL STABILITY ANALYSIS: CIRCLE INTERCHANGE RECONSTRUCTION, RETAINING WALL 31, SN 016-1820, CHICAGO, IL

SCALE: GRAPHICAL

APPENDIX C-2

DRAWN BY: NSB
CHECKED BY: MWS




1145 N. Main Street
Lombard, IL 60148
www.wangeng.com

FOR AECOM

1100-04-01


APPENDIX D

I:\4340 AM - pwr\AECOM-NA-AWS\aescomonline\local\AECOM_D502_NA\Documents\01\Americas\Transportation\60269938_Circle\Phase_II\000_CAD\008_Structure\Sheet\016R20-62A76-SHT-1SL-002.dgn



CROSS SECTION

(Looking Upstation, Sta. 8546+77.99 to Sta. 8547+77.43)



CROSS SECTION

(Looking Upstation, Sta. 8547+77.43 to Sta. 8548+87.21)

* The M.S.E. Wall supplier's internal stability design shall account for the anchorage slab's bearing pressure surcharge of 1.0 ksf and horizontal sliding force of 0.83 kips/ft of wall.

TABLE 1 - WALL ELEVATIONS

Station	Offset	Elevation A	Elevation B	Elevation C	Elevation D	Elevation E	Elevation F	Elevation G	Elevation H	Elevation I
8546+77.99	20.41' Lt.	585.83	582.33	580.25	578.50	584.07	580.33	576.83	586.53	-
8546+98.14	21.62' Lt.	587.01	583.51	581.43	579.68	584.03	580.30	576.80	585.00	585.73
8547+28.38	23.43' Lt.	589.15	585.65	583.57	581.82	583.76	580.10	576.60	584.48	586.44
8547+58.65	25.25' Lt.	591.42	587.92	585.83	584.08	583.27	579.69	576.19	583.17	590.33
8547+88.98	25.25' Lt.	593.64	590.14	588.05	586.30	582.56	578.89	575.39	583.95	591.67
8548+19.32	25.25' Lt.	595.48	591.98	589.90	588.15	581.78	578.03	574.53	582.36	592.73
8548+49.65	25.25' Lt.	596.90	593.40	591.32	589.57	581.17	577.33	573.83	580.31	593.72
8548+68.45	26.46' Lt.	597.65	594.15	592.06	590.31	580.79	577.01	573.51	580.40	594.16
8548+87.21	27.67' Lt.	598.32	594.82	592.74	590.99	580.45	576.72	573.22	581.08	594.69

Elevation A - Top of Parapet
 Elevation B - Finished Grade at B.F. of Wall
 Elevation C - Top of Coping
 Elevation D - Bottom of Coping / Top of Exposed Panel Line
 Elevation E - Top of Slope at F.F. of Wall
 Elevation F - Finished Grade at F.F. of Barrier
 Elevation G - Top of Theoretical Leveling Pad
 Elevation H - Existing Grade at F.F. of Wall
 Elevation I - Top of Existing Wall

LEGEND:

B.F. - denotes Back Face.
 F.F. - denotes Front Face.

CROSS SECTION AND DETAILS
RETAINING WALL 31 ALONG MADISON NB EXIT RAMP
F.A.I. RTE. 90/94 (KENNEDY EXPRESSWAY)
SECTION 2015-019R
COOK COUNTY
STATION 8546+77.99 TO STATION 8548+87.21
STRUCTURE NO. 016-1820



USER NAME = wjcolletti	DESIGNED - JNP	REVISED -
	CHECKED - WJC/MDS	REVISED -
PLOT SCALE = 0.17' / in.	DRAWN - JNP	REVISED -
PLOT DATE = 5/10/2019	CHECKED - WJC/MDS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


SHEET NO. 2 OF 2 SHEETS

F.A.I. RTE. 90/94	SECTION 2015-019R	COUNTY COOK	TOTAL SHEETS 2	SHEET NO. 2
CONTRACT NO. 62A76			ILLINOIS FED. AID PROJECT	

APPENDIX E

DATE	
BY	
FINAL SURVEY NO.	
SURVEY PLOTTED	
NOTE BOOK	
AREAS CHECKED	

DATE	
BY	
ORIGINAL SURVEY NO.	
SURVEY PLOTTED	
NOTE BOOK	
AREAS CHECKED	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn
 USER NAME = zmzaranko
 PLOT SCALE = 20.0000' / in.
 PLOT DATE = 5/1/2019

DESIGNED -
 DRAWN -
 CHECKED -
 DATE - \$DATE

REVISED -
 REVISED -
 REVISED -
 REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**


**CROSS SECTIONS
 RETAINING WALL NO. 31**

SCALE: 10'H 5'V SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT	1
			CONTRACT NO. 62A76	
ILLINOIS FED. AID PROJECT				


DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
FINAL SURVEY NOTE BOOK NO.	

DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
ORIGINAL SURVEY NOTE BOOK NO.	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn	DESIGNED -	REVISED -
USER NAME = zmzaranko	DRAWN -	REVISED -
PLOT SCALE = 20.0000' / in.	CHECKED -	REVISED -
PLOT DATE = 5/1/2019	DATE - \$DATE	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**CROSS SECTIONS
RETAINING WALL NO. 31**


SCALE: 10'H 5'V SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT 2	2
CONTRACT NO. 62A76				

ILLINOIS FED. AID PROJECT


DATE	
BY	
FINAL SURVEY NO.	
SURVEY PLOTTED	
TEMPLATE AREAS CHECKED	
NOTE BOOK NO.	

DATE	
BY	
ORIGINAL SURVEY NO.	
SURVEY PLOTTED	
TEMPLATE AREAS CHECKED	
NOTE BOOK NO.	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn
 USER NAME = zmzaranko
 PLOT SCALE = 20.0000' / in.
 PLOT DATE = 5/1/2019

DESIGNED -
 DRAWN -
 CHECKED -
 DATE - \$DATE

REVISED -
 REVISED -
 REVISED -
 REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**CROSS SECTIONS
 RETAINING WALL NO. 31**


SCALE: 10'H 5'V SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT 3	
CONTRACT NO. 62A76				

ILLINOIS FED. AID PROJECT


DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
FINAL SURVEY NOTE BOOK NO.	

DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
ORIGINAL SURVEY NOTE BOOK NO.	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn
 USER NAME = zmzaranko
 PLOT SCALE = 20.0000' / in.
 PLOT DATE = 5/1/2019

DESIGNED -	REVISIED -
DRAWN -	REVISIED -
CHECKED -	REVISIED -
DATE - \$DATE	REVISIED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**CROSS SECTIONS
 RETAINING WALL NO. 31**


SCALE: 10'H 5'V SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT 4	
				CONTRACT NO. 62A76

ILLINOIS FED. AID PROJECT


DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
FINAL SURVEY	
NOTE BOOK	
NO.	

DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
ORIGINAL SURVEY	
NOTE BOOK	
NO.	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn	DESIGNED -	REVISED -
USER NAME = zmzaranko	DRAWN -	REVISED -
PLOT SCALE = 20.0000' / in.	CHECKED -	REVISED -
PLOT DATE = 5/1/2019	DATE - \$DATE	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**CROSS SECTIONS
RETAINING WALL NO. 31**

SCALE: 10'H 5'V SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT 5	
CONTRACT NO. 62A76				
ILLINOIS FED. AID PROJECT				


DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS CHECKED	
FINAL SURVEY NOTE BOOK NO.	

DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS CHECKED	
ORIGINAL SURVEY NOTE BOOK NO.	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn	DESIGNED -	REVISED -
USER NAME = zmzaranko	DRAWN -	REVISED -
PLOT SCALE = 20.0000' / in.	CHECKED -	REVISED -
PLOT DATE = 5/1/2019	DATE - \$DATE	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**CROSS SECTIONS
RETAINING WALL NO. 31**


SCALE: 10'H 5'V SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT 6	# 6
CONTRACT NO. 62A76				

ILLINOIS FED. AID PROJECT

DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
FINAL SURVEY NOTE BOOK NO.	

DATE	
BY	
SURVEYED	
PLOTTED	
TEMPLATE	
AREAS	
CHECKED	
ORIGINAL SURVEY NOTE BOOK NO.	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn	DESIGNED -	REVISED -
USER NAME = zmzaranko	DRAWN -	REVISED -
PLOT SCALE = 20.0000' / in.	CHECKED -	REVISED -
PLOT DATE = 5/1/2019	DATE - \$DATE	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**CROSS SECTIONS
RETAINING WALL NO. 31**

SCALE: 10H 5V SHEET OF SHEETS STA. TO STA.


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT 7	
CONTRACT NO. 62A76				

ILLINOIS FED. AID PROJECT

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


DATE	
BY	
FINAL SURVEY NO.	
SURVEY PLOTTED	
NOTE BOOK	
AREAS CHECKED	

DATE	
BY	
ORIGINAL SURVEY NO.	
SURVEY PLOTTED	
NOTE BOOK	
AREAS CHECKED	



NOTES

EXISTING UTILITIES SHOWN ARE BASED ON SUE LOCATE INFORMATION. DEPTHS OF UTILITIES ARE BASED ON ASSUMED DEPTHS OR RECORD INFORMATION IF AVAILABLE. EXTENTS OF UNDERGROUND STRUCTURES ARE ESTIMATED BASED ON UTILITY ATLAS INFORMATION, EXISTING AND PROPOSED SEWER IS SHOWN BASED ON SURVEY DATA, ATLAS INFORMATION AND THE PROPOSED PLANS.



D162A76-EXH-XS-ZZ-WRK.dgn	DESIGNED -	REVISED -
USER NAME = zmzaranko	DRAWN -	REVISED -
PLOT SCALE = 20.0000' / in.	CHECKED -	REVISED -
PLOT DATE = 5/1/2019	DATE - \$DATE	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**CROSS SECTIONS
RETAINING WALL NO. 31**

SCALE: 10H 5V SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2015-D18R	COOK	#TOT	8
				CONTRACT NO. 62A76

ILLINOIS FED. AID PROJECT