TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	P'ROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R R	\boxtimes	\blacksquare	EMERGENCY VEHICLE LIGHT DETECTOR	R	~	•	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE		<u></u>	<u>—(1)—</u>
RAILROAD CONTROL CABINET		B ≻√ B	▶⋖	CONFIRMATION BEACON	R ₀ (]	o-G	⊷ 1	NOT 14 17 C, UNLESS NOTES CHERRISE		<i>y</i> -	
COMMUNICATIONS CABINET	[CC] ^R	ECC	CC	HANDHOLE	R □	2		COAXIAL CABLE		<u>—</u> ©—	<u> </u>
MASTER CONTROLLER		EMC	MC	HANDHULE						~	
MASTER MASTER CONTROLLER	q	EMMC	MMC	HEAVY DUTY HANDHOLE	R	H		VENDOR CABLE FOR CAMERA		XÝ	V
UNINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	ZAU	DOUBLE HANDHOLE	Ř SS		XX	COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		6	6
SERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT		۹ 4 <u>-</u>	- -	JUNCTION BOX	Ŕ	Q	ø	FIBER OPTIC CABLE		(125)	
FELEPHONE CONNECTION P) POLE OR (G) GROUND MOUNT	ਕੇ [<u>ੱ</u>]	P.	P	GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	D	STANCE OF SUPERISCHED		NO. 62.5/125, MM12F FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		— <u>2</u> 45—	—24F)—
STEEL MAST ARM ASSEMBLY AND POLE	¹⁷ O	0	•	AND CABLE.	<u></u>					7	
LUMINUM MAST ARM ASSEMBLY AND POLE	() ()	Q112===		COMMON TRENCH			CT	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		-	-
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	^R O ⊅ ·······	0-×	⊕ ———	COILABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		5	CNC S	NOTED ON PLANS) GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		c —	c,⊪_•
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH PTZ CAMERA	R _Q	PZI	PIZ	INTERSECTION ITEM		I	IP.	OR (S) SERVICE		13	"
SIGNAL POST	8	0	•	REMOVE ITEM	R ·			CONTROLLER CABINET AND	RCF		
EMPORARY WOOD POLE (CLASS 5 OR	°O R⊗	8	©	RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED			
BETTERU 45 FOOT (13.7m) MINIMUM	⊗ > <u>r</u>	>-~	> <u> </u>	ABANDON ITEM 12" (300mm) TRAFFIC SIGNAL SECTION	A;	(R)	R	STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	CRMF		
IGNAL HEAD	R		-			t Dentil		ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF O		
IGNAL HEAD CONSTRUCTION STAGES NUMBERS INDICATE THE CONSTRUCTION STAGE)	→ >	_	2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF		
IGNAL HEAD WITH BACKPLATE	+ P	+[>>	+			R	R	FOUNDATION TO BE REMOVED	<u>○->t</u>		
IGNAL HEAD OPTICALLY PROGRAMMED	R —D''?''	— >b.,	- > ′′₽′′	SIGNAL FACE			G	SIGNAL POST AND FOUNDATION	SMF O		
LASHER INSTALLATION S DENOTES SOLAR POWER)	R ○ Ç>′F″	O- ⊳ ″F″	•'F''			6	4 Y 4 G	TO BE REMOVED INTERSECTION & SAMPLING (SYSTEM) DETECTOR		[IS]	IS
EDESTRIAN SIGNAL HEAD	R.	-[]	-1			R	R	SAMPLING (SYSTEM) DETECTOR			S
EDESTRIAN PUSHBUTTON DETECTOR	R (**)	©	®	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		Ğ	G	EXISTING INTERSECTION LOOP DETECTOR		[<u>-</u>]	
CCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	<u></u> @A≥S	APS O O O O O O O O O O O O O			(♣) (♣)	4 Y 4 G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTO EXISTING PREFORMED INTERSECTION LOOP DETECTOR	२	<u> </u>	
LLUMINATED SIGN 'NO LEFT TURN''	r 5	5	(S)				ири	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTO	₹	#I	
LLUMINATED SIGN	15			12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		(59) (w)		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		; [2]	RIS
NO RIGHT TURN"	0	Ø	®	12" (300mm) PEDESTRIAN SIGNAL HEAD				PREFORMED SAMPLING (SYSTEM) DETECTOR		֓֞֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	PS
ETECTOR LOOP, TYPE I		[]		INTERNATIONAL SYMBOL, OUTLINED		10.4-07			***************************************	W- 2-9	41
REFORMED DETECTOR LOOP)	9	12" (300mm) PEDESTRIAN ŞIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		(*)	*	RAILROAD SYMBOLS			
ICROWAVE VEHICLE SENSOR	R Mil	Ma	₩	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		(€) C	₽ C X D			EXISTING	PROPOSED
IDEO DETECTION CAMERA	\$ \(\frac{1}{2}\)	(V)	(V)	RADIO INTERCONNECT		O -1111 O		RAILROAD CONTROL CABINET		R R	
IDEO DETECTION ZONE					1.			RAJLROAD CANTILEVER MAST ARM	∑ -c	Z - 2- X	X C
	R			RADIO REPEATER	RERR	ERR	RR	FLASHING SIGNAL	And the	XoX	XOX
AN, TILT, ZOOM CAMERA	FIZE		PIZ)	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,		—(5)—					
MIRELESS DETECTOR SENSOR	^R ₩	W	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED		<i>>=</i> /	<u> </u>	CROSSING GATE		X0X	X0 X=
VIRELESS ACCESS POINT	<u>R</u>		(r	GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)	(1)	CROSSBUCK		75	*
NAME = USER NAME = bacendl 		ESIGNED - DAGZBÇK RAWN - BCK	REVISED - STATE OF ILLINOIS					DISTRICT ONE F.A.P. SECTION COUNTY SH			
PLOY SCALE, = 56,4996 17 1									361	C6-0C214-18-RP TS-05	CONTRACT NO.