

1' 0" VERIFY

1 1/2" RADIUS AT ALL FOUR CORNERS

HANDICAPPED PARKING LOGO  
COLOR, HEIGHT OF POLE, AND  
DIMENSIONS OF SIGN TO BE  
INSTALLED PER GOVERNMENTAL  
REQUIREMENTS AND ADA GUIDELINES.

54" VERIFY

1' 6" VERIFY

2" x 2" 3/16" STEEL TUBE  
PAINT TO MATCH STEEL  
PLATE ABOVE

2"

FINISH GRADE (CONDITION VARIES  
SEE PLAN)


6" MIN.

1' 6" VERIFY

1' 0" VERIFY

8" DIAMETER  
CONCRETE FOOTING

- HANDICAPPED PARKING  
SIGN & POST

AGGREGATE SUBGRADE IMPROVEMENT. 4<sup>2</sup>

COMPACTED SUBGRAD

4" SOLID YELLOW PAVEMENT MARKING  
@ 45° ON 4' CENTERS

6" RADIUS

PAINT TO MATCH SHOPPING CENTER STANDARD OR AS REQUIRED.

2'0"

5"

1'

1'0"

8"

1'9"

2'0"

23°

1'0"

3"

1'6"

8"

CENTER OF PARKING SPACE

CONFIRM DIMENSIONS, CONFIGURATION, AND COLORS WITH LOCAL GOVERNMENTAL AGENCY AND ADA GUIDELINES

- EAST ISLAND CONCRETE JOINTING PLAN

