

**EROSION CONTROL BLANKET**

LOCATION	LENGTH (FOOT)	AVERAGE WIDTH (FOOT)	AREA (SQ YD)
<b>SECTION A:</b>			
<b>W.B.</b>			
LT STA 58+50 TO 69+50	1,100	8	978
LT STA 69+50 TO 83+00	1,350	8	1,200
LT STA 83+00 TO 94+00	1,100	8	978
LT STA 94+00 TO 106+00	1,200	8	1,067
LT STA 106+00 TO 118+00	1,200	8	1,067
LT STA 118+00 TO 129+00	1,100	8	978
LT STA 129+00 TO 134+00	500	8	444
<b>SECTION B:</b>			
<b>W.B.</b>			
LT STA 10+00 TO 45+47	485	8	431
LT STA 45+47 TO 81+56	1,422	8	1,264
LT STA 81+56 TO 117+57	1,842	8	1,637
LT STA 117+57 TO 142+03	1,801	8	1,601
<b>TOTAL</b>			<b>11,644</b>

**TEMPORARY EROSION CONTROL SEEDING**

LOCATION	LENGTH (FOOT)	AVERAGE WIDTH (FOOT)	QUANTITIES (POUND)
<b>SECTION A:</b>			
<b>W.B.</b>			
LT STA 58+50 TO 69+50	1100.0	8	20.20
LT STA 69+50 TO 83+00	1350.0	8	24.79
LT STA 83+00 TO 94+00	1100.0	8	20.20
LT STA 94+00 TO 106+00	1200.0	8	22.04
LT STA 106+00 TO 118+00	1200.0	8	22.04
LT STA 118+00 TO 129+00	1100.0	8	20.20
LT STA 129+00 TO 134+00	500.0	8	9.18
<b>SECTION B:</b>			
<b>W.B.</b>			
LT STA 10+00 TO 45+47	485	8	8.91
LT STA 45+47 TO 81+56	1,422	8	26.11
LT STA 81+56 TO 117+57	1,842	8	33.83
LT STA 117+57 TO 142+03	1,801	8	33.07
<b>TOTAL</b>			<b>240.6</b>

**PERIMETER EROSION BARRIER**

LOCATION	QUANTITIES (FOOT)
<b>SECTION A &amp; B:</b>	
<b>W.B.</b>	
(TO BE PLACED BY THE ENGINEER ABOUT EVERY 200' / 20' EACH)	5,000.00
<b>TOTAL</b>	<b>5,000.00</b>

**SAW CUTTING\***

LOCATION	LENGTH (FOOT)
<b>SECTION A:</b>	
<b>W.B.</b>	
LT STA. 59+00 TO 80+00	2,100
LT STA. 83+29 TO 99+00	1,571
LT STA. 100+72 TO 109+07	835
LT STA. 110+80 TO 134+00	2,320
<b>SECTION B:</b>	
<b>W.B.</b>	
LT STA. 10+00 TO 59+77	4,977
LT STA. 63+29 TO 91+27	2,798
LT STA. 91+52 TO 142+05	5,053
<b>TOTAL</b>	<b>19,654</b>

\* SAW CUTTING SHALL BE PERFORMED AT THE EDGE OF EXISTING SHOULDER TO PROVIDE A CLEAN EDGE. EXISTING SHOULDERS ARE APPROXIMATELY 10" THICK. NO ADDITIONAL COMPENSATIONS WILL BE ALLOWED FOR VARIATION THICKNESSES

**HOT MIX ASPHALT SHOULDER 10"**

LOCATION	LENGTH (FOOT)	WIDTH (FOOT)	AREA (SQ YD)
<b>SECTION A:</b>			
<b>W.B.</b>			
<b>4' WIDE</b>			
LT STA. 125+67 TO 134+00	833	4	370
<b>6' WIDE</b>			
LT STA. 59+00 TO 80+00	2100	6	1,400
LT STA. 83+29 TO 99+00	1571	6	1,047
LT STA. 100+72 TO 109+07	835	6	557
LT STA. 110+80 TO 125+67	1487	6	991
<b>SECTION B:</b>			
<b>W.B.</b>			
<b>4' WIDE</b>			
LT STA. 10+00 TO 65+07	5507	4	2,448
<b>6' WIDE</b>			
LT STA. 65+07 TO 139+84	7477	6	4,985
<b>4' WIDE</b>			
LT STA. 139+84 TO 142+05	221	4	98
<b>TOTAL</b>			<b>11,896</b>