

RESURFACING				
		MICROSURFACING SINGLE PASS TYPE II	BITUMINOUS MATERIALS PRIME COAT	MIXTURE FOR CRACKS, JOINTS, & FLANGWAYS
STATIONS	LENGTH	SQ YD	GALLON	TON
8+22 TO 66+30	5,808.0	1291	103	0.30
97+98 TO 129+66	3,168.0	704	56	0.17
145+50 TO 172+66	2,716.0	604	48	0.14
TOTALS		2598	208	1

PAVEMENT MARKING										
LOCATION	DESCRIPTION	LENGTH	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL	PAINT PAVEMENT MARKING - LINE 4"	PAINT PAVEMENT MARKING - LINE 6"	TEMPORARY PAVEMENT MARKING - LINE 4"	TEMPORARY PAVEMENT MARKING - LINE 6"	PAVEMENT MARKING REMOVAL	SHORT TERM PAVEMENT MARKING	WORK ZONE PAVEMENT MARKING REMOVAL
				YELLOW FOOT	YELLOW FOOT	YELLOW FOOT	YELLOW FOOT			
STATIONS		FOOT	EACH	FOOT	FOOT	FOOT	FOOT	SQ FT	FOOT	SQ FT
0+00	INTERSECTION OF IL 72 AND IL 23									
0+00 TO 8+22	NO WORK									
8+22 TO 13+91	DOUBLE SOLID	569		2,276		1138		379	56	19
13+91 TO 20+01	SOLID LT, DASH RT	610		1,220	300	610	150	278	60	20
20+01 TO 34+34	DASH	1,433			720		360	180	144	48
34+34 TO 43+85	DASH LT, SOLID RT	951		1,902	480	951	240	437	96	32
43+85 TO 60+68	SOLID LT, DASH RT	1,683		3,366	840	1683	420	770	168	56
60+68 TO 65+92	DASH	524			260		130	65	52	17
65+92 TO 77+41	DASH LT, SOLID RT	1,149		2,298	580	1149	290	528	116	39
77+41 TO 87+74	SOLID LT, DASH RT	1,033		2,066	520	1033	260	474	104	35
87+74 TO 87+76	GAP	2								
87+76 TO 98+52	DASH LT, SOLID RT	1,076		2,152	540	1076	270	493	108	36
98+52 TO 112+47	DOUBLE SOLID	1,395		5,580		2790		929	140	47
112+47 TO 121+58	SOLID LT, DASH RT	911		1,822	460	911	230	418	92	31
121+58 TO 125+08	DASH	350			180		90	45	36	12
125+08 TO 131+03	DASH LT, SOLID RT	595		1,190	300	595	150	273	60	20
131+03 TO 143+83	DOUBLE SOLID	1,280		5,120		2560		852	128	43
143+83 TO 145+11	S.N. 019-0033	128		512		256				
145+11 TO 145+64	DOUBLE SOLID	53		212		106		35	4	1
145+64 TO 148+29	SOLID LT, DASH RT	265		530	140	265	70	123	28	9
148+29 TO 169+25	DASH	2,096			1040		520	260	212	71
169+25 TO 172+66	DASH LT, SOLID RT	341		682	180	341	90	159	36	12
TOTALS		3,111	135	30,928	6540	15,464	3270	6699	1640	546