



LEGEND

EXISTING		PROPOSED
-----	STORM CULVERT	-----
-----	R.O.W.	-----
←	SURFACE FLOW	→
~	DITCH FLOW	~
[Wetland symbol]	WETLAND	
—A—	ELECTRICAL OVERHEAD LINE	
□	ELECTRICAL POLE	
◀	RCP FLARED END SECTION	
—T—	AT&T BURRIED CABLE	
-965-	CONTOURS	

- NOTE:**
1. THE TEMPORARY DITCH SHALL HAVE MINIMUM SIDE SLOPE 2:1 BOTTOM WIDTH OF 2 FEET AND MINIMUM 0.3% SLOPE. THE BOTTOM ELEVATION SHALL BE SUFFICIENT TO REROUTE EXISTING DITCH FLOW.
 2. DE-ENERGIZING COMED'S DISTRIBUTION LINES(=34,000 VOLTS) OR TRANSMISSION LINES (>34,000 VOLTS) MAY BE NECESSARY IN ORDER TO ACCOMODATE CONTRACTOR'S EQUIPMENT. COSTS MAY BEINVOLVED. CALL 1(800) EDISON1.
 3. THE STATION AND OFFSET ARE MEASURED FROM THE END OF PIPE.

FILE NAME = #FILES
 PLOT SCALE = 1/8"=1'-0"
 USER NAME =

AEG Ltd.
 3100 Dundee Road, Suite 502, Northbrook, IL 60062
 847.753.8020 office 847.753.8023 fax

DESIGNED - JX	REVISED -
DRAWN - JX	REVISED -
CHECKED - CW	REVISED -
DATE - 3/11/2014	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**US 14
 OVER LAWRENCE CREEK TRIBUTARY**

**DRAINAGE AND UTILITY
 PLAN-STAGE 2**

SCALE: 1"=50' SHEET OF SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
066	21B-R	MCHENRY	40	10
CONTRACT NO. 60V25				
ILLINOIS FED. AID PROJECT				