



NOTES:

1. The area immediately west of the pavement should be backfilled so the drop off height is less than or equal to 12".
2. Part of temporary pavement will remain and be used as southbound shoulder.

- * Remove portions of temporary pavement as needed to construct pavement in Stage III Construction.
- ** Remove temporary pavement outside limits of shoulder and install Mounted Guardrail during Stage IV Construction.

HBM
ENGINEERING GROUP, LLC
CONSULTING & DESIGN
INSPECTION & TESTING
RESEARCH & TESTING

4415 WEST HARRISON ST.
SUITE 231
HILLSIDE, IL 60162
PHONE: (708) 236-0900
FAX: (708) 236-0901

USER NAME = mustafa.alobaidi
FILE NAME = 0560086-60V25-003-Stage Const Dtl2.dgn
PLOT SCALE = N.T.S.
PLOT DATE = 5/2/2014

DESIGNED - JMG, MAF
CHECKED - MI
DRAWN - JMG, PH
CHECKED - MI, MAI

REVISED
REVISED
REVISED
REVISED

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**STAGE CONSTRUCTION DETAILS II
STRUCTURE NO. 056-0086**

SHEET NO. S-3 OF 11 SHEETS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
066	21B-R	MCHENRY	40	23
CONTRACT NO. 60V25				
ILLINOIS FED. AID PROJECT				