

PATCHING SCHEDULE	CLASS A PATCHES, THPE II, 8 INCH	CLASS A PATCHES, TYPE III, 8 INCH	CLASS A PATCHES, TYPE II, 12 INCH	CLASS A PATCHES, TYPE III, 12 INCH	CLASS A PATCHES, TYPE II, 14 INCH	CLASS B PATCHES, TYPE II, 11 INCH	CLASS B PATCHES, TYPE III, 11 INCH	CLASS B PATCHES, TYPE II, 11 INCH	CLASS B PATCHES, TYPE II, 13 INCH	CLASS B PATCHES, TYPE III, 13 INCH	CLASS B PATCHES, TYPE II, 16 INCH	CLASS B PATCHES, TYPE III, 16 INCH	SAW CUTS	DOWEL BARS, 1 1/2"	TIE BARS, 1 1/4"	PAVEMENT FABRIC	PATCHING REINFORCEMENT	PAVED SHOULDER REMOVAL	HOT-MIX ASPHALT SHOULDERS
	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD	FOOT	EACH	EACH	SQ YD	SQ YD	SQ YD	TON
EASTBOUND	-	-	-	-	120.1	-	-	-	-	-	126.5	56.0	1678	300	14	56.0	120.1	3616.4	2835.2
WESTBOUND	-	-	-	-	-	-	-	-	-	-	828.2	20.0	4296	1680	7	20.0	-	3616.4	2835.2
RAMP A	-	-	-	-	-	-	-	-	49.2	15.6	-	-	880	370	-	15.6	-	-	-
RAMP B	-	-	-	-	-	-	-	-	29.7	-	-	-	160	68	-	-	-	-	-
RAMP C	-	-	-	-	-	-	-	-	55.0	-	-	-	310	130	-	-	-	-	-
RAMP D	-	-	-	-	-	-	-	-	9.3	-	-	-	54	24	-	-	-	-	-
WEIGH STATION OFF RAMP	-	-	-	-	-	39.3	16.7	80.8	-	-	-	-	492	124	57	97.5	-	-	-
WEIGH STATION	55.8	24.9	55.8	24.9	-	-	-	-	-	-	-	-	1464	-	-	-	385.4	-	-
TOTALS:	56	25	56	25	120	39	17	81	143	16	955	76	9334	2696	78	189	506	7233	5670

GUARDRAIL SCHEDULE	GUARDRAIL REMOVAL	TRAFFIC BARRIER TERMINAL, TYPE 6	TRAFFIC BARRIER TERMINAL, TYPE 6B	TRAFFIC BARRIER TERMINAL, TYPE 6B (SPECIAL)	TRAFFIC BARRIER TERMINAL, TYPE 2	STEEL PLATE BEAM GUARD RAIL, TYPE A, 6 FOOT POSTS	TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) TANGENT	TERMINAL MARKERS - DIRECT APPLIED	GUARDRAIL MARKERS, TYPE A
	FOOT	EACH	EACH	EACH	EACH	FOOT	EACH	EACH	EACH
I 70 EB									
SN 026-0076 PIER PROTECTION	854.0	0.0	0.0	1.0	1.0	487.5	1.0	1.0	8.0
STA. 827+11 TO STA. 827+77	66.0	0.0	0.0	0.0	1.0	162.5	1.0	1.0	4.0
SN 026-0054 PIER PROTECTION	468.0	0.0	1.0	0.0	0.0	162.5	1.0	1.0	4.0
STA. 872+02 TO STA. 874+30	228.0	0.0	0.0	0.0	1.0	162.5	1.0	1.0	4.0
SN 026-0078 PIER PROTECTION	369.0	0.0	1.0	0.0	0.0	162.5	1.0	1.0	4.0
I 70 WB									
SN 026-0076 PIER PROTECTION	680.0	0.0	1.0	0.0	0.0	162.5	1.0	1.0	4.0
SN 026-0054 PIER PROTECTION	467.0	0.0	1.0	0.0	0.0	162.5	1.0	1.0	4.0
SN 026-0078 PIER PROTECTION	442.0	0.0	1.0	0.0	0.0	162.5	1.0	1.0	4.0
OVERHEAD STURCTURE									
SN 026-0049 SE CORNER	367.0	1.0	0.0	0.0	0.0	250.0	1.0	1.0	4.0
SN 026-0049 SW CORNER	363.0	1.0	0.0	0.0	0.0	250.0	1.0	1.0	4.0
SN 026-0049 NE CORNER	367.0	1.0	0.0	0.0	0.0	250.0	1.0	1.0	4.0
SN 026-0049 NW CORNER	380.0	1.0	0.0	0.0	0.0	262.5	1.0	1.0	4.0
TOTALS=	5051.0	4.0	5.0	1.0	3.0	2637.5	12.0	12.0	52.0