



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

September 12, 2018

SUBJECT Various Routes
Section D1 GRVD INT PVMNT MRK 18-37
Various Counties
Contract No. 46475
Item No. 1, September 21, 2018 Letting
Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised the Table of Contents to the Special Provisions.
2. Added page 48 to the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

Jack A. Elston, P.E.
Bureau Chief
Bureau of Design and Environment

A handwritten signature in black ink, reading "Ted B. Walschleger, P.E." with a stylized flourish at the end.

By: Ted B. Walschleger, P. E.
Engineer of Project Management

cc: Anthony Quigley, Region 1, District 1; Tim Kell

MS/ab

TABLE OF CONTENTS

LOCATION OF IMPROVEMENT	1
COMPLETION DATE.....	1
DESCRIPTION OF IMPROVEMENTS	1
TRAFFIC CONTROL PLAN.....	1
FAILURE TO OPEN TRAFFIC LANES TO TRAFFIC.....	2
KEEPING THE EXPRESSWAY OPEN TO TRAFFIC	3
TRAFFIC CONTROL AND PROTECTION (EXPRESSWAYS).....	4
TEMPORARY INFORMATION SIGNING.....	8
GENERAL CONSTRUCTION REQUIREMENTS.....	9
SPEED DISPLAY TRAILER (D1)	10
WORK ORDERS	11
FAILURE TO COMPLETE A WORK ORDER ON TIME.....	11
PREFORMED PLASTIC PAVEMENT MARKING TYPE D – D-1.....	12
45 MIL HOT SPRAY THERMOPLASTIC PAVEMENT MARKING:	14
QUANTITIES	20
FINAL CLEAN UP.....	21
FINAL INSPECTION AND PAYMENT	21
COMPENSABLE DELAY COSTS (BDE).....	21
CONSTRUCTION AIR QUALITY – DIESEL RETROFIT (BDE)	25
DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION (BDE).....	27
EQUIPMENT PARKING AND STORAGE (BDE)	38
GROOVING FOR RECESSED PAVEMENT MARKINGS (BDE)	39
LIGHTS ON BARRICADES (BDE)	42
PAVEMENT MARKING REMOVAL (BDE)	43
PAYMENTS TO SUBCONTRACTORS (BDE)	44
PORTABLE CHANGEABLE MESSAGE SIGNS (BDE)	44
PROGRESS PAYMENTS (BDE)	45
SUBCONTRACTOR AND DBE PAYMENT REPORTING (BDE).....	46
SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE)	46
WEEKLY DBE TRUCKING REPORTS (BDE).....	47
CONTRAST PREFORMED PLASTIC PAVEMENT MARKING D-1	48

REVISED 9/12/18

CONTRAST PREFORMED PLASTIC PAVEMENT MARKING D-1

Revise the first paragraph of Article 780.07(b) of the Standard Specifications to read:

“(b) Type B or C or D - Standard Application. Standard application of conventional preformed plastic pavement markings shall consist of applying the markings to the pavement surface or to the bottom of a groove recessed in the pavement surface as specified on the plans. Standard application of contrast preformed plastic pavement markings shall consist of applying the markings to the bottom of a groove recessed in the pavement surface. Both conventional and contrast preformed plastic pavement markings shall only be applied when the air temperature is at least 50 °F (10 °C) and rising and the pavement temperature is at least 70 °F (21 °C). However, application of the markings will not be allowed after October 15.”

Add the following paragraph after the fourth paragraph of Article 780.14 of the Standard Specifications:

“The applied line width specified for contrast pavement markings shall include both the white/yellow reflective portion and the black nonreflective portion of the marking.”

Revise the first paragraph of Article 1095.03 of the Standard Specifications to read:

“**1095.03 Preformed Plastic Pavement Markings.** The material shall consist of a white or yellow (as specified) weather resistant, reflective film meeting the requirements specified herein. Where contrast markings are specified, the white or yellow reflective film shall be bordered along both the left and right edges by a 1 1/2 in. (38 mm) wide black weather resistant, nonreflective film also meeting the requirements specified herein.”

Revise the table in Article 1095.03(a) of the Standard Specifications to read:

“Components	Minimum Percent By Weight	
	White or Yellow	Black
Resins and Plasticizers	20 %	20 %
Pigment and Fillers	30 %	30 %
Graded Glass Beads	25 %	- - “

Revise the first paragraph of Article 1095.03(h) of the Standard Specifications to read:

“Glass beads shall be uniformly distributed throughout the white or yellow portions of the material only. A top coating of beads shall be bonded to or directly embedded into the surface of the markings in order to produce immediate retroreflectivity.”

ADDED 9/12/18