

DISTRICT 2 STANDARDS

4-16-25

FULL SIZE

- 3.1 Mailbox Turnout in Curb and Gutter Section
- 4.1 PC Concrete Islands and Medians Accessible to the Disabled
- 5.1 Standard Outlet for Curb and Gutter
- 6.1 Precast Reinforced Concrete Flat Slab Top Centered and Offset Manhole - 36" Opening
- 11.1 Concrete End Sections for Parallel Pipe Culverts 15" thru 84" Dia.
- 12.1 Concrete End Sections for Parallel Pipe Arch Culverts 15" thru 84" Dia.
- 14.1 Traversable Pipe Grate for Parallel Drainage Structure
- 20.1 Hot-Mix Asphalt Approaches and Mailbox Returns
- 25.1 Entrance Approaches – Urban Area
- 26.1 ADA Curb Ramp Pavement Removal And Replacement
- 32.1 Sewer and Water Main Crossings
- 33.1 Concrete Collars for Pipe or Box Culvert Extensions
- 34.1 Work Zone Sign Details
- 35.1 Urban Lane Inside Closure, Multilane, 2W, with Mountable Median
- 36.1 Temporary Road Closure Expressway
- 37.1 Traffic Control for Three Lane Section
- 38.1 Traffic Control for Transition Areas
- 39.1 Traffic Control Typical Weave
- 40.1 Traffic Control for Road Closure
- 41.1 Typical Pavement Markings
- 53.1 Remove and Re-erect Steel Plate Beam Guardrail
- 54.1 Traffic Barrier Terminal, Type 2 (27" height)
- 55.1 Reflectors (Special)
- 68.1 Slotted Drain Pipe (Variable Height)
- 71.1 Detail of Flood Gate
- 72.1 40' Single Lane Median Crossover (45 mph Work Zone Speed Limit)
- 73.1 50' Single Lane Median Crossover (45 mph Work Zone Speed Limit)
- 74.1 64' Single Lane Median Crossover (45 mph Work Zone Speed Limit)
- 75.1 40' Single Lane Median Crossover (55 mph Work Zone Speed Limit)
- 76.1 50' Single Lane Median Crossover (55 mph Work Zone Speed Limit)
- 77.1 64' Single Lane Median Crossover (55 mph Work Zone Speed Limit)
- 78.1 88' Single Lane Median Crossover (55 mph Work Zone Speed Limit)
- 79.1 40' Two Lane Median Crossover (45 mph Work Zone Speed Limit)
- 80.1 50' Two Lane Median Crossover (45 mph Work Zone Speed Limit)
- 81.1 64' Two Lane Median Crossover (45 mph Work Zone Speed Limit)
- 82.1 40' Two Lane Median Crossover (55 mph Work Zone Speed Limit)
- 83.1 50' Two Lane Median Crossover (55 mph Work Zone Speed Limit)
- 84.1 64' Two Lane Median Crossover (55 mph Work Zone Speed Limit)
- 85.1 88' Two Lane Median Crossover (55 mph Work Zone Speed Limit)
- 86.1 Beveled Pipe & Guard Detail for Median Crossover
- 90.1 Traffic Barrier Terminal, Type 6B (Special)
- 92.1 Details of Planting and Bracing Trees

District 2 Standards Designer Notes
Full Size District 2 Standards

- 3.1 Use when a mailbox turnout is needed in a curb & gutter section and there isn't a parking lane or a mail delivery lane.
- 4.1 Use this when there are cross walks that will go through an island or median. Specify which option the contractor is required to use when building the Concrete Median (Special).
- 5.1 Use this when you need an outlet for curb and gutter, other than type B-6.24
- 11.1 This is to be used for pipe culverts, Class D under all sideroads.
- 12.1 This is to be used for EQRS pipe culverts, Class D under all sideroads.
- 14.1 Use this whenever you use District Standards 10.1, 11.1 & 12.1 and the culvert is within the main line clear zone.
- 20.1 Include for rural entrances and sideroads on 3R projects, reconstruction projects, or for new entrances. Do not include on 3P or Smart resurfacing projects.
- 25.1 Include for urban entrances with curb & gutter on 3R projects, reconstruction projects, or for new entrances. Do not include on 3P or Smart resurfacing projects.
- 26.1 Use this on all projects with ADA curb ramps requiring HMA replacement in front of curb & gutter.
- 32.1 Include in urban projects with proposed storm sewers or water mains.
- 33.1 Use this for pipe or box culvert extensions. Fill in the information in the table for the Bill of Materials.
- 34.1 Work Zone Sign Details. Include this when you have any of the following:
 - Include in projects where the clear width through a work zone with temporary concrete barrier wall will be 16.0 feet or less.
 - Include when using Traffic Control and Protection Standard 701316 or 701321.
 - Use this in conjunction with the special provision Traffic Control for Narrow Lanes which is under the Traffic Control Plan. Use this on one-lane stage construction jobs when the lane is less than 13'-6" measured from the toe of the barrier wall to the guardrail or bridge wall.
 - Use this when using District Standard 37.1 and 38.1.
 - Use this on low volume entrances that are between the traffic signals on Highway Standard 701316 or 701321.
 - Include this for any milling of the mainline pavement.
- 35.1 Use this when it is necessary to close the inside lane on an urban project. Also include Highway Standard 701606 and the pay item for 701606.
- 36.1 Use this district standard for any short term closure of an expressway at a diamond interchange.

District 2 Standards Designer Notes

- 37.1 Use this district standard for work that will require a lane closure in a three lane section such as a truck climbing lane.
- 38.1 Use this district standard when there is a transition from a four lane section that transitions to a two lane section.
- 39.1 Include on 4 lane highways where the contractor may change a portion of the work to the opposite lane.
- 40.1 Include for a mainline road closure.
- 41.1 Include in projects with pavement marking or raised reflective pavement markers.
- 53.1 Use this to remove and re-erect an old type steel plate beam guardrail which has 6" block outs and a 27½" rail height.
- 54.1 Use this when installing a Traffic Barrier Terminal, Type 2 on the old type of steel plate beam guardrail with a 27½" rail height.
- 55.1 This will be used on all projects with guardrail, permanent barrier wall and bridge structures.
Use pay items:
- X7820007 Guardrail Reflectors, Type C (Special)
- X7820008 Barrier Wall Reflectors (Special)
- X6350110 Delineators (Special)
(Do not use the pay items Guardrail Reflectors Type A & B or Barrier Wall Reflectors Type B & C)
- 68.1 This can be used to increase drainage in curb & gutter with very flat grades (less than 0.3%). Also include this when constructing median crossovers.
- 71.1 Use if a property owner has a fenced field with livestock and a stream or river. The flood gate will be placed near the right-of-way to prevent livestock from leaving the field through the waterway. During high water, the flood gate will open to let water and debris through.
- 72.1, 73.1, 74.1, 75.1, 76.1, 77.1, 78.1 Use on single lane median crossovers of the median width specified and for the work zone speed limit. Include District Standard 86.1. If there are overlays on the existing PCC pavement, installing tie bars into the existing PCC pavement will not work. Talk to the Construction Field Engineer or your Project Engineer for more information.
- 79.1, 80.1, 81.1, 82.1, 83.1, 84.1, 85.1 Use on two lane median crossovers of the median width specified and for the work zone speed limit. Include District Standard 86.1. If there are overlays on the existing PCC pavement, installing tie bars into the existing PCC pavement will not work. Talk to the Construction Field Engineer or your Project Engineer for more information.
- 90.1 Use this on 4-lane highways that go under dual structures and the piers required shielding. The outside of the piers are shielded with impact attenuators. The gap between the piers is shielded using Traffic Barrier Terminal Type 6B (Special). The Traffic Barrier Terminal Type 6B (Special) is

District 2 Standards Designer Notes
required on both sides of the piers.

Design Note: The **length** of the double thrie beam between the piers **must be added on the elevation on the District Standard.**

92.1

Include when planting new ball & burlapped trees.

DISTRICT 2 STANDARDS

4-13-16

½ SIZE

- 10.2 Inlets, Special
- 11.2 Inlets, Special (Type A Gutter)
- 12.2 Double Inlet, Special
- 13.2 Frame & Grate for Inlets, Special
- 13.2a Frame & Grate for Inlets, Special
- 13.2b Frame & Grate for Inlets, Special
- 13.2c Frame & Grate for Inlets, Special
- 13.2d Frame & Grate for Inlets, Special
- 14.2 Inlets, Special, No. 1
- 15.2 Inlets, Special, No. 2
- 20.2 Standard Inlet for Type A Gutter (Special)
- 21.2 Standard Inlet for Curb & Gutter
- 30.2 Field Tile Junction Vaults 2' and 3' Dia.
- 31.2 Treatment of Field Tile Systems Under Ditches
- 32.2 Sign Panel - Type 1 (Special)
- 33.2 Special Drainage Outlet
- 34.2 Inlet Stand Pipe
- 35.2 Guardrail Erosion Control Treatments
- 36.2 Paved Ditch (Special)
- 37.2 Underdrain for Across Road (AR) Culverts
- 44.2 Reserved Parking Sign Detail
- 45.2 Superelevation Transition on Two-Lane Highway
- 46.2 Hot-Mix Asphalt Approaches and Mailbox Returns for Single Lift (SMART) Resurfacing Projects
- 47.2 Hot-Mix Asphalt Approaches and Mailbox Returns for Two Lifts (3P) Resurfacing Projects
- 48.2 Safety Edge (SMART Projects)
- 49.2 Safety Edge (3P Projects)
- 60.2 Deleted 4-15-15
- 61.2 Slotted Drain Pipe for Type A Gutter (Special)
- 63.2 Pipe Handrail for Steps
- 64.2 Pipe Handrail, Special – for Retaining Walls
- 66.2 Permanent Survey Markers, Type II
- 73.2 Automatic Flap Gate
- 81.2 Riprapped Culvert Energy Basin
- 89.2 Termination of Dead End Roads
- 90.2 Mechanical Joints for Concrete Pipe and Box Culverts
- 93.2 Typical Aggregate Base Sideroad
- 94.2 Traffic Control & Protection at Turn Bays (To Remain Open to Traffic)

District 2 Standards Designer Notes

½ Size District 2 Standards

- 10.2 This is used for drainage in a curb & gutter section. The diagonal grate is included in the cost. The diagonal grate is bicycle safe. If the inlet is in a driveway which has a depressed curb, the grate on the bottom left hand side will be used. The cost of this grate is also included in the cost of the inlet special. When using this do not include 13.2, 13.2a, 13.2b, 13.2c or 13.2d.
- 11.2 This is used for drainage in a Type A gutter. The grate is included in the cost of the inlet.
- 12.2 This is used when extra inlet capacity is needed. For example, in a sag condition.
- 13.2 These are different types of frame & grates for inlet specials. One of these can
13.2a be used to replace broken frame & grates on inlets to be adjusted or
13.2b reconstructed. Select the one that matches the existing. All of them are
13.2c bicycle safe.
13.2d
- 14.2 This has been used in medians where the gutter flag is less than 24".
- 15.2 This has been used in medians where the curb is only 2"± high. For example, near the nose of a ramped median.
- 20.2 Use this on the inlet end of Type A Gutter (Special)
- 21.2 Use this on the inlet end of Combination Concrete Curb & Gutter
- 30.2 If there is existing field tile on your job or think there could be field tile, include this standard. Also include a pay item for junction vaults.
- 31.2 If there is storm sewer or field tile under a ditch with 24" or less of cover, include this standard. Include the pay item for Miscellaneous Concrete.
- 32.2 Use this where the bridge is less than 24" wider than the roadway surface. This is very rare on a state route, but should be used on bridges on detour routes on County or Township roads.
- 33.2 This is a special drainage outlet to be used on existing pavements with drainage problems. The existing underdrains might not be working, or there is water pumping out of the joint between the pavement and shoulder.
- 34.2 This can be used to replace existing field tile stand pipes. The existing stand pipe is usually an orange perforated 6" pipe, 24" to 36" high, near the outlet end of a culvert. This could also be a new installation if requested by the property owner during Phase I or during negotiations.

District 2 Standards Designer Notes

7-20-16

- 35.2 This is an erosion control treatment at guardrail that Operations has used for years. The downside is the erosion control curb tends to further tilt the guardrail over time. This can be used to replace existing erosion control curb or at selected locations. A better treatment for slopes at guardrail is Perimeter Erosion Barrier, Special (Dist. Std. 8.4).
- 36.2 Paved ditch is rarely used in District 2. It tends to crack and water seeps under the concrete, causing it to be undermined. Once undermined it collapses, causing an erosion problem. Where it can be used is on very flat ditch grades, less than 0.2%. In this case, velocity is low, but the paved ditch could silt in. Operations could clean the paved ditch and the paved ditch establishes the grade line.
- 37.2 Include when installing or removing across road culverts in sags or on grades greater than 2%. The purpose of this is to prevent water pumping out of the joints of the pavement patch. Add the pay items for Pipe Underdrains, Type 2 and Concrete Headwalls for Pipe Drains.
- 44.2 This is to be used on all disabled parking stalls.
- 45.2 Include this on projects that correct existing superelevations, or on new pavements on superelevations. Not to be used on 3P or Smart projects because existing superelevations are not changed.
- 46.2 Include this on all Smart resurfacing projects.
- 47.2 Include this on all 3P resurfacing projects.
- 48.2 Include in Smart resurfacing projects with paved shoulders 3' or less.
- 49.2 Include in 3P resurfacing projects with paved shoulders 3' or less.
- 60.2 Deleted 4-15-15
- 61.2 This can be used to increase drainage in curb & gutter or Gutter, Type A (Special) where the longitudinal grade is less than 0.3%. Use 68.1 when constructing median crossovers.
- 63.2 Include this when constructing new steps.
- 64.2 Include this when handrails are needed on retaining walls. Not all retaining walls need handrails. Retaining walls that are supporting and adjacent to sidewalks or parking lots usually need a handrail. Landscaping walls to retain earth in front of a house usually don't need handrails.

District 2 Standards Designer Notes

4-13-16

- 66.2 Include this when using the pay item for Permanent Survey Marks. Do not include Highway Standard 667101 because Standard 66.2 is 5' deep and requires a witness marker.
- 73.2 Use this on entrance pipes or berm pipes adjacent to a river or canal. This will prevent water from the river or canal backing up into the ditch.
- 81.2 This is one option to control erosion at the ends of culverts with very high velocities. There is a design process to determine the dimensions in the chart. Consult with the Hydraulics Engineer on its use.
- 89.2 Include this at the end of dead end roads like a cul-de-sac or hammer head turn around.
- 90.2 Use this at locations where pipe culverts or box culvert joints could separate. Most culverts do not require the ties, so this is rarely used. One application is where the culvert outlets into a river. There could be erosion at the end of the culvert so the end section or sections of the culvert could tip or fall off. In this case, only the last one or two sections were tied.
- 93.2 Include this when sideroads are constructed with 3"± of incidental on an aggregate base and the mainline has 8" HMA shoulders. This standard includes 4' HMA shoulders on the sideroad return, which will be placed monolithically when the return is resurfaced.
- 94.2 Include this on multi-lane roads when the traffic lane is closed adjacent to a left or right turn lane and the turn lane is to remain open to traffic.

DISTRICT 2 STANDARDS

2-28-23

¼ SIZE

- 8.4 Perimeter Erosion Barrier, Special
- 11.4 Concrete Curb (Special)
- 12.4 Concrete Curb (Special) (Adjacent to Resurfacing)
- 13.4 Combination Concrete Curb & Gutter, Type _____, Special
- 15.4 Gutter Outlet Adjacent to Stabilized Shoulders
- 16.4 Concrete Gutter, Type A, with Flume
- 17.4 Catch Basins or Inlets to be Adjusted or Reconstructed
- 18.4 Curb & Gutter Outlet, Special
- 19.4 Riprap at End Sections
- 19.4a Concrete Revetment Mat at End Sections
- 20.4 Grading Around Wingwalls
- 21.4 Aggregate Ditch for Flexible Ditch Lining
- 22.4 Hot Mix-Asphalt Shoulder
- 23.4 Detail of Hot-Mix Asphalt Shoulder at Guardrail
- 24.4 Pavement Breaking Detail
- 27.4 Concrete Headwalls for Pipe Underdrains for Structures
- 28.4 Cast-in-Place Reinforced Concrete End Sections
- 29.4 Silicone Joint Seal (Concrete Details)
- 30.4 Stone Wells, Special
- 31.4 Parking Blocks
- 32.4 Pavement Patching for Hot-Mix Asphalt Surfaced Pavement
- 33.4 Pavement Patching Detail
- 34.4 Thrust Block Details
- 35.4 Sidewalk and Driveway Pavement Pay Areas
- 36.4 Concrete Gutter, Type A (Special)
- 37.4 Delineator and Post Orientation
- 38.4 Edge of Pavement Repair
- 43.4 Required Cold Milled Surface Texture
- 44.4 Slab Movement Detection Device
- 46.4 Aerial Speed Check Zones
- 50.4 Typical Benching Detail on Existing Embankment
- 51.4 Typical Construction of Embankments with Granular Material
- 63.4 Land Section & Reference Markers
- 70.4 Tree Wall
- 71.4 Detail of Concrete Steps
- 79.4 Inlets, Special, No. 3
- 79.4a Inlets, Special, No. 4
- 79.4b Inlets, Special, No. 5
- 79.4c Inlets, Special, No. 6
- 79.4d Inlets, Special, No. 7
- 79.4e Inlets, Special, No. 8
- 79.4f Nose Type for Inlet Top Slab
- 79.4g Inlets, Special, No. 3, 4, 5, 6 Reinforcement Detail
- 79.4h Inlets, Special, No. 7 & 8 Reinforcement Detail
- 80.4 Inlets to be Reconstructed with New Standard 542546 Frame & Grate
- 83.4 Grate, Special
- 87.4 Typical Median Crossover Closure (with Emergency Opening)
- 88.4 Drain for Aggregate Bases in Urban Areas
- 91.4 Rumble Resurfacing
- 96.4 Drain for Aggregate Base Course
- 97.4 Subgrade Replacement
- 98.4 Typical Median Crossover Closure



¼ Size District 2 Standards

- 8.4 This can be used on Smart & 3P resurfacing projects to maintain a maximum 9% cross slope on the aggregate shoulder in front of existing guardrail. The guardrail could also be removed and re-erected or replaced if it is extremely tipped, out of alignment, damaged, not to current standards, or the height is more than 3" high or low from the initial standard used to install it. Smart projects are allowed up to 15% of the total contract cost for spot safety improvements. 3P projects can also have spot safety improvements, but both projects require BDE approval. Include pay items for Steel Plate Beam Guardrail, Type A (Special), and Aggregate Wedge Shoulder, Type B.
- 11.4, 12.4 & 13.4 These can be used when a new median or curb & gutter is placed on bare concrete pavement. This isn't used much because the first thing necessary is bare concrete, and there isn't much bare concrete in our District.
- 15.4 This is used to replace existing gutter outlets adjacent to a HMA shoulder. District 2 doesn't construct new gutter adjacent to stabilized shoulders; curb & gutter is used. Therefore, when curb & gutter is constructed adjacent to a stabilized shoulder, use Highway Standard 606101.
- 16.4 This is a specialized gutter outlet. Do not use this on curb & gutter. An example of when it would be used is to outlet the gutter over the top of a culvert headwall.
- 17.4 Use this standard for adjustment of catch basins or inlets.
- 18.4 This is a specialized curb & gutter outlet. This can be used when there is a ditch behind the curb & gutter and there aren't any inlets with frame & grate or Winnebago's in the curb & gutter.
- 19.4 Use this when RIPRAP is required at culvert end section. Check the hydraulic report for the apron length and the size of the riprap to be used. Be sure to show the dimensions on the plans.
- 19.4a Use this when concrete revetment mat is required at an end section. There is a table on the standard which needs to be filled out. Check the hydraulic report for the apron length. Be sure to show the dimensions on the plans.
- 20.4 Use this on across road culverts that have wingwalls that are not parallel with the culvert. This is a guide for the Resident Engineer & Contractor on how to construct the dirt around wingwalls.
- 21.4 If riprap is needed in ditches to control erosion, use this standard. Specify the pay item for Class A3 or A4. Add the dimensions to the typical section. The height of the riprap on the side slopes should extend approximately 6" higher than the computed depth of water in the ditch.
- 22.4 Use this for new HMA shoulders. If guardrail will be installed before the surface course is placed, like on staged bridge projects, use District Standard 23.4
- 23.4 Use this on projects where guardrail will be installed before the surface course is placed. This allows the guardrail to be installed and the shoulder resurfaced to the post so the posts do not have to be removed and re-erected. For example, staged bridge projects require guardrail to be installed for Stage 2, but all of the surface course is placed after the bridge is completed. If new HMA shoulders are constructed and guardrail will be installed after the HMA shoulder is installed, use District Standard 22.4.



- 24.4 Use this on projects with large changes in vertical alignment from the existing pavement to a new full depth pavement. This will require a thick resurfacing taper, pavement breaking, and variable depth subbase granular material.
- 27.4 Use this if the pipe underdrain for structures behind the bridge abutment will outlet into the riprap on the bridge cone. If not, use Highway Standard 601101.
- 28.4 Use this if storm sewer or field tile outlets through the backslope of the ditch. This can also be used for Cast-in-Place Reinforced Concrete End Section 8" or 10".
- 29.4 Include this standard if #16 Polymer Concrete is checked on the Recurring Special Provision check sheet.
- 30.4 This can be used in sandy soils to drain areas with poor drainage or no outlets. Materials must take soil borings to determine if the stone well will function properly.
- 31.4 This can be used in parking lots or for diagonal parking if there isn't a curb or curb & gutter.
- 32.4 Use this standard for peek-a-boo patching. Peek-a-boo patching is used to remove and replace the existing HMA on top of concrete pavement, up to a maximum of 8" thick.
- 33.4 Use this standard for pavement patching when the existing HMA overlay thickness is 8" or thicker.
- 34.4 Include this when constructing new water mains, or moving or relocating fire hydrants. Do not include this for the thrust blocks on Highway Standard 610001.
- 35.4 Use this standard in urban areas when removing and replacing sidewalk and driveway pavements.
- 36.4 When constructing concrete gutter, District 2 has a flat bottom gutter which is easier to construct. Do not include Highway Standard 606101. For gutter inlets, include #20.2 Standard Inlet for Type A Gutter (Special), and for outlets include #15.4 Gutter Outlet Adjacent to Stabilized Shoulder.
- 37.4 Include when installing new delineators. The purpose of rotating the post 180° is to give more support for the delineators so it doesn't break off.
- 38.4 Include this standard on 3P projects when there are areas along the edge of pavement that are badly deteriorated. Also include the appropriate Recurring Special Provision.
- 43.4 Include this standard if #13 HMA Surface Correction is checked on the Recurring Special Provisions check sheet. This milling is for surface corrections that will not be resurfaced. To date this has not been used in District 2.
- 44.4 Include this standard if #12 Subsealing of Concrete Pavements is checked on the Recurring Special Provisions check sheet. This is used with the pay items Dry Grout Solids and Holes Drilled. To date this has not been used in District 2.

- 46.4 This is used when replacing existing aerial speed check zones on resurfacing projects. Field check the project to determine if any exist.
- 50.4 Include this when adding embankment on an existing slope that is 4' high or more.
- 51.4 Use on any project that will be widening the existing embankment, contact Geotech with any questions.
- 63.4 Include this if Land Sections or ¼ Section Corners will be disturbed. Check with Land Acquisition for the existing section locations.
- 70.4 This can be used to save a tree on a slope that will be excavated. Usually there is a commitment in the project report to save a tree that requires a tree well.
- 71.4 Include this detail for installing or replacing steps adjacent to sidewalk.
- 79.4 These inlets, known as Winnebago's. No. 3 & 4, can be used with storm sewer up to 36" diameter, No. 5 & 6 can be used with storm sewer up to 24" diameter, 79.4a No. 7 can be used with storm sewer up to 48" diameter, and No. 8 can be used 79.4b with storm sewer up to 60" diameter. No. 4 & 6 have open backs for drainage 79.4c behind the inlets. Do not use Winnebago's with curb & gutter with gutter flags 79.4d less than 24", it makes the cross slope of the gutter flag too steep. This can be 79.4e dangerous for bicyclists, or people stepping off of the curb. Instead, use an 79.4f inlet with a frame & grate to fit the curb & gutter. When using 79.4, 79.4a, 79.4g 79.4b, or 79.4c, also include 79.4f & 79.4g. When using 79.4d & 79.4e, also 79.4h include 79.4f & 79.4h.
- 80.4 This can be used to lower an existing 3' x 3' median inlet.
- 83.4 Use this to replace broken grates or to replace a grate that isn't bicycle safe. Measure the existing grate to ensure this will fit.
- 87.4 Use this on permanent median crossovers where an emergency opening is needed. If an emergency opening isn't needed, use District Standard 98.4. Check with Operations to see if an opening is needed.
- 88.4 Use this in urban areas with new pavement, subbase, and storm sewer. The purpose of this is to drain the subbase.
- 91.4 This is usually used to replace existing rumble strips in the traffic lane before stop signs. It can also be used at new locations to reduce accidents.
- 96.4 Use this on new pavements with subbase where there will be ditches. Place one in all low points and others at approximately 250' intervals.
- 97.4 Include this for full depth patching. The quantity for subgrade replacement will be approximately 10-20% of the area of the full depth patches. Remember to include the BDE special provision for Aggregate Subgrade Improvement.
- 98.4 Use this on permanent median crossovers where an emergency opening is not needed. If an emergency opening is needed, use District Standard 87.4. Check with Operations to see if an opening is needed.

MAILBOX TURNOUT IN CURB AND GUTTER SECTION



COMMERCIAL ENTRANCE WITH MAILBOX TURNOUT



TYPICAL CROSS SECTION

PRIVATE ENTRANCE WITH MAILBOX TURNOUT

GENERAL NOTES

- 1.) THE LONGITUDINAL CURB EXPANSION JOINT SHALL CONFORM TO SECTION 1051 OF THE STANDARD SPECIFICATIONS.
- 2.) THE MAILBOX TURNOUT CROSS SLOPE WILL BE AS SHOWN ABOVE, AS SHOWN ON THE STATION CROSS SECTIONS OR AS DIRECTED BY THE ENGINEER.
- 3.) THE MAILBOX TURNOUT SHALL BE CONSTRUCTED WITH SCORED GROOVES, AS SPECIFIED IN ARTICLE 423.06 OF THE STANDARD SPECIFICATIONS, AT APPROXIMATELY 10 FT. CENTERS. IN THE EVENT THERE IS EXISTING OR PROPOSED SIDEWALK PRESENT, THESE SCORED GROOVES SHALL BE PLACED IN LINE WITH EVERY OTHER JOINT IN THE ADJACENT SIDEWALK.
- 4.) THE WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD FOR P.C. CONCRETE DRIVEWAY PAVEMENT OF THE THICKNESS SPECIFIED IN THE PLANS WHICH PRICE SHALL INCLUDE THE LONGITUDINAL CURB EXPANSION JOINT AND MONOLITHIC CURBS AS SHOWN, AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- 5.) SEE THE DISTRICT STANDARD 25.1 FOR ADDITIONAL DETAILS.
- 6.) MAILBOXES SHALL BE INSTALLED TO CURRENT UNITED STATES POSTAL SERVICE MAILBOX GUIDELINES.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 3041
FILE NAME: DISTRICT 2 STANDARD


USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 1-10-19
	DRAWN -	REVISED - 1-03-18
	CHECKED -	REVISED - 10-17-11
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS FEB. 410 PROJECT	


PC CONCRETE ISLANDS AND MEDIANS ACCESSIBLE TO THE DISABLED




SIDE CURB DETAIL




TYPICAL PLAN OF MEDIAN ISLAND




LARGE ISLAND
(Free Flow Design)




INTERMEDIATE ISLAND
(For Right Turn Lane Design)



SMALL ISLAND
(For Typical Design)




SECTION A-A



SECTION B-B

OPTION 1



OPTION 2

General Notes:
See Standard 606301 and plan sheets for station & offsets, radii, dimensions, and details not shown.

See Standard 424031 for sidewalk details not shown.

The sidewalk should drain to the low side of the Island. If necessary the sidewalk shall be sloped to drain at 1%.

See the plan general notes for the type of curb & gutter to be used on islands.

The sidewalk should not be closer than 36 from the corner of the Island.

Keyed longitudinal construction joints shall be constructed without tie bars.

Medians and large islands shall consist of PCC Sidewalk 5, Concrete Median Surface 4, and Combination Concrete Curb & Gutter, Type M or B of the size specified. Median island can also be solid concrete medians.

Locations, layouts, and widths of the flush sidewalk area, shall be determined by the designer and shown on the plans.

Small islands will be measured for payment from E.O.P. to E.O.P. using either option 1 or option 2, as specified in the plans, and will be paid for at the contract unit price per SQ FT for CONCRETE MEDIAN (SPECIAL) which shall include the combination curb & gutter, sidewalk, aggregate fill, concrete median surface, and solid concrete median.

Omit detectable warnings when distance between back of curbs is less than 6'.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 4041
FILE NAME: DISTRICT 2 STANDARD


USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 4-16-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/17/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

STANDARD OUTLET FOR CURB & GUTTER



Class SI Concrete shall be used throughout.

NOTES

Tie bars shall be No. 6 at 24 centers unless otherwise shown.

Gutter outlet shall be tied to the pavement in accordance with details for longitudinal construction joint shown on Standard 420001.

If the average grade of pavement for the distance from Section A-A to D-D exceeds 2%, this distance shall be increased 6' for each 1% increase in grade.

When curb and gutter is constructed adjacent to flexible pavement, a 1 expansion joint shall be installed at construction joints.

QUANTITY

For Section F-F = 0.069 cu. yds. concrete per ft.

TYPE OF CURB & GUTTER	TABLE OF DIMENSIONS															CONCRETE QUANTITY A-A TO E-E AND CURTAIN WALL FOR 9 PAV'T (CU YDS)	CONCRETE QUANTITY A-A TO E-E AND CURTAIN WALL FOR 10 PAV'T (CU YDS)			
	SECTION A-A				SECTION B-B				SECTION C-C									R ₁	R ₂	R ₃
	A	B	C	D	E	F	G	H	I	J	K	L	M	N						
B-6.12	6	6	1	12	3	7 1/2	13 3/4	2 3/4	4	3	12 1/2	26 1/2	5	6	1	2	8	1.87	1.89	
B-6.18	6	6	1	18	3 1/4	9 1/4	22	3	5	3 1/2	14 1/4	28 3/4	5 1/2	5 1/2	1	4	10	2.18	2.20	
M-4.06	4	3	4	6	3	9 1/2	10 1/2	2	4	3	13	25	3	6	3	5	11	1.78	1.79	
M-4.12	4	3	4	12	3 1/2	9 1/4	13 1/4	2 1/4	6	3	13 1/2	26 1/2	5	6	3	5	9	1.89	1.91	
M-4.18	4	3	4	18	3 1/2	9 1/4	22	3	5	3 1/2	14 1/4	28 3/4	5 1/2	5 1/2	3	4	10	2.11	2.13	
M-4.24	4	3	4	24	5	11 1/2	26	3 1/4	4	3 1/4	15	38	5 1/2	5	3	6	12	2.34	2.37	
M-6.06	6	2	6	6	2 1/4	9 1/4	10 1/2	2	4	2 1/2	13	25	3	6	2	5	10	1.84	1.86	
M-6.12	6	2	6	12	3 1/2	8 1/2	13 1/4	2 1/4	6	3	13 1/2	26 1/2	5	6	2	2	9	1.96	1.98	
M-6.18	6	2	6	18	3 1/2	9 1/4	22	3	5	3 1/2	14 1/4	28 3/4	5 1/2	5 1/2	2	4	10	2.18	2.20	
M-6.24	6	2	6	24	5 1/4	11	26	3 3/4	4	3 3/4	17 1/4	38	5 1/2	5	2	3 1/4	16	2.46	2.49	

MODEL: 5041
FILE NAME: DISTRICT 2 STANDARD


USER NAME = ISDOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 11-12-14
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING




FLAT SLAB TOP JOINT CONFIGURATIONS
FOR D = 4'-0" (1.22 m) THRU D = 6'-0" (1.83 m)
(Shown at access hole)


See Top Slab Joint Configurations for D=36 (900) and D=4'-0" (1.22 m)



SECTION THRU FLAT SLAB TOP
FOR D = 4'-0" (1.22 m) THRU D = 6'-0" (1.83 m)




PLAN - FLAT SLAB TOP FOR D = 4'-0" (1.22 m)
(Showing layout of bottom reinforcement bars and c bars)




FLAT SLAB TOP JOINT CONFIGURATIONS
FOR D = 7'-0" (2.13 m) THRU D = 10'-0" (3.05 m)
(Shown at access hole)

See Top Slab Joint Configurations



SECTION THRU FLAT SLAB TOP
FOR D = 7'-0" (2.13 m) THRU D = 10'-0" (3.05 m)



#6 (#19) bars bottom. Bundle first bar with closest WWR bar to the opening and place second bar ±3 (75) away.

PLAN - FLAT SLAB TOP FOR D = 4'-0" (1.22 m)
(Showing layout of welded wire reinforcement and c bars)

TABLE

D	T	D ₀ (min.)	t
4'-0" (1.2 m)		9 (225)	
5'-0" (1.5 m)		9.5 (238)	
6'-0" (1.8 m)		10 (250)	
7'-0" (2.1 m)	See applicable Standards	10.5 (265)	
8'-0" (2.4 m)		10.5 (265)	
9'-0" (2.7 m)		12 (305)	
10'-0" (3.1 m)		13 (330)	

FLAT SLAB TOP REINFORCEMENT FOR D = 4'-0" (1.22 m)

Location	WWR (each direction)		Rebar		Bar Size
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size		#6 (#19)

GENERAL NOTES

The flat slab top may be used in lieu of the tapered tops shown on Standards 602001, 602016, or 602306 at the option of the Contractor or when field conditions prohibit the use of tapered tops.

Lifting holes shall be located in the sections as per the manufacturer's recommendations.

All dimensions are in inches (millimeters) unless otherwise shown.

MODEL: 6041_Sheet1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -

DESIGNED -	REVISED - 4-3-25
DRAWN -	REVISED - 3-23-23
CHECKED -	REVISED -
DATE -	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.
--------	-------	----	--------	------	---------

F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
				CONTRACT NO.
				ILLINOIS FED. AID PROJECT


PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING




PLAN - FLAT SLAB TOP FOR D = 5'-0" (1.52 m)
(Showing layout of bottom reinforcement bars and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 5'-0" (1.52 m)

Location	WWR (each direction)		Rebar		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size		#6 (#19)




PLAN - FLAT SLAB TOP FOR D = 6'-0" (1.83 m)
(Showing layout of bottom reinforcement bars and c bars)



PLAN - FLAT SLAB TOP FOR D = 5'-0" (1.52 m)
(Showing layout of welded wire bottom reinforcement and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 6'-0" (1.83 m)

Location	WWR (each direction)		Rebar		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size		#6 (#19)



PLAN - FLAT SLAB TOP FOR D = 6'-0" (1.83 m)
(Showing layout of welded wire bottom reinforcement and c bars)

All dimensions are in Inches (millimeters) unless otherwise shown.

USER NAME = jdot/district 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS NO.
CONTRACT NO.			
ILLINOIS FED. AID PROJECT			


PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING



PLAN - FLAT SLAB TOP FOR D = 7'-0" (2.13 m)
(Showing layout of reinforcement bars and c bars)




PLAN - FLAT SLAB TOP FOR D = 7'-0" (2.13 m)
(Showing layout of reinforcement bars and c bars)



PLAN - FLAT SLAB TOP FOR D = 8'-0" (2.44 m)
(Showing layout of welded wire reinforcement and c bars)

#6 (#19) bars bottom. Bundle first bar with closest WWR bar to the opening and place second bar ±3 (75) away.



PLAN - FLAT SLAB TOP FOR D = 8'-0" (2.44 m)
(Showing layout of reinforcement bars and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 7'-0" (2.13 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		Bar Size
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	
Top	0.11 sq. in./ft.	18	0.11 sq. in./ft.	18	#4
Mat	(233 sq. mm/m)	(450)	(233 sq. mm/m)	(450)	(#13)
Bottom	* 0.88 sq. in./ft.	6	See plan view for rebar orientation and spacing and this table for bar size		#6
Mat	(1863 sq. mm/m)	(150)			(#19)

* Only one layer of WWR permitted to avoid congestion.

FLAT SLAB TOP REINFORCEMENT FOR D = 8'-0" (2.44 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		Bar Size
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	
Top	0.11 sq. in./ft.	18	0.11 sq. in./ft.	18	#4
Mat	(233 sq. mm/m)	(450)	(233 sq. mm/m)	(450)	(#13)
Bottom	* 0.88 sq. in./ft.	6	See plan view for rebar orientation and spacing and this table for bar size		#6
Mat	(1863 sq. mm/m)	(150)			(#19)

All dimensions are in Inches (millimeters) unless otherwise shown.

MODEL: 8041_Rev03
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -


DESIGNED -	4-3-25
DRAWN -	3-23-23
CHECKED -	
DATE -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS NO.
CONTRACT NO.									
ILLINOIS FED. AID PROJECT									

PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING



PLAN - FLAT SLAB TOP FOR D = 9'-0" (2.74 m)
(Showing layout of reinforcement bars and c bars)



PLAN - FLAT SLAB TOP FOR D = 9'-0" (2.74 m)
(Showing layout of welded wire reinforcement and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 9'-0" (2.74 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Top Mat	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	#4 (#13)
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size (#19)		

* Only one layer of WWR permitted to avoid congestion.

All dimensions are in Inches (millimeters) unless otherwise shown.

MODEL: 9014 Sheets
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING



PLAN - FLAT SLAB TOP FOR D = 10'-0" (3.05 m)
(Showing layout of reinforcement bars and c bars)



PLAN - FLAT SLAB TOP FOR D = 10'-0" (3.05 m)
(Showing layout of welded wire reinforcement and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 10'-0" (3.05 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Top Mat	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	#4 (#13)
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size		

* Only one layer of WWR permitted to avoid congestion.

All dimensions are in Inches (millimeters) unless otherwise shown.

MODEL: 10ft_slabs
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.
--------	-------	----	--------	------	---------

F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				


PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING




PLAN - FLAT SLAB TOP FOR D = 4'-0" (1.22 m)
(Showing layout of bottom reinforcement bars and c bars)




PLAN - FLAT SLAB TOP FOR D = 5'-0" (1.52 m)
(Showing layout of bottom reinforcement bars and c bars)




PLAN - FLAT SLAB TOP FOR D = 6'-0" (1.83 m)
(Showing layout of bottom reinforcement bars and c bars)



PLAN - FLAT SLAB TOP FOR D = 4'-0" (1.22 m)
(Showing layout of bottom welded wire reinforcement and c bars)



PLAN - FLAT SLAB TOP FOR D = 5'-0" (1.52 m)
(Showing layout of bottom welded wire reinforcement and c bars)



PLAN - FLAT SLAB TOP FOR D = 6'-0" (1.83 m)
(Showing layout of bottom welded wire reinforcement and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 4'-0 (1.22 m)

Location	WWR (each direction)		Rebar		Bar Size
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size	6 (#19)	#6 (#19)

FLAT SLAB TOP REINFORCEMENT FOR D = 5'-0" (1.52 m)

Location	WWR (each direction)		Rebar		Bar Size
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size	6 (#19)	#6 (#19)

FLAT SLAB TOP REINFORCEMENT FOR D = 6'-0" (1.83 m)

Location	WWR (each direction)		Rebar		Bar Size
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size	6 (#19)	#6 (#19)

All dimensions are in Inches (millimeters) unless otherwise shown.

MODEL: 8041_Rev08
FILE NAME: DISTRICT 2 STANDARD


USER NAME = I007/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING




PLAN - FLAT SLAB TOP FOR D = 7'-0" (2.13 m)
(Showing layout of reinforcement bars and c bars)




PLAN - FLAT SLAB TOP FOR D = 7'-0" (2.13 m)
(Showing layout of welded wire reinforcement and c bars)

#6 (#19) bars bottom. Bundle first bar with closest WWR bar to the opening and place second bar ± 3 (75) away.



PLAN - FLAT SLAB TOP FOR D = 8'-0" (2.44 m)
(Showing layout of welded wire reinforcement and c bars)

All dimensions are in Inches (millimeters) unless otherwise shown.



PLAN - FLAT SLAB TOP FOR D = 8'-0" (2.44 m)
(Showing layout of reinforcement bars and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 7'-0" (2.13 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Top	0.11 sq. in./ft.	18	0.11 sq. in./ft.	18	#4
Mat	(233 sq. mm/m)	(450)	(233 sq. mm/m)	(450)	(#13)
Bottom	* 0.88 sq. in./ft.	6	See plan view for rebar orientation and spacing and this table for bar size		
Mat	(1863 sq. mm/m)	(150)	(#19)		

* Only one layer of WWR permitted to avoid congestion.

FLAT SLAB TOP REINFORCEMENT FOR D = 8'-0" (2.44 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Top	0.11 sq. in./ft.	18	0.11 sq. in./ft.	18	#4
Mat	(233 sq. mm/m)	(450)	(233 sq. mm/m)	(450)	(#13)
Bottom	* 0.88 sq. in./ft.	6	See plan view for rebar orientation and spacing and this table for bar size		
Mat	(1863 sq. mm/m)	(150)	(#19)		

* Only one layer of WWR permitted to avoid congestion.

MODEL: 8glt_slab7
FILE NAME: DISTRICT 2 STANDARD


USERNAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. FILE:	SECTION	COUNTY	TOTAL SHEETS NO.
CONTRACT NO.									
ILLINOIS FEDERAL PROJECT									

PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING



PLAN - FLAT SLAB TOP FOR D = 9'-0" (2.74 m)
(Showing layout of reinforcement bars and c bars)



PLAN - FLAT SLAB TOP FOR D = 9'-0" (2.74 m)
(Showing layout of welded wire reinforcement and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 9'-0" (2.74 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Top Mat	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	#4 (#13)
Bottom Mat	* 0.86 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size		

* Only one layer of WWR permitted to avoid congestion.

All dimensions are in Inches (millimeters) unless otherwise shown.

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


REGION 2 / DISTRICT 2 STANDARD

USER NAME = IS07/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
								CONTRACT NO.		
								ILLINOIS FED. AID PROJECT		

MODEL: sgt_slab8
FILE NAME: DISTRICT 2 STANDARD

PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING



PLAN - FLAT SLAB TOP FOR D = 10'-0" (3.05 m)
(Showing layout of reinforcement bars and c bars)



PLAN - FLAT SLAB TOP FOR D = 10'-0" (3.05 m)
(Showing layout of welded wire reinforcement and c bars)

FLAT SLAB TOP REINFORCEMENT FOR D = 10'-0" (3.05 m)

Location	WWR (each direction)		Rebar (each direction except as noted)		
	A _s (min.)	Spacing (max.)	A _s (min.)	Spacing (max.)	Bar Size
Top Mat	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	0.11 sq. in./ft. (233 sq. mm/m)	18 (450)	#4 (#13)
Bottom Mat	* 0.88 sq. in./ft. (1863 sq. mm/m)	6 (150)	See plan view for rebar orientation and spacing and this table for bar size		

* Only one layer of WWR permitted to avoid congestion.

MODEL: 10ft_slabs
FILE NAME: DISTRICT 2 STANDARD

USER NAME = 1007/DISTRICT 2	DESIGNED -	REVISED - 4-3-25
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

PRECAST REINFORCED CONCRETE FLAT SLAB TOP CENTERED AND OFFSET MANHOLE – 36" OPENING



NEENAH: R-4349-D
5.4 sq. ft. Opening



SECTION A-A

MODEL: 804_Sheet10
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT / DISTRICT 2	DESIGNED -	REVISED - 4-27-23
	DRAWN -	REVISED - 3-23-23
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				


CONCRETE END SECTIONS FOR PARALLEL PIPE CULVERTS 15" THRU 84" DIA.



ELEVATION



PLAN



END VIEW
(Showing pipes)

* This dimension shall be increased by 1" for CIP field construction. See General Notes.

GENERAL NOTES

The concrete end sections detailed herein for flexible type pipe culverts are restricted to use with parallel type drainage structures only and traversable pipe grating placed perpendicular to the sidewalls. When traversable pipe grating placed parallel to the sidewalls is required, use standard 542001 or 542011.

A segment of pipe culvert shall be cast into the backwall of the concrete end section such that a minimum of 4 ft of pipe culvert extends from the back face of the end section as shown in Elevation.


Segments of pipe culvert shall be joined in accordance with Article 542 of the Standard Specifications except bands for corrugated steel or aluminum culverts shall conform to the length requirements shown in elevation and have the same corrugations as the culvert pipe. These bands will be included in cost of the pipe.

The number of segments shown in elevation is for example only. The length and number of precast sections required to construct the end section shall be determined by the Contractor. See roadway plans for slope (V:H) and pipe inside diameter.


2 1/4" x 2 1/4" x D" plate washers shall be provided under each nut required for the anchor rods. Holes in the walls for the culvert tie assembly may be drilled using core bits in lieu of formed holes.

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).

All dimensions are in inches unless otherwise shown.




TIE PLATE DETAIL



1" \varnothing Anchor rods with 2 1/4" x 2 1/4" x D" R washers installed in 1 1/2" dia. formed holes in end section walls

SECTION A-A

(Showing end section tie details)



RESTRAINT ANGLE DETAIL

MODEL: 1001_Sheet1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = J007/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 5-09-14
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD


F.A. RITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

SCALE: SHEET OF SHEETS STA. TO STA.

CONCRETE END SECTIONS FOR PARALLEL PIPE CULVERTS 15" THRU 84" DIA.




LONGITUDINAL SECTION
(Showing bottom slab and backwall reinforcement.)



SECTION B-B
(Showing backwall reinforcement for pipes.)


LAP DIMENSION

- #4 bar = 17"
- #5 bar = 21"
- #6 bar = 25"



SECTION D-D

* The Contractor may use lap splices for the sidewall reinforcement at the locations shown.



SECTION C-C

PARALLEL PIPE CULVERT END SECTION DIMENSIONS

Pipe I.D.	Tables IB, IC, IIIA, AND IIIB				
	R	S	L		
			Slope of End Section		
			1:4	1:6	1:10
15"	25"	16"	9'-0"	13'-2"	21'-6"
18"	28"	18"	10'-0"	14'-8"	24'-0"
21"	31"	22"	11'-0"	16'-2"	26'-6"
24"	35"	24"	12'-4"	18'-2"	29'-10"
30"	3'-5"	30"	14'-4"	21'-2"	34'-10"
36"	3'-11"	36"	16'-4"	24'-2"	39'-10"
42"	4'-5"	3'-6"	18'-4"	27'-2"	44'-10"
48"	5'-0"	4'-0"	20'-8"	30'-8"	50'-8"
54"	5'-4"	4'-6"	22'-0"	32'-8"	54'-0"
60"	5'-10"	5'-0"	24'-0"	35'-8"	59'-0"
66"	6'-4"	5'-6"	26'-0"	38'-8"	64'-0"
72"	6'-10"	6'-0"	28'-0"	41'-8"	69'-0"
78"	7'-4"	6'-6"	30'-0"	44'-8"	74'-0"
84"	7'-10"	7'-0"	32'-0"	47'-8"	79'-0"

The above *Tables* are referenced from Article 542.03 of the Standard Specifications.

REINFORCEMENT SCHEDULE

PIPES		
Pipe I.D.	As1m	
	Bar Size	Bar Spacing
15"	#4	12"
18"	#4	12"
21"	#4	12"
24"	#4	12"
30"	#4	12"
36"	#4	12"
42"	#4	12"
48"	#4	8"
54"	#4	8"
60"	#5	8"
66"	#5	8"
72"	#5	8"
78"	#5	8"
84"	#6	8"

MODEL: 10p1_sheer2
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IJ007/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 5-09-14
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
								CONTRACT NO.		
								ILLINOIS FED. AID PROJECT		

CONCRETE END SECTIONS FOR PARALLEL PIPE CULVERTS 15" THRU 84" DIA.

QUANTITIES

Pipe I.D.	Tables IB, IC, IIIA, AND IIIB								
	Concrete yd ³			Reinforcement without Lap lbs.			Reinforcement with Lap lbs.		
	Slope of End Section			Slope of End Section			Slope of End Section		
	1:4	1:6	1:10	1:4	1:6	1:10	1:4	1:6	1:10
15*	1.4	1.9	2.8	250	330	510	270	350	540
18*	1.6	2.2	3.4	290	400	600	310	420	640
21*	2.0	2.7	4.2	330	450	690	360	480	740
24*	2.3	3.2	5.0	370	510	790	400	550	850
30*	3.1	4.3	6.7	490	680	1060	520	720	1130
36*	3.9	5.5	8.7	580	810	1270	620	870	1360
42*	4.9	6.9	10.9	720	1020	1610	770	1080	1710
48*	6.0	8.6	13.7	940	1320	2090	1010	1420	2240
54*	6.9	9.8	15.7	1090	1540	2440	1160	1650	2610
60*	8.1	11.6	18.6	1410	2000	3190	1530	2180	3480
66*	9.5	13.6	21.8	1650	2360	3780	1780	2560	4100
72*	10.9	15.7	25.2	1840	2630	4220	1990	2850	4580
78*	12.4	17.9	28.9	2110	3040	4900	2280	3280	5290
84*	14.1	20.3	32.8	2710	3910	6320	2970	4290	6950


The above quantities are estimates and provided for information only. Actual quantities may vary depending upon the final layout of reinforcement and number of segments determined by the Contractor.

For cast-in-place construction, increase concrete volumes by approximately 12%.


MODEL: 10pt_Sheet3
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2 / DISTRICT 2 STANDARD	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
	DRAWN -	REVISED - 5-09-14								
	CHECKED -	REVISED -								
PLOT DATE = 4/17/2025	DATE -	REVISED -								
					SCALE:	SHEET OF SHEETS	STA. TO STA.	CONTRACT NO.		
					ILLINOIS FEDERAL PROJECT					


CONCRETE END SECTIONS FOR PARALLEL PIPE ARCH CULVERTS 15" THRU 84" DIA.



ELEVATION



PLAN



END VIEW
(Showing pipe arches)

* This dimension shall be increased by 1 1/2" for CIP field construction. See General Notes.

GENERAL NOTES

The concrete end sections detailed herein for flexible type pipe culverts are restricted to use with parallel type drainage structures only and traversable pipe grating placed perpendicular to the sidewalls. When traversable pipe grating placed parallel to the sidewalls is required, use standard 542001 or 542011.

A segment of pipe culvert shall be cast into the backwall of the concrete end section such that a minimum of 4 ft of pipe culvert extends from the back face of the end section as shown in Elevation.


Segments of pipe culvert shall be joined in accordance with Article 542 of the Standard Specifications except bands for corrugated steel or aluminum culverts shall conform to the length requirements shown in elevation and have the same corrugations as the culvert pipe. These bands will be included in cost of the pipe.

The number of segments shown in elevation is for example only. The length and number of precast sections required to construct the end section shall be determined by the Contractor. See roadway plans for slope (V:H) and pipe inside diameter.


2 1/4" x 2 1/4" x D" plate washers shall be provided under each nut required for the anchor rods. Holes in the walls for the culvert tie assembly may be drilled using core bits in lieu of formed holes.

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).

All dimensions are in inches unless otherwise shown.




TIE PLATE DETAIL



1" Ø Anchor rod with 2 1/4" x 2 1/4" x D" washers installed in 1 1/8" dia. formed holes in end section walls

SECTION A-A
(Showing end section tie details)



RESTRAINT ANGLE DETAIL

MODEL: 1204L_Sheet1
FILE NAME: DISTRICT 2 STANDARD


USER NAME = JDOT/DISTRICT 2	DESIGNED -	REVISED - 5-09-14
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
ILLINOIS FED. AID PROJECT										

CONCRETE END SECTIONS FOR PARALLEL PIPE ARCH CULVERTS 15" THRU 84" DIA.



LONGITUDINAL SECTION
(Showing bottom slab and backwall reinforcement.)




SECTION B-B
(Showing backwall reinforcement for arches.)

LAP DIMENSION

- #4 bar = 17"
- #5 bar = 21"
- #6 bar = 25"

* The Contractor may use lap splices for the sidewall reinforcement at the locations shown.



SECTION C-C


PARALLEL PIPE ARCH CULVERT END SECTION DIMENSIONS

Equivalent Round Size	Culvert		Table III, Corrugation : 2" x 1/2"						Culvert		Table III, Corrugation : 3" x 1"					
	Span	Rise	R	S	L			Span	Rise	R	S	L				
					Slope of End Section							Slope of End Section				
					1:4	1:6	1:10					1:4	1:6	1:10		
15"	17"	13"	23"	18"	8'-4"	12'-2"	19'-10"	-	-	-	-	-	-	-		
18"	21"	15"	25"	22"	9'-0"	13'-2"	21'-6"	-	-	-	-	-	-	-		
21"	24"	18"	28"	24"	10'-0"	14'-8"	24'-0"	-	-	-	-	-	-	-		
24"	28"	20"	30"	28"	10'-8"	15'-8"	25'-8"	-	-	-	-	-	-	-		
30"	35"	24"	34"	36"	12'-0"	17'-8"	29'-0"	-	-	-	-	-	-	-		
36"	42"	29"	39"	3'-6"	13'-8"	20'-2"	33'-2"	40"	31"	3'-6"	40"	14'-8"	21'-8"	35'-8"		
42"	49"	33"	3'-7"	4'-2"	15'-0"	22'-2"	36'-6"	46"	36"	3'-11"	3'-10"	16'-4"	24'-2"	39'-10"		
48"	57"	38"	4'-0"	4'-10"	16'-8"	24'-8"	40'-8"	53"	41"	4'-5"	4'-6"	18'-4"	27'-2"	44'-10"		
54"	64"	43"	4'-5"	5'-4"	18'-4"	27'-2"	44'-10"	60"	46"	4'-10"	5'-0"	20'-0"	29'-8"	49'-0"		
60"	71"	47"	4'-9"	6'-0"	19'-8"	29'-2"	48'-2"	66"	51"	5'-3"	5'-6"	21'-8"	32'-2"	53'-2"		
66"	77"	52"	5'-2"	6'-6"	21'-4"	31'-8"	52'-4"	73"	55"	5'-8"	6'-2"	23'-4"	34'-8"	57'-4"		
72"	83"	57"	5'-7"	7'-0"	23'-0"	34'-2"	56'-6"	81"	59"	6'-0"	6'-10"	24'-8"	36'-8"	60'-10"		
78"	-	-	-	-	-	-	-	87"	63"	6'-5"	7'-4"	26'-4"	39'-2"	64'-10"		
84"	-	-	-	-	-	-	-	95"	67"	6'-9"	8'-0"	27'-8"	41'-2"	68'-2"		

The above "Tables" are referenced from Article 542.03 of the Standard Specifications.

REINFORCEMENT SCHEDULE

PIPE ARCHES		
Equivalent Round Size	As1m	
	Bar Size	Bar Spacing
15"	#4	12"
18"	#4	12"
21"	#4	12"
24"	#4	12"
30"	#4	12"
36"	#4	12"
42"	#4	12"
48"	#4	12"
54"	#4	8"
60"	#4	8"
66"	#4	8"
72"	#5	8"
78"	#5	8"
84"	#5	8"



SECTION D-D

USER NAME = IJ007/DISTRICT 2	DESIGNED -	REVISED - 5408-14	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2 / DISTRICT 2 STANDARD			F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	DRAWN -	REVISED -									
	CHECKED -	REVISED -									
PLOT DATE = 4/17/2025	DATE -	REVISED -					SCALE:	SHEET	OF	SHEETS	STA.
										CONTRACT NO.	
										ILLINOIS FED. AID PROJECT	

CONCRETE END SECTIONS FOR PARALLEL PIPE ARCH CULVERTS 15" THRU 84" DIA.

QUANTITIES

Equivalent Round Size	Table IIA, Corrugation: 21" x 1/2"									Table IIA, Corrugation: 3" x 1"								
	Concrete yd ³			Reinforcement without Lap lbs.			Reinforcement with Lap lbs.			Concrete yd ³			Reinforcement without Lap lbs.			Reinforcement with Lap lbs.		
	Slope of End Section			Slope of End Section			Slope of End Section			Slope of End Section			Slope of End Section			Slope of End Section		
	1:4	1:6	1:10	1:4	1:6	1:10	1:4	1:6	1:10	1:4	1:6	1:10	1:4	1:6	1:10	1:4	1:6	1:10
15"	1.3	1.8	2.7	240	320	480	250	330	500	-	-	-	-	-	-	-	-	-
18"	1.5	2.1	3.2	270	360	540	290	370	570	-	-	-	-	-	-	-	-	-
21"	1.8	2.5	3.8	310	420	630	330	450	670	-	-	-	-	-	-	-	-	-
24"	2.1	2.8	4.4	360	480	730	380	510	780	-	-	-	-	-	-	-	-	-
30"	2.7	3.7	5.7	420	570	860	440	610	920	-	-	-	-	-	-	-	-	-
36"	3.4	4.6	7.2	520	700	1070	550	740	1140	3.6	5.0	7.8	560	770	1200	600	820	1270
42"	4.1	5.7	8.9	630	860	1340	660	910	1420	4.4	6.1	9.6	640	890	1380	680	940	1470
48"	5.0	7.0	11.0	740	1010	1560	780	1070	1650	5.5	7.7	12.2	800	1120	1750	840	1180	1860
54"	5.9	8.4	13.2	940	1320	2060	1000	1400	2190	6.4	9.1	14.4	980	1380	2170	1050	1470	2310
60"	6.9	9.7	15.4	1050	1470	2300	1110	1560	2440	7.4	10.6	16.8	1120	1580	2500	1190	1680	2670
66"	8.0	11.3	17.9	1190	1680	2630	1260	1780	2800	8.7	12.4	19.7	1320	1870	2960	1390	1980	3140
72"	9.1	12.9	20.6	1540	2190	3490	1660	2350	3770	9.9	14.1	22.4	1660	2360	3760	1790	2550	4060
78"	-	-	-	-	-	-	-	-	-	11.1	15.9	25.5	1880	2700	4320	2010	2900	4640
84"	-	-	-	-	-	-	-	-	-	12.4	17.8	28.5	2050	2940	4690	2200	3150	5040


The above quantities are estimates and provided for information only. Actual quantities may vary depending upon the final layout of reinforcement and number of segments determined by the Contractor.

For cast-in-place construction, increase concrete volumes by approximately 12%.


MODEL: 12011_Sheet3
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 5-09-14	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2 / DISTRICT 2 STANDARD	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
	DRAWN -	REVISED -								
	CHECKED -	REVISED -								
PLOT DATE = 4/17/2025	DATE -	REVISED -								
SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____					CONTRACT NO. _____					
					ILLINOIS FEDERAL PROJECT					

TRAVERSABLE PIPE GRATE FOR PARALLEL DRAINAGE STRUCTURE



LONGITUDINAL SECTION




PLAN VIEW

GENERAL NOTES


The minimum edge distance from the center of a hole to the free edge of a structural shape or plate shall be 1½" unless noted otherwise.

This standard shall only be used on concrete end sections for parallel drainage structures.

The Contractor may install the thru bolts using drilling and grouting in lieu of providing a formed hole using steel pipe. Installation shall be in accordance with Article 509.06 using a method that results in the annulus surrounding the bolt being completely filled with adhesive. The method of drilling shall not result in spalled concrete at the exit face. Epoxy grouted thru bolts shall be snug tightened followed by an additional 1/3 turn on the interior nut at final installation. Cost included with Traversable Pipe Grate.



SECTION A-A
(4" Ø pipe not shown for clarity.)



VIEW B-B

MODEL: 1491L_Sheet1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 5-09-14
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

TRAVERSABLE PIPE GRATE FOR PARALLEL DRAINAGE STRUCTURE

PIPE GRATE SCHEDULE FOR PARALLEL BOX CULVERTS

BOX SIZE		(<2 FT COVER)					
		SLOPE OF END SECTION					
		1:4		1:6		1:10	
SPAN (FT.)	RISE (FT.)	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe
3	2	5 @ 2'-7"	12'-11"	8 @ 2'-7"	20'-8"	12 @ 2'-7"	31'-0"
3	3	7 @ 2'-7"	18'-1"	11 @ 2'-7"	28'-5"	17 @ 2'-7"	43'-11"
4	2	5 @ 3'-7"	17'-11"	8 @ 3'-7"	28'-8"	13 @ 3'-7"	46'-7"
4	3	8 @ 3'-7"	28'-8"	11 @ 3'-7"	39'-5"	18 @ 3'-7"	64'-6"
4	4	10 @ 3'-7"	35'-10"	14 @ 3'-7"	50'-2"	23 @ 3'-7"	82'-5"
5	2	6 @ 4'-7"	27'-6"	8 @ 4'-7"	36'-8"	13 @ 4'-7"	59'-7"
5	3	8 @ 4'-7"	36'-8"	11 @ 4'-7"	50'-5"	18 @ 4'-7"	82'-6"
5	4	10 @ 4'-7"	45'-10"	14 @ 4'-7"	64'-2"	23 @ 4'-7"	105'-5"
5	5	12 @ 4'-7"	55'-0"	17 @ 4'-7"	77'-11"	28 @ 4'-7"	128'-4"
6	2	6 @ 5'-7"	33'-6"	8 @ 5'-7"	44'-8"	13 @ 5'-7"	72'-7"
6	3	8 @ 5'-7"	44'-8"	11 @ 5'-7"	61'-5"	18 @ 5'-7"	100'-6"
6	4	10 @ 5'-7"	55'-10"	14 @ 5'-7"	78'-2"	23 @ 5'-7"	128'-5"
6	5	12 @ 5'-7"	67'-0"	17 @ 5'-7"	94'-11"	28 @ 5'-7"	156'-4"
6	6	14 @ 5'-7"	78'-2"	20 @ 5'-7"	111'-8"	33 @ 5'-7"	184'-3"
7	2	6 @ 6'-7"	39'-6"	8 @ 6'-7"	52'-8"	13 @ 6'-7"	85'-7"
7	3	8 @ 6'-7"	52'-8"	11 @ 6'-7"	72'-5"	18 @ 6'-7"	118'-6"
7	4	10 @ 6'-7"	65'-10"	14 @ 6'-7"	92'-2"	23 @ 6'-7"	151'-5"
7	5	12 @ 6'-7"	79'-0"	17 @ 6'-7"	111'-11"	28 @ 6'-7"	184'-4"
7	6	14 @ 6'-7"	92'-2"	20 @ 6'-7"	131'-8"	33 @ 6'-7"	217'-3"
7	7	16 @ 6'-7"	105'-4"	23 @ 6'-7"	151'-5"	38 @ 6'-7"	250'-2"
8	2	6 @ 7'-7"	45'-6"	8 @ 7'-7"	60'-8"	13 @ 7'-7"	98'-7"
8	3	8 @ 7'-7"	60'-8"	11 @ 7'-7"	83'-5"	18 @ 7'-7"	136'-6"
8	4	10 @ 7'-7"	75'-10"	14 @ 7'-7"	106'-2"	23 @ 7'-7"	174'-5"
8	5	12 @ 7'-7"	91'-0"	17 @ 7'-7"	128'-11"	28 @ 7'-7"	212'-4"
8	6	14 @ 7'-7"	106'-2"	20 @ 7'-7"	151'-8"	33 @ 7'-7"	250'-3"
8	7	16 @ 7'-7"	121'-4"	23 @ 7'-7"	174'-5"	38 @ 7'-7"	288'-2"
8	8	18 @ 7'-7"	136'-6"	26 @ 7'-7"	197'-2"	43 @ 7'-7"	326'-1"
9	2	6 @ 8'-7"	51'-6"	8 @ 8'-7"	68'-8"	13 @ 8'-7"	111'-7"
9	3	8 @ 8'-7"	68'-8"	11 @ 8'-7"	94'-5"	18 @ 8'-7"	154'-6"
9	4	10 @ 8'-7"	85'-10"	14 @ 8'-7"	120'-2"	23 @ 8'-7"	197'-5"
9	5	12 @ 8'-7"	103'-0"	17 @ 8'-7"	145'-11"	28 @ 8'-7"	240'-4"
9	6	14 @ 8'-7"	120'-2"	20 @ 8'-7"	171'-8"	33 @ 8'-7"	283'-3"
9	7	16 @ 8'-7"	137'-4"	23 @ 8'-7"	197'-5"	38 @ 8'-7"	326'-2"
9	8	18 @ 8'-7"	154'-6"	26 @ 8'-7"	223'-2"	43 @ 8'-7"	369'-1"
9	9	20 @ 8'-7"	171'-8"	30 @ 8'-7"	257'-6"	48 @ 8'-7"	412'-0"
10	2	6 @ 9'-7"	57'-6"	9 @ 9'-7"	86'-3"	14 @ 9'-7"	134'-2"
10	3	8 @ 9'-7"	76'-8"	12 @ 9'-7"	115'-0"	19 @ 9'-7"	182'-1"
10	4	10 @ 9'-7"	95'-10"	15 @ 9'-7"	143'-9"	24 @ 9'-7"	230'-0"
10	5	12 @ 9'-7"	115'-0"	18 @ 9'-7"	172'-6"	29 @ 9'-7"	277'-11"
10	6	14 @ 9'-7"	134'-2"	21 @ 9'-7"	201'-3"	34 @ 9'-7"	325'-10"
10	7	16 @ 9'-7"	153'-4"	24 @ 9'-7"	230'-0"	39 @ 9'-7"	373'-9"
10	8	18 @ 9'-7"	172'-6"	27 @ 9'-7"	258'-9"	44 @ 9'-7"	421'-8"
10	9	20 @ 9'-7"	191'-8"	30 @ 9'-7"	287'-5"	49 @ 9'-7"	469'-7"
10	10	22 @ 9'-7"	210'-10"	33 @ 9'-7"	316'-3"	54 @ 9'-7"	517'-6"

PIPE GRATE SCHEDULE FOR PARALLEL BOX CULVERTS

BOX SIZE		(<2 FT COVER)					
		SLOPE OF END SECTION					
		1:4		1:6		1:10	
SPAN (FT.)	RISE (FT.)	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe
11	2	6 @ 10'-7"	63'-6"	9 @ 10'-7"	95'-3"	14 @ 10'-7"	148'-2"
11	3	8 @ 10'-7"	84'-8"	12 @ 10'-7"	127'-0"	19 @ 10'-7"	201'-1"
11	4	10 @ 10'-7"	105'-10"	15 @ 10'-7"	158'-9"	24 @ 10'-7"	254'-0"
11	6	14 @ 10'-7"	148'-2"	21 @ 10'-7"	222'-3"	34 @ 10'-7"	359'-10"
11	8	18 @ 10'-7"	190'-6"	27 @ 10'-7"	285'-9"	44 @ 10'-7"	465'-8"
11	10	23 @ 10'-7"	243'-5"	33 @ 10'-7"	349'-3"	54 @ 10'-7"	571'-6"
11	11	25 @ 10'-7"	264'-7"	36 @ 10'-7"	381'-0"	59 @ 10'-7"	624'-5"
12	2	6 @ 11'-7"	69'-6"	9 @ 11'-7"	104'-3"	15 @ 11'-7"	173'-9"
12	3	8 @ 11'-7"	92'-8"	12 @ 11'-7"	139'-0"	20 @ 11'-7"	231'-8"
12	4	10 @ 11'-7"	115'-10"	15 @ 11'-7"	173'-9"	25 @ 11'-7"	289'-7"
12	6	15 @ 11'-7"	173'-9"	21 @ 11'-7"	243'-3"	35 @ 11'-7"	405'-5"
12	8	19 @ 11'-7"	220'-1"	27 @ 11'-7"	312'-9"	45 @ 11'-7"	521'-3"
12	10	23 @ 11'-7"	266'-5"	33 @ 11'-7"	382'-3"	55 @ 11'-7"	637'-1"
12	12	27 @ 11'-7"	312'-9"	39 @ 11'-7"	451'-9"	65 @ 11'-7"	752'-11"

PIPE GRATE SCHEDULE FOR PARALLEL BOX CULVERTS

BOX SIZE		(>2 FT COVER)					
		SLOPE OF END SECTION					
		1:4		1:6		1:10	
SPAN (FT.)	RISE (FT.)	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe
3	2	5 @ 2'-7"	12'-11"	7 @ 2'-7"	18'-1"	11 @ 2'-7"	28'-5"
3	3	7 @ 2'-7"	18'-1"	10 @ 2'-7"	25'-10"	16 @ 2'-7"	41'-4"
4	2	5 @ 3'-7"	17'-11"	7 @ 3'-7"	25'-1"	12 @ 3'-7"	43'-0"
4	3	7 @ 3'-7"	25'-1"	10 @ 3'-7"	35'-10"	17 @ 3'-7"	60'-11"
4	4	9 @ 3'-7"	32'-3"	13 @ 3'-7"	46'-7"	22 @ 3'-7"	78'-10"
5	2	5 @ 4'-7"	22'-11"	7 @ 4'-7"	32'-1"	12 @ 4'-7"	55'-0"
5	3	7 @ 4'-7"	32'-1"	11 @ 4'-7"	50'-5"	17 @ 4'-7"	77'-11"
5	4	9 @ 4'-7"	41'-3"	14 @ 4'-7"	64'-2"	22 @ 4'-7"	100'-10"
5	5	11 @ 4'-7"	50'-5"	17 @ 4'-7"	77'-11"	27 @ 4'-7"	123'-9"
6	2	5 @ 5'-7"	27'-11"	8 @ 5'-7"	44'-8"	12 @ 5'-7"	67'-0"
6	3	7 @ 5'-7"	39'-1"	11 @ 5'-7"	61'-5"	17 @ 5'-7"	94'-11"
6	4	9 @ 5'-7"	55'-10"	14 @ 5'-7"	78'-2"	23 @ 5'-7"	128'-5"
6	5	12 @ 5'-7"	67'-0"	17 @ 5'-7"	94'-11"	28 @ 5'-7"	156'-4"
6	6	14 @ 5'-7"	78'-2"	20 @ 5'-7"	111'-8"	33 @ 5'-7"	184'-3"

Follow (<2 FT Cover) table for all other sizes

MODEL: 14911_Sheet2
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 5/09-14
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
SCALE:	SHEET	OF	SHEETS	STA. TO STA.

TRAVERSABLE PIPE GRATE FOR PARALLEL DRAINAGE STRUCTURE

PIPE GRATE SCHEDULE FOR PARALLEL PIPE CULVERTS 15" THRU 84" DIA.

Pipe I.D.	SLOPE OF END SECTION					
	1:4		1:6		1:10	
	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe
15"	3 @ 0'-11"	2'-9"	4 @ 0'-11"	3'-8"	6 @ 0'-11"	5'-6"
18"	3 @ 1'-1"	3'-3"	5 @ 1'-1"	5'-5"	7 @ 1'-1"	7'-7"
21"	4 @ 1'-5"	5'-8"	5 @ 1'-5"	7'-1"	9 @ 1'-5"	12'-9"
24"	5 @ 1'-7"	7'-11"	6 @ 1'-7"	9'-6"	10 @ 1'-7"	15'-10"
30"	6 @ 2'-1"	12'-6"	8 @ 2'-1"	16'-8"	13 @ 2'-1"	27'-1"
36"	7 @ 2'-7"	18'-1"	10 @ 2'-7"	25'-10"	15 @ 2'-7"	38'-9"
42"	8 @ 3'-1"	24'-8"	11 @ 3'-1"	33'-11"	18 @ 3'-1"	55'-6"
48"	9 @ 3'-7"	32'-3"	13 @ 3'-7"	46'-7"	21 @ 3'-7"	75'-3"
54"	10 @ 4'-1"	40'-10"	14 @ 4'-1"	57'-2"	23 @ 4'-1"	93'-11"
60"	11 @ 4'-7"	50'-5"	15 @ 4'-7"	68'-9"	25 @ 4'-7"	114'-7"
66"	12 @ 5'-1"	61'-0"	17 @ 5'-1"	86'-5"	28 @ 5'-1"	142'-4"
72"	13 @ 5'-7"	72'-7"	18 @ 5'-7"	100'-6"	30 @ 5'-7"	167'-6"
78"	14 @ 6'-1"	85'-2"	20 @ 6'-1"	121'-8"	33 @ 6'-1"	200'-9"
84"	15 @ 6'-7"	98'-9"	21 @ 6'-7"	138'-3"	35 @ 6'-7"	230'-5"

MODEL: 14r11_Sheet3
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 5/09/14	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2 / DISTRICT 2 STANDARD	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
	DRAWN -	REVISED -								
	CHECKED -	REVISED -								
PLOT DATE = 4/17/2025	DATE -	REVISED -			SCALE:	SHEET OF SHEETS	STA. TO STA.	CONTRACT NO.		
					ILLINOIS FED. AID PROJECT					

TRAVERSABLE PIPE GRATE FOR PARALLEL DRAINAGE STRUCTURE

PIPE GRATE SCHEDULE FOR PARALLEL PIPE ARCH CULVERTS 15" THRU 84" DIA.

SLOPE OF END SECTION						
Pipe I.D.	Table IIA, Corrugation : 21" x 1/2"					
	1:4		1:6		1:10	
	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe
15"	2 @ 1'-1"	2'-2"	3 @ 1'-1"	3'-3"	5 @ 1'-1"	5'-5"
18"	3 @ 1'-5"	4'-3"	4 @ 1'-5"	5'-8"	6 @ 1'-5"	8'-6"
21"	3 @ 1'-7"	4'-9"	5 @ 1'-7"	7'-11"	7 @ 1'-7"	11'-1"
24"	4 @ 1'-11"	7'-8"	5 @ 1'-11"	9'-7"	8 @ 1'-11"	15'-4"
30"	4 @ 2'-7"	10'-4"	6 @ 2'-7"	15'-6"	10 @ 2'-7"	25'-10"
36"	5 @ 3'-1"	15'-5"	7 @ 3'-1"	21'-7"	12 @ 3'-1"	37'-0"
42"	6 @ 3'-9"	22'-6"	9 @ 3'-9"	33'-9"	14 @ 3'-9"	52'-6"
48"	7 @ 4'-5"	30'-11"	10 @ 4'-5"	44'-2"	16 @ 4'-5"	70'-8"
54"	8 @ 4'-11"	39'-4"	11 @ 4'-11"	54'-1"	18 @ 4'-11"	88'-6"
60"	8 @ 5'-7"	44'-8"	12 @ 5'-7"	67'-0"	20 @ 5'-7"	111'-8"
66"	9 @ 6'-1"	54'-9"	13 @ 6'-1"	79'-1"	22 @ 6'-1"	133'-10"
72"	10 @ 6'-7"	65'-10"	15 @ 6'-7"	98'-9"	24 @ 6'-7"	158'-0"
78"	-	-	-	-	-	-
84"	-	-	-	-	-	-

PIPE GRATE SCHEDULE FOR PARALLEL PIPE ARCH CULVERTS 15" THRU 84" DIA.

SLOPE OF END SECTION						
Pipe I.D.	Table IIA, Corrugation : 3" x 1"					
	1:4		1:6		1:10	
	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe
15"	-	-	-	-	-	-
18"	-	-	-	-	-	-
21"	-	-	-	-	-	-
24"	-	-	-	-	-	-
30"	-	-	-	-	-	-
36"	6 @ 2'-11"	17'-6"	8 @ 2'-11"	23'-4"	13 @ 2'-11"	37'-11"
42"	7 @ 3'-5"	23'-11"	10 @ 3'-5"	34'-2"	15 @ 3'-5"	51'-3"
48"	8 @ 4'-1"	32'-8"	11 @ 4'-1"	44'-11"	18 @ 4'-1"	73'-6"
54"	9 @ 4'-7"	41'-3"	12 @ 4'-7"	55'-0"	20 @ 4'-7"	91'-10"
60"	9 @ 5'-1"	45'-9"	14 @ 5'-1"	71'-2"	22 @ 5'-1"	111'-10"
66"	10 @ 5'-9"	57'-6"	15 @ 5'-9"	86'-3"	24 @ 5'-9"	138'-0"
72"	11 @ 6'-5"	70'-7"	16 @ 6'-5"	102'-8"	26 @ 6'-5"	166'-10"
78"	12 @ 6'-11"	83'-0"	17 @ 6'-11"	117'-7"	28 @ 6'-11"	193'-8"
84"	12 @ 7'-7"	91'-0"	18 @ 7'-7"	136'-6"	30 @ 7'-7"	227'-6"

MODEL: 14911_Sheet4
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 5/09/14
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

TRAVERSABLE PIPE GRATE FOR PARALLEL DRAINAGE STRUCTURE





PIPE GRATE SCHEDULE FOR PARALLEL ELLIPTICAL PIPE CULVERTS 15" THRU 72" DIA.

Pipe I.D.	SLOPE OF END SECTION					
	1:4		1:6		1:10	
	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe	Pipes No. / Length	Total Length of Pipe
15"	3 @ 2'-7"	7'-9"	5 @ 2'-7"	12'-11"	7 @ 2'-7"	18'-1"
18"	3 @ 2'-7"	7'-9"	5 @ 2'-7"	12'-11"	7 @ 2'-7"	18'-1"
21"	5 @ 3'-3"	16'-3"	7 @ 3'-3"	22'-9"	12 @ 3'-3"	39'-0"
24"	5 @ 3'-3"	16'-3"	7 @ 3'-3"	22'-9"	12 @ 3'-3"	39'-0"
27"	6 @ 3'-7"	21'-6"	8 @ 3'-7"	28'-8"	13 @ 3'-7"	46'-7"
30"	6 @ 3'-11"	23'-6"	9 @ 3'-11"	35'-3"	14 @ 3'-11"	54'-10"
36"	7 @ 4'-7"	32'-1"	10 @ 4'-7"	45'-10"	16 @ 4'-7"	73'-4"
42"	8 @ 5'-5"	43'-4"	11 @ 5'-5"	59'-7"	18 @ 5'-5"	97'-6"
48"	9 @ 6'-1"	54'-9"	13 @ 6'-1"	79'-1"	20 @ 6'-1"	121'-8"
54"	10 @ 6'-9"	67'-6"	14 @ 6'-9"	94'-6"	23 @ 6'-9"	155'-3"
60"	11 @ 7'-7"	83'-5"	15 @ 7'-7"	113'-9"	25 @ 7'-7"	189'-7"
66"	11 @ 8'-3"	90'-9"	17 @ 8'-3"	140'-3"	27 @ 8'-3"	222'-9"
72"	12 @ 8'-11"	107'-0"	18 @ 8'-11"	160'-6"	30 @ 8'-11"	267'-6"





MODEL: 14r11_Sheet5
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS07/DISTRICT 2	DESIGNED -	REVISED - 5/09/14	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2 / DISTRICT 2 STANDARD	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
	DRAWN -	REVISED -								
	CHECKED -	REVISED -								
PLOT DATE = 4/17/2025	DATE -	REVISED -			SCALE:	SHEET OF SHEETS	STA. TO STA.	CONTRACT NO.		
					ILLINOIS FED. AID PROJECT					

HOT-MIX ASPHALT APPROACHES AND MAILBOX RETURNS



- NOTE**
- TURNOUTS ARE TO BE CONSTRUCTED ON THE APPROACH SIDE OF ALL PE & CE REGARDLESS IF A MAILBOX IS PRESENT.
 - ALL PE & CE ARE TO BE SURFACED TO RIGHT OF WAY LINE. AREA BEHIND RIGHT OF WAY SHALL MATCH EXISTING SURFACE.
 - ALL PE & CE TO BE CONSTRUCTED WITH AN 8" AGGREGATE BASE COURSE, TYPE B AND WITH A 2 1/2" INCIDENTAL HOT-MIX ASPHALT SURFACING, UNLESS OTHERWISE NOTED.
 - FE ARE TO BE AGGREGATE TO RIGHT OF WAY OR TOUCH DOWN, WHICH EVER IS GREATEST.
 - EXCAVATION REQUIRED FOR PLACEMENT OF AGGREGATE BASE COURSE SHALL BE INCLUDED IN THE COST OF THE AGGREGATE BASE COURSE.
 - ON ENTRANCES THE CONTRACTOR HAS THE OPTION OF USING RADIUS RETURNS, USE RADIUS OF 20' TO 60'.
 - SIDE ROADS SHALL HAVE 3" INCIDENTAL PLACED IN TWO 1 1/2" LIFTS.



MODEL: 20p11
FILE NAME: DISTRICT 2 STANDARD

USER NAME = I007/DISTRICT 2	DESIGNED - 8-03-17	REVISED - 8-03-17
	DRAWN - 1-13-17	REVISED - 1-13-17
	CHECKED - 6-27-14	REVISED - 6-27-14
PLOT DATE = 4/7/2025	DATE - 8-27-13	REVISED - 8-27-13


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

ENTRANCE APPROACHES – URBAN AREA


ENTRANCE ON RADIUS



PRIVATE ENTRANCE





INDUSTRIAL-COMMERCIAL-RECREATIONAL
HIGH-VOLUME TRAFFIC GENERATOR



CURB NOT TO BE PLACED IN SIDEWALK AREAS.


SEC B-B




A MINIMUM OF 440 FEET SHALL BE MAINTAINED BETWEEN CENTER LINES OF ADJACENT DRIVEWAYS.
 20° DESIRABLE, 45° MIN. ANGLE PERMITTED ONLY FOR ONE-WAY DRIVEWAYS.
 60° MIN. ANGLE FOR TWO-WAY DRIVEWAYS.

NOTE: #1 ENCROACHMENT ON THE ADJACENT PROPERTY OWNER LAND REQUIRES HIS OR HER WRITTEN APPROVAL.


** 4'-10" IF HIGHWAY CURBED.
 AT EDGE OF SHOULDER IF HIGHWAY UNCURBED.



LOW TO MODERATE VOLUME COMMERCIAL ENTRANCE




PRIVATE ENTRANCE




ASCENDING APPROACH

*** SIDEWALK TO BE CONSTRUCTED AS PCC DRIVEWAY PAVEMENT THROUGH THE WIDTH OF THE DRIVEWAY. SEE DIST. STD. 35.4

*** 4.0% DESIRABLE
 6.0% MAX. COMMERCIAL
 8.0% MAX. NON-COMMERCIAL




DESCENDING APPROACH
(NO SIDEWALK)




DESCENDING APPROACH
(WITH SIDEWALK)

NOTE: CURVED ENTRANCE RETURNS MAY BE USED FOR LOW TO MODERATE VOLUME LOCATIONS WITH REVIEW ON A CASE-BY-CASE BASIS.



COMMERCIAL ENTRANCE ON SKEW
(LOW TO MODERATE VOLUME)



PRIVATE ENTRANCE ON SKEW

MODEL: 2564T
 FILE NAME: DISTRICT 2 STANDARD

USER NAME =	IB07/DISTRICT 2
DESIGNED -	
DRAWN -	
CHECKED -	
PLOT DATE =	4/7/2025

DESIGNED -	7-19-18
DRAWN -	1-03-18
CHECKED -	6-27-14
DATE -	12-07-10


REVISD -	7-19-18
REVISD -	1-03-18
REVISD -	6-27-14
REVISD -	12-07-10

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.
F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	NO.	
CONTRACT NO.					
ILLINOIS FEB. 410 PROJECT					

ADA CURB RAMP PAVEMENT REMOVAL AND REPLACEMENT



PAVEMENT REMOVAL



PAVEMENT REPLACEMENT

GENERAL NOTES:

SEE STANDARD 606001 FOR CONCRETE CURB AND COMBINATION CURB AND GUTTER DETAILS NOT SHOWN.

SEE STANDARD 420001 FOR KEYED CONSTRUCTION JOINT DETAILS

SAW CUTTING/ SCORING SHALL BE INCLUDED IN THE UNIT COST OF HOT-MIX ASPHALT SURFACE REMOVAL.

FULL DEPTH PAVEMENT REMOVAL SHALL BE INCLUDED IN THE UNIT COST OF COMBINATION CURB AND GUTTER REMOVAL.

PORTLAND CEMENT CONCRETE NEEDED TO FILL IN THE FORMWORK AREA IN FRONT OF THE COMBINATION CURB AND GUTTER SHALL BE INCLUDED IN THE UNIT COST OF COMBINATION CONCRETE CURB AND GUTTER.

IF THERE IS A CHANGE IN RADIUS AND THE DISTANCE BETWEEN THE NEW COMBINATION CURB AND GUTTER AND THE EXISTING PAVEMENT IS 4FT OF GREATER, THE PCC IN FRONT OF THE CURB AND GUTTER SHALL BE TIED TO THE NEW COMBINATION CURB AND GUTTER AND THE EXISTING PAVEMENT WITH TIE BARS. TIE BARS SHALL BE INCLUDED IN THE UNIT COST OF COMBINATION CONCRETE CURB AND GUTTER.

CONSTRUCTION SEQUENCE

1. REMOVE EXISTING FULL DEPTH PAVEMENT AND CURB AND GUTTER
2. FORM AND POUR COMBINATION CONCRETE CURB AND GUTTER
3. REPLACE FULL DEPTH PAVEMENT WITH PORTLAND CEMENT CONCRETE (UP TO 3" FROM FINISHED SURFACE ELVATION TO ALLOW FOR HMA OVERLAY)
4. HOT-MIX ASPHALT REMOVAL AND REPLACEMENT.

NOTES:

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

** COST INCLUDED IN OTHER PAY ITEMS PER GENERAL NOTES

*** IF W > 24" TIE BARS SHALL BE USED INSTEAD OF A KEYED CONSTRUCTION JOINT

MODEL: 26.rvt
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 1-10-22
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD




SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FEDERAL PROJECT				

SEWER AND WATER MAIN CROSSINGS

THIS DETAIL IS FOR UNKNOWN UTILITIES UNLESS QUANTITIES ARE INCLUDED IN THE PLANS THE EXTRA WORK WILL BE PAID FOR IN ACCORDANCE WITH ARTICLE 109.04.

WHEN PROPOSED SEWER (OR WATER) IS LOCATED 10'-0" OR MORE FROM EXISTING WATER (OR SEWER) NO SPECIAL CONSTRUCTION REQUIRED.

WHEN PROPOSED SEWER (OR WATER) IS LOCATED LESS THAN 10'-0" FROM EXISTING WATER (OR SEWER) DETAILS BELOW SHALL APPLY.




CASING SHALL BE CAST IRON WITH AN INSIDE DIAMETER 2" LARGER IN DIAMETER THAN ENCASED PIPE OUTSIDE DIAMETER WITH BOTH ENDS OF CASING SEALED


AT GRADE CROSSING OF SANITARY AND STORM SEWER

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

POINT LOADS SHALL NOT BE ALLOWED BETWEEN SEWER OR SEWER CASING AND WATER MAIN
PROVIDE ADEQUATE SUPPORT FOR EXISTING WATER MAIN TO PREVENT DAMAGE DUE TO SETTLEMENT OF SEWER TRENCH




PROVIDE ADEQUATE SUPPORT FOR EXISTING WATER MAIN TO PREVENT DAMAGE DUE TO SETTLEMENT OF SEWER TRENCH
MAINTAIN 18 MINIMUM VERTICAL SEPARATION FOR 10 FT. HORIZONTALLY



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED


PROPOSED SEWER LINE BELOW EXISTING WATER MAIN

PROVIDE ADEQUATE SUPPORT FOR EXISTING SEWER LINE TO PREVENT DAMAGE DUE TO SETTLEMENT
PLACE TRENCH BACKFILL FOR 10 FT. ON EITHER SIDE OF SEWER LINE



CASING SHALL BE CAST IRON WITH AN INSIDE DIAMETER 2" LARGER IN DIAMETER THAN ENCASED PIPE OUTSIDE DIAMETER WITH BOTH ENDS OF CASING SEALED


PROVIDE ADEQUATE SUPPORT FOR EXISTING WATER MAIN TO PREVENT DAMAGE DUE TO SETTLEMENT OF SEWER TRENCH
MAINTAIN 18 MINIMUM VERTICAL SEPARATION FOR 10 FT. HORIZONTALLY



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

PROPOSED WATER MAIN BELOW EXISTING SEWER LINE

POINT LOADS SHALL NOT BE ALLOWED BETWEEN WATER MAIN OR WATER MAIN CASING AND SEWER




CASING SHALL BE CAST IRON WITH AN INSIDE DIAMETER 2" LARGER IN DIAMETER THAN ENCASED PIPE OUTSIDE DIAMETER WITH BOTH ENDS OF CASING SEALED

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

PROPOSED WATER MAIN ABOVE EXISTING SEWER LINE

PROVIDE ADEQUATE SUPPORT FOR SEWER TO PREVENT SETTLING AND BREAKING THE WATER MAIN.



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

EXISTING WATER MAIN BELOW PROPOSED SEWER LINE WITH MINIMUM 18 VERTICAL SEPARATION

MODEL: 2041
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS007/DISTRICT 2	DESIGNED -
	DRAWN -
	CHECKED -
PLOT DATE = 4/17/2025	DATE -

REVISED - 10-17-11
REVISED -
REVISED -
REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

WORK ZONE SIGN DETAILS

ILLINOIS STANDARD G20-I100



COLOR LEGEND AND BORDER BACKGROUND BLACK ORANGE NON-REFLECTORIZED REFLECTORIZED

SIGN SIZE	DIMENSIONS											
	A	B	C	D	E	F	G	H	J	K	L	M
60 x 36	60.00	36.00	2.25	6.4	21.80	16.40	10.00	22.40	13.20	15.50	10.50	10.00

SIGN SIZE	SERIES BY LINE			MARGIN	BORDER
	1	2	3		
60 x 36	5C	5C	5C	0.625	0.875

Sign not to scale

GENERAL NOTES


All work to furnish and install these signs shall be included in the cost of the specified traffic control standards and shall not be paid separately.

All Illinois Standard signs shall conform to the latest edition of the "Illinois Standard Highway Signs Book" in effect on the date of invitation for bids.

Signs shall meet the applicable portions of Sections 701 and 720 of the Standard Specifications.

All dimensions are in inches unless otherwise noted.

ILLINOIS STANDARD W8-I107



COLOR LEGEND AND BORDER BACKGROUND BLACK ORANGE NON-REFLECTORIZED REFLECTORIZED

SIGN SIZE	DIMENSIONS									
	A	B	C	D	E	F	G	H	J	
48 x 48	48.00	3.00	25.00	34.80	34.20	24.94	9.00	1.00	10.00	

SIGN SIZE	SERIES BY LINE			MARGIN	BORDER
	1	2	3		
48 x 48	7C	7C	7C	1.250	0.750

Sign not to scale

MODEL: 2491L_Sheet1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT / DISTRICT 2	DESIGNED -	REVISED - 3-02-16
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


REGION 2 / DISTRICT 2 STANDARD

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

WORK ZONE SIGN DETAILS

ILLINOIS STANDARD W12-I102



GENERAL NOTES

All work to furnish and install these signs shall be included in the cost of the specified traffic control standards and shall not be paid separately.

All Illinois Standard signs shall conform to the latest edition of the "Illinois Standard Highway Signs Book" in effect on the date of Invitation for bids.

Signs shall meet the applicable portions of Sections 701 and 720 of the Standard Specifications.

All dimensions are in inches unless otherwise noted.

COLOR	LEGEND AND BORDER BACKGROUND	BLACK FL ORANGE	NON-REFLECTORIZED REFLECTORIZED
-------	------------------------------	-----------------	---------------------------------


SIGN SIZE	DIMENSIONS	
	A	B
48 x 48	48.00	3.00

① Illinois Standard signs W12-I102 and W12-I103 shall be used as described in the special provisions.

SIGN SIZE	SERIES BY LINE	MARGIN	BORDER
	1		
48 x 48	12C	0.750	1.250

Sign not to scale

ILLINOIS STANDARD W12-I103



COLOR	LEGEND AND BORDER BACKGROUND (WIDTH)	BLACK WHITE FL ORANGE	NON-REFLECTORIZED REFLECTORIZED
-------	--------------------------------------	-----------------------	---------------------------------

SIGN SIZE	DIMENSIONS											
	A	B	C	D	E	F	G	H	J	K	L	M
48 x 48	48.00	3.00	38.40	13.20	19.20	32.00	22.00	26.20	12.00	24.00	10.00	11.00

SIGN SIZE	SERIES BY LINE				MARGIN	BORDER
	1	2	3	4		
48 x 48	6C	8D	6D	6D	0.750	1.250

Sign not to scale

XX'-XX" WIDTH AND X MILES ARE VARIABLE TOP AND BOTTOM OF BACKGROUND WHITE

MODEL: 2491L_Sheet2
FILE NAME: DISTRICT 2 STANDARD

USER NAME = JDOT/DISTRICT 2	DESIGNED -	REVISED - 3-02-16
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FEDERAL PROJECT				

WORK ZONE SIGN DETAILS

ROAD CLOSED TO OVERSIZED LOADS



STOP LINE SIGN FOR TEMPORARY SIGNALS



COLOR LEGEND AND BORDER BACKGROUND BLACK ORANGE NON-REFLECTORIZED REFLECTORIZED

Permit Loads - Loads Over 13 Feet; 3.0" Radius, 1.3" Border;
 [NO OVERSIZE -] D; [OVERWEIGHT LOADS] D 85% spacing; [XX MILES AHEAD] D;
 Table of letter and object lefts.

N	O	O	V	E	R	S	I	Z	E	-
11.7	18.1	30.0	36.2	42.8	48.4	54.4	60.7	63.5	69.5	80.8

O	V	E	R	W	E	I	G	H	T	L	O	A	D	S
2.6	8.6	15.0	20.4	26.2	33.4	38.8	41.3	47.4	53.2	64.5	69.9	75.9	82.9	88.7

X	X	M	I	L	E	S	A	H	E	A	D
7.6	13.6	25.3	32.3	35.1	40.6	46.2	57.9	65.1	71.4	76.6	83.7

Sign not to scale

COLOR LEGEND AND BORDER BACKGROUND BLACK WHITE NON-REFLECTORIZED REFLECTORIZED

SIGN SIZE	SERIES BY LINE		
	1	2	3
24 x 24	4C	4C	4C

Sign not to scale

GENERAL NOTES

All work to furnish and install these signs shall be included in the cost of the specified traffic control standards and shall not be paid separately.

All Illinois Standard signs shall conform to the latest edition of the "Illinois Standard Highway Signs Book" in effect on the date of invitation for bids.

Signs shall meet the applicable portions of Sections 701 and 720 of the Standard Specifications.

All dimensions are in inches unless otherwise noted.

MODEL: 24x24_Signs3
 FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 3/02-16
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

**ENTRANCE SIGN FOR USE
WITH TEMPORARY SIGNALS**

WORK ZONE SIGN DETAILS

2



COLOR LEGEND AND BORDER BACKGROUND BLACK ORANGE NON-REFLECTORIZED REFLECTORIZED

2.25" Radius, 0.88" Border, 0.50" Indent;
[CAUTION] D; [ONE LANE ROAD] D;
[FOLLOW TRAFFIC] D; [FLOW] D

2 This sign shall be installed at entrances located between the temporary signals as shown in the staging plans.

Table Of Widths And Spaces

22.31	C	3.36	0.62	A	4.18	0.94	U	3.36	0.94	T	3.04	0.94	I	0.78	1.17	O	3.52	1.17	N	3.36	22.31
-------	---	------	------	---	------	------	---	------	------	---	------	------	---	------	------	---	------	------	---	------	-------

8.23	O	3.51	1.17	N	3.36	1.18	E	3.04
------	---	------	------	---	------	------	---	------

5.00	L	3.05	0.31	A	4.18	0.94	N	3.36	1.17	E	3.05
------	---	------	------	---	------	------	---	------	------	---	------

5.00	R	3.36	0.93	O	3.52	0.94	A	4.18	0.93	D	3.36	8.23
------	---	------	------	---	------	------	---	------	------	---	------	------

7.43	F	3.04	0.94	O	3.52	1.17	L	3.04	0.94	L	3.05	0.94	O	3.51	0.94	W	4.37
------	---	------	------	---	------	------	---	------	------	---	------	------	---	------	------	---	------

5.00	T	3.05	0.94	R	3.36	0.94	A	4.18	0.93	F	3.05	0.94	F	3.04	0.94	I	0.78	1.18	C	3.35	7.43
------	---	------	------	---	------	------	---	------	------	---	------	------	---	------	------	---	------	------	---	------	------

27.60	F	3.05	0.94	L	3.04	0.94	O	3.52	0.93	W	4.38	27.60
-------	---	------	------	---	------	------	---	------	------	---	------	-------

Sign not to scale

GENERAL NOTES


All work to furnish and install these signs shall be included in the cost of the specified traffic control standards and shall not be paid separately.

All Illinois Standard signs shall conform to the latest edition of the "Illinois Standard Highway Signs Book" in effect on the date of invitation for bids.

Signs shall meet the applicable portions of Sections 701 and 720 of the Standard Specifications.

All dimensions are in inches unless otherwise noted.

STAY IN YOUR LANE



COLOR LEGEND AND BORDER BACKGROUND BLACK ORANGE NON-REFLECTORIZED REFLECTORIZED

48.0" across sides 3.8" Radius, 1.0" Border, 0.6" Indent;
"STAY" E Mod; "IN YOUR" E Mod; "LANE" E Mod;

Table of Letter and Object Lefts

S	T	A	Y
20.7	26.8	31.6	38.0

I	N	Y	O	U	R
13.2	15.9	26.7	33.9	40.5	46.8

L	A	N	E
20.9	25.8	33.1	39.4

Sign not to scale

MODEL: 2441L_Sheet4
FILE NAME: DISTRICT 2 STANDARD


USER NAME = JBOY/DISTRICT 2	DESIGNED -	REVISED - 3-02-16
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RT#	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

URBAN LANE INSIDE CLOSURE, MULTILANE, 2-WAY, WITH MOUNTABLE MEDIAN



W20-1(O)-48
For Maintenance



W20-1103(O)-48
For construction



W20-5L(O)-48



W4-2L(O)-48



W20-7(O)-48



W1-6R(O)-6030



W4-2L(O)-48



W20-5L(O)-48



W20-1(O)-48
For maintenance



W20-1103(O)-48
For construction

SYMBOLS

- WORK AREA
- CLOSED LANE
- ARROW BOARD
- SIGN ON PORTABLE OR PERMANENT SUPPORT
- CONE, DRUM OR BARRICADE
- FLAGGER WITH TRAFFIC CONTROL SIGN.
- WORKER ON FOOT

SIGN SPACING	
Posted Speed	Sign Spacing
55	500' (150 m)
50-45	350' (100 m)
<45	200' (60 m)

- ① Refer to SIGN SPACING TABLE for distances.
- ② Use flagger and flagger sign only when flagger is required per Article 701.13(b).
- ③ Devices at 10' centers from edge of radius return to edge of radius return when left turns are prohibited due to actively working in the intersection.
- ④ Cones at 20' (6 m) centers for 250' (75 m). Additional cones may be placed at 40' (12 m) centers. When drums or Type I or Type II barricades are used, the interval between devices may be doubled (excluding devices in Intersections).
- ⑤ Cones, drums or barricades at 20' (6 m) centers in taper.
- ⑥ No equipment, materials, vehicles, or other hazards are allowed in the closed lane in the opposite direction within 100' of a worker on foot.

GENERAL NOTES

This Standard Is used where at any time, day or night, any vehicle, equipment, workers or their activities encroach on the pavement requiring the closure of one or more traffic lanes in an Urban area.

Calculate L as follows:

SPEED LIMIT

40 mph (70 km/h) or less:

45 mph (80 km/h) or greater:

W = Width of offset in feet (meters).

S = Normal posted speed mph (km/h).

All dimensions are in Inches (millimeters) unless otherwise shown.

Lane closures in the opposite direction shall be removed when no workers are present.

Cones or reflectorized cones shall not be used during hours of darkness.

This Traffic Control detail shall be included in the cost of Traffic Control and Protection Standard 701606.

FORMULAS

English (Metric)

$$L = \frac{WS^2}{60} \quad L = \frac{WS^2}{150}$$

$$L = (W)(S) \quad L = 0.65(W)(S)$$

MODEL: 2694T
FILE NAME: DISTRICT 2 STANDARD


USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 7-22-14
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
								CONTRACT NO.		
								ILLINOIS FED. AID PROJECT		

TEMPORARY ROAD CLOSURE EXPRESSWAY



GENERAL NOTES

1. MAINTENANCE OF TRAFFIC IS ACCORDING TO STANDARDS 701400, AND 701401 (NIGHT) OR 701406 (DAY ONLY).
2. TYPE II BARRICADES OR DRUMS AT EXIT RAMP WITH LIGHTS AT 20' CENTERS (NO LESS THAN FOUR DRUMS).

SYMBOLS

- ┆ SIGN
- DIRECTION INDICATOR BARRICADE WITH LIGHT
- TYPE II BARRICADE OR DRUM WITH LIGHT
- FLAGGER WITH TRAFFIC CONTROL SIGN
- ┆ TYPE III BARRICADE WITH FLASHERS
- ☐ PORTABLE CHANGEABLE MESSAGE SIGN
- ↓ ARROW BOARD

SIGNING ACCORDING TO SPECIFIED STANDARDS

MODEL: 206P1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS07 / DISTRICT 2	DESIGNED -	REVISED - 4-20-17
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/7/2025	DATE -	REVISED - 4-04-11


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

TRAFFIC CONTROL FOR THREE LANE SECTION CASE 1



- ① Use flagger and flagger signs only when flagger is required per Article 701.13(b).
- ② Cones at 20' centers for 250'. Additional cones may be placed at 40' centers. When drums or type I or II barricades are used, the interval between devices may be doubled.

SYMBOLS

- WORK AREA
- SIGN
- FLAGGER WITH TRAFFIC CONTROL SIGN
- CONE, DRUM OR BARRICADE
- TYPE III BARRICADE

THIS TRAFFIC CONTROL DETAIL SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

MODEL: 3761L_Sheet1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 8-27-13
	CHECKED -	REVISED - 7-30-13
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
								CONTRACT NO.		
								ILLINOIS FED. AID PROJECT		

TRAFFIC CONTROL FOR THREE LANE SECTION

CASE 2

W20-1103(0)-48



W20-1103(0)-48



- ① Use flagger and flagger signs only when flagger is required per Article 701.13(b).
- ② Cones at 20' centers for 250', Additional cones may be placed at 40' centers. When drums or type I or II barricades are used, the interval between devices may be doubled.

SYMBOLS



WORK AREA



SIGN



FLAGGER WITH TRAFFIC CONTROL SIGN



CONE, DRUM OR BARRICADE

THIS TRAFFIC CONTROL DETAIL SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

*IF THE WORK ENDS WITHIN 2500 FEET OF THE TRANSITION WHEN THE SPEED IS > 40 MPH OR 1500 FEET FOR ALL OTHER SPEEDS, THE CLIMBING LANE SHALL REMAIN CLOSED AS SHOWN.

MODEL: 3761L_Sheet2
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 8-27-13
	CHECKED -	REVISED - 7-30-13
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

TRAFFIC CONTROL FOR THREE LANE SECTION

CASE 3



MODEL: 3761L_Sheet3
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 8-27-13
	CHECKED -	REVISED - 7-30-13
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

TRAFFIC CONTROL FOR THREE LANE SECTION

CASE 4

W20-1103(0)-48



NOTE: DO NOT OPEN THE CLIMBING LANE UNLESS THERE IS AT LEAST 1/2 MILE BEFORE THE LANE ENDS.

SYMBOLS

- WORK AREA
- SIGN
- FLAGGER WITH TRAFFIC CONTROL SIGN
- CONE, DRUM OR BARRICADE
- TYPE III BARRICADE

② Cones at 20' centers for 250'. Additional cones may be placed at 40' centers. When drums or type I or II barricades are used, the interval between devices may be doubled.

THIS TRAFFIC CONTROL DETAIL SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

CASE 4 APPLIES WHEN NO WORKERS ARE PRESENT. WHEN WORKERS ARE PRESENT, TWO LANES SHALL BE CLOSED AND TRAFFIC CONTROL SHALL BE ACCORDING TO CASE 3.

MODEL: 3791L_Sheet4
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT / DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 8-27-13
	CHECKED -	REVISED - 7-30-13
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
								CONTRACT NO.		
								ILLINOIS FED. AID PROJECT		

TRAFFIC CONTROL FOR TRANSITION AREAS

CASE 1



GENERAL NOTES

THIS DETAIL IS TO BE USED IN CONJUNCTION WITH THE APPLICABLE MULTILANE TRAFFIC CONTROL AND PROTECTION STANDARD.

1. If applicable, use if shown on applicable multilane Traffic Control and Protection Standard being used.
2. If the work is within 2500 feet of the transition when the speed is > 40 mph, or 1500 feet for all other speeds, the detail shall be used.
3. WORK ZONE SPEED LIMIT 55 SIGN ASSEMBLY shall be replaced with WORK ZONE SPEED LIMIT 45 SIGN ASSEMBLY where the workers are within 500 feet of the transition.

THIS TRAFFIC CONTROL DETAIL SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

MODEL: 2041L_Sheet1
FILE NAME: DISTRICT 2 STANDARD


USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 4-20-17
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 1-16-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD				F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.		
						ILLINOIS	FED. AID PROJECT	

TRAFFIC CONTROL FOR TRANSITION AREAS

CASE 2



MODEL: 2041L_Sheet2
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 4-20-17
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 1-16-13


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

TRAFFIC CONTROL FOR TRANSITION AREAS

CASE 3



GENERAL NOTES
 THIS DETAIL IS TO BE USED IN CONJUNCTION WITH THE APPLICABLE MULTILANE TRAFFIC CONTROL AND PROTECTION STANDARD.

1. If applicable, Use if shown on applicable multilane Traffic Control and Protection Standard being used.
2. If the work is within 2500 feet of the transition when the speed is > 40 mph, or 1500 feet for all other speeds, the detail shall be used.
3. WORK ZONE SPEED LIMIT 55 SIGN ASSEMBLY shall be replaced with WORK ZONE SPEED LIMIT 45 SIGN ASSEMBLY where the workers are within 500 feet of the transition.

THIS TRAFFIC CONTROL DETAIL SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

NOTE: STANDARDS 701301 AND 701306 SHALL NOT BE USED WITHIN 500 FEET OF THE TRANSITION.

- FLAGGER WITH TRAFFIC CONTROL SIGN
- DRUMS OR BARRICADES WITH LIGHTS
- WORK AREA

MODEL: 2041L_Sheet3
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 4-20-17	
	DRAWN -	REVISED - 1-05-16	
	CHECKED -	REVISED - 8-27-13	
PLOT DATE = 4/17/2025	DATE -	REVISED - 3-05-12	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
								CONTRACT NO.			
								ILLINOIS FED. AID PROJECT			

TRAFFIC CONTROL FOR TRANSITION AREAS

CASE 4



GENERAL NOTES
 THIS DETAIL IS TO BE USED IN CONJUNCTION WITH THE APPLICABLE MULTILANE TRAFFIC CONTROL AND PROTECTION STANDARD.

1. If applicable. Use if shown on applicable multilane Traffic Control and Protection Standard being used.
2. If the work is within 2500 feet of the transition when the speed is > 40 mph, or 1500 feet for all other speeds, the detail shall be used.
3. WORK ZONE SPEED LIMIT 55 SIGN ASSEMBLY shall be replaced with WORK ZONE SPEED LIMIT 45 SIGN ASSEMBLY where the workers are within 500 feet of the transition.

THIS TRAFFIC CONTROL DETAIL SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

- FLAGGER WITH TRAFFIC CONTROL SIGN
- DRUMS OR BARRICADES WITH LIGHTS
- WORK AREA

NOTE: STANDARDS 701301 AND 701306 SHALL NOT BE USED WITHIN 500 FEET OF THE TRANSITION.

MODEL: 2004L_Sheet4
 FILE NAME: DISTRICT 2 STANDARD


USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 4-20-17
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/7/2025	DATE -	REVISED - 3-05-12

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

TRAFFIC CONTROL TYPICAL WEAVE



SYMBOLS

- DRUM WITH STEADY BURN MONO-DIRECTIONAL LIGHT
- ┆ SIGN

STANDARD WEAVE CONDITIONS FOR DIFFERENT SPEED LIMITS

POSTED SPEED LIMIT	WEAVE LENGTH
65 MPH OR HIGHER	780 FT.
55 MPH	660 FT.
45 MPH	540 FT.

GENERAL NOTES:

USE ON LONG 4-LANE PROJECTS WHERE THE CONTRACTOR MAY CHANGE A PORTION OF THE WORK TO THE OPPOSITE LANE.

USE WHERE THE PROJECT IS ADJACENT TO ANOTHER AND THE CONTRACTOR COULD BE WORKING ON DIFFERENT LANES.

TEMPORARY PAVEMENT MARKING SHALL BE USED WHEN TYPICAL WEAVE IS USED FOR 14 DAYS OR MORE.

TRAFFIC CONTROL TYPICAL WEAVE SHALL BE INCLUDED IN THE COST OF THE SPECIFIC TRAFFIC CONTROL STANDARDS OF ITEMS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 20941
FILE NAME: DISTRICT 2 STANDARD


USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 6-27-14
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/7/2025	DATE -	REVISED - 10-17-11

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS	FED. AID PROJECT

TRAFFIC CONTROL FOR ROAD CLOSURE




①

SIGN SPACING TABLE	
Posted Speed	Sign Spacing
45 MPH and above	500'
Below 45 MPH	250'

②

SIGN LEGEND	
Posted Speed Limit	Distance
45 MPH and above	1000'
Below 45 MPH	500'

ROAD CLOSED TO THRU TRAFFIC BARRICADE SET UP



Type III Barricades and R11-4-4830 signs shall be as shown in "Road Closed to Thru Traffic" detail on Highway Standard 701901. If the distance "D" exceeds 2000' an additional set of barricades and R11-4-4830 shall be placed at each end of the work area.

SYMBOLS

-  Work area
-  Type III Barricade with Flashers
-  Sign with flashing light

GENERAL NOTES

- Longitudinal dimensions may be adjusted to fit field conditions.
- Side roads requiring all three signs as shown in CONDITION I (Major Sideroad Closure), shall be listed in the special provision.
- ** Where local access is to be maintained, barricades are to be set up as shown in "Road Closed to Thru Traffic". Type III Barricades and R11-2-4830 signs shall be as shown in "Road Closed to All Traffic" detail on Highway Standard 701901.
- All dimensions are in inches unless otherwise shown.

TYPICAL APPLICATION FOR ROAD CLOSURE

MODEL: 40941
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT / DISTRICT 2	DESIGNED -	REVISED - 8-03-17
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/7/2025	DATE -	REVISED - 10-17-11


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS	FEB. 40 PROJECT

TYPICAL PAVEMENT MARKINGS

TYPICAL PAVEMENT MARKING FOR FLUSH MEDIAN AT LEFT TURN LANE




MEDIAN PAVEMENT MARKING




** ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

TYPICAL ISLAND OFFSET SHOULDER WIDTH




TYPICAL MARKING FOR PAINTED ISLANDS

NOTE:
* 45° TO LOCAL TAN.



STANDARD CROSSWALK MARKING

See Schedules for Locations



* Distance to the nearest edge of the intersecting roadway in the absence of a marked crosswalk.

MODEL: 4101L_Sheet1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 6-27-14
	DRAWN -	REVISED - 3-05-12
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RT#	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS FED. AID PROJECT	

TYPICAL PAVEMENT MARKINGS

ARROW LAYOUT




SYMBOLS

- ◀ ONE-WAY AMBER MARKER
- ◁ ONE-WAY CRYSTAL MARKER
- ◆ TWO-WAY AMBER MARKER

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


TYPICAL PAVEMENT MARKING FOR FLUSH MEDIAN



RECOMMENDED SPACING BETWEEN DIAGONALS (IN FEET)

Speed Limit Range	Continuous Median Area	Intersection Channelization	Objects (Islands)
less than 30MPH	50'	15'	10'
30-40MPH	75'	20'	15'
45MPH & over	75'	30'	20'

NOTE: If the spacing recommended in the Table does not permit at least five diagonal lines in the area being marked, the spacing from the next lowest speed range should be used. The recommended spacing is measured parallel to the pavement center line.



MODEL: 4101L_Sheet2
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS07/DISTRICT 2	DESIGNED -	REVISED - 6-27-14
	DRAWN -	REVISED - 3-05-12
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

TYPICAL PAVEMENT MARKINGS



MULTI-LANE / DIVIDED



* REDUCE TO 40' O.C. ON CURVES WHERE ADVISORY SPEEDS ARE 10 MPH LOWER THAN POSTED SPEEDS.


** USE DOUBLE MARKERS WHEN ADT \geq 20,000

*** CENTERLINE SKIP DASH PAVEMENT MARKING SPEED LIMIT LESS THAN 40 MPH USE 4" LINE. SPEED LIMIT 40 MPH AND OVER USE 6" LINE.


MULTI-LANE / UNDIVIDED & ONE WAY

(FOR MULTI-LANE UNDIVIDED HIGHWAYS USE THIS
DETAIL NOT HIGHWAY STANDARD 781001)

TYPICAL PARKING SPACING



TYPICAL PAVEMENT MARKING FOR TWO LANE SECTION - NO PASSING ZONES



MODEL: 410PL_Sheet3
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT / DISTRICT 2	DESIGNED -	REVISED - 6-27-14
	DRAWN -	REVISED - 8-27-13
	CHECKED -	REVISED - 11-28-12
PLOT DATE = 4/7/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. DIST.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
--------	-------	----	--------	------	---------	------------	---------	--------	--------------	-----------


CONTRACT NO.									
ILLINOIS FED. AID PROJECT									

TYPICAL PAVEMENT MARKINGS


** 6" WHITE ON INTERSTATES, WHERE THE SPEED LIMIT IS 65 MPH, OR WHEN DIRECTED BY THE ENGINEER.
4" WIDE AT ALL OTHER LOCATIONS.

NOTE: GORE HATCHING PLACED ONLY WHEN SCHEDULED IN THE PLANS

EXIT RAMP




ENTRANCE RAMP



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

CLOVERLEAF



MODEL: 4101L_Sheet4
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 9-15-23
	DRAWN -	REVISED - 8-27-13
	CHECKED -	REVISED - 10-18-11
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
										ILLINOIS FED. AID PROJECT


TYPICAL PAVEMENT MARKINGS

EDGE OF 24" PAVEMENT MARKING SHOULD CORRESPOND TO REFERENCE POINT SET IN FIELD.



**SLOW CURVE ARROW
HIGH-SPEED STANDARD MARKING**

(POSTED SPEED LIMIT 40 MPH OR GREATER)




**SLOW CURVE ARROW
LOW-SPEED STANDARD MARKING**

(POSTED SPEED LIMIT 35 MPH OR LESS)

TABLE 1A

POSTED SPEED	WARNING SPEED							
	20	25	30	35	40	45	50	55
VALUE OF X (FT.)								
20 *	100							
25 *	100	100						
30 *	100	100	100					
35 *	100	100	100	100				
40 *	100	100	100	100	100			
45 *	125	110	100	100	100	100		
50 *	225	200	175	135	100	100	100	
55 *	300	275	250	200	175	135	100	100

* NOTE: ON ROADWAYS WITH A POSTED SPEED LIMIT OF 35 MPH OR LESS, USE THE 35'-6" PAVEMENT MARKING LEGEND AS SHOWN IN THE SLOW CURVE ARROW, LOW-SPEED STANDARD MARKING. ON ALL OTHER ROADWAYS, USE THE 50'-0" PAVEMENT MARKING LEGEND AS SHOWN ON THE SLOW CURVE ARROW, HIGH-SPEED STANDARD MARKING.



**TYPICAL LAYOUT AND PLACEMENT OF
SUPPLEMENTAL CURVE PLACEMENT MARKING**

MODEL: 41011_01m05
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT/DISTRICT 2
DESIGNED -
DRAWN -
CHECKED -
PLOT DATE = 4/17/2025

DESIGNED -
DRAWN -
CHECKED -
DATE -

REVISED - 4-17-25
REVISED -
REVISED -
REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE: SHEET 50 OF SHEETS STA. TO STA.


F.A. RITE. SECTION COUNTY TOTAL SHEETS SHEET NO.
CONTRACT NO.
ILLINOIS FED. AID PROJECT

REMOVE AND REERECT STEEL PLATE BEAM GUARDRAIL




TYPE A

6'-3" Typical post spacing




SECTION A-A




TYPE B

37 1/2" Closed post spacing




SECTION C-C




TYPE D

Double steel plate beam guardrail
6'-3" typical post spacing



TYPE C

37 1/2" Block-out spacing



SECTION B-B

GENERAL NOTES

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).

All dimensions are in inches unless otherwise shown.

The existing steel posts may be drilled to match the bolt pattern shown herein for the wood block-out, or a new steel post shall be provided.

This detail is applicable to the guardrail system used prior to January 1, 2007. For details on the Midwest Guardrail System, see Standard 630001.

MODEL: 2001L_Sheet1
FILE NAME: DISTRICT 2 STANDARD

USER NAME = I007/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 10-19-11
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -





**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

REMOVE AND REERECT STEEL PLATE BEAM GUARDRAIL



NOTE
Plate A shall be placed between rail element and block-out at non-splice mounting points only when steel block-outs are used.



MODEL: 2014_Sheet2
FILE NAME: DISTRICT 2 STANDARD


USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 10-19-11
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						ILLINOIS FED. AID PROJECT				


REMOVE AND REERECT STEEL PLATE BEAM GUARDRAIL



SPLICE PLATE





RAIL ELEMENT SPLICE




NOTE

Anchor plate T shall be used to attach cable assembly to guardrail when required on traffic barrier terminals.

ANCHOR PLATE T DETAILS



END SECTION




NOTE

When end shoe is attached to a bridge parapet which has an expansion joint, the bolts shall be provided with a locknut or double nut and shall be tightened only to a point that will allow guardrail movement.

The standard end shoe shall be attached to the concrete with pre-drilled or self-drilling anchor bolts. The anchor cone shall be set flush with the surface of the concrete.

Externally threaded studs protruding from the surface of the concrete will not be permitted.

END SHOE



ALTERNATE END SHOE

MODEL: 2041L_Sheet3
FILE NAME: DISTRICT 2 STANDARD



USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 10-19-11
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
										CONTRACT NO.
										ILLINOIS FED. AID PROJECT


REMOVE AND REERECT STEEL PLATE BEAM GUARDRAIL




Note:
If it is necessary for D to be more than 18" and less than 10'4" (bridge curb and gutter (Std. 606001) shall be used in front of and in advance of the guardrail.

GUARDRAIL PLACED BEHIND CURB

(D - O desirable to 120" maximum)



WOOD BLOCK-OUT AND STEEL POST DETAILS




Note:
Ledge line is top of rock ledge or hard slag fill.

ELEVATION

FOOTING FOR POST WHEN IMPERVIOUS MATERIAL IS ENCOUNTERED

V	W	L	
		Steel Post	Wood Post
0 - 18	24	21	23
>18 - 41.5	12	8	10
>41.5 - 53.5	12 - 0	8	10



CABLE ASSEMBLY

(40,000 lbs. min. breaking strength)
Tighten to taut tension.

MODEL: 5091L_Sheet4
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 10-19-11
	CHECKED -	REVISED -
PLOT DATE = 4/7/2025	DATE -	REVISED -








STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

SCALE: SHEET OF SHEETS STA. TO STA.

TRAFFIC BARRIER TERMINAL, TYPE 2 (27" HEIGHT)



GENERAL NOTES

See Standard 630001 for details of guardrail not shown.

The bearing plate K shall be held in position by (2) two eight penny nails driven into the post and bent over the top of the plate.

All dimensions are in Inches unless otherwise shown.

MODEL: 54-R1T
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 10-18-11
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS FED. AID PROJECT	


REFLECTORS (SPECIAL)

DELINEATOR REPLACEMENT


③ REPLACING 3 BUTTON DELINEATOR




② REPLACING 2 BUTTON DELINEATOR



① STRAIGHT REFLECTOR / DELINEATOR



SIDE VIEW



NOTE:

REFLECTOR REPLACEMENT SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER EACH FOR GUARDRAIL REFLECTORS, TYPE C (SPECIAL), WHICH INCLUDES ALL MOUNTING HARDWARE OUTLINED IN SECTION 635 OF THE SPEC BOOK.

DELINEATOR INSTALLATION (REFLECTOR AND POST) SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER EACH FOR DELINEATORS (SPECIAL), WHICH INCLUDES ALL MOUNTING HARDWARE OUTLINED IN SECTION 635 OF THE SPEC BOOK.


REFLECTORS INSTALLED ON TWO LANE ROADS SHALL BE DOUBLE SIDED AND BOTH SIDES SHALL BE CRYSTAL.

REFLECTORS INSTALLED ON CENTER BARRIER OR IN THE MEDIAN SHALL BE DOUBLE SIDED AND BOTH SIDES SHALL BE YELLOW.

REFLECTORS INSTALLED ON DIVIDED HIGHWAYS ON THE OUTSIDE OF THE ROADWAY SHALL BE DOUBLE SIDED CRYSTAL.

SPACING FOR REFLECTORS SHALL BE ACCORDING TO STANDARD 782006 UNLESS OTHERWISE NOTED IN THE PLANS.

REFLECTORS FOR GUARDRAIL BLOCK OUT OR DELINEATOR POST




MOUNTED ON A GUARDRAIL BLOCK OUT

REFLECTORS SHALL BE MOUNTED DIRECTLY TO BLOCK OUTS.

REFLECTORS MOUNTED ON WOODEN OR PLASTIC OR METAL BLOCK OUT SHALL BE MOUNTED USING TWO 2 1/2" GALVANIZED SCREWS WITH WASHERS OR TWO SELF TAPPING GALVANIZED SCREWS WITH WASHERS.


ADDITIONAL SHEETING MAY BE ADDED AS NEEEDED FOR TURN AROUNDS AS SHOWN IN THE PLANS




MOUNTED ON A DELINEATOR POST

TOP OF REFLECTOR PLACED FLUSH WITH TOP OF POST UNLESS DOUBLE SIDED REFLECTOR IS CALLED FOR, THEN REFLECTOR SHALL BE PLACED SUCH THAT THE REFLECTOR IS ABOVE THE TOP OF THE POST AND VISIBLE.


ADDITIONAL HOLES SHALL BE DRILLED IN THE REFLECTORS AS SHOWN ABOVE.



DELINEATORS SHALL BE INSTALLED ACCORDING TO STANDARD 635001 EXCEPT THAT THE POST SHALL BE ROTATED 180°. THE POST WILL HAVE THE WIDE SIDE FACING TRAFFIC AND THE REFLECTOR ATTACHED AS SHOWN ABOVE.




REFLECTORS MOUNTED ON BARRIER WALL



SIDE VIEW

Cross section may be "T" or "L" shaped and may have side supports at ends.



NOTE:

REFLECTORS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER EACH FOR BARRIER WALL REFLECTORS (SPECIAL), WHICH PRICE SHALL ALSO INCLUDE SCREWS, WASHERS OR AN APPROVED BONDING AGENT.

REFLECTORS INSTALLED ON TWO LANE ROADS SHALL BE DOUBLE SIDED AND BOTH SIDES SHALL BE CRYSTAL.

REFLECTORS INSTALLED ON CENTER BARRIER SHALL BE DOUBLE SIDE AND BOTH SIDES SHALL BE AMBER.

REFLECTORS INSTALLED ON DIVIDED HIGHWAYS ALONG THE OUTSIDE OF THE HIGHWAY SHALL BE DOUBLE SIDED CRYSTAL.

SPACING FOR REFLECTORS SHALL BE ACCORDING TO STANDARD 782006 UNLESS OTHERWISE NOTED IN THE PLANS.

LEGEND

OR = DELINEATOR

[Diamond Pattern] = REFLECTIVE AREA

MODEL: 5694T
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT / DISTRICT 2	DESIGNED -	REVISED - 3-07-25
	DRAWN -	REVISED - 3-07-24
	CHECKED -	REVISED - 4-27-23
PLOT DATE = 4/7/2025	DATE -	REVISED - 6-21-21

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
										CONTRACT NO.
										ILLINOIS FED. AID PROJECT

LOADING CONDITION	MAX. EXTENDER HEIGHT - "H"
H20/H25 * 750 PSI CONCRETE	19"

* 125 PSI TIRE PRESSURE





PLATE EXTENDERS
7 GA. GALVANIZED PLATE
PER ASTM A761
SLOPE AS REQUIRED.



GENERAL

Class S1 Concrete shall be used throughout. This specification covers Slotted Drain used for the removal of water as shown on the plans. The Slotted Drain shall be Corrugated Pipe Culvert with Integral Slotted Drains. Before placing the concrete adjacent to the pipe, the slot shall be covered by either thin flat metal sheeting or by a board notched to fit over the grate bars. This covering must fit closely in the slot to prevent entry of concrete into the pipe. Paving over the slotted drain will then be one continuous operation over the protected drain. The protection for the drain slot shall then be removed. The pipe shall drain into the side of the inlet. The opening where the slot is removed shall be covered to prevent concrete from entering the pipe. The Corrugated Steel Pipe used in the Slotted Drain shall meet the requirements of AASHTO M36/ASTM A760. The CMP shall be ALUMINIZED STEEL Type 2. The diameter shall be as shown on the plans. Steel grating shall meet the galvanizing requirements of AASHTO M111. This work will be paid for at the contract unit price per foot for SLOTTED DRAIN of the pipe diameter specified WITH VARIABLE SLOT, or SLOTTED DRAIN, of the pipe diameter specified, WITH 6" SLOT, and shall include concrete and grating for depth specified on plans. Use approved end cap to prevent concrete entry into the pipe during gutter construction on the upstream end of the pipe.

CONNECTIONS

The Corrugated Steel Pipe shall have a minimum of two rolled annular ends. The Slotted Drain bands shall be modified HUGGER Bands to secure the pipe and prevent infiltration of the backfill. When the Slotted Drain is banded together, the adjacent grates shall have a maximum 3" gap.

GRATES

The grates shall be manufactured from ASTM A670, Grade 36 steel. The spacers and bearing bars (sides) shall be 3/16" material ±0.008". The spacers shall be on 6" centers and welded on both sides to each bearing bar (sides) with four (4) 1/4" x 1/4" long 3/16" fillet welds on each side of the bearing bar. The plate extender shall be 7 gage steel meeting ASTM A761. The engineer may call for tensile strength tests on the grate if the grate is not in compliance with the above spacer specifications. If tensile strength tests are called for, minimum results for an in-place spacer pulled perpendicular to the bearing bar shall be:
T = 12,000 pounds for 2-1/2" grate
T = 15,000 pounds for 6" grate

GALVANIZING

The grate and plate extenders shall be galvanized in accordance with ASTM A123 except with a 2 oz. galvanized coating.





GRATE ATTACHED TO CSP

The grate shall be fillet welded with a minimum weld 1" long to the CSP on each side of the grate at every other corrugation.

TOLERANCES - FINISHED SLOTTED DRAIN - 20' LENGTHS

Vertical Bow = ± 3/8"
Horizontal Bow = ± 5/8"
Twist = ± 1/2"

SLOTTED DRAIN PIPE



SECTION A-A
DETAIL WITH MESH
(TRAPEZOIDAL GALVANIZED GRATE SHOWN)








GAGE OF PIPE	STANDARD SIZES					
	DIAMETER OF PIPE					
12"	15"	18"	24"	30"	36"	
16	X	X	X	X	X	
14	X	X	X	X	X	
12	N.A.	N.A.	N.A.	N.A.	X	

GRATE TYPE	"A"	
		VERT
TRAP	2-1/2"	2-1/4"
TRAP	6"	3"

VERT = VERTICAL
TRAP = TRAPEZOIDAL

SLOTTED DRAIN NOTES

- GRATING IS AVAILABLE IN DEPTHS OF 2-1/2" AND 6".
- VERTICAL GRATING (STRAIGHT SIDES) WITH VERTICAL SPACERS IS ALSO AVAILABLE.
- FOR 6" VERTICAL & TRAPEZOIDAL REQUIREMENTS, THE SLOTTED DRAIN BAND MAY BE FURNISHED WITH THE 4" TECHCO BAND ANGLE.
- DIMENSIONS ARE SUBJECT TO MANUFACTURING TOLERANCES.
- DIMENSIONS FOR H AND H AS REQUIRED.
- H AND H MEASURED FROM TOP OF GRATE TO BOTTOM OF GRATE.



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 4804T
FILE NAME: DISTRICT 2 STANDARD




USER NAME = IBOOT/DISTRICT 2	DESIGNED -	REVISED - 1-05-16
	DRAWN -	REVISED - 6-27-14
	CHECKED -	REVISED - 10-18-11
PLLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RITE:	SECTION	COUNTY	TOTAL SHEET NO.
CONTRACT NO.									
ILLINOIS FEB. 40 PROJECT									

DETAIL OF FLOOD GATE



QUANTITIES FOR 2 DEADMEN
 0.3 CU.YD CLASS SI CONCRETE
 36 LBS REINFORCEMENT BARS

DETAIL OF PRECAST CONCRETE DEADMAN



QUANTITIES FOR 2 DEADMEN
 0.7 CU. YD. CLASS SI CONCRETE

DETAIL OF CAST-IN-PLACE CONCRETE DEADMAN


BILL OF MATERIALS

QUAN.	UNIT	ITEM
FT		1/2 DIA. GALVANIZED WIRE ROPE
EACH		1/2 DIA. x 15 GALVANIZED EYE BOLTS WITH NUTS AND WASHERS
EACH		1/2 DIA. GALVANIZED TURNBUCKLES
EACH		1/2 DIA. GALVANIZED CABLE CLAMPS
EACH		5x5x3/4 STEEL WASHER PLATES
EACH		PRECAST CONCRETE DEADMEN OR CAST-IN-PLACE CONCRETE DEADMEN
FT		12 CREOSOTED TIMBER PILE (INCLUDES FURNISHING AND DRIVING TIMBER PILE)

NOTE:
 THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER EACH FOR

BILL OF MATERIALS

QUANTITY	UNIT	ITEM
	FT	2 x 4 TREATED LUMBER
	FT	GALVANIZED BARBED WIRE
	FT	SPECIAL STEEL CHANNEL SC 25, 2 1/2 x 2 1/2
	EACH	1/2 x 3 GALVANIZED STEEL BOLTS AND WASHERS
	EACH	1/2 x 2 GALVANIZED STEEL U-BOLTS
	EACH	GALVANIZED CABLE CLAMPS
	LBS	GALVANIZED FENCE STAPLES



DETAIL 'A'
 EXPLODED VIEW OF FLOOD GATE TO CABLE

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

NOTE:
 PRECAST CONCRETE DEADMEN AND CAST-IN-PLACE CONCRETE DEADMEN SHALL BE CONSTRUCTED OF CLASS SI CONCRETE

MODEL: 7104T
 FILE NAME: DISTRICT 2 STANDARD

USER NAME = I007/DISTRICT 2	DESIGNED -	REVISED - 8-09-12
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. DIST.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

40' SINGLE LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 55 MPH, WORK ZONE SPEED LIMIT 45 MPH)

TYPICAL SECTION






TABLE OF OFFSETS AND DROPS						
Distance feet from location station	0	60'	75'	100'	125'	143.73'
Offsets feet from inside edge of pavement	20'	18'	15.32'	11.37'	8.06'	6.00'
Drop feet from inside edge of pavement	0.0'	0.0'	0.0'	0.0'	0.0'	0.0'



SECTION A-A
(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)



SECTION A-A
(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)


GENERAL NOTES

- Construction of median crossover shall conform to the requirement of current Standard Specifications.
- Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.
- Pavement, subbase, & shoulder quantities are:

(1340.88 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(1250.80 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(45.1 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(402.52 Sq. Yds.)	HMA SHOULDERS 6"
- Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.
- See District Standard 61.2 or 68.1 for details for the slotted drain.
- See District Standard 86.1 for details for the beveled pipe & guard.
- The crossover is designed using a 45mph design speed.
- The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.
- The PCC Pavement 10" (Jointed) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106
- The PCC Pavement 10" (Jointed) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (Jointed).

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL.

MODEL: 72041
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 12-07-10

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

50' SINGLE LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 55 MPH, WORK ZONE SPEED LIMIT 45 MPH)

TYPICAL SECTION






TABLE OF OFFSETS AND DROPS							
Distance feet from location station	0'	53'	75'	100'	125'	150.00'	161.73'
Offsets feet from inside edge of pavement	25'	23'	18.57'	14.14'	10.37'	7.25'	6.00'
Drop feet from inside edge of pavement	0.5'	0.46'	0.37'	0.28'	0.021'	0.15'	0.12'

GENERAL NOTES

- Construction of median crossover shall conform to the requirement of current Standard Specifications.
- Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.
- Pavement, subbase, & shoulder quantities are:


(1634.94 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(1533.52 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(52.9 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(472.79 Sq. Yds.)	HMA SHOULDERS 6"
- Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.
- See District Standard 61.2 or 68.1 for details for the slotted drain.
- See District Standard 86.1 for details for the beveled pipe & guard.
- The crossover is designed using a 45mph design speed.
- The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.
- The PCC Pavement 10" (Jointed) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106
- The PCC Pavement 10" (Jointed) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (Jointed).



① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

SECTION A-A
(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL.

MODEL: 7041
FILE NAME: DISTRICT 2 STANDARD

USER NAME = J007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 12-07-10

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

64' SINGLE LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 55 MPH, WORK ZONE SPEED LIMIT 45 MPH)

TYPICAL SECTION





TABLE OF OFFSETS AND DROPS									
Distance feet from location station	0	46'	50'	75'	100'	125'	150'	175'	185.20'
Offsets feet from inside edge of pavement	32'	30'	29.02'	23.32'	18.28'	13.90'	10.17'	7.08'	6'
Drop feet from inside edge of pavement	0.64'	0.6'	0.58'	0.47'	0.37'	0.28'	0.20'	0.14'	0.12'


GENERAL NOTES

- Construction of median crossover shall conform to the requirement of current Standard Specifications.
- Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.
- Pavement, subbase, & shoulder quantities are:

(2071.96 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(1956.64 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(62.5 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(558.24 Sq. Yds.)	HMA SHOULDERS 6"
- Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.
- See District Standard 61.2 or 68.1 for details for the slotted drain.
- See District Standard 86.1 for details for the beveled pipe & guard.
- The crossover is designed using a 45mph design speed.
- The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.
- The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106
- The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).




SECTION A-A
(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)



SECTION A-A
(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving



TYPICAL PLAN

- Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.
- Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.
- TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL.

MODEL: 74RPT
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 12-07-10

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD			
SCALE:	SHEET	OF	SHEETS
			STA. TO STA.

F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

40' SINGLE LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION




TABLE OF OFFSETS AND DROPS							
Distance feet from location station	0	77'	100'	125'	150'	175'	183.23
Offsets feet from inside edge of pavement	20'	18'	14.79'	11.69'	8.98'	6.67'	6'
Drop feet from inside edge of pavement	0.4'	0.36'	0.3'	0.23'	0.18'	0.13'	0.12'

GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(1709.35 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(1596.03 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(57.1 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(509.64 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

ⓐ Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL.

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/7/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

50' SINGLE LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION




TABLE OF OFFSETS AND DROPS									
Distance feet from location station	0'	68'	75'	100'	125'	150'	175'	200'	206.02'
Offsets feet from inside edge of pavement	25'	23'	21.84'	17.87'	14.50'	11.43'	8.76'	6.49'	6'
Drop feet from inside edge of pavement	0.5'	0.46'	0.44'	0.36'	0.29'	0.23'	0.175'	0.13'	0.12'

GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(2084.0 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(1956.55 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(67.1 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(598.67 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 14' front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30' cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A


(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)



SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

Ⓢ Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving



TYPICAL PLAN

Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/7/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

64' SINGLE LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION




TABLE OF OFFSETS AND DROPS										
Distance feet from location station	0	60'	75'	100'	125'	150'	175'	200'	225'	236.83'
Offsets feet from inside edge of pavement	32'	30'	27.18'	22.80'	18.84'	15.27'	12.11'	9.35'	6.98'	6'
Drop feet from inside edge of pavement	0.64'	0.6'	0.54'	0.456'	0.377'	0.31'	0.24'	0.187'	0.139'	0.12'

GENERAL NOTES

- Construction of median crossover shall conform to the requirement of current Standard Specifications.
- Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.
- Pavement, subbase, & shoulder quantities are:

(2651.79 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(2509.74 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(79.2 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(707.03 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.
See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL.

MODEL: 77641
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/7/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.										
ILLINOIS FED. AID PROJECT										

88' SINGLE LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION



GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(3704.06 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(3535.98 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(96.79 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(864.23 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TABLE OF OFFSETS AND DROPS

Distance feet from location station	0	50'	75'	100'	125'	150'	175'	200'	225'	250'	275'	283.50'
Offsets feet from inside edge of pavement	44'	42'	36.44'	31.30'	26.57'	22.25'	18.34'	14.83'	11.72'	9.01'	6.70'	6'
Drop feet from inside edge of pavement	0.88'	0.84'	0.73'	0.63'	0.53'	0.43'	0.37'	0.30'	0.23'	0.18'	0.13'	0.12'



TYPICAL PLAN

Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/17/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS FED. AID PROJECT	

40' TWO LANE MEDIAN CROSSOVER (POSTED SPEED LIMIT 55 MPH, WORK ZONE SPEED LIMIT 45 MPH)

TYPICAL SECTION




TABLE OF OFFSETS AND DROPS						
Distance feet from location station	0	76.95	100'	125'	150'	168.69'
Offsets feet from inside edge of pavement	20'	18'	14.22'	10.70'	7.79'	6.00'
Drop feet from inside edge of pavement	0.4'	0.36'	0.28'	0.21'	0.16'	0.12'

GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(1,685.28 Sq. Yds.) (1,572.43 Sq. Yds.) (57.28 Tons) (511.45 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12" P.C.C. PAVEMENT 10" (JOINTED) 2" HMA SURFACE COURSE, MIX "C", N50 HMA SHOULDERS 6"
---	---

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 45mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

Ⓢ Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

MODEL: 7994T
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 4-04-11

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
								CONTRACT NO.		
								ILLINOIS FED. AID PROJECT		

50' TWO LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 55 MPH, WORK ZONE SPEED LIMIT 45 MPH)

TYPICAL SECTION




TABLE OF OFFSETS AND DROPS

Distance feet from location station	0	65.72	75	100	125	150	175	188.01
Offsets feet from inside edge of pavement	25'	23'	21.95'	17.35'	13.37'	9.99'	7.21'	6.00'
Drop feet from inside edge of pavement	0.5'	0.46'	0.44'	0.35'	0.27'	0.20'	0.14'	0.12'

GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(2029.23 Sq. Yds.) (1904.29 Sq. Yds.) (65.64 Tons) (586.07 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12\"/>
---	--

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12\"/>

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 45mph design speed.

The end of the pipe guard shall be set where a minimum 14' front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10\"/>

The PCC Pavement 10\"/>



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

MODEL: 2004T
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 4-04-11

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				

64' TWO LANE MEDIAN CROSSOVER (POSTED SPEED LIMIT 55 MPH, WORK ZONE SPEED LIMIT 45 MPH)

TYPICAL SECTION




TABLE OF OFFSETS AND DROPS

Distance feet from location station	0	62.41'	75'	100'	125'	150'	175'	200'	212.87'
Offsets feet from inside edge of pavement	32'	30'	27.14'	21.82'	17.33'	13.35'	9.97'	7.20'	6.00'
Drop feet from inside edge of pavement	0.64'	0.60'	0.54'	0.44'	0.35'	0.27'	0.20'	0.14'	0.12'

GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(2534.76 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(2394.89 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(75.73 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(676.15 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 45mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30' cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 8-27-13
PLOT DATE = 4/17/2025	DATE -	REVISED - 4-04-11

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

REGION 2 / DISTRICT 2 STANDARD


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.
CONTRACT NO.					
ILLINOIS FED. AID PROJECT					

MODEL: 81041
FILE NAME: DISTRICT 2 STANDARD

40' TWO LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION



Distance feet from location station	0	100.33	125	150	175	200	220.57
Offsets feet from inside edge of pavement	20'	18'	14.88'	12.07'	9.60'	7.48'	6.00'
Drop feet from inside edge of pavement	0.40'	0.36'	0.30'	0.24'	0.19'	0.15'	0.12'

GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(2142.56 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(2003.87 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(71.01 Tons)	2" HMA SURFACE COURSE, MIX 'C', N50
(634.04 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

USER NAME = IJ007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/7/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS FED. AID PROJECT	

50' TWO LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION



GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(2593.23 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(2438.79 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(81.92 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(731.46 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 14' front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

Ⓢ Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

Distance feet from location station	0	90.88	100	125	150	175	200	225	246
Offsets feet from inside edge of pavement	25'	23'	21.63'	18.10'	14.93'	12.11'	9.64'	7.52'	6.00'
Drop feet from inside edge of pavement	0.50'	0.46'	0.43'	0.36'	0.30'	0.24'	0.19'	0.15'	0.12'



TYPICAL PLAN

Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISD - 2-26-19
	DRAWN -	REVISD - 1-05-16
	CHECKED -	REVISD - 6-27-14
PLOT DATE = 4/7/2025	DATE -	REVISD - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

64' TWO LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION



GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(3256.59 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(3082.80 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(95.09 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(848.99 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (JOINTED) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (JOINTED) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (JOINTED).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)




SECTION A-A

(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TABLE OF OFFSETS AND DROPS

Distance feet from location station	0	81.32	100'	125'	150'	175'	200'	225'	250'	275'	278.80'
Offsets feet from inside edge of pavement	32'	30'	26.79'	22.80'	19.16'	15.88'	12.95'	10.37'	8.14'	6.26'	6.00'
Drop feet from inside edge of pavement	0.64'	0.60'	0.54'	0.46'	0.38'	0.32'	0.26'	0.21'	0.16'	0.13'	0.12'



TYPICAL PLAN

Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL

MODEL: 244RT
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT / DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/7/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

88' TWO LANE MEDIAN CROSSOVER

(POSTED SPEED LIMIT 65 MPH OR HIGHER, WORK ZONE SPEED LIMIT 55 MPH)

TYPICAL SECTION



GENERAL NOTES

Construction of median crossover shall conform to the requirement of current Standard Specifications.

Slotted drain shall be constructed of 14 or 16 gauge corrugated metal roadway pipe modified to accommodate slotted drain as shown.

Pavement, subbase, & shoulder quantities are:

(4481.22 Sq. Yds.)	AGGREGATE SUBGRADE IMPROVEMENT, 12"
(4279.37 Sq. Yds.)	P.C.C. PAVEMENT 10" (JOINTED)
(114.14 Tons)	2" HMA SURFACE COURSE, MIX "C", N50
(1019.14 Sq. Yds.)	HMA SHOULDERS 6"

Elbows and Caps shall be considered included to the SLOTTED DRAIN 12" WITH 6" SLOT.

See District Standard 61.2 or 68.1 for details for the slotted drain.


See District Standard 86.1 for details for the beveled pipe & guard.

The crossover is designed using a 55mph design speed.

The end of the pipe guard shall be set where a minimum 1:4 front slope can be constructed from each side of pipe guard to the HMA shoulder.


The PCC Pavement 10" (Jointed) shall be constructed according to Section 420 of the Standard Specifications and Highway Standards 420001, 420101, & 420106

The PCC Pavement 10" (Jointed) shall be tied to adjacent existing concrete pavement and the concrete encasement for the slotted drain. The tie bars shall be No.6 bars 24" long @ 30" cts. and installed according to the applicable portions of Article 420.05(b) of the Standard Specifications. The cost of the bars to be included in the cost of the PCC Pavement 10" (Jointed).



SECTION A-A

(USE TO MAINTAIN MEDIAN DRAINAGE THROUGH THE CROSSOVER)



SECTION A-A


(WHEN CROSSOVER IS AT MEDIAN HIGH POINT)

① Duct tape or wood blocks shall be used to cover slotted drain during construction of crossover paving

TABLE OF OFFSETS AND DROPS

Distance feet from location station	0	70.25' ①	75'	100'	125'	150'	175'	200'	225'	250'	275'	300'	325'	329.24' ②
Offsets feet from inside edge of pavement	44'	42'	41.00'	35.93'	31.23'	26.86'	22.86'	19.22'	15.94'	13.00'	10.42'	8.18'	6.29'	6.00'
Drops feet from inside edge of pavement	0.88'	0.84'	0.82'	0.72'	0.62'	0.54'	0.46'	0.38'	0.32'	0.26'	0.21'	0.16'	0.13'	0.12'

TYPICAL PLAN



Unless otherwise specified, when the median crossover is to be removed, the Contractor shall be required to saw full-depth along the shoulder line 6' from edge of pavement. The 6' adjacent to the edge of pavement shall remain in place and be used as shoulders. The cost of Sawing shall be included in the Pavement Removal.

Longitudinal joints shall be sawed at a max 12' width. All joints shall be sealed.

TRAFFIC CONTROL STANDARD 701416 IS TO BE USED WITH THIS DETAIL


USER NAME = IS007/DISTRICT 2	DESIGNED -	REVISED - 2-26-19
	DRAWN -	REVISED - 1-05-16
	CHECKED -	REVISED - 6-27-14
PLOT DATE = 4/17/2025	DATE -	REVISED - 8-27-13

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD

F.A. SITE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

BEVELED PIPE & GUARD DETAIL FOR MEDIAN CROSSOVER



PLAN VIEW

12 PIPE REINFORCING SCHEDULE			
Mark Req'd	Bar Size	Length	No.
a	5	110	2
b	5	32	2
c	8	34	10

18 PIPE REINFORCING SCHEDULE			
Mark Req'd	Bar Size	Length	No.
a	5	162	2
b	5	38	2
c	8	40	18

GENERAL NOTES:


Details shown hereon are for the construction of beveled pipe and guard. Alternate designs, methods of construction or materials may be submitted to the Engineer for approval. All methods of construction and materials involved shall conform to current Standard Specifications.

Reinforcing steel used in construction of "Beveled Pipe and Guard" shall be deformed bars meeting the requirements of Article 1006.10 of the Standard Specifications. All steel bars shall be hot-dip galvanized in accordance with ASTM A 123 specifications.


Concrete used in construction of the beveled pipe and guard shall be Class "SI" Concrete.

The corrugated metal pipe shall be cut to fit the 1:8 foreslope. Slots shall be cut into the C.M.P. for placement of the 'b' and 'c' bars. After the foreslope has been placed, the 'b' and 'c' bars shall be fitted into the slots cut in the C.M.P., so they will be in proper position when the concrete collar is poured.

This work shall be paid for at the contract unit price per Each for "Beveled Pipe and Guard", as shown hereon and as directed by the Engineer.




SECTION A-A



SECTION B-B

TABLE OF DIMENSIONS				
PIPE SIZE	A	B	C	D
12	9'-6"	36	6'	10'
18	13'-10"	42	10'-4"	14'-10"

TYPICAL SECTION THRU CENTERLINE OF MEDIAN CROSSOVER



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 26041
FILE NAME: DISTRICT 2 STANDARD

USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 5-27-09
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						CONTRACT NO.				
						ILLINOIS FED. AID PROJECT				



PLAN

* With standard washers. After tightening, cut the anchor bolts flush with the nuts and damage the nuts to prevent them from loosening.



ELEVATION

GENERAL NOTES

This work shall be done according to Section 631 of the Standard Specifications and this detail.

See Standard 630001 for details of guardrail not shown.

Thrie beam rail shall be bolted to block-out at all posts.

Posts located above pier foundation shall have plate attached to post and anchored to foundation.

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).

All dimensions are in inches unless otherwise shown.

The Traffic barrier Terminal, Type 6B (Special) will be measured for payment, complete in place, in units of each.

This work shall be paid for at the contract unit price per each for TRAFFIC BARRIER TERMINAL, TYPE 6B (SPECIAL).




PLATE DETAIL

MODEL: 9001L_Sheet1
FILE NAME: DISTRICT 2 STANDARD


USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 10-18-11
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS	FEB. 410 PROJECT


TRAFFIC BARRIER TERMINAL, TYPE 6B (SPECIAL)




SECTION A-A




WOOD BLOCKOUT DETAIL




THRIE BEAM END SHOE DETAIL




MODIFIED THICKNESS DETAIL
WOOD BLOCKOUTS A, B, C, & D



WOOD BLOCKOUT D



WOOD BLOCKOUT C



WOOD BLOCKOUT A & B

MODEL: 90d11_Sheet2
FILE NAME: DISTRICT 2 STANDARD

USER NAME = ISOT/DISTRICT 2	DESIGNED -	REVISED - 10-18-11
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

DETAILS OF PLANTING AND BRACING TREES





TREES SMALLER THAN 4 1/2 IN DIAMETER




SMALL	A	B	C	D	E	F
TREE SIZE	DIAMETER OF BALL OR ROOT SYS.	DEPTH OF HOLE EXCAVATION	WIDTH OF HOLE EXCAVATION	THICKNESS OF MULCH COVER	DEPTH OF BALL OR ROOT SYS.	VOLUME OF MULCH COVER CU. YDS.
5'-6'	16	10	30	4	12	0.54
5'-6' BB	16	10	30	4	12	0.54
6'-7' BB	18	12	30	4	14	0.54
7'-8' BB	20	11	30	4	13	0.54
8'-10' BB	24	14	36	4	16	0.61
10'-12' BB	26	15	36	4	17	0.61


LARGE	A	B	C	D	E	F
TREE SIZE	DIAMETER OF BALL OR ROOT SYS.	DEPTH OF HOLE EXCAVATION	WIDTH OF HOLE EXCAVATION	THICKNESS OF MULCH COVER	DEPTH OF BALL OR ROOT SYS.	VOLUME OF MULCH COVER CU. YDS.
0-2	20	11	36	4	13	0.61
2-2 1/2 BB	24	14	48	4	16	0.78
2 1/2-3 BB	28	17	48	4	19	0.78
3-3 1/2 BB	32	17	60	4	19	0.96
3 1/2-4 BB	36	20	60	4	22	0.96
4-4 1/2 BB	40	22	72	4	24	1.16
4 1/2-5 BB	44	24	72	4	26	1.16
5-5 1/2 BB	48	27	84	4	29	1.38



PLANT HARDINESS ZONE MAP
U.S. DEPARTMENT OF AGRICULTURE
AGRICULTURAL RESEARCH SERVICE
PUBLICATION NO. 814



TREES OVER 4 1/2 IN DIAMETER



ALL DIMENSIONS ARE IN INCHES
UNLESS OTHERWISE NOTED.

MODEL: 9204T
FILE NAME: DISTRICT 2 STANDARD


USER NAME = IDOT/DISTRICT 2	DESIGNED -	REVISED - 10-18-11
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 4/17/2025	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	F.A. RTEL.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
									CONTRACT NO.	
									ILLINOIS FED. AID PROJECT	


INLETS, SPECIAL



SEC. A-A



SEC. B-B



NOTES

SEE STANDARD 602701 FOR DETAILS OF STEPS.

EXCEPT AS NOTED HEREON INLET SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.

THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTED SECTIONS.




ALL VOIDS AROUND PIPE ENTRANCE, BOTH INSIDE AND OUTSIDE, SHALL BE SEALED WITH MORTAR.

WEIGHT OF CAST IRON FRAME & GRATE = 530 lbs. ± . STEPS SHALL BE OMITTED WHEN DEPTH OF "H" IS LESS THAN 5 ft.

CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT. PRECAST CONCRETE SHALL BE IN ACCORDANCE WITH ARTICLES 504.01 THRU 504.05 OF THE STANDARD SPECIFICATIONS EXCEPT THAT CONCRETE STRENGTH SHALL BE 4,000 psi AFTER 28 DAYS.

THE CONTRACT UNIT PRICE EACH FOR INLETS, SPECIAL SHALL INCLUDE THE COST OF CONSTRUCTING THE INLET BOX, FURNISHING AND INSTALLING THE FRAME AND GRATE, THE CAST IRON STEPS (IF USED), THE PRECAST FLOOR SLABS, SAND CUSHION (WHEN USED) AND REINFORCEMENT BARS.

DETAIL OF FRAME & GRATE





* THIS GRATE TO BE USED WITHOUT CURB BOX WHEN INLET IS IN DRIVEWAY.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 10pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED - 6-27-14									CONTRACT NO.			
REVISED - 10-13-11									ILLINOIS FED. AID PROJECT			
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.						

INLETS, SPECIAL (TYPE A GUTTER)




* THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.

THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.


SEC. A-A

FRAME AND GRATES TYPE 9



NOTES

- SEE STANDARD 602701 FOR DETAILS OF STEPS.
- EXCEPT AS NOTED HEREON INLET SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.
- THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTED SECTIONS.
- ALL VOIDS AROUND PIPE ENTRANCE, BOTH INSIDE AND OUTSIDE, SHALL BE SEALED WITH MORTAR.
- WEIGHT OF CAST IRON FRAME & GRATE = 440 LBS.
- STEPS SHALL BE OMITTED WHEN DEPTH OF "H" IS LESS THAN 5 FT.



SECTION B-B


CAST FRAME (GRAY IRON) WT. 320 LBS.

DETAIL OF FRAME & GRATE

NOTES

- CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT. PRECAST CONCRETE SHALL BE IN ACCORDANCE WITH ARTICLES 504.01 THRU 504.05 OF THE STANDARD SPECIFICATIONS EXCEPT THAT CONCRETE STRENGTH SHALL BE 4,000 PSI AFTER 28 DAYS.
- THE CONTRACT UNIT PRICE EACH FOR INLETS, SPECIAL SHALL INCLUDE THE COST OF CONSTRUCTING THE INLET BOX, FURNISHING AND INSTALLING THE FRAME AND GRATE, THE STEPS (IF USED), THE PRECAST FLOOR SLAB, SAND CUSHION (WHEN USED) AND REINFORCEMENT BARS.


SECTION A-A



LOCKING DEVICE DETAIL F

GENERAL NOTES

- THE MATERIAL FOR STEEL GRATE SHALL CONFORM TO ARTICLE 1006.04 OF THE STANDARD SPECIFICATIONS.
- THE USE OF EITHER A CAST GRATE OR A STEEL GRATE WITH THE CAST FRAME SHALL BE THE OPTION OF THE CONTRACTOR.
- THE CAST GRATE MAY BE MADE OF EITHER GRAY IRON OR DUCTILE IRON CONFORMING TO THE STANDARD SPECIFICATIONS. DUCTILE IRON CASTING SHALL BE GRADE 65-45-12
- ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.




END VIEW

STEEL GRATE WT. 95 LBS.

SECTION E-E

FINISH: STEEL GRATE SHALL BE GIVEN ONE SHOP COAT OF BLACK BITUMINOUS PAINT.



SECTION D-D


CAST GRATE 120 lbs.

SECTION C-C
 ○ = 6 1/4 max. (typ.)
 ⊙ = 3/4 min. (typ.)

MODEL: 11p02
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 6-27-14					CONTRACT NO.				
REVISED - 10-13-11					ILLINOIS FED. AID PROJECT				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.			

DOUBLE INLET, SPECIAL



NOTES

SEE STANDARD 602701 FOR DETAILS OF STEPS.

EXCEPT AS NOTED HEREON DOUBLE INLET SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.

THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTED SECTIONS.

ALL VOIDS AROUND PIPE ENTRANCE, BOTH INSIDE AND OUTSIDE, SHALL BE SEALED WITH MORTAR.



R-3295-2 DOUBLE UNIT OR EQUIVALENT.

STEPS SHALL BE OMITTED WHEN DEPTH OF "H" IS LESS THAN 5 FOOT.


CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT. PRECAST CONCRETE SHALL BE IN ACCORDANCE WITH ARTICLES 504.01 THRU 504.05 OF THE STANDARD SPECIFICATIONS EXCEPT THAT CONCRETE STRENGTH SHALL BE 4,000 PSI AFTER 28 DAYS.

CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT. THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL SHALL INCLUDE THE COST OF CONSTRUCTING THE INLET BOX, FURNISHING AND INSTALLING THE FRAME AND GRATE, THE STEPS (IF USED), THE PRECAST FLOOR SLABS, SAND CUSHION (WHEN USED) AND REINFORCEMENT BARS.

DETAIL OF FRAME & GRATE



SECTION B-B




SECTION A-A

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 12pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 7-16-15					CONTRACT NO.				
REVISED - 10-13-11	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		


FRAME AND GRATE FOR INLETS, SPECIAL




PLAN OF FRAME
WITHOUT GRATE AND CURB BOX




TRANSVERSE SECTION




LONGITUDINAL SECTION



PLAN OF GRATE



SECTION A-A



SECTION B-B


ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

R 3246 OR EQUIVALENT
APPROXIMATE WEIGHT - 495 LBS.


MODEL: 13pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-13-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.


FRAME AND GRATE FOR INLETS, SPECIAL



PLAN OF FRAME
WITHOUT GRATE AND CURB BOX




TRANSVERSE SECTION



LONGITUDINAL SECTION



PLAN OF GRATE



SECTION A-A


ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

R 3067 OR EQUIVALENT
APPROXIMATE WEIGHT - 465 LBS.


MODEL: 13p12a
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-13-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.


FRAME AND GRATE FOR INLETS, SPECIAL




PLAN OF FRAME
WITHOUT GRATE AND CURB BOX




TRANSVERSE SECTION



LONGITUDINAL SECTION



PLAN OF GRATE



SECTION A-A


ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

R 3067 OR EQUIVALENT
APPROXIMATE WEIGHT - 490 LBS.


MODEL: 13p12b
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-13-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.


FRAME AND GRATE FOR INLETS, SPECIAL




PLAN OF FRAME
WITHOUT GRATE AND CURB BOX



TRANSVERSE SECTION



LONGITUDINAL SECTION



PLAN OF GRATE


ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

R 3067 OR EQUIVALENT
APPROXIMATE WEIGHT - 510 LBS.


MODEL: 13p12c
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-13-11									
REVISED -					CONTRACT NO.				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT	

FRAME AND GRATE FOR INLETS, SPECIAL




PLAN OF FRAME



PLAN OF GRATE *

* THIS GRATE TO BE USED WITHOUT CURB BOX WHEN INLET IS IN DRIVEWAY.




ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

R-3290-A OR EQUIVALENT
APPROXIMATE WEIGHT OF CAST IRON FRAME & GRATE - 530 LBS.

MODEL: 13p12d
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 4-14-15	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 6-27-14									
REVISED - 10-14-11					CONTRACT NO.				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT	


INLETS, SPECIAL, NO. 1



SEC. A-A

* THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.

THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.



SEC. B-B

NOTES

SEE STANDARD 602701 FOR DETAILS OF STEPS.

EXCEPT AS NOTED HEREON INLET SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.

THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTED SECTIONS.

ALL VOIDS AROUND PIPE ENTRANCE, BOTH INSIDE AND OUTSIDE, SHALL BE SEALED WITH MORTAR.

STEPS SHALL BE OMITTED WHEN DEPTH OF "H" IS LESS THAN 5 FEET.


BOTH INLET SPECIAL NO. 1 SHALL DRAIN VERTICALLY TO THE ACROSS ROAD CULVERT LOCATED BENEATH.

CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT. PRECAST CONCRETE SHALL BE IN ACCORDANCE WITH ARTICLES 504.01 THRU 504.05 OF THE STANDARD SPECIFICATIONS EXCEPT THAT CONCRETE STRENGTH SHALL BE 4,000 psi AFTER 28 DAYS.


THE CONTRACT UNIT PRICE EACH FOR INLETS, SPECIAL, NO.1 SHALL INCLUDE THE COST OF CONSTRUCTING THE INLET BOX, FURNISHING AND INSTALLING THE FRAME AND GRATE, THE STEPS (IF USED), THE PRECAST FLOOR SLABS, SAND CUSHION (WHEN USED) AND REINFORCEMENT BARS.

FRAME AND GRATE # R-3503-B OR EQUIVALENT

DETAIL OF FRAME & GRATE



SEC. A-A



SEC. B-B

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 14pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED -	1-05-16
REVISED -	6-27-14
REVISED -	10-14-11

REGION 2 / DISTRICT 2 STANDARD


REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.
-----------	--------	-------	----	--------	------	---------

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

INLETS, SPECIAL, NO. 2



SEC. A-A



SEC. B-B

* THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.
THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.

NOTES

SEE STANDARD 602701 FOR DETAILS OF STEPS.

EXCEPT AS NOTED HEREON INLET SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.

THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTED SECTIONS.

ALL VOIDS AROUND PIPE ENTRANCE, BOTH INSIDE AND OUTSIDE, SHALL BE SEALED WITH MORTAR.

STEPS SHALL BE OMITTED WHEN DEPTH OF "H" IS LESS THAN 5 FOOT.


INLET SPECIAL NO. 2 SHALL MATCH THE EXISTING STORM SEWER AS SHOWN ON THE PLANS.

CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT. PRECAST CONCRETE SHALL BE IN ACCORDANCE WITH ARTICLES 504.01 THRU 504.05 OF THE STANDARD SPECIFICATIONS EXCEPT THAT CONCRETE STRENGTH SHALL BE 4,000 psi AFTER 28 DAYS.


THE CONTRACT UNIT PRICE EACH FOR INLETS, SPECIAL, NO.2 SHALL INCLUDE THE COST OF CONSTRUCTING THE INLET BOX, FURNISHING AND INSTALLING THE FRAME AND GRATE, THE STEPS (IF USED), THE PRECAST FLOOR SLABS, AND CUSHION (WHEN USED) REINFORCEMENT BARS, AND REMOVAL OF ANY EXCESS STORM SEWER.

FRAME AND GRATE # R-3461 OR EQUIVALENT

DETAIL OF FRAME & GRATE



SEC. A-A





SEC. B-B


MODEL: 15p12
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 6-27-14									
REVISED - 10-14-11					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	


STANDARD INLET FOR TYPE A GUTTER (SPECIAL)



- QUANTITY -
Section A-A to C-C
1.2 Cu. Yds.
Class SI Concrete



Section A-A



Section B-B


Class SI Concrete shall be used throughout.
The gutter inlet will be paid for at the contract
unit price per cubic yard for Class SI Concrete (OUTLETS)

ALL DIMENSIONS ARE IN INCHES UNLESS
OTHERWISE NOTED.

MODEL: 20pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 12-04-13	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

STANDARD INLET FOR CURB & GUTTER



NOTES


Class SI Concrete shall be used throughout.

The Curb and Gutter inlet will be paid for at the contract unit price per cubic yard for Class SI Concrete (OUTLETS).


Joints shall be constructed in accordance with the requirements of Article 606.07 of the Standard Specifications.

When curb and gutter is constructed adjacent to flexible pavement, a 1" expansion joint shall be installed at construction joints.


All dimensions are in inches unless otherwise noted.



SECTION A-A



SECTION B-B




SECTION C-C

TYPE OF CURB & GUTTER	TABLE OF DIMENSIONS								CONCRETE QUANTITY A-A TO C-C (CU YDS)
	A	B	C	D	E	F	G	R	
B-6.06	6	15	4'	1	6	6	7	1	0.87
B-6.12	12	18.25	4'	1	6	6	7	1	0.95
B-6.18	18	27.25	4' 9"	1	6	6	7	1	1.18
B-6.24	24	32.4	4' 9"	1	6	6	7	1	1.30
M-4.06	6	17.8	3' 9"	4	3	4	7	3	0.75
M-4.12	12	18.25	4'	4	3	4	7	3	0.91
M-4.18	18	27.25	4' 9"	4	3	4	7	3	1.14
M-4.24	24	32.4	4' 9"	4	3	4	7	3	1.25
M-6.06	6	17.8	3' 9"	6	2	6	8	3	0.86
M-6.12	12	18.25	4'	6	2	6	8	2	0.96
M-6.18	18	27.25	4' 9"	6	2	6	8	2	1.20
M-6.24	24	32.4	4' 9"	6	2	6	8	2	1.30

MODEL: 21pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025



REVISED - 11-12-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED - 8-27-13												
REVISED - 10-10-06									CONTRACT NO.			
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT				

FIELD TILE JUNCTION VAULTS 2' AND 3' DIA.




FRAME & LID FOR
2' VAULT

FRAME & LID FOR
3' VAULT




TOTAL WEIGHT: 146 LBS.

TOTAL WEIGHT: 280 LBS.



PLAN



CAST-IN-PLACE CONCRETE
SECTION A-A


GENERAL NOTES:

THE FRAME AND LID IS REQUIRED ON ALL JUNCTION VAULTS.
THE FRAME AND LID SHALL BE INSTALLED FLUSH WITH THE GROUND.


FRAME AND LIDS:

R-6040 OR EQUIVALENT (2')
R-6080 OR EQUIVALENT (3')

ALTERNATE MATERIALS FOR WALLS	T
BRICK MASONRY	8
CAST-IN-PLACE CONCRETE	6
CONCRETE MASONRY UNIT	5
PRECAST REINFORCED CONCRETE SECTION	3



PRECAST REINFORCED
CONCRETE SLAB



PREFABRICATED CONCRETE SLAB,
WHEN THE PRECAST REINFORCED
CONCRETE SECTION ALTERNATE
IS USED.

ALTERNATE METHODS

ALL DIMENSIONS ARE IN INCHES
UNLESS OTHERWISE NOTED.


MODEL: 30pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-03-18	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 6-27-14									
REVISED - 10-14-11									
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.		
							ILLINOIS	FED. AID PROJECT	



TREATMENT OF FIELD TILE SYSTEMS UNDER DITCHES

PAVED DITCH

TO BE USED IF COVER OVER THE PIPE AT THE BOTTOM OF THE DITCH IS LESS THAN 10 inches





WELDED WIRE REINFORCEMENT WEIGHING NOT LESS THAN 58 lbs./100 sq. ft.



CONCRETE SLAB

TO BE USED IF COVER OVER THE PIPE AT THE BOTTOM OF THE DITCH IS 10 INCHES TO 24 INCHES



NOTES

THIS WORK SHALL BE DONE IN ACCORDANCE WITH ARTICLE 611.04 OF THE STANDARD SPECIFICATION.

THE CONCRETE SLAB AND PAVED DITCH WILL BE PAID FOR AT THE CONCRETE UNIT PRICE PER CUBIC YARD FOR MISCELLANEOUS CONCRETE.



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 31pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-14-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

SIGN PANEL – TYPE 1 (SPECIAL)


SIGN LAY OUT FOR NARROW BRIDGES ON TWO-WAY ROADWAYS
(WHERE THE BRIDGE IS LESS THAN 24 WIDER THAN THE ROADWAY SURFACE.)




TYPICAL CHEVRON



FRONT VIEW



BACK VIEW



TYPICAL SIGN

NOTES

STRIPES ON THE FACE OF THE SIGN SHALL SLOPE TOWARDS THE EDGE OF PAVEMENT ON BOTH SIDES OF THE ROADWAY.

WHEN THE GUARDRAIL IS PRESENT THE DISTANCE FROM THE EDGE OF THE SIGN SHALL BE POSITIONED WITH THE FACE OF THE GUARDRAIL, AS SHOWN.


ALL MOUNTING HARDWEAR SHALL BE ALUMINUM, STAINLESS STEEL, OR ZINC OR CADMIUM PLATED STEEL AND SHALL BE INCLUDED TO THE COST OF THE INSALLATION.

PLACEMENT OF CHEVRON ALIGNMENT SIGNS ALONG THE 25 TO 1 TAPER WILL CONFORM TO THE DEPARTMENT OF TRANSPORTATION'S STANDARDS MANUAL UNDER THE SECTION FOR GUARDRAIL PLACEMENT.

ALL LEFT SIDE MARKERS SHALL BE OMITTED FOR FOUR-LANE, TWO-WAY BRIDGE APPLICATIONS.

* REFER TO THE BUREAU OF TRAFFIC'S SPECIFICATIONS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



NOTE: MINIMUM OF TWO BOLTS PER POST REQUIRED.

DETAIL OF MOUNTING SIGN TO POST

MODEL: 32pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-14-11									
REVISED -									
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.		
							ILLINOIS	FED. AID PROJECT	


INLET STAND PIPE

Inlet Stand Pipe

Inlet Stand Pipe shall be included in the contract unit price per FOOT for STORM SEWERS (SPECIAL) 6". Which shall include the following items--one 36" above ground section with 1" holes, one variable depth below ground section with small holes, one 6" tee section, collars (if needed) and end caps (if needed) as directed by the engineer.

Storm Sewer shall be paid for at the contract unit price per foot for STORM SEWERS (SPECIAL) 6". According to Article 611.04.

Field Tile Junction Vault shall be constructed according to District Standard 30.2 and paid for at the contract unit price each for FIELD TILE JUNCTION VAULTS for size specified in the plans.




MODEL: 34pi2
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 10-14-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									CONTRACT NO.
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		

GUARDRAIL EROSION CONTROL TREATMENTS

GENERAL NOTES: EROSION CONTROL CURB


1. This work shall consist of grading as needed, installing hardware, 2" x 10" treated timber boards and incidental hot-mix asphalt surfacing in front of steel plate beam guardrail in accordance with plan details.
2. Timber shall be treated in accordance with Article 1007.12 Waterborne preservatives "asa" and "cca" shall have a minimum retention of 0.40 lbs./cu.ft.
3. This work will be paid for at the contract unit price per foot for EROSION CONTROL CURB (pay code Z0020800).



**TYPICAL SECTION
WITH EROSION CONTROL CURB**

GENERAL NOTES: GUARDRAIL AGGREGATE EROSION CONTROL

1. This work shall consist of furnishing and installing, Geotextile Fabric and staples, and furnishing, placing and shaping crushed aggregate around and behind Steel Plate Beam Guardrail posts in accordance with Plan Details.
2. Before placing the aggregate and the Geotextile Fabric, weeds and grass shall be removed from the area to be covered.
3. After the area has been prepared, and in a dry condition, the Geotextile Fabric shall be placed with a 12" minimum overlay. A knife cut for guardrail post installation is necessary.
4. The aggregate shall be deposited, compacted and shaped by either mechanical or hand methods, in a manner reasonably true to line and grade.
5. The Contractor shall have the option of placing the guardrail before or after the Geotextile Fabric and aggregate are in place. If the guardrail is placed after the Geotextile Fabric and aggregate, then any voids must be filled and the aggregate returned to line and grade.
6. Materials shall meet following requirements:
 - A. The crushed aggregate shall be CA1 gradation in accordance with Article 1004.01 of the Standard Specifications.
 - B. The aggregate shall meet class D quality requirements as outlined in Article 1004.01 of the Standard Specifications with the following exceptions:
 - 1) Revise the maximum allowable percentage of weighted average loss when the material is subjected to 5 cycles of the Sodium Sulfate Soundness Test from 25% as shown under class D of the quality chart in Article 1004.01(b) of the Standard Specifications to 40%.
 - 2) Revise the maximum allowable percentage of wear as determined by the Los Angeles Abrasion Method from 45% as shown under as shown under class D of the quality chart in Article 1004.01(b) of the Standard Specifications to 65%.
 - 3) The sum of the percentage of weighted average loss when the material is subjected to 5 cycles of the Sodium Sulfate Soundness Test; and the percentage of wear as determined by the Los Angeles Abrasion Method, shall not exceed 95%.
 - C. The Geotextile Fabric shall be nonwoven fabric in accordance with Article 1080.02 of the Standard Specifications.
7. This work will be paid for at the contract unit price per ton for GUARDRAIL AGGREGATE EROSION CONTROL (pay code Z0001002).






**TYPICAL SECTION
WITHOUT EROSION CONTROL CURB**

MODEL: 35pi2
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD			F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
REVISED - 10-14-11										
REVISED -				CONTRACT NO.						
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO	STA.	ILLINOIS FED. AID PROJECT		

PAVED DITCH (SPECIAL)



SIDE ELEVATION SHOWING METHOD OF BURYING UP STREAM AND DOWN STREAM END OF PAVED DITCH.

(SEE NOTE)

NOTES:

CLASS SI CONCRETE SHALL BE USED THROUGHOUT.

WELDED WIRE REINFORCEMENT SHALL BE 6 X 6 MESH, NO. 4 GAUGE, 58 lbs/100 sq ft, CONFORMING TO THE REQUIREMENTS OF A.S.T.M. A1064.

1/2" PREMOULDED JOINT FILLER SHALL BE PLACED AT THE JUNCTION OF PAVED DITCH WITH ANY OTHER STRUCTURE.

CUT-OFF WALLS SHALL BE COSTRUCTED MONOLITHICALLY WITH THE PAVED DITCH.

AT THE OPTION OF THE CONTRACTOR, NO. 4 L 20 REINFORCING BARS PLACED AT 12 CENTERS LONGITUDINALLY IN PAVED DITCH AND VERTICALLY IN CUT-OFF WALLS IN LIEU OF THE WELDED WIRE FABRIC.

THE SOIL PLACED OVER THE 24 FLATTENED SECTION OF THE DITCH SHALL BE TAMPED FIRMLY. THIS WORK SHALL BE INCLUDED IN THE UNIT PRICE FOR PAVED DITCH.

PAVED DITCH SHALL BE CONSTRUCTED IN ACCORDANCE WITH ARTICLES 606.01 THROUGH 606.13.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

* THE GEOTECHNICAL FABRIC IS INCLUDED IN THE PAVED DITCH.


BASIS OF PAYMENT

PAVED DITCH (SPECIAL) WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT MEASURED IN PLACE INCLUDING THE COST OF FURNISHING AND PLACING THE JOINT FILLER, THE WELDED WIRE REINFORCEMENT OR THE NO. 4 REINFORCING BARS, AND THE NECESSARY EXCAVATION AND DISPOSAL OF SURPLUS MATERIALS.

MODEL: 36p12
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-14-11									
REVISED -					CONTRACT NO.				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		

UNDERDRAIN FOR ACROSS ROAD (AR) CULVERTS



NOTES:

IN SAG CONDITIONS INSTALL PIPE UNDERDRAINS, TYPE 2, 4" ON BOTH SIDES OF CULVERT.

ON HIGHWAY GRADES GREATER THAN 2% INSTALL PIPE UNDERDRAINS, TYPE 2, 4" ON THE HIGH SIDE OF THE CULVERT.

THIS WORK SHALL BE COMPLETED ACCORDING TO SECTION 601 OF THE STANDARD SPECIFICATIONS.


THE UNDERDRAIN SHALL EXTEND UNTIL INTERSECTING WITH THE SIDE SLOPES. THE PIPES SHALL DRAIN INTO CONCRETE HEADWALLS. (SEE ARTICLE 601.05 OF THE STANDARD SPECIFICATIONS AND HIGHWAY STANDARD 601101).

THE UNDERDRAIN SHALL BE A MINIMUM OF 12" BELOW THE EXISTING PAVEMENT.

PIPE UNDERDRAINS WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT FOR PIPE UNDERDRAINS, TYPE 2, 4".


CONCRETE HEADWALLS WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER EACH FOR CONCRETE HEADWALLS FOR PIPE DRAINS.

A DELINEATOR SHALL BE PLACED AT EACH CONCRETE HEADWALL. THESE BE PAID FOR AT THE CONTRACT UNIT PRICE PER EACH FOR DELINEATORS.




NOTES:

(HIGHWAY GRADE GREATER THAN 2%)



NOTES:


(IN SAG CONDITION)
(PIPE DRAIN ON EACH SIDE)





MODEL: 37p02
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 8-03-17	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED - 7-13-16												
REVISED - 1-05-16					CONTRACT NO.							
REVISED - 6-27-14					SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT

RESERVED PARKING SIGN DETAIL



DISABLED PARKING STRIPING




MODEL: 44pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 4-19-18	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 1-05-16									
REVISED - 6-27-14					CONTRACT NO.				
REVISED - 10-14-11					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

SUPERELEVATION TRANSITION ON TWO-LANE HIGHWAY

W = LANE WIDTH
e = DESIGN SUPERELEVATION RATE








TRANSITION CURVE TABLE

CURVE PI STA.	SUPERELEVATION "e"	W	SUPERELEVATION TRANSITION LENGTH	TANGENT RUNOUT DISTANCE	SUPERELEVATION RUNOFF LENGTH

MODEL: 45pi2
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 11-09-06	REGION 2 / DISTRICT 2 STANDARD			F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -								
REVISED -				CONTRACT NO.				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT	

HOT-MIX ASPHALT APPROACHES & MAILBOX RETURNS FOR SINGLE LIFT (SMART) RESURFACING PROJECTS




NOTE: EXISTING HMA PE's, CE's, SR's, & MB TURNOUTS
Place 1 1/2" Incidental Hot-Mix Asphalt Surfacing on entrance to conform to the existing configuration.

EXISTING AGG. PE's & CE's
Place 2" Incidental Hot-Mix Asphalt Surfacing on existing entrance to conform to the present configuration.

EXISTING AGG. SIDEROADS
Place 3" Incidental Hot-Mix Asphalt Surfacing on sideroad to conform to the present configuration.

EXISTING AGG. MAILBOX TURNOUTS
Existing Agg. Mailbox Turnouts shall be constructed as shown below.








	6'	8'
AGG BASE CSE T-B (TON)	24.5	31.1
INC HMA SURF 2" (TON)	7.3	9.8
BIT PRIME COAT (POUND)	120	161

MODEL: 46p12
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 1-05-16								
REVISED - 7-21-15								
REVISED - 10-21-08								
REVISED -	SCALE:	SHEET OF SHEETS	STA. TO STA.	CONTRACT NO.				
				ILLINOIS FED. AID PROJECT				

HOT-MIX ASPHALT APPROACHES & MAILBOX RETURNS FOR TWO LIFT (3P) RESURFACING PROJECTS




NOTE: EXISTING HMA PE's, CE's, SR's, & MB TURNOUTS
Place 2 ¼" Incidental Hot-Mix Asphalt Surfacing on entrance to conform to the existing configuration.

EXISTING AGG. PE's & CE's
Place 2 ¼" Incidental Hot-Mix Asphalt Surfacing on existing entrance to conform to the present configuration.

EXISTING AGG. SIDEROADS
Place 3" Incidental Hot-Mix Asphalt Surfacing on sideroad to conform to the present configuration.

EXISTING AGG. MAILBOX TURNOUTS
Existing Agg. Mailbox Turnouts shall be constructed as shown below.



	6'	8'
AGG BASE CSE T-B (TON)	24.5	31.1
INC HMA SURF 2 ¼" (TON)	8.2	11.0
BIT PRIME COAT (POUND)	120	161

MODEL: 47p02
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED -	1-05-16
REVISED -	7-21-15
REVISED -	6-27-14
REVISED -	10-21-08

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

SAFETY EDGE (SMART PROJECT)



NO MILLING: ADJACENT SHOULDER FLUSH WITH OR LOWER THAN EXISTING PAVEMENT



MILLING: WITH ADJACENT SHOULDER FLUSH WITH OR HIGHER THAN MILLED SURFACE

NOTES : THE DEVICE WHICH FORMS THE SAFETY EDGE SHALL BE MOUNTED ON THE PAVER SCREED AGAINST THE END GATE AND SHALL BE REMOVABLE OR BE ABLE TO BE LIFTED WHEN NOT IN USE. THE DEVICE SHALL BE DESIGNED TO MAINTAIN CONTACT WITH SURFACE OF THE SHOULDER AND ALLOW AUTOMATIC TRANSITION TO CROSS ROADS, DRIVEWAYS AND OBSTRUCTIONS. THE DEVICE SHALL ALSO CONSTRAIN THE HMA MATERIAL AND INCREASE THE CONSOLIDATION OF THE EXTRUDED PROFILE. THE USE OF A CONVENTIONAL SINGLE PLATE STRIKE-OFF WILL NOT BE ALLOWED.


① PRIOR TO THE PLACEMENT OF THE HMA SAFETY EDGE, IF THE ADJACENT AGGREGATE OR EARTH SHOULDER IS HIGHER THAN THE MILLED SURFACE, THE AREA REQUIRED FOR PLACEMENT OF THE SAFETY EDGE SHALL BE BROUGHT FLUSH WITH THE MILLED SURFACE IN A MANNER APPROVED BY THE ENGINEER. THIS WORK SHALL BE CONSIDERED INCLUDED IN THE CONTRACT UNIT PRICE PER TON FOR HOT-MIX ASPHALT SURFACE COURSE OF THE TYPE SPECIFIED.

ROLLERS WILL NOT BE ALLOWED ON THE SLOPED FACE OF THE SAFETY EDGE.


MODEL: 48pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
REVISED - 10-11-13											
REVISED -					CONTRACT NO.						
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT				

SAFETY EDGE (3P PROJECTS)



NO MILLING: ADJACENT SHOULDER FLUSH WITH OR LOWER THAN EXISTING PAVEMENT



MILLING: WITH ADJACENT SHOULDER FLUSH WITH OR HIGHER THAN MILLED SURFACE

NOTES : THE DEVICE WHICH FORMS THE SAFETY EDGE SHALL BE MOUNTED ON THE PAVER SCREED AGAINST THE END GATE AND SHALL BE REMOVABLE OR BE ABLE TO BE LIFTED WHEN NOT IN USE. THE DEVICE SHALL BE DESIGNED TO MAINTAIN CONTACT WITH SURFACE OF THE SHOULDER AND ALLOW AUTOMATIC TRANSITION TO CROSS ROADS, DRIVEWAYS AND OBSTRUCTIONS. THE DEVICE SHALL ALSO CONSTRAIN THE HMA MATERIAL AND INCREASE THE CONSOLIDATION OF THE EXTRUDED PROFILE. THE USE OF A CONVENTIONAL SINGLE PLATE STRIKE-OFF WILL NOT BE ALLOWED.









ROLLERS WILL NOT BE ALLOWED ON THE SLOPED FACE OF THE SAFETY EDGE.

① PRIOR TO THE PLACEMENT OF THE HMA SAFETY EDGE, IF THE ADJACENT AGGREGATE OR EARTH SHOULDER IS HIGHER THAN THE MILLED SURFACE, THE AREA REQUIRED FOR PLACEMENT OF THE SAFETY EDGE SHALL BE BROUGHT FLUSH WITH THE MILLED SURFACE IN A MANNER APPROVED BY THE ENGINEER. THIS WORK SHALL BE CONSIDERED INCLUDED IN THE CONTRACT UNIT PRICE PER TON FOR HOT-MIX ASPHALT SURFACE COURSE OF THE TYPE SPECIFIED.

MODEL: 49pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-11-13									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	


SLOTTED DRAIN PIPE FOR TYPE A GUTTER (SPECIAL)



GAGE OF PIPE	DIAMETER OF PIPE					
	12"	15"	18"	24"	30"	36"
16	X	X	X	X	X	X
14	X	X	X	X	X	X
12	N.A.	N.A.	N.A.	N.A.	X	X

GRATE TYPE	"A"	
VERT	2-1/2"	1-3/4"
VERT	6"	1-3/4"
TRAP	2-1/2"	2-1/4"
TRAP	6"	3"

VERT = VERTICAL
TRAP = TRAPEZOIDAL



- SLOTTED DRAIN NOTES**
- GRATING IS AVAILABLE IN DEPTHS OF 2 1/2" AND 6".
 - VERTICAL GRATING (STRAIGHT SIDES) WITH VERTICAL SPACERS IS ALSO AVAILABLE.
 - FOR 6" VERTICAL & TRAPEZOIDAL REQUIREMENTS, THE SLOTTED DRAIN BAND MAY BE FURNISHED WITH THE 4" TECHCO BAND ANGLE.
 - DIMENSIONS ARE SUBJECT TO MANUFACTURING TOLERANCES.
 - REFERENCE CONTECH BAND MANUAL DWG. NO. 1008466 FOR BAND DETAILS.

MANUFACTURING TOLERANCES

- VERTICAL BOW ± 3/8"
- HORIZONTAL BOW ± 5/8"
- TWIST ± 1/2"


NOTES

CLASS SI CONCRETE SHALL BE USED THROUGHOUT.

THE SLOTTED DRAIN SHALL BE CORRUGATED PIPE CULVERT WITH INTEGRAL SLOTTED DRAINS. BEFORE PLACING THE CONCRETE ADJACENT TO THE PIPE, THE SLOT SHALL BE COVERED BY EITHER THIN, FLAT METAL SHEETING OR BY A BOARD NOTCHED TO FIT OVER THE GRATE BARS. THIS COVERING MUST FIT CLOSELY IN THE SLOT TO PREVENT ENTRY OF CONCRETE INTO THE PIPE. PAVING OVER THE SLOTTED DRAIN WILL THEN BE ONE CONTINUOUS OPERATION OVER THE PROTECTED DRAIN. THE PROTECTION FOR THE DRAIN SLOT SHALL THEN BE REMOVED. THE PIPE SHALL DRAIN INTO THE SIDE OF THE INLET. THE OPENING WHERE THE SLOT IS REMOVED SHALL BE COVERED TO PREVENT CONCRETE FROM ENTERING THE PIPE.

THE CORRUGATED STEEL PIPE USED IN THE SLOTTED DRAIN SHALL MEET THE REQUIREMENTS OF AASHTO M-36/ASTM A 760. THE CMP SHALL BE GALVANIZED OR ALUMINIZED STEEL TYPE 2. STEEL GRATING SHALL MEET THE GALVANIZING REQUIREMENTS OF AASHTO M-111. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT FOR SLOTTED DRAIN PIPE, AND SHALL INCLUDE ELBOWS.

USE APPROVED END CAP TO PREVENT CONCRETE ENTRY INTO THE PIPE DURING GUTTER CONSTRUCTION ON THE UPSTREAM END OF PIPE.




ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 61p02
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED -	1-05-16	REGION 2 / DISTRICT 2 STANDARD			F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -	6-27-14								
REVISED -	10-14-11								
REVISED -		SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.	
								ILLINOIS	FED. AID PROJECT

PIPE HANDRAILS FOR STEPS




HANDRAIL FOR CONCRETE STEPS




3/4" Dia. Galv. Steel Anchor Rod Thd'd both ends with Heavy Hex Nut Washer & two Hex Nuts

ANCHOR ROD DETAIL

(Included in the cost of Hand or Safety Rail)



Extension at Bottom of Run Detail



Extension at Top of Run Detail

Notes:

Stairways shall have continuous handrails both sides of all stairs.

The inside handrail on switchback or dogleg stairs shall always be continuous.

Gripping surfaces shall be uninterrupted by newel posts, other construction elements, or obstructions.

Ends of handrail shall be either rounded or returned smoothly to floor, wall, or post.


Hand & safety rails shall not rotate within their fittings.

The clear space between hanrails and any wall shall be 1 1/2"

Handrail shall conform to Section 509 with the exception that all pipe and connections shall be welded galvanized or aluminum according to Article 1006.30, or 1006.34.

The diameter of the gripping surface of the handrail shall be 1-1/4" to 1-1/2"

This work shall be paid for at the contract unit price per FOOT for PIPE HANDRAIL.




POST BASE PLATE DETAIL

(Included in the cost of Hand or Safety Rail)

MODEL: 63p12
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-14-11					CONTRACT NO.				
REVISED -									
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.			

PIPE HANDRAIL, SPECIAL – FOR RETAINING WALLS



PIPE HANDRAIL, SPECIAL - FOR RETAINING WALL
(See details for Installation options)

Notes:

Gripping surfaces shall be uninterrupted by construction elements, or obstructions.

Ends of handrail shall be rounded.

Handrail shall not rotate within their fittings.


Handrail shall conform to Section 509 with the exception that all pipe and connections shall be welded galvanized or aluminum according to Article 1006.30, or 1006.34.

The diameter of the gripping surface of the handrail shall be 1-1/4" to 1-1/2"


Handrail required when wall height difference is 4' or greater

Drilling of blocks will be necessary for reinforcement placement.


This work shall consist of furnishing and erecting Handrails as listed above and according to this detail. This work shall be paid for at the contract UNIT price per FOOT for PIPE HANDRAIL, SPECIAL.




PIPE HANDRAIL, SPECIAL - FOR RETAINING WALL
(Option 1)



PIPE HANDRAIL, SPECIAL - FOR RETAINING WALL
(Option 2-Block depth greater than 20")




PIPE HANDRAIL, SPECIAL - FOR RETAINING WALL
(Option 3 - Block depth 12" to 19")




MODEL: 64pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 12-03-14									
REVISED - 2-01-10									
REVISED -	SCALE:	SHEET OF SHEETS	STA. TO STA.			CONTRACT NO.			
						ILLINOIS FED. AID PROJECT			

PERMANENT SURVEY MARKERS, TYPE II




BRASS OR ALUMINUM TABLET





Tablet constructed in rock ledge or concrete.

TYPE II



DETAIL A

Use pure cement and water or approved epoxy to seal marker tablet in rock ledge, concrete pavement or structure. Hole shall be 1 1/2" diameter.




TYPE II

CAST-IN-PLACE MARKER

No. 3 bars to be 30" for 36" min. & 3'-6" for 4'-0" min.


ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

WITNESS MARKER FOR PERMANENT SURVEY MARKERS, TYPE II



GENERAL NOTES


A WITNESS MARKER SHALL BE INSTALLED WITHIN 1' OF ALL PERMANENT SURVEY MARKERS TYPE II EXCEPT IN AREAS WHERE THE MARKER IS IN THE SIDEWALK. THIS WORK WILL BE INCLUDED TO THE CONTRACT UNIT PRICE PER EACH FOR PERMANENT SURVEY MARKERS, TYPE II.




MODEL: 66p02
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED - 10-14-11									CONTRACT NO.			
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT


AUTOMATIC FLAP GATE



FRONT ELEVATION



SECTION



SECTION SHOWING METHOD OF APPLICATION TO CORRUGATED METAL PIPE

IT IS INTENDED THAT THE AUTOMATIC FLAP GATES SHALL BE A COMMERCIAL PRODUCT PRODUCED BY A RELIABLE MANUFACTURER. THE GATE MAY BE MADE OF CAST IRON, CAST STEEL OR OTHER SUITABLE MATERIALS. THE DESIGN MAY DIFFER FROM THE DRAWING IF IT WILL WORK IN A SATISFACTORY, TROUBLE FREE MANNER AND WILL WITHSTAND THE WATER PRESSURE AT THE INSTALLATION LOCATION. THE GATE SHALL BE APPROVED BY THE ENGINEER.

THE SIZE OF AUTOMATIC FLAP GATES SHALL REFER TO THE DIAMETER OF THE OUTLET PIPE OR OPENING.

THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR FLAP GATE OF THE SIZE SPECIFIED AND SHALL INCLUDE ALL MATERIALS AND COMPLETE INSTALLATION.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


TABLE OF DIMENSIONS

DIAM	A	B	C	D	E	F	G	H	J	T
8	10 3/4	1 3/8	5 ¢	10	1/2	1 1/8	3 ¢	1 1/4	3/8	3/8
10	12 3/4	1 3/8	7 1/8	12 1/4	1/2	1 1/8	4 3/8	1 1/2	1/2	¢
12	14 3/4	1 3/8	8 1/2	14 1/2	1/2	1 1/8	5 1/8	1 1/2	1/2	1/2
14	17 1/4	1 3/8	9 7/8	16 3/4	1/2	1 1/4	5 ¢	1 1/2	1/2	¢
15	17 3/4	1 3/8	10 5/8	17 3/4	1/2	1 1/4	6 1/4	1 1/2	1/2	¢
16	19 1/4	1 3/8	11 1/4	18 3/4	1/2	1 1/4	6 5/8	1 1/2	1/2	¢
18	22 1/4	2	12 5/8	21	3/4	1 ¢	7 ¢	1 3/4	¢	¢
20	24 3/4	2	14 1/8	23 3/4	3/4	1 3/8	8 1/4	1 3/4	5/8	5/8
21	25 1/4	2	14 1/8	24 1/4	3/4	1 3/8	8 ¢	1 3/4	5/8	5/8
24	28 1/4	2	17	27 1/2	3/4	1 1/2	9 3/4	1 3/4	5/8	5/8
30	35 1/4	2 1/2	20 1/2	34	1	1 ¢	12	2	1 ¢	5/8
36	41 1/2	2 1/2	25	40 7/8	1	2 ¢	14 ¢	2 1/4	1 1/8	¢
42	47 1/2	2 1/2	29 3/4	47	1	2 ¢	16 5/8	2 1/4	1 1/8	3/4
48	53 1/2	2 1/2	34	54	1	2 3/4	19 ¢	2 1/4	1 3/8	3/4
54	60 3/4	2 1/2	38	62 1/4	1 1/4	2 3/4	22	3	1 1/2	7/8
60	67	2 1/2	42	68 1/2	1 1/4	2 3/4	24 1/4	3	1 1/2	¢
66	73 3/8	2 1/2	47	75	1 1/4	2 7/8	26 1/2	3	1 1/2	1
72	79	2 1/2	51	82	1 1/4	3	29	3	1 1/2	1
78	86	2 1/2	55 1/4	88 3/4	1 1/4	3 1/2	31 3/8	3	1 5/8	1 1/8
84	92 1/2	3 1/2	59 1/2	95 1/2	1 1/2	3 1/2	33 3/4	3	1 3/4	1 1/4

MODEL: 73p12
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED - 10-14-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -							CONTRACT NO.		
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		

RIPRAPPED CULVERT ENERGY BASIN




SECTION

STATION	G	W ₀	L _p	L _a	H _s	H _b	D ₁	D ₂



NOTE B: WARP BASIN TO CONFORM TO NATURAL STREAM CHANNEL.



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 81p12
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025


REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.				
REVISED - 10-14-11									CONTRACT NO.				
REVISED -									ILLINOIS FED. AID PROJECT				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.	TO	STA.		

TERMINATION OF DEAD END ROADS


NOTES: A "NO OUTLET" (36"x36" YELLOW) SIGN SHALL BE ERECTED SLIGHTLY BEYOND THE LAST ROAD INTERSECTING THE ROAD WITH NO OUTLET. IF THIS INTERSECTION IS MORE THAN 1500 FT FROM TERMINATION POINT, OR IF SIGHT DISTANCE TO THE CLOSURE IS LESS THAN 500 FT, A ROAD ENDS 500 FT (WB-I6) SIGN SHALL BE ERECTED 500 FT IN ADVANCE OF THE TERMINATION OF THE ROAD. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER EACH FOR "TERMINATION OF DEAD END ROADS" WHICH PRICE SHALL INCLUDE ALL LABOR, MATERIALS AND EQUIPMENT NECESSARY TO INSTALL THE SIGNS AND DELINEATORS.

USE 4X6 WOOD POSTS INSTALLED IN ACCORDANCE WITH SECTION 730 OF STANDARD SPECIFICATIONS FOR TRAFFIC CONTROL ITEMS. USE APPLICABLE PARTS OF STANDARD 720001 FOR SIGN MOUNTING.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



TERMINATION SIGNING





TRAFFIC CONTROL
TYPICAL CUL-DE-SAC

MODEL: 89pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 11-12-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-14-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	




MECHANICAL JOINTS FOR CONCRETE PIPE AND BOX CULVERTS

THE CULVERT TIES SHALL BE INCLUDED IN THE COST OF THE CONCRETE PIPE CULVERTS OR THE PRECAST CONCRETE BOX CULVERT. THE MECHANICAL TIES SHALL BE ON THE OUTSIDE OF THE CULVERT. THE NUTS AND WASHERS SHALL BE PLACED ON THE INSIDE OF THE CULVERT AND COVERED WITH MASTIC JOINT SEALER CONFORMING TO SECTION 1055 IN THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.



PLACEMENT OF HOLES		
BOX CULVERT FEET	PIPE SIZE INCHES	THREAD DIAMETER
	12	3/4 ROLLED THREADS (SEE NOTE 4)
	15	
	18	
	21	
	24	
	27	
3x2 3x3 4x2 4x3 4x4 5x3 5x4 5x5 6x * 7x * 8x * 9x * 10x *	30	3/4 CUT OR ROLLED
	33	
	36	
	42	
	48	
	54	
	60	
	66	
	72	
	78	
11 X * AND GREATER	84	1 CUT OR ROLLED
	90	
	96	
	102	
	108	
	120	
	132	1 1/4
	138 AND GREATER	



- NOTES:**
- HOLES SHALL BE CAST-IN OR DRILLED 16 FROM OUTSIDE EDGE OF JOINT.
 - NUTS AND WASHERS ARE NOT REQUIRED ON INSIDE OF 27 DIAM. PIPE OR LESS.
 - TIES ARE NOT REQUIRED FOR BELL PIPE 24 AND SMALLER. ON OTHER SIZES TIE MAY BE INSERTED FROM INSIDE.
 - CUT THREADS MAY BE USED IF WASHER AND NUT ARE USED.
 - PIPE SIZE LISTED IS INSIDE DIAM. OF ROUND PIPE OR EQUIVALENT DIAM. OF PIPE ARCH OR ELLIPTICAL.
 - GALVANIZING OF TIES IS REQUIRED.
 - ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



MODEL: 90pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED - 11-12-14									CONTRACT NO.			
REVISED - 10-14-11									ILLINOIS FED. AID PROJECT			
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.						

TYPICAL AGGREGATE BASE SIDEROAD




ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 93pi2
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-14-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT	

TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)



LEGEND

-  WORK AREA
-  LANE OPEN TO TRAFFIC
-  TYPE I OR II BARRICADE OR DRUM WITH FLASHING BURNING LIGHT
-  DRUM OR BARRICADE WITH STEADY BURN LIGHT
-  SIGN (SEE DETAIL)
-  TYPE I OR II CHECK BARRICADE WITH STEADY LIGHT BURN

GENERAL NOTES

CONES MAY BE SUBSTITUTED FOR BARRICADES OR DRUMS AT HALF THE SPACING DURING DAY OPERATIONS. CONES SHALL BE A MINIMUM OF 28 IN HEIGHT.

STEADY BURNING LIGHTS WILL NOT BE REQUIRED ON BARRICADES OR DRUMS FOR DAY OPERATIONS. ALL LIGHTS WILL BE MONODIRECTIONAL.

TEMPORARY PAVEMENT MARKING SHALL BE PLACED THROUGHOUT THE BARRICADED AREA OF EACH BAY WHERE THE CLOSURE TIME IS GREATER THAN FOURTEEN DAYS.

THIS APPLICATION ALSO APPLIES WHEN WORK IS BEING PERFORMED IN THE RIGHT LANE(S) AND THE RIGHT TURN BAY IS TO REMAIN OPEN. UNDER THIS CONDITION, "RIGHT TURN LANE" R3-100 24 X 24 AND M6-2R 21 X 15 SHALL BE USED.

THESE CONTROLS SHALL SUPPLEMENT MAINLINE TRAFFIC CONTROL FOR LANE CLOSURES. LONGITUDINAL DIMENSIONS MAY BE ADJUSTED TO FIT FIELD CONDITIONS.


TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) SHALL BE INCLUDED IN THE COST SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 94pi2
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 10-14-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		

PERIMETER EROSION BARRIER, SPECIAL




GENERAL NOTES

- THIS WORK SHALL BE DONE IN ACCORDANCE TO THE APPLICABLE PORTIONS OF SECTION 630 OF THE STANDARD SPECIFICATIONS.
- POST SPACING SHALL BE 6'-3".
- STEEL PLATE BEAM GUARDRAIL SHALL BE ACCORDING TO THE REQUIREMENTS OF AASHTO M 180, TYPE 1, CLASS A.
- STEEL PLATE BEAM GUARDRAIL AND STEEL POSTS SHALL BE IN ACCORDANCE WITH ARTICLES 1006.23 AND 1006.25 OF THE STANDARD SPECIFICATIONS.
- ALL SECTIONS OF GUARDRAIL SHALL BE BOLTED TOGETHER.
- RAIL ELEMENTS SHALL BE BOLTED TO POST.
- BOTTOM OF RAIL SHALL BE EMBEDDED INTO THE FORESLOPE UNTIL NO GAP EXISTS BETWEEN THE BOTTOM OF THE RAIL AND THE EXISTING GROUND.
- GEOTEXTILE FABRIC SHALL BE PLACED BEHIND THE RAIL ELEMENT AND ON THE GROUND BEHIND THE EXISTING GUARDRAIL BEFORE PLACING THE AGGREGATE WEDGE SHOULDERS. THE INSTALLATION AND MATERIAL FOR GEOTEXTILE FABRIC SHALL BE ACCORDING TO SECTION 210 OF THE STANDARD SPECIFICATIONS.
- AT LOCATIONS WHERE THERE ARE GAPS UNDER THE RAIL ANOTHER RAIL ELEMENT SHALL BE PLACED BELOW THE FIRST RAIL AND BOLTED TO IT. THE ADDITIONAL RAIL ELEMENTS WILL BE PAID AT THE CONTRACT UNIT PRICE PER FOOT FOR STEEL PLATE BEAM GUARD RAIL, TYPE A (SPECIAL).
- STEEL PLATE BEAM GUARDRAIL, 6' STEEL GUARDRAIL POSTS, AND GEOTEXTILE FABRIC SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT FOR PERIMETER EROSION BARRIER, SPECIAL.
- AGGREGATE SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER TON FOR AGGREGATE WEDGE SHOULDER, TYPE B.

MODEL: 8pt4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 9-16-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

CONCRETE CURB (SPECIAL)



CONCRETE CURB (SPECIAL) SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 606 OF THE STANDARD SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS, STANDARD 606001 AND THIS DRAWING.

CLASS SI CONCRETE SHALL BE USED THROUGHOUT.

HOLES 1-1/2"Ø AND 5" DEEP SHALL BE DRILLED IN THE EXISTING CONCRETE PAVEMENT AT 5'-0" CENTERS. NO. 4 REINFORCEMENT BARS () LONG SHALL BE GROUTED IN THE HOLES AND A NO. 4 REINFORCEMENT BAR SHALL BE INSTALLED LONGITUDINALLY IN THE CURB.

JOINTS OF A TYPE SIMILAR TO THAT IN THE UNDERLYING PAVEMENT (EXPANSION OR CONTRACTION) SHALL BE INSTALLED IN THE CONCRETE CURB IN ALIGNMENT WITH THE JOINTS IN THE PAVEMENT.

THE COST OF ALL MATERIALS AND LABOR REQUIRED TO INSTALL THE JOINTS AND REINFORCEMENT BARS IN THE CURB SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOOT FOR CONCRETE CURB (SPECIAL).

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 11p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 9-16-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

COMBINATION CONCRETE CURB & GUTTER, TYPE , SPECIAL

COMBINATION CONCRETE CURB AND GUTTER, TYPE SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 606 OF THE STANDARD SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS, STANDARD 606001 AND THIS DRAWING.


HOLES 1-1/2" Ø AND 5" DEEP SHALL BE DRILLED IN THE EXISTING CONCRETE PAVEMENT AT 5'-0" CENTERS. NO. 4 REINFORCEMENT BARS " LONG SHALL BE GROUDED IN THE HOLES AND A NO. 4 REINFORCEMENT BAR SHALL BE INSTALLED LONGITUDINALLY IN THE CURB.

JOINTS OF A TYPE SIMILAR TO THAT IN THE UNDERLYING PAVEMENT (EXPANSION OR CONTRACTION) SHALL BE INSTALLED IN THE CONCRETE CURB AND GUTTER IN ALIGNMENT WITH THE JOINTS IN THE PAVEMENT.

GUTTER FLAG 12" OR GREATER IN WIDTH SHALL BE REINFORCED WITH WELDED WIRE REINFORCEMENT, 6 x 6 MESH NO. 4 WIRE, NOT WEIGHING LESS THAN 58 lbs/100 sq. ft.

THE COST OF ALL MATERIALS AND LABOR REQUIRED TO INSTALL THE JOINTS, REINFORCEMENT BARS AND WELDED WIRE REINFORCEMENT IN THE CURB AND GUTTER SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE PER FOOT FOR COMBINATION CONCRETE CURB AND GUTTER, TYPE , SPECIAL.

CLASS SI CONCRETE SHALL BE USED THROUGHOUT.



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 13p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 9-16-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

GUTTER OUTLET ADJACENT TO STABILIZED SHOULDER





NOTE:

IF THE AVERAGE GRADE OF PAVEMENT FOR THE DISTANCE A-C EXCEEDS 2%, THIS DISTANCE SHALL BE INCREASED 6' FOR EACH 1% INCREASE IN GRADE.

3 % 30'	2.93 CU. YD.
4 % 36'	3.51 CU. YD.
5 % 42'	4.10 CU. YD.
6 % 48'	4.68 CU. YD.



- QUANTITIES -
 SECTIONS A-A TO C-C AND CURTAIN WALL 2.34 CU. YDS. CLASS SI CONCRETE
 SECTION D-D = 0.079 CU. YDS./ft.



NOTES:



CLASS SI CONCRETE SHALL BE USED THROUGHOUT. THE GUTTER OUTLET WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CU. YD. FOR CLASS SI CONCRETE (OUTLETS), WHICH PRICE SHALL INCLUDE THE COST OF THE WELDED WIRE REINFORCEMENT

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 15p14
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
REVISED - 9-30-11										
REVISED -										
REVISED -										
SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.				
						ILLINOIS	FED. AID PROJECT			

CONCRETE GUTTER, TYPE A, WITH FLUME



EDGE OF PAVEMENT TO SECTION A-A INCLUDING TWO CUTOFF WALLS 1.02 CU YDS
SECTION B-B 0.059 CU. YD./FT.



NOTES:

CLASS SI CONCRETE SHALL BE USED THROUGHOUT. THE GUTTER SHALL BE TIED TO ITS FLUME AS SHOWN. THE FLUME SHALL BE REINFORCED WITH WELDED WIRE REINFORCEMENT HAVING A WEIGHT OF AT LEAST 58 lbs/100 sq. ft., WITH 6 x 6 MESH, NO. 4 WIRE. FLUME SHALL ALSO HAVE TWO CUTOFF WALLS AS SHOWN. COST OF FLUME PORTION INCLUDING ALL MATERIALS AND LABOR SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CU. YD. FOR CLASS SI CONCRETE (OUTLET).

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 16p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED -	1-05-16
REVISED -	6-27-14
REVISED -	9-30-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD				
SCALE:	SHEET	OF	SHEETS	STA.
				TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
		ILLINOIS	FED. AID PROJECT	

CATCH BASIN OR INLETS TO BE ADJUSTED OR RECONSTRUCTED

(DETAILS FOR CURB & GUTTER REPLACEMENT)

CONCRETE CURB AND GUTTER SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 606 OF THE STANDARD SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS, STANDARD 606001 AND THIS DRAWING.

CLASS SI CONCRETE SHALL BE USED THROUGHOUT. A HOLE 1-1/2 IN DIAMETER AND 9 DEEP SHALL BE DRILLED IN THE EXISTING CONCRETE CURB AS SHOWN. A 1-1/4 X 18 SMOOTH DOWEL BAR SHALL BE GROUTED IN THE HOLE LONGITUDINALLY.


JOINTS OF A TYPE SIMILAR TO THAT IN THE UNDERLYING PAVEMENT (EXPANSION OR CONTRACTION) SHALL BE INSTALLED IN THE CONCRETE CURB IN ALIGNMENT WITH THE JOINTS IN THE PAVEMENT.

THE PROPOSED CONFIGURATION OF THE CURB AND GUTTER SHALL MATCH THAT REMOVED.

THE LOCATION OF THE DOWEL BAR SHALL BE DETERMINED BY THE ENGINEER.

ALL EXISTING TIE BARS IN EDGE OF PAVEMENT SLAB THRU REPLACEMENT AREA SHALL BE CUT OFF.

THE WORK SHALL BE DONE IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS AND INCLUDES THE REMOVAL AND REPLACEMENT OF SOD, CONCRETE PAVEMENT AND/OR CURB AND GUTTER ADJACENT TO CATCH BASINS OR INLETS TO BE ADJUSTED OR RECONSTRUCTED AND SHALL BE INCLUDED IN THE PAY ITEM OF CATCH BASINS OR INLETS TO BE ADJUSTED OR RECONSTRUCTED AS SPECIFIED.



WHEN "A" IS GREATER THAN 2, 2-NO. 4 BARS SHALL BE PLACED AS SHOWN.



SAME REPAIR AS INDICATED ON OTHER SIDE OF FRAME AND GRATE.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 17p14
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025


REVISED - 9-30-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -									
REVISED -									
SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.			
						ILLINOIS	FED. AID PROJECT		

CURB AND GUTTER OUTLET, SPECIAL



QUANTITY OF CONCRETE
SECTION A-A = 0.07 CU.YD./FT.
8' SECTION OF CURB & GUTTER UP TO
SECTION A-A = 0.75 CU.YD.

SECTION A-A



SECTION C-C

NOTE:


CLASS SI CONCRETE SHALL BE USED THROUGHOUT. CURB AND GUTTER OUTLET SHALL BE TIED TO PAVEMENT SLAB WITH 2 TIE BARS, 30 LONG - 30 CENTERS. OUTLET SHALL BE TIED TO CURB AND GUTTER AT CONTRACTION JOINTS AS SHOWN. GUTTER OUTLET AND PAVED DITCH SHALL BE REINFORCED WITH WELDED WIRE REINFORCEMENT HAVING A WEIGHT OF AT LEAST 58 lbs/100 sq. ft. WITH 6 x 6 MESH, NO. 4 WIRE. COST TO BE INCLUDED IN THE UNIT PRICE PER CUBIC YARD FOR CLASS SI CONCRETE (OUTLET).

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 18p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 9-30-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

RIPRAP AT END SECTIONS



FLARED END SECTION




STANDARD END SECTION


L_A = APRON LENGTH (ft)

IF THE CULVERT OUTLETS INTO A DEFINED CHANNEL, RIPRAP BANK TO BANK FOR LENGTH $(L)_A$

STANDARD END SECTION:
542001 (PIPE), 542011 (ELLIPTICAL)
DISTRICT STANDARD 10.1 (BOX).



CULVERT WITH HEADWALL



CULVERT WITH WING WALLS



MODEL: 19p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED -	7-13-16
REVISED -	11-12-14
REVISED -	2-10-14
REVISED -	

REGION 2 / DISTRICT 2 STANDARD				
SCALE:	SHEET	OF	SHEETS	STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

GRADING AROUND WINGWALLS




NOTES
SEE CROSS SECTIONS FOR THE APPROPRIATE FRONTSLOPE TO BE USED.

MODEL: 20pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 5-27-09	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

AGGREGATE DITCH FOR FLEXIBLE DITCH LINING



THIS WORK SHALL BE DONE IN ACCORDANCE WITH SECTION 281. AGGREGATE DITCH WILL BE MEASURED FOR PAYMENT IN PLACE AND THE AREA COMPUTED IN SQUARE YARDS OF ACTUAL SURFACE AREA.


AGGREGATE DITCH WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD FOR STONE RIPRAP CLASS A3 OR STONE RIPRAP CLASS A4 THE FILTER FABRIC SHALL BE PAID ACCORDING TO SECTION 282. FILTER FABRIC WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD FOR FILTER FABRIC.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 21p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 7-05-12	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

HOT-MIX ASPHALT SHOULDER



GENERAL NOTES

THE HOT-MIX ASPHALT SHOULDER SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 482 EXCEPT THE TOP LIFT SHALL BE HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50. THE WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER TON FOR HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 AND SQUARE YARD FOR HOT-MIX ASPHALT SHOULDERS OF THE THICKNESS SPECIFIED.

USE HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50. WHEN RESURFACING EXISTING HOT-MIX ASPHALT SHOULDERS. THE THICKNESS IS SHOWN ON THE TYPICAL SECTIONS. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER TON FOR HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50.


REMOVAL OF MATERIAL FOR PLACEMENT OF THE HOT-MIX ASPHALT SHOULDER TO BE PAID FOR IN UNITS FOR EXCAVATING AND GRADING EXISTING SHOULDERS OR IN CUBIC YARDS FOR EARTH EXCAVATION OR EARTH EXCAVATION WIDENING.

* 4% WHEN MAINLINE IS ON TANGENT. FOR CROSS SLOPE ON SUPERELEVATION SECTION, SEE HIGHWAY STANDARD 482001 OR 482006.

MODEL: 22p14
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 3-13-13									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

DETAIL OF HOT-MIX ASPHALT SHOULDER AT GUARDRAIL



t = SEE TYPICAL SECTIONS FOR THICKNESS

GENERAL NOTES

THE TOP LIFT SHALL NOT BE PLACED BEHIND THE GUARDRAIL POSTS. WHEN PLACING THE TOP LIFT THE RAIL MUST BE REMOVED FROM THE POSTS. THE POST SHALL NOT BE REMOVED. THE RAIL ELEMENT SHALL BE REINSTALLED WITHIN 72 HOURS OF THE COMPLETION OF THE SURFACE COURSE.

THE HEIGHT OF THE GUARDRAIL SHALL BE SET 24⁷/₈" FROM THE FINISHED SURFACE.


THE HOT-MIX ASPHALT SHOULDER SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 482 EXCEPT THE TOP LIFT SHALL BE HOT-MIX ASPHALT SURFACE COURSE, MIXTURE C, N50. THE WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER TON FOR HOT-MIX ASPHALT SURFACE COURSE, MIXTURE "C", N50 AND SQUARE YARD FOR HOT-MIX ASPHALT SHOULDERS OF THE THICKNESS SPECIFIED. THE REMOVAL & REINSTALLATION OF THE GUARDRAIL WILL BE INCLUDED IN THE COST OF THE HOT-MIX ASPHALT SURFACE COURSE, MIXTURE C, N50.

* 4% WHEN MAINLINE IS ON TANGENT. FOR CROSS SLOPE ON SUPERELEVATED SECTION, SEE HIGHWAY STANDARD 482001 OR 482006.

MODEL: 23p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 6-27-14									
REVISED - 8-27-13					CONTRACT NO.				
REVISED - 3-13-13					SCALE:	SHEET	OF	SHEETS	STA.




PAVEMENT BREAKING DETAIL



MODEL: 24pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 3-19-13	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

CONCRETE HEADWALLS FOR PIPE UNDERDRAINS FOR STRUCTURES



CLASS SI CONCRETE

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 27pi4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED -	9-28-17
REVISED -	11-12-14
REVISED -	10-03-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD



SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
		ILLINOIS	FED. AID PROJECT	

CAST-IN-PLACE REINFORCED CONCRETE END SECTIONS

NOTES


1. ANY STORM SEWER OR FIELD TILE OUTLET INTO A DITCH SHALL HAVE A HEADWALL BUILT IN ACCORDANCE WITH THIS DETAIL.
2. COST OF FURNISHING AND INSTALLING WELDED WIRE REINFORCEMENT SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE EACH OF THE SIZE SPECIFIED. WELDED WIRE REINFORCEMENT TO WEIGH NOT LESS THAN 58 lbs/100 sq. ft.



DIAMETER = EXISTING TILE DIA. +2
(6" MIN. DIA.)

SEE STANDARD 601101 FOR
DETAIL OF RODENT SHIELD

WELDED WIRE
REINFORCEMENT
SEE NOTE



MODEL: 28pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED -	1-05-16
REVISED -	10-09-12
REVISED -	
REVISED -	

REGION 2 / DISTRICT 2 STANDARD

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

SILICONE JOINT SEAL (CONCRETE DETAILS)




ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 29pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	


STONE WELLS, SPECIAL



PLAN
SINGLE STONE WELL



PLAN
DOUBLE STONE WELL



NOTE:



THE INSIDE LINER OF THE STONE WELL SHALL BE A 24 CORRUGATED METAL PIPE OF THE SAME QUALITY AS SPECIFIED FOR PIPE CULVERTS, TYPE I. THE PERFORATIONS SHALL BEGIN 15 FROM THE TOP OF THE STONE WELL AT THE RATE OF 4 HOLES PER SQUARE FOOT. THE SIZE OF THE HOLES SHALL NOT BE LESS THAN 5/16 OR MORE THAN 5/8 DIAMETER. DOUBLE STONE WELL TO BE PAID FOR AS TWO (2) STONE WELLS. STANDARD GRATE TYPE 8 (STD. 604036) WILL BE USED. THE CONTRACT UNIT PRICE FOR STONE WELLS, SPECIAL SHALL INCLUDE ALL MATERIALS AND LABOR FOR THE COMPLETE IN PLACE STONE WELL.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 30pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-03-11									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

PARKING BLOCKS



GENERAL NOTES

CLASS SI CONCRETE SHALL BE USED THROUGHOUT.

ANCHOR PINS SHALL BE 3/4 DIAMETER, 36 LONG.

THE COST OF THE MATERIAL, LABOR AND EQUIPMENT NECESSARY TO INSTALL THE PARKING BLOCKS WITH ANCHOR PINS SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE PER EACH FOR PARKING BLOCKS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


* OR AS DIRECTED BY THE ENGINEER.

END OF SURFACE COURSE

MODEL: 31p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
REVISED -										
REVISED -										
REVISED -										
SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.				
						ILLINOIS	FED. AID PROJECT			

PAVEMENT PATCHING FOR HOT-MIX ASPHALT SURFACED PAVEMENT



LIFT PLACEMENT:
 $t < 4"$ MAY BE PLACED IN ONE LIFT.
 $t > 4"$ TO BE PLACED IN TWO LIFTS WITH 2" MIN. COMPACTED TOP LIFT.

SEQUENCE OF CONSTRUCTION:

1. REMOVE THE EXISTING HOT-MIX ASPHALT SURFACE.
2. RESIDENT ENGINEER WILL DETERMINE IF LOCATION IS TO BE PATCHED OR TO ONLY REPLACE HOT-MIX ASPHALT SURFACE.
3. REMOVE AND REPLACE FULL DEPTH PATCHES AT LOCATIONS DIRECTED BY THE ENGINEER.
4. REPLACE HOT-MIX ASPHALT SURFACE OVER FULL DEPTH PATCHES AND AT LOCATIONS OF HOT-MIX ASPHALT SURFACE REMOVAL.

GENERAL NOTES:


1. FOR BASIS OF PAYMENT: SEE THE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 32p14
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

PAVEMENT PATCHING DETAIL



LIFT PLACEMENT:
TO BE PLACED
IN TWO LIFTS WITH
2" MIN. COMPACTED
TOP LIFT.

SEQUENCE OF CONSTRUCTION:

1. REMOVE THE EXISTING HOT-MIX ASPHALT SURFACE.
2. REPLACE HOT-MIX ASPHALT SURFACE.

GENERAL NOTES:


1. FOR BASIS OF PAYMENT: SEE THE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 33p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA.	TO STA.	ILLINOIS

THRUST BLOCK DETAILS




REDUCING CROSS


BRACE PLUG AGAINST
UNDISTURBED EARTH




PLUGGED CROSS



90° ELBOW




TEE



BRACE PLUG AGAINST
UNDISTURBED EARTH

PLUGGED TEE



VERTICAL BEND

NOTES:
ALL BLOCKS TO BEAR AGAINST UNDISTURBED EARTH.
ARROWS INDICATE DIRECTION OF THRUST.
ALL BLOCKS TO BE CLASS SI CONCRETE.
ALL FITTINGS SHOWN IN PLAN EXCEPT VERTICAL BEND.



ALL DIMENSIONS ARE IN INCHES UNLESS
OTHERWISE NOTED.

MODEL: 34pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

SIDEWALK AND DRIVEWAY PAVEMENT PAY AREAS

- PAY FOR AS
-  SIDEWALK REMOVAL
 -  DRIVEWAY PAVEMENT REMOVAL
 -  PCC SIDEWALK 5
 -  PCC DRIVEWAY PAVEMENT 7




FOR DETAILS ON DIMENSIONS AND GRADES, SEE DISTRICT STANDARD 25.1 OR PLANS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 35pi4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 6-27-14	REGION 2 / DISTRICT 2 STANDARD			F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-03-11								
REVISED -				CONTRACT NO.				
REVISED -				SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	

CONCRETE GUTTER, TYPE A (SPECIAL)



NOTES:


THIS WORK SHALL BE DONE IN ACCORDANCE WITH THIS DETAIL AND STANDARD 606101
 THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT FOR
 CONCRETE GUTTER, TYPE A (SPECIAL).

ALL DIMENSIONS ARE IN INCHES UNLESS
 OTHERWISE NOTED.


MODEL: 36p14
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA.	TO STA.	ILLINOIS

DELINEATOR AND POST ORIENTATION



SECTION D-D




DELINEATORS SHALL BE INSTALLED ACCORDING TO STANDARD 635001 EXCEPT THAT THE POST SHALL BE ROTATED 180°. THE POST WILL HAVE THE WIDE SIDE FACING TRAFFIC AND THE DELINEATOR ATTACHED AS SHOWN ABOVE.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 37pi4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.



EDGE OF PAVEMENT REPAIR



MODEL: 38pt4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 4-04-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	


REQUIRED COLD MILLED SURFACE TEXTURE



NOTES

1. Cold Milling shall consist of two processes: Cutting with carbide teeth mounted on a rotating drum, and planing with a moldboard mounted immediately behind the cutting drum.
2. Other similar patterns will be acceptable if they consist of a smooth, flat, planed surface interspersed with a pattern of discontinuous longitudinal striations.


ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



MODEL: 43pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -									
REVISED -									
SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.			
						ILLINOIS	FED. AID PROJECT		

SLAB MOVEMENT DETECTION DEVICE



ELEVATION

NOTES


Dial gauges shall be spring loaded in order to measure both extension and compression.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 44pt4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -	SCALE: SHEET OF SHEETS STA. TO STA.				CONTRACT NO.				
REVISED -					ILLINOIS		FED. AID PROJECT		

AERIAL SPEED CHECK ZONES




USE THERMOPLASTIC PAVEMENT MARKINGS MEETING THE REQUIREMENTS OF SECTION 782 OF THE STANDARD SPECIFICATIONS.

POLICE AERIAL SPEED CHECK ZONES

ESTABLISHED ZONES AND NEW ZONES REQUESTED BY THE ILLINOIS STATE POLICE SHALL BE MARKED CONSISTENT WITH THE REQUIREMENTS OF SECTION 3B.21 OF THE MUTCD. WHEN NEW ZONES ARE PLACED IT WILL BE NECESSARY TO HAVE A REPRESENTATIVE OF THE STATE POLICE PRESENT SO THAT THE ACCURACY OF THE MEASUREMENT CAN BE ATTESTED TO IN COURT.

PAVEMENT MARKING DETAIL



ILLINOIS STATE POLICE

DISTRICT 1 STERLING 815/632-4010
 DISTRICT 7 EAST MOLINE 309/752-4915
 DISTRICT 16 PECATONICA 815/239-1152

CARROLL, LEE, OGLE, WHITESIDE
 HENRY, ROCK ISLAND
 BOONE, JO DAVIESS, STEPHENSON, WINNEBAGO


BASIS OF PAYMENT:

THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT FOR AERIAL SPEED CHECK MARKING.

MODEL: 46pt4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 6-27-14									
REVISED - 8-27-13					CONTRACT NO.				
REVISED - 10-03-11					SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	



TYPICAL BENCHING ON EXISTING EMBANKMENT



MODEL: 50pt4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISI	REVISI	REVISI	REVISI	REGION 2 / DISTRICT 2 STANDARD			F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISI	REVISI	REVISI	REVISI				SCALE:	SHEET	OF	SHEETS	STA.
REVISI	REVISI	REVISI	REVISI				ILLINOIS	FED. AID PROJECT			

TYPICAL CONSTRUCTION OF EMBANKMENTS WITH GRANULAR MATERIAL




 GRANULAR MATERIAL
 COHESIVE MATERIAL

NOTES:

WHEN THE CONTRACTOR ELECTS TO USE A GRANULAR TYPE OF MATERIAL TO CONSTRUCT THE NEW EMBANKMENT, A 3' THICK COHESIVE MATERIAL WILL BE REQUIRED ON THE SLOPE CONSTRUCTED CONCURRENTLY WITH THE GRANULAR EMBANKMENT LIFTS.

IF THE CONTRACTOR SWITCHES BETWEEN GRANULAR TYPES OF MATERIAL LIFTS AND COHESIVE MATERIAL LIFTS IN THE NEWER EMBANKMENT, FRENCH DRAINS SHALL BE CONSTRUCTED EVERY 250' ACCORDING TO ARTICLE 601.06. THE COST OF MATERIALS AND LABOR WILL BE INCLUDED IN THE CONTRACT UNIT PRICE OF EARTH EXCAVATION.





FRENCH DRAIN DETAIL

MODEL: 51p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 11-01-21	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED -												
REVISED -									CONTRACT NO.			
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT

TREE WALL



HEIGHT OF WALL DEPENDENT ON SLOPE OF THE CUT.
 * THE RADIUS OF THE TREE WALL SHALL BE DETERMINED BY MULTIPLYING 6 BY THE DIAMETER OF THE TREE, WITH A MAXIMUM OF A 12 FOOT RADIUS.
 USE 8" HIGH BLOCKS EXCEPT WHEN HEIGHT OF WALL IS LESS THAN 24", THEN 4" HIGH BLOCKS SHALL BE USED.

NOTES

SPECIAL CARE SHALL BE TAKEN BY THE CONTRACTOR NOT TO DISTURB THE EARTH OR THE ROOTS WITHIN THE PROPOSED TREE WALL.


THESE TREE WALLS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE FOOT FOR "SEGMENTAL CONCRETE BLOCK WALL" INCLUDED IN THIS SHALL BE THE FACE OF THE WALL THAT ARE BURIED.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 70pt4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 10-03-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
REVISED -										
REVISED -										
REVISED -										
SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.				
						ILLINOIS	FED. AID PROJECT			


DETAIL OF CONCRETE STEPS



END ELEVATION



SECTION A-A



PLAN

TABLE OF TREADS & RISERS

SLOPE TREAD RISER

SLOPE	TREAD	RISER
1:2	12"	6"
1:3	15"	5"
1:4	17"	4 1/4"

WHERE SLOPES FALL BETWEEN THOSE SHOWN IN THE TABLE ABOVE, THE STAIR RAIL SHOULD FIT THE SLOPE AND THE TREAD IN INCHES x THE RISER IN INCHES SHOULD BE BETWEEN 72 AND 78.

EXAMPLE:

FOR A 1:4 SLOPE USE $y = \text{RISER HEIGHT } 4y = 75"$.
 SOLVING $y \approx \frac{75}{4}$, $y = 4.3"$ (USE 4 1/4" FOR CONVENIENCE.)
 TREAD WOULD THEN BE $4 \frac{1}{4} \times 4 = 17"$

COST OF REINFORCEMENT BARS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER LBS FOR REINFORCEMENT BARS.


CLASS SI CONCRETE SHALL BE USED THROUGHOUT, WHICH SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CUBIC YARD FOR CONCRETE STEPS

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 71pt4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 8-27-13	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
REVISED - 10-03-11										
REVISED -										
REVISED -										
SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	CONTRACT NO.				
						ILLINOIS	FED. AID PROJECT			

INLETS, SPECIAL, NO. 3



FRONT VIEW

SEE STANDARD 602701 FOR DETAILS OF STEPS.


1" PREFORMED EXPANSION JOINTS AS SHOWN SHALL BE PROVIDED ON EACH SIDE OF INLET.

CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT.

THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTAL SECTIONS.


REINFORCEMENT FOR INLETS, SPECIAL, NO. 3 SHALL BE ACCORDING TO DISTRICT STANDARD 79.4g

LIGHT WEIGHT MANHOLE CASTING




TOTAL WEIGHT 160 LBS.

SLOPE TOP SLAB TO MATCH FINAL CONDITIONS



SEC. A-A



TOP VIEW

STEPS AT 12 TO 16 CTS.

*THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.

THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6" SHORT TO ALLOW FOR FIELD ADJUSTMENTS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

NOTES

STEPS SHALL BE OMITTED WHEN DEPTH OF INLET IS LESS THAN 5 FOOT

THE INLET SHALL BE CAST IN PLACE OR PRECAST.

EXCEPT AS NOTED HEREON INLETS, SPECIAL, NO. 3 SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.

THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL NO. 3 SHALL INCLUDE THE COST OF FURNISHING AND INSTALLING THE FRAME, LID, REINFORCEMENT BARS, FLOOR AND TOP SLABS, CAST IRON STEPS (IF USED).

THE CURB AND GUTTER WILL BE PAID FOR SEPARATELY AND WILL BE MEASURED THROUGH THE INLET.

THE CURB AND GUTTER ADJACENT TO AND 6 FOOT ON EITHER SIDE OF THE INLET SHALL BE CONSTRUCTED AS SHOWN WITH NO ADDITIONAL COMPENSATION FOR THE TRANSITION.

ALL PIPE UNDERDRAIN CONNECTIONS WHEN SPECIFIED SHALL BE DONE IN ACCORDANCE WITH ART. 601 OF THE STANDARD SPECIFICATIONS. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER (FOOT) FOR PIPE UNDERDRAINS, TYPE 2 OR PIPE UNDERDRAINS (SPECIAL) OF THE DIAMETER SPECIFIED WHICH PRICE SHALL INCLUDE THE CA7 OR CA16 AND THE CONNECTION TO THE INLET.

**WHEN INLET IS CONSTRUCTED IN RETURN, THE TOP OF SLAB SHALL CONFORM TO THE RADIUS OF THE RETURN.

MODEL: 79pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED -	1-05-16
REVISED -	8-27-13
REVISED -	10-03-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		


INLETS, SPECIAL, NO. 4



FRONT VIEW


SEE STANDARD 602701 FOR DETAILS OF STEPS.
 1" PREFORMED EXPANSION JOINTS AS SHOWN SHALL BE PROVIDED ON EACH SIDE OF INLET.
 CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT.
 THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTAL SECTIONS.
 REINFORCEMENT FOR INLETS, SPECIAL, NO. 4 SHALL BE ACCORDING TO DISTRICT STANDARD 79.4g

LIGHT WEIGHT MANHOLE CASTING



TOTAL WEIGHT 160 LBS.

SLOPE TOP SLAB TO MATCH FINAL CONDITIONS




SEC. A-A

STEPS AT 12 TO 16 CTS.
 *THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.
 THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.

NOTES

STEPS SHALL BE OMITTED WHEN DEPTH OF INLET IS LESS THAN 5 FOOT
 THE INLET SHALL BE CAST IN PLACE OR PRECAST.
 EXCEPT AS NOTED HEREON INLETS, SPECIAL, NO. 4 SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.
 THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL NO. 4 SHALL INCLUDE THE COST OF FURNISHING AND INSTALLING THE FRAME, LID, REINFORCEMENT BARS, FLOOR AND TOP SLABS, CAST IRON STEPS (IF USED).
 THE CURB AND GUTTER WILL BE PAID FOR SEPARATELY AND WILL BE MEASURED THROUGH THE INLET.
 THE CURB AND GUTTER ADJACENT TO AND 6 FOOT ON EITHER SIDE OF THE INLET SHALL BE CONSTRUCTED AS SHOWN WITH NO ADDITIONAL COMPENSATION FOR THE TRANSITION.
 ALL PIPE UNDERDRAIN CONNECTIONS WHEN SPECIFIED SHALL BE DONE IN ACCORDANCE WITH ART. 601 OF THE STANDARD SPECIFICATIONS. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER (FOOT) FOR PIPE UNDERDRAINS, TYPE 2 OR PIPE UNDERDRAINS (SPECIAL) OF THE DIAMETER SPECIFIED WHICH PRICE SHALL INCLUDE THE CA7 OR CA16 AND THE CONNECTION TO THE INLET.



TOP VIEW

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 79pl4a
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED -	1-05-16
REVISED -	8-27-13
REVISED -	10-04-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

INLETS, SPECIAL, NO. 4


79.4a

INLETS, SPECIAL, NO. 5



FRONT VIEW

SLOPE TOP SLAB TO MATCH FINAL CONDITIONS



SEC. A-A


STEPS AT 12 TO 16 CTS.
 *THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.
 THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.
 ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

NOTES


SEE STANDARD 602701 FOR DETAILS OF STEPS.
 1" PREFORMED EXPANSION JOINTS AS SHOWN SHALL BE PROVIDED ON EACH SIDE OF INLET.
 CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT.
 THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTAL SECTIONS.
 REINFORCEMENT FOR INLETS, SPECIAL, NO. 5 SHALL BE ACCORDING TO DISTRICT STANDARD 79.4g

STEPS SHALL BE OMITTED WHEN DEPTH OF INLET IS LESS THAN 5 FOOT
 THE INLET SHALL BE CAST IN PLACE OR PRECAST.
 EXCEPT AS NOTED HEREON INLETS, SPECIAL, NO. 5 SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.
 THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL NO. 5 SHALL INCLUDE THE COST OF FURNISHING AND INSTALLING THE FRAME, LID, REINFORCEMENT BARS, FLOOR AND TOP SLABS, CAST IRON STEPS (IF USED).
 THE CURB AND GUTTER WILL BE PAID FOR SEPARATELY AND WILL BE MEASURED THROUGH THE INLET.
 THE CURB AND GUTTER ADJACENT TO AND 6 FOOT ON EITHER SIDE OF THE INLET SHALL BE CONSTRUCTED AS SHOWN WITH NO ADDITIONAL COMPENSATION FOR THE TRANSITION.
 ALL PIPE UNDERDRAIN CONNECTIONS WHEN SPECIFIED SHALL BE DONE IN ACCORDANCE WITH ART. 601 OF THE STANDARD SPECIFICATIONS. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER (FOOT) FOR PIPE UNDERDRAINS, TYPE 2 OR PIPE UNDERDRAINS (SPECIAL) OF THE DIAMETER SPECIFIED WHICH PRICE SHALL INCLUDE THE CA7 OR CA16 AND THE CONNECTION TO THE INLET.

LIGHT WEIGHT MANHOLE CASTING



TOTAL WEIGHT 160 LBS.



**WHEN INLET IS CONSTRUCTED IN RETURN, THE TOP OF SLAB SHALL CONFORM TO THE RADIUS OF THE RETURN.


MODEL: 79pl4b
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED -	1-05-16
REVISED -	8-27-13
REVISED -	10-04-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD				
SCALE:	SHEET	OF	SHEETS	STA. TO STA.


F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

INLETS, SPECIAL, NO. 6



FRONT VIEW

SLOPE TOP SLAB TO MATCH FINAL CONDITIONS



SEC. A-A


STEPS AT 12 TO 16 CTS.
 *THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.
 THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.

NOTES


SEE STANDARD 602701 FOR DETAILS OF STEPS.
 1" PREFORMED EXPANSION JOINTS AS SHOWN SHALL BE PROVIDED ON EACH SIDE OF INLET.
 CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT.
 THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTAL SECTIONS.
 REINFORCEMENT FOR INLETS, SPECIAL, NO. 6 SHALL BE ACCORDING TO DISTRICT STANDARD 79.4g

STEPS SHALL BE OMITTED WHEN DEPTH OF INLET IS LESS THAN 5 FOOT
 THE INLET SHALL BE CAST IN PLACE OR PRECAST.
 EXCEPT AS NOTED HEREON INLETS, SPECIAL, NO. 6 SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.
 THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL NO. 6 SHALL INCLUDE THE COST OF FURNISHING AND INSTALLING THE FRAME, LID, REINFORCEMENT BARS, FLOOR AND TOP SLABS, CAST IRON STEPS (IF USED).
 THE CURB AND GUTTER WILL BE PAID FOR SEPARATELY AND WILL BE MEASURED THROUGH THE INLET.
 THE CURB AND GUTTER ADJACENT TO AND 6 FOOT ON EITHER SIDE OF THE INLET SHALL BE CONSTRUCTED AS SHOWN WITH NO ADDITIONAL COMPENSATION FOR THE TRANSITION.
 ALL PIPE UNDERDRAIN CONNECTIONS WHEN SPECIFIED SHALL BE DONE IN ACCORDANCE WITH ART. 601 OF THE STANDARD SPECIFICATIONS. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER (FOOT) FOR PIPE UNDERDRAINS, TYPE 2 OR PIPE UNDERDRAINS (SPECIAL) OF THE DIAMETER SPECIFIED WHICH PRICE SHALL INCLUDE THE CA7 OR CA16 AND THE CONNECTION TO THE INLET.

LIGHT WEIGHT MANHOLE CASTING



TOTAL WEIGHT 160 LBS.



TOP VIEW

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 79pl4c
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED -	1-05-16
REVISED -	8-27-13
REVISED -	10-05-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD


SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				

INLETS, SPECIAL, NO. 6


79.4c

INLETS, SPECIAL, NO. 7



FRONT VIEW

SLOPE TOP SLAB TO MATCH FINAL CONDITIONS



SEC. A-A


STEPS AT 12 TO 16 CTS.
 *THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.
 THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.
 ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

NOTES


SEE STANDARD 602701 FOR DETAILS OF STEPS.
 1" PREFORMED EXPANSION JOINTS AS SHOWN SHALL BE PROVIDED ON EACH SIDE OF INLET.
 CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT.
 THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTAL SECTIONS.
 REINFORCEMENT FOR INLETS, SPECIAL, NO. 7 SHALL BE ACCORDING TO DISTRICT STANDARD 79.4h

STEPS SHALL BE OMITTED WHEN DEPTH OF INLET IS LESS THAN 5 FOOT
 THE INLET SHALL BE CAST IN PLACE OR PRECAST.
 EXCEPT AS NOTED HEREON INLETS, SPECIAL, NO. 7 SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.
 THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL NO. 7 SHALL INCLUDE THE COST OF FURNISHING AND INSTALLING THE FRAME, LID, REINFORCEMENT BARS, FLOOR AND TOP SLABS, CAST IRON STEPS (IF USED).
 THE CURB AND GUTTER WILL BE PAID FOR SEPARATELY AND WILL BE MEASURED THROUGH THE INLET.
 THE CURB AND GUTTER ADJACENT TO AND 6 FOOT ON EITHER SIDE OF THE INLET SHALL BE CONSTRUCTED AS SHOWN WITH NO ADDITIONAL COMPENSATION FOR THE TRANSITION.
 ALL PIPE UNDERDRAIN CONNECTIONS WHEN SPECIFIED SHALL BE DONE IN ACCORDANCE WITH ART. 601 OF THE STANDARD SPECIFICATIONS. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER (FOOT) FOR PIPE UNDERDRAINS, TYPE 2 OR PIPE UNDERDRAINS (SPECIAL) OF THE DIAMETER SPECIFIED WHICH PRICE SHALL INCLUDE THE CA7 OR CA16 AND THE CONNECTION TO THE INLET.

LIGHT WEIGHT MANHOLE CASTING



TOTAL WEIGHT 160 LBS.



TOP VIEW

**WHEN INLET IS CONSTRUCTED IN RETURN, THE TOP OF SLAB SHALL CONFORM TO THE RADIUS OF THE RETURN.


MODEL: 79pl4d
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED -	1-05-16
REVISED -	8-27-12
REVISED -	10-05-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD				
SCALE:	SHEET	OF	SHEETS	STA.
				TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
	ILLINOIS	FED. AID PROJECT		


INLETS, SPECIAL, NO. 8



FRONT VIEW


SEE STANDARD 602701 FOR DETAILS OF STEPS.
 1" PREFORMED EXPANSION JOINTS AS SHOWN SHALL BE PROVIDED ON EACH SIDE OF INLET.
 CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT.
 THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTAL SECTIONS.
 REINFORCEMENT FOR INLETS, SPECIAL, NO. 8 SHALL BE ACCORDING TO DISTRICT STANDARD 79.4h

LIGHT WEIGHT MANHOLE CASTING



TOTAL WEIGHT 160 LBS.

SLOPE TOP SLAB TO MATCH FINAL CONDITIONS




SEC. A-A

STEPS AT 12 TO 16 CTS.
 *THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.
 THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.
 ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

NOTES

STEPS SHALL BE OMITTED WHEN DEPTH OF INLET IS LESS THAN 5 FOOT
 THE INLET SHALL BE CAST IN PLACE OR PRECAST.
 EXCEPT AS NOTED HEREON INLETS, SPECIAL, NO. 8 SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.
 THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL NO. 8 SHALL INCLUDE THE COST OF FURNISHING AND INSTALLING THE FRAME, LID, REINFORCEMENT BARS, FLOOR AND TOP SLABS, CAST IRON STEPS (IF USED).
 THE CURB AND GUTTER WILL BE PAID FOR SEPARATELY AND WILL BE MEASURED THROUGH THE INLET.
 THE CURB AND GUTTER ADJACENT TO AND 6 FOOT ON EITHER SIDE OF THE INLET SHALL BE CONSTRUCTED AS SHOWN WITH NO ADDITIONAL COMPENSATION FOR THE TRANSITION.
 ALL PIPE UNDERDRAIN CONNECTIONS WHEN SPECIFIED SHALL BE DONE IN ACCORDANCE WITH ART. 601 OF THE STANDARD SPECIFICATIONS. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER (FOOT) FOR PIPE UNDERDRAINS, TYPE 2 OR PIPE UNDERDRAINS (SPECIAL) OF THE DIAMETER SPECIFIED WHICH PRICE SHALL INCLUDE THE CA7 OR CA16 AND THE CONNECTION TO THE INLET.



TOP VIEW

**WHEN INLET IS CONSTRUCTED IN RETURN, THE TOP OF SLAB SHALL CONFORM TO THE RADIUS OF THE RETURN.






MODEL: 79pt4e
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED	1-05-16
REVISED	8-27-13
REVISED	10-05-11
REVISED	

REGION 2 / DISTRICT 2 STANDARD				
SCALE:	SHEET	OF	SHEETS	STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

NOSE TYPE FOR INLET TOP SLAB



ALL DIMENSIONS ARE IN INCHES
UNLESS OTHERWISE NOTED.

MODEL: 79pl4f
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED -	4-14-15
REVISED -	10-05-11
REVISED -	
REVISED -	

REGION 2 / DISTRICT 2 STANDARD




SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		CONTRACT NO.		
		ILLINOIS FED. AID PROJECT		

NOSE TYPE FOR INLET TOP SLAB

79.4f

INLETS, SPECIAL, NO. 3, 4, 5, 6 REINFORCEMENT DETAIL



* THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.

THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.

- ** 4'-0" TO 8'-0" - NO. 5 REINF. BARS AT 12 CTS. E.W.
- 8'-0" TO 13'-0" - NO. 5 REINF. BARS AT 10 CTS. E.W.
- 13'-0" TO 15'-0" - NO. 5 REINF. BARS AT 8 CTS. E.W.

- *** 7 SPA. AT 8" INLET SPECIAL # 3, 4
- 5 SPA AT 7-5/8" INLET SPECIAL # 5, 6

- **** 2 REBARS FOR INLET SPECIAL # 3 & 4 @ 65"
- 4 REBARS FOR INLET SPECIAL # 5 & 6 @ 24"

NOTES

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

TOP SLAB REINFORCEMENT TO BE EPOXY COATED BARS.

MODEL: 79pt4g
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025




REVISED -	4-13-16
REVISED -	8-27-13
REVISED -	10-05-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD

SCALE:	SHEET	OF	SHEETS	STA.	TO STA.
--------	-------	----	--------	------	---------

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

INLETS, SPECIAL, NO. 7 & 8 REINFORCEMENT DETAIL



* THE WALL ADJUSTMENTS SHALL BE MADE WITH CONCRETE BUILDING BRICK OR CLASS SI CONCRETE.

THE HEIGHT OF THE BOX MAY BE CONSTRUCTED 6 SHORT TO ALLOW FOR FIELD ADJUSTMENTS.

- ** 4'-0" TO 8'-0" - NO. 5 REINF. BARS AT 12 CTS. E.W.
- 8'-0" TO 13'-0" - NO. 5 REINF. BARS AT 10 CTS. E.W.
- 13'-0" TO 15'-0" - NO. 5 REINF. BARS AT 8 CTS. E.W.

*** NO. 5 REINFORCEMENT BARS 10 SPA @ 8"

NOTES

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

TOP SLAB REINFORCEMENT TO BE EPOXY COATED BARS.

MODEL: 79pt4h
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED -	4-13-16
REVISED -	8-27-13
REVISED -	10-05-11
REVISED -	

REGION 2 / DISTRICT 2 STANDARD


SCALE:	SHEET	OF	SHEETS	STA.	TO STA.
--------	-------	----	--------	------	---------

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

INLETS TO BE RECONSTRUCTED WITH NEW STANDARD 542546 FRAME AND GRATE



PLAN VIEW



NOTES:

THIS WORK SHALL BE DONE IN ACCORDANCE WITH STANDARD 542546 AND THIS DETAIL.

CLASS SI CONCRETE SHALL BE USED THROUGHOUT. THE PROPOSED TOP CAN BE CAST IN PLACE OR PRECAST.

THE EXISTING FRAME & GRATE SHALL BE REMOVED AND DISPOSED OF BY THE CONTRACTOR.

THE CONCRETE SHALL BE REMOVED BY DRILLING, CHIPPING, SAWING, OR OTHER METHOD APPROVED OF BY THE ENGINEER.


THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR INLETS TO BE RECONSTRUCTED WITH NEW STANDARD 542546 FRAME AND GRATE WHICH SHALL INCLUDE REMOVING THE FRAME & GRATE & CONCRETE, EXPANSION TIE ANCHORS, CLASS SI CONCRETE, AND FURNISHING & INSTALLING FRAME & GRATE (EITHER STEEL OR DUCTILE IRON).

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 80pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-05-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED -												
REVISED -									CONTRACT NO.			
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT

GRATE, SPECIAL



ALL DIMENSIONS ARE IN INCHES
UNLESS OTHERWISE NOTED.

PLAN VIEW OF CAST IRON GRATE

1-3/8 DIAGONAL BARS WITH
1-1/4 OPENINGS

NOTES

THE CONTRACTOR SHALL FIELD CHECK
THE SIZE OF THE EXISTING GRATE
BEFORE ORDERING THE NEW GRATE
TO INSURE THE CORRECT SIZE.

THIS WORK SHALL BE PAID FOR AT THE
CONTRACT UNIT PRICE PER EACH FOR
SPECIAL GRATE NO. 1.

THE EXISTING GRATES ARE TO BE SALVAGED
AND TO BECOME THE PROPERTY OF THE .

MODEL: 83p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-05-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
REVISED -												
REVISED -									CONTRACT NO.			
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT

TYPICAL MEDIAN CROSSOVER CLOSURE (WITH EMERGENCY OPENING)


GENERAL NOTES

WOOD POSTS, CABLE, AND SIGN SUPPORTS SHALL BE IN ACCORDANCE WITH SECTIONS 634 & 636 OF THE STANDARD SPECIFICATIONS. THE PANELS SHALL BE ANCHORED TO THE 3/8 CABLE IN SUCH A MANNER SO THEY CANNOT SLIDE ALONG THE CABLE.

THE RETROREFLECTIVE SHEETING USED FOR THE PANELS SHALL MEET THE REQUIREMENTS OF SECTION 1091 OF THE STANDARD SPECIFICATIONS AND SHALL BE ON BOTH SIDES.

ALL PANELS SHALL HAVE ALTERNATING REFLECTORIZED WHITE & RED STRIPES SLOPING DOWNWARD AT 45° TOWARD THE SIDE ON WHICH TRAFFIC WILL PASS AND ON BOTH SIDES OF PANEL. THE DRILLING OF 3 AND 6 HOLES SHALL BE INCLUDED IN THE COST OF THE MEDIAN CLOSURE.

THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR MEDIAN CLOSURE.



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 87pi4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025


REVISED -	1-05-16
REVISED -	1-17-12
REVISED -	
REVISED -	

REGION 2 / DISTRICT 2 STANDARD

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS		FED. AID PROJECT		

DRAIN FOR AGGREGATE BASES IN URBAN AREAS



NOTES

DRAINS WILL BE REQUIRED AT ALL INLETS IN "SAG" AREAS AND AS INDICATED IN THE PLANS.

THIS WORK SHALL BE COMPLETED ACCORDING TO SECTION 601 OF THE STANDARD SPECIFICATIONS.


THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT FOR PIPE UNDERDRAINS, TYPE 2 OF THE DIAMETER SPECIFIED WHICH PRICE SHALL INCLUDE THE CA7 OR CA16 AND THE CONNECTION TO THE INLET.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.


MODEL: 88p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-05-11									
REVISED -					CONTRACT NO.				
REVISED -	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS	FED. AID PROJECT	

RUMBLE RESURFACING



GROOVED



DETAIL "A"

NOTES


- THE GROOVES SHALL BE CONSTRUCTED WITH A MILLING MACHINE CAPABLE OF COLD MILLING THE EXISTING SURFACE IN THE PATTERN SHOWN.
- RUMBLE RESURFACING SHALL BE MEASURED FOR PAYMENT IN PLACE AND THE AREA COMPUTED IN SQUARE YARDS. THE LENGTH SHALL BE THE DISTANCE FROM OUTSIDE EDGE TO OUTSIDE EDGE OF THE GROOVE WHICH WILL BE APPROXIMATELY 25'. THE WIDTH SHALL BE 1' LESS THAN LANE WIDTH.
- RUMBLE STRIPS SHALL BE CONSTRUCTED AS SHOWN AND PAID FOR PER SQUARE YARD AS RUMBLE RESURFACING.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 91p14
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 10-05-11	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED -									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

DRAIN FOR AGGREGATE BASE COURSE




ALL DIMENSIONS ARE IN INCHES
UNLESS OTHERWISE NOTED.

NOTES:

The rock outlets shall be constructed using CA7 and will be paid for at the contract unit price per CUBIC YARD for FRENCH DRAINS. The thickness shall be the same as the adjacent sub-base material as noted on the plans and shall include the cost of the filter fabric. The Rock outlets will be measured in CU YD, the width being 36 by the length shown above. The cost of the CA6 or CA10 under the shoulder shall be included in the contract unit price per SQ. YD. for AGGREGATE SUBGRADE IMPROVEMENT of the thickness specified. The fabric to be used shall conform to the Geotechnical Fabric For French Drains.

ROCK OUTLET AT ALL LOW POINTS TO BE 36 WIDE AND EXTEND TO FORESLOPE




SECTION A-A

NOTE: Slope same as shoulder with 2% min.

MODEL: 96pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 8-27-13	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 10-09-12									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.

SUBGRADE REPLACEMENT



NOTES:

THE CA 02 SHALL BE COMPACTED IN A MANNER APPROVED BY THE ENGINEER. IF THE MOISTURE CONTENT OF THE MATERIAL IS SUCH THAT COMPACTION SATISFACTORY TO THE ENGINEER CANNOT BE OBTAINED, SUFFICIENT WATER SHALL BE ADDED SO THAT SATISFACTORY COMPACTION CAN BE OBTAINED.

THE CA 02 SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CU YD FOR AGGREGATE SUBGRADE IMPROVEMENT WHICH SHALL ALSO INCLUDE ALL EARTH EXCAVATION.

THE GEOTECHNICAL REINFORCEMENT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQ YD FOR GEOTECHNICAL REINFORCEMENT.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 97pi4
 FILE NAME: DISTRICT 2 STANDARD
 PLOT DATE = 4/17/2025

REVISED - 3-13-13	REGION 2 / DISTRICT 2 STANDARD			F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
REVISED -									
REVISED -				CONTRACT NO.					
REVISED -				SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT		

TYPICAL MEDIAN CROSSOVER CLOSURE


GENERAL NOTES

WOOD POSTS, CABLE, AND SIGN SUPPORTS SHALL BE IN ACCORDANCE WITH SECTIONS 634 & 636 OF THE STANDARD SPECIFICATIONS. THE PANELS SHALL BE ANCHORED TO THE 3/8 CABLE IN SUCH A MANNER SO THEY CANNOT SLIDE ALONG THE CABLE.

THE RETROREFLECTIVE SHEETING USED FOR THE PANELS SHALL MEET THE REQUIREMENTS OF SECTION 1091 OF THE STANDARD SPECIFICATIONS AND SHALL BE ON BOTH SIDES.

ALL PANELS SHALL HAVE ALTERNATING REFLECTORIZED WHITE & RED STRIPES SLOPING DOWNWARD AT 45° TOWARD THE SIDE ON WHICH TRAFFIC WILL PASS AND ON BOTH SIDES OF PANEL. THE DRILLING OF 3 HOLES SHALL BE INCLUDED TO THE MEDIAN CLOSURE.

THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR MEDIAN CLOSURE.



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

MODEL: 98pt4
FILE NAME: DISTRICT 2 STANDARD
PLOT DATE = 4/17/2025

REVISED - 1-05-16	REGION 2 / DISTRICT 2 STANDARD				F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
REVISED - 1-16-12									
REVISED -					CONTRACT NO.				
REVISED -					SCALE:	SHEET	OF	SHEETS	STA.